

Milwaukee®

Nothing but **HEAVY DUTY.**™



2019/20

TO DEVELOP AND PRODUCE **‘NOTHING BUT HEAVY DUTY™’** POWERTOOLS IS ONLY ONE PART OF THE **MILWAUKEE® PROMISE.**

These tools need to last day in and day out. For this reason, serviceability is incorporated into every tool produced.

All powertools leave the factory with a complete documentation package including instructions for use, listing of customer service centres and safety instructions. Milwaukee® has a worldwide service network.

Should a problem arise requiring assistance or support at short notice, you can rely on our service centres/ agents worldwide.

The global network ensures that our customers’ needs and requirements are shared to influence future product development.

Expertise and competence gained over many years ensures a fast and efficient professional repair service.



Milwaukee® tools strive to meet and surpass all international and European standards and directives for both design and safety. Constant research and development programs aim to anticipate and fulfil future market trends in all regulatory and efficiency requirements. Milwaukee® is, amongst others, an active member of EPTA (European Power Tool Association) and so is proudly aligned to all industry measurement standards agreed by the organization.

EXPERIENCE THE HEAVY DUTY DIFFERENCE

TOOLS BUILT TO DO THE JOB BETTER.

At Milwaukee®, Heavy Duty is more than just a slogan. It is a promise to offer the best to professional users. Milwaukee® engineers don’t just design tools.

They design tools to get the job done better, faster, reliably and safely.

www.milwaukeetool.eu



ALL YOU HAVE TO DO TO TAKE ADVANTAGE OF OUR EXTENDED WARRANTY OFFER IS TO REGISTER ONLINE. NOTHING BUT HEAVY DUTY™

HEAVY DUTY WARRANTY:



Milwaukee® offers a 3 year warranty on tools and up to 2 year warranty on REDLITHIUM-ION™ batteries, when registered.

Every Milwaukee® tool is tested according to a comprehensive certified process before leaving the factory and is guaranteed to be “NOTHING BUT HEAVY DUTY™” qualified.

At Milwaukee® we take great pride in the products and services we offer to our professional customers. With this in mind we are pleased to offer additional protection by extending our warranty period up to 3 years.

This service is available to you at no cost if you register your new Milwaukee® power tool and battery within 30 days of the purchase date.

All you need to do in order to receive this Milwaukee® service: register your tool online!

Follow the link on www.milwaukeetool.eu.

The warranty extension is only available in those countries listed on our warranty registration website. The extended warranty offer excludes products used in the hire industry, battery chargers and accessories supplied.

For full terms and conditions please see www.milwaukeetool.eu



M18

**UPGRADE.
OUTWORK.
OUTLAST.**

IF IT'S **M18** IT FITS

ONE KEY
UNLOCKING THE DIGITAL JOBSITE



M18 FUEL



ONE SYSTEM
OVER

145
TOOLS

RED LITHIUM-ION™
HIGH OUTPUT
BATTERY TECHNOLOGY

PERFORMANCE DRIVEN.
TRADE FOCUSED.
SYSTEM WIDE.

RED LITHIUM-ION™
HIGH OUTPUT
BATTERY TECHNOLOGY

RED LITHIUM-ION™

NEW M18 FUEL™

PERFORMANCE DRIVEN REDESIGN.


M18 FUEL™ is engineered for the most demanding tradesmen in the world. M18 FUEL™ delivers extreme performance in a compact structure and features three Milwaukee® exclusive innovations - the POWERSTATE™ brushless motor, REDLITHIUM-ION™ battery pack and REDLINK PLUS™ intelligence hardware and software - that deliver incredible power, run time and durability.

Simply put, M18 FUEL™ offers the best, full system technology that drives, protects and powers your cordless tools.

**HIGHER POWER
EFFICIENCY***
UNDER LOAD

**NEW
ADVANCED***
HEAVY DUTY CHUCK

**NEW
EXTREME***
COMPACT DESIGN



1 POWERSTATE™ BRUSHLESS MOTOR

- Milwaukee® designed and built brushless motor
- Provides increased efficiency
- Lasts longer and delivers maximum power*



M18 FUEL™

DRIVEN TO OUTPERFORM.™



2 REDLINK PLUS™ INTELLIGENCE

- Individual cell monitoring to optimise tool run time and ensure long term pack durability
- Advanced system electronics with unique digital performance enhancement
- Total system communication with overload protection increases tool life



3 REDLITHIUM-ION™ BATTERY PACKS

- Total system communication with overload protection increases tool life
- Fade-free performance to deliver more run time and more work over pack life
- Fuel gauge displays remaining charge
- Operates down to -20°C

REDLITHIUM-ION™

H₃ REDLITHIUM-ION™
HIGH OUTPUT BATTERY TECHNOLOGY



M18

OVER **145** **M18** **TOOLS**

REDLITHIUM-ION™ AND REDLITHIUM-ION™ HIGH OUTPUT™ SUPERIOR PACK CONSTRUCTION

IT LASTS LONGER, THINKS FASTER & WORKS HARDER*

- BATTERY FUEL GAUGE**
Displays remaining run time
- PATENTED REDLINK™ INTELLIGENCE**
Protects the pack in abusive situations, provides optimum performance and monitors the cells for maximum life
- SHOCK RESPONSIVE SEPARATORS**
Prevents pack failure from vibration or drops
- SINGLE PIECE CELL CARRIER**
Full enclosure protects cells and provides a strong structure delivering maximum durability
- RUBBER OVERMOLD**
Protects cells and pack during drops and provides maximum life
- LATCH COVER**
Prevents water from entering pack through the latch buttons
- WATER PROTECTION BARRIER**
Routes water away from the electronics and out of the battery pack
- ELECTRONIC COATING**
Protects the electronics from water and condensation
- TEMP CONTROL CELL FRAME**
Provides a strong structure and transfers energy efficiently for maximum life
- REDLITHIUM-ION™ BATTERY CELLS**
Provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life

* Compared with previous Milwaukee® battery technology. Results dependent on voltage, tool and application.

WATER ELECTRONICS THERMAL IMPACT



NEW GENERATION REDLITHIUM-ION™ HIGH OUTPUT™ BATTERIES


CHECK OUT OUR LATEST RUN TIME VIDEOS ON MILWAUKEE TOOL EUROPE
youtube.com/milwaukeetoolurope

REDLITHIUM-ION™ CELLS	<ul style="list-style-type: none"> High power cell Fade free performance Lasts in extreme environments 	<p>IN ADDITION</p> <ul style="list-style-type: none"> New larger cell Higher power density Runs cooler Lower electrical resistance
REDLINK™ ELECTRONICS	<ul style="list-style-type: none"> Individual cell monitoring Digital overload protection System performance optimisation M18™ system compatibility 	<p>IN ADDITION</p> <ul style="list-style-type: none"> New high power processor Higher current handling Maintains existing M18™ system compatibility
CONSTRUCTION	<ul style="list-style-type: none"> Best-in-class pack construction Long-lasting reliability Proven durability on the jobsite 	<p>IN ADDITION</p> <ul style="list-style-type: none"> New ground up construction Improved current flow Lower temperature rise
BENEFITS	<p>WORKS FASTER, LONGER, HARDER & EXTREMER*</p> <ul style="list-style-type: none"> Up to 20% more power* Up to 2.5x more run-time* Up to 2x longer battery life* Works down to -20°C 	<p>MOST POWERFUL MILWAUKEE® BATTERY EVER</p> <ul style="list-style-type: none"> Up to 50% more power** Up to 33% more run-time(**) (***) Runs up to 50% cooler** Works down to -28°C
APPLICATION RECOMMENDATION	<p>ALL PROFESSIONAL TRADE APPLICATIONS</p>	<p>HIGH DEMAND APPLICATIONS REQUIRING HIGH OUTPUT CURRENT</p>
RANGE		

* Vs Standard Lithium-Ion technologies

** Vs Standard REDLITHIUM-ION™ batteries in high current draw applications
*** 12.0 Ah vs 9.0 Ah and 3.0 Ah vs 2.0 Ah

IF IT'S **M18** IT FITS



ONE-KEY™

UNLOCKING THE DIGITAL JOBSITE™

CUSTOMISE. TRACK. MANAGE.

Since its launch in 2016, ONE-KEY™ has been designed to deliver multiple advantages across all levels of your organisation. Combining a free-to-use inventory program with the industry's smartest tools, ONE-KEY™ provides a new level of control and access to information that will revolutionise the way work gets done. Get started today to streamline your productivity.

DOWNLOAD THE FREE ONE-KEY™ APP VIA THE APP STORE OR GOOGLE PLAY STORE.



CUSTOMISE

- Customise the output of your machine to suit your application
- Utilising customisation increases tool run time and accessory life saving you time and money
- Save and share configurations between tools



TRACK

- Track your ONE-KEY™ tools and TICK™ through the ONE-KEY™ user network
- ONE-KEY™ updates your tool or TICK™'s location any time it comes within 30 m Bluetooth® range of our user network
- If your tool is lost or stolen, remotely lock it by sending a command through the ONE-KEY™ user network



NEW

Geo-Fencing allows you to build a digital boundary around your jobsite, warehouse or storage facility for greater control on the movement of tools and equipment

MANAGE

- Add any tool or asset to the ONE-KEY™ inventory management software giving any size user a complete solution to asset management
- **Places management** gives users the ability to assign inventory to a dedicated jobsite, homebase or vehicle
- **Barcode scanning** enables users to pair a barcode with any tool or asset in there inventory
- Set service reminders to notify you when tool or asset is due for service



M18 FHM

M18 FUEL™ ONE-KEY™ 8 KG SDS-MAX DRILLING AND BREAKING HAMMER

M18 FUEL

- The M18 FHM is the most productive SDS-Max tool Milwaukee® have produced, delivering AC style power with the flexibility of the cordless M18™ platform
- Next generation POWERSTATE™ brushless motor: This is Milwaukee®'s most powerful motor utilising higher grade magnets and 175% more copper vs previous motors
- Next generation REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- New REDLITHIUM-ION™ High Output™ 12.0 Ah battery pack provides superior pack construction, electronics and fade-free performance to deliver the most work per charge than any other Milwaukee® battery pack
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- Trigger lock on prevents users from having to hold trigger during long periods of chipping applications
- Large anti-vibration back handle supports two handed drilling applications whilst minimising vibration exposure



	M18 FHM-0C	M18 FHM-121C
Voltage (V)	18	18
Battery type	Li-ion	Li-ion
Battery pack capacity (Ah)	–	12.0
No. of batteries supplied	0	1
Charger supplied	–	130 min
Tool reception	SDS-Max	SDS-Max
Blow energy (EPTA)(J)	11.0	11.0
Full load hammer action (bpm)	0 - 2900	0 - 2900
No load speed (rpm)	0 - 380	0 - 380
Max. drilling concrete (mm)	45	45
Max. drilling tunnel bit (mm)	65	65
Max. drilling core bit (mm)	150	150
Vibration drilling (m/s²)	9.4	9.4
Vibration chiseling (m/s²)	7.8	7.8
Weight with battery pack (kg)	–	10.2
Supplied in	Kitbox	Kitbox
Article Number	4933464893	4933464894

SDS-MAX DRILL BIT - 4 CUT - Ø28 MM, TOTAL LENGTH 570 MM

Article Number 4932352779



AUTOSTOP™ - maximum control, advanced safety



Trigger lock on



ONE-KEY™ tracking and security

M18 CHM | M18 FUEL™ 5 KG SDS-MAX DRILLING AND BREAKING HAMMER

M18 FUEL

- The world's first 18V 5 kg SDS-Max hammer for maximum versatility and portability with equal performance to an AC tool
- Milwaukee® designed and built brushless POWERSTATE™ motor provides corded drilling performance
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- High demand 9.0 Ah REDLITHIUM-ION™ battery pack delivers up to 5x more run time, up to 35% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies
- Robust magnesium gear housing for tough environments, exact seat fitting of gear components and better cooling
- Roto-stop and multi position chisel function gives 12 different positions to optimise working angle and end-user ergonomics
- Low 10.6 m/s² vibration construction which enhances usage time per day
- Safety clutch protects operator and machine if drill bit jams
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 CHM-0C	M18 CHM-902C
Battery pack capacity (Ah)	–	9.0
No. of batteries supplied	0	2
Charger supplied	–	95 min
Tool reception	SDS-Max	SDS-Max
Blow energy (EPTA)(J)	6.1	6.1
Full load hammer action (bpm)	0 - 3000	0 - 3000
No load speed (rpm)	0 - 450	0 - 450
Max. drilling concrete (mm)	40	40
Max. drilling tunnel bit (mm)	65	65
Max. drilling core bit (mm)	100	100
Vibration drilling (m/s²)	10.6	10.6
Vibration chiseling (m/s²)	9.6	9.6
Weight with battery pack (kg)	–	6.6
Supplied in	Kitbox	Kitbox
Article Number	4933451362	4933451361

M18 CHPX | M18 FUEL™ HIGH PERFORMANCE 4-MODE SDS-PLUS HAMMER WITH FIXTEC CHUCK

M18 FUEL

- Milwaukee® designed and built brushless POWERSTATE™ motor
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- High powered motor gives corded tool performance
- Hardest hitting cordless SDS hammer in its class. Powerful hammer mechanism delivers 4.0 J (EPTA) of impact energy at low 8.6 m/s² vibrations thanks to the new dual rail anti-vibration system
- All metal gear case - optimum seating of the gears for enhanced service life
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility
- FIXTEC system - keyless chuck changing
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Compatible with M18-28 CPDEX dust extractor
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 CHPX-0X	M18 CHPX-502X	M18 CHPX-902X
Battery pack capacity (Ah)	–	5.0	9.0
No. of batteries supplied	0	2	2
Charger supplied	–	59 min	95 min
Tool reception	SDS-Plus	SDS-Plus	SDS-Plus
Blow energy (EPTA)(J)	4.0	4.0	4.0
Max. drilling wood (mm)	30	30	30
Max. drilling steel (mm)	13	13	13
Max. drilling concrete (mm)	28	28	28
Max. percussion rate (bpm)	0 - 5000	0 - 5000	0 - 5000
Vibration drilling (m/s²)	8.6	8.6	8.6
Vibration chiseling (m/s²)	7.1	7.1	7.1
Weight with battery pack (kg)	–	4.3	4.6
Supplied in	HD Box	HD Box	HD Box
Article Number	4933451431	4933451380	4933451469

M18 CHX | M18 FUEL™ 4-MODE SDS-PLUS HAMMER WITH FIXTEC CHUCK

M18 FUEL

- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 2x longer motor life and up to 25% more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Second hardest hitting SDS hammer in its class. Powerful hammer mechanism delivers 2.5 J of impact energy at low 8.9 m/s² vibrations
- Compact, ergonomic design for increased end user comfort
- All metal gear case - optimum seating of the gears for enhanced service life
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility
- FIXTEC system - keyless chuck changing
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Compatible with M18 CDEX dust extractor



	M18 CHX-0X	M18 CHX-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
Tool reception	SDS-Plus	SDS-Plus
Blow energy (EPTA)(J)	2.5	2.5
Max. drilling wood (mm)	30	30
Max. drilling steel (mm)	13	13
Max. drilling concrete (mm)	26	26
Max. percussion rate (bpm)	0 - 4900	0 - 4900
Vibration drilling (m/s²)	8.9	8.9
Vibration chiseling (m/s²)	9.5	9.5
Weight with battery pack (kg)	–	3.5
Supplied in	HD Box	HD Box
Article Number	4933451430	4933451381

HD18 HX | M18™ 4-MODE SDS-PLUS HAMMER WITH FIXTEC CHUCK

- High powered motor gives corded tool performance
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Powerful hammer mechanism: delivers 2.4 J (EPTA) of impact energy
- All metal gear case: optimum seating for gears to enhance service life
- 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility
- Variolock and hammer stop function
- FIXTEC system - keyless chuck changing
- Mechanical clutch: protects tool when bit binds up
- Anti-Vibration-System delivers max. comfort by minimising vibration
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	HD18 HX-0	HD18 HX-402C
Battery pack capacity (Ah)	–	4.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
Tool reception	SDS-Plus	SDS-Plus
Blow energy (EPTA)(J)	2.4	2.4
Max. drilling wood (mm)	30	30
Max. drilling steel (mm)	13	13
Max. drilling concrete (mm)	24	24
Max. percussion rate (bpm)	4200	4200
Vibration drilling (m/s²)	12.2	12.2
Vibration chiseling (m/s²)	7.4	7.4
Weight with battery pack (kg)	–	3.7
Supplied in	–	Kitbox
Article Number	4933408320	4933441280

DE16 VAC ASSIST UNIVERSAL EXTRACTOR, INCLUDES: 1 X SIDE HANDLE AND 3 X NECK COLLARS-ALLOWS FITTING TO DRILLS WITH GEAR NECK FROM Ø 43 - 59 MM. 2 X DRILLING NOZZLES (49902301).

Article Number 4932430835



HD18 H | M18™ 4-MODE SDS-PLUS HAMMER

- High powered motor gives corded tool performance
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Powerful hammer mechanism: delivers 2.4 J (EPTA) of impact energy
- All metal gear case: optimum seating for gears to enhance service life
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility
- Variolock and hammer stop function
- Mechanical clutch: protects tool when bit binds up
- Anti-Vibration-System: delivers max. comfort by minimising vibration
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	HD18 H-402C
Battery pack capacity (Ah)	4.0
No. of batteries supplied	2
Charger supplied	80 min
Tool reception	SDS-Plus
Blow energy (EPTA)(J)	2.4
Max. drilling wood (mm)	30
Max. drilling steel (mm)	13
Max. drilling concrete (mm)	24
Max. percussion rate (bpm)	4200
Vibration drilling (m/s²)	12.2
Vibration chiseling (m/s²)	7.4
Weight with battery pack (kg)	3.5
Supplied in	Kitbox
Article Number	4933443468

DE16 VAC ASSIST UNIVERSAL EXTRACTOR, INCLUDES: 1 X SIDE HANDLE AND 3 X NECK COLLARS-ALLOWS FITTING TO DRILLS WITH GEAR NECK FROM Ø 43 - 59 MM. 2 X DRILLING NOZZLES (49902301).

Article Number 4932430835



M18 BH | M18™ COMPACT 2-MODE SDS-PLUS HAMMER

- Superior power to weight ratio in its class 2.5 kg 1.2 J (EPTA)
- Milwaukee®'s high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- 2-mode operation: choose rotary hammer or rotation only for maximum versatility
- Low vibration value of 10.3 m/s²
- Optimised hammer drilling from 4 to 10 mm, max diameter 16 mm
- Forward & reverse switch for added versatility in fastening applications
- 43 mm neck size - compatible with M12 DE dust extractor
- Fuel gauge displays remaining charge
- Brightest LED workspace illumination
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 BH-0	M18 BH-402C
Battery pack capacity (Ah)	–	4.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
Tool reception	SDS-Plus	SDS-Plus
Blow energy (EPTA)(J)	1.2	1.2
Max. drilling wood (mm)	16	16
Max. drilling steel (mm)	10	10
Max. drilling concrete (mm)	16	16
Max. percussion rate (bpm)	7000	7000
Vibration drilling (m/s²)	10.3	10.3
Weight with battery pack (kg)	–	2.5
Supplied in	–	Kitbox
Article Number	4933443320	4933443330

M18-28 CPDEX | M18-28 FUEL™ SDS-PLUS DUST EXTRACTOR

- Designed to collect dust effectively with automatic operation from the tools on/off trigger switch
- HEPA filter: widely regarded as the ultimate filter that traps all sizes of particles with an efficiency rating of 99.75%
- Large dust collection box
- Dust extraction aluminium tube is adjustable according to the size of the drill bit and length 16 mm max and 90 mm depth
- Compatible with M18 CHPX & M28 CHPX
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18-28 CPDEX-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Max. drill bit diameter (mm)	16
Max. drilling depth (mm)	90
Max. drill bit length (mm)	160
Stroke length (mm)	100
Weight without battery pack (kg)	1.6
Supplied in	–
Article Number	4933446810

M18 FUEL™ HIGH PERFORMANCE SDS-PLUS HAMMER WITH DEDICATED DE

Article Number 4933448180



M18 CDEX | M18 FUEL™ SDS-PLUS DUST EXTRACTOR

- Designed to collect dust effectively with automatic operation from the tools on/off trigger switch
- HEPA Filter: widely regarded as the ultimate filter that traps all sizes of particles with an efficiency rating of 99.75%
- Large dust collection box
- Dust extraction aluminium tube is adjustable according to the size of the drill bit and length 16 mm max and 90 mm depth
- Compatible with M18 CHX
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 CDEX-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Max. drill bit diameter (mm)	16
Max. drilling depth (mm)	90
Max. drill bit length (mm)	160
Stroke length (mm)	100
Weight without battery pack (kg)	1.6
Supplied in	–
Article Number	4933447450

M18 FUEL™ SDS-PLUS HAMMER WITH DEDICATED DE

Article Number 4933448185



M18 ONEPD2

M18 FUEL™ ONE-KEY™ PERCUSSION DRILL

- Higher power efficiency under load - outstanding torque of 135 Nm
- Extreme compact design of 175 mm length for access into tight spaces
- Advanced heavy duty chuck providing increased bit grip
- Connect via Bluetooth® with the Milwaukee® ONE-KEY™ app
- Customise anti-kickback control via ONE-KEY™ app
- ONE-KEY™ tool tracking & security offers a Cloud-based inventory management platform that supports both location tracking and theft prevention
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite
- Configure to any application choosing optimum tool settings for repeatable precision
- Control speed, torque, start and end speeds, anti-kickback functions and LED
- All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all Milwaukee® M18™ batteries

ONE-KEY™
UNLOCKING THE DIGITAL JOBSITE.



Complete tool customisation via ONE-KEY™ app



Customise anti-kickback control via ONE-KEY™ app



Inventory functionality for total fleet management

	M18 ONEPD2-0X	M18 ONEPD2-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed gear 1 (rpm)	0 - 550	0 - 550
No load speed gear 2 (rpm)	0 - 2000	0 - 2000
Chuck capacity (mm)	13	13
Max. drilling wood (mm)	89	89
Max. drilling steel (mm)	16	16
Max. drilling masonry (mm)	16	16
Max. percussion rate (bpm)	0 - 32,000	0 - 32,000
Max. torque (Nm)	135	135
Weight with battery pack (kg)	–	2.2
Supplied in	HD Box	HD Box
Article Number	4933464526	4933464527

M18 FUEL

M18 FPD2

M18 FUEL™ PERCUSSION DRILL

- Higher power efficiency under load - outstanding torque of 135 Nm
- Extreme compact design of 175 mm length for access into tight spaces
- Advanced heavy duty chuck providing increased bit grip
- Milwaukee® designed and built brushless POWERSTATE™ motor for heavy application under load
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Battery fuel gauge displays remaining charge
- 40 percent brighter LED workspace illumination - vs previous model
- All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all Milwaukee® M18™ batteries



Extreme compact design of 175 mm length



Advanced heavy duty chuck providing increased bit grip



40 percent brighter LED workspace illumination - vs previous model

	M18 FPD2-0X	M18 FPD2-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed gear 1 (rpm)	0 - 550	0 - 550
No load speed gear 2 (rpm)	0 - 2000	0 - 2000
Chuck capacity (mm)	13	13
Max. drilling wood (mm)	89	89
Max. drilling steel (mm)	16	16
Max. drilling masonry (mm)	16	16
Max. percussion rate (bpm)	0 - 32,000	0 - 32,000
Max. torque (Nm)	135	135
Weight with battery pack (kg)	–	2.2
Supplied in	HD Box	HD Box
Article Number	4933464263	4933464264

M18 FUEL

M18 ONEDD2 | M18 FUEL™ ONE-KEY™ DRILL DRIVER

- Higher power efficiency under load - outstanding torque of 135 Nm
- Extreme compact design of 175 mm length for access into tight spaces
- Advanced heavy duty chuck providing increased bit grip
- ONE-KEY™ tool customisation allows the user to optimise their tool for a specific application
- Customise anti-kickback control via ONE-KEY™ app
- ONE-KEY™ tool tracking & security offers a Cloud-based inventory management platform that supports both location tracking and theft prevention
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite
- Configure to any application choosing optimum tool settings for repeatable precision
- Control speed, torque, start and end speeds, anti-kickback functions and LED
- All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all Milwaukee® M18™ batteries



ONE-KEY™ **M18 FUEL**

	M18 ONEDD2-0X	M18 ONEDD2-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed gear 1 (rpm)	0 - 550	0 - 550
No load speed gear 2 (rpm)	0 - 2000	0 - 2000
Chuck capacity (mm)	13	13
Max. drilling wood (mm)	89	89
Max. drilling steel (mm)	16	16
Max. torque (Nm)	135	135
Weight with battery pack (kg)	–	2.1
Supplied in	HD Box	HD Box
Article Number	4933464524	4933464525

M18 FDD2 | M18 FUEL™ DRILL DRIVER

- Higher power efficiency under load - outstanding torque of 135 Nm
- Extreme compact design of 175 mm length for access into tight spaces
- Advanced heavy duty chuck providing increased bit grip
- Milwaukee® designed and built brushless POWERSTATE™ motor for heavy application under load
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Battery fuel gauge displays remaining charge
- 40 percent brighter LED workspace illumination - vs previous model
- All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 FDD2-0X	M18 FDD2-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed gear 1 (rpm)	0 - 550	0 - 550
No load speed gear 2 (rpm)	0 - 2000	0 - 2000
Chuck capacity (mm)	13	13
Max. drilling wood (mm)	89	89
Max. drilling steel (mm)	16	16
Max. torque (Nm)	135	135
Weight with battery pack (kg)	–	2.1
Supplied in	HD Box	HD Box
Article Number	4933464266	4933464267

M18 FUEL

M18 BLPD2

M18™ BRUSHLESS PERCUSSION DRILL

- New brushless motor design delivers 40% more torque than previous model - up to 82 Nm
- Compact design (180 mm in length) provides excellent balance and control, ideal for overhead applications or work in tight spaces
- Advanced 13 mm heavy duty metal chuck for quick bit changes and superior bit retention
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Optimised speed for faster drilling & fastening (0 - 550 / 0 - 1800 rpm)
- On board fuel gauge and LED light
- All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all Milwaukee® M18™ batteries



Measuring only 180 mm in length



Advanced 13 mm heavy duty metal chuck



LED light

	M18 BLPD2-0X	M18 BLPD2-402X	M18 BLPD2-502X
Battery pack capacity (Ah)	–	4.0	5.0
No. of batteries supplied	0	2	2
Charger supplied	–	47 min	59 min
No load speed gear 1 (rpm)	0 - 550	0 - 550	0 - 550
No load speed gear 2 (rpm)	0 - 1800	0 - 1800	0 - 1800
Chuck capacity (mm)	13	13	13
Max. drilling wood (mm)	76	76	76
Max. drilling steel (mm)	13	13	13
Max. drilling masonry (mm)	16	16	16
Max. percussion rate (bpm)	0 - 28,800	0 - 28,800	0 - 28,800
Max. torque (Nm)	82	82	82
Weight with battery pack (kg)	–	2.1	2.1
Supplied in	HD Box	HD Box	HD Box
Article Number	4933464516	4933464560	4933464517

M18 BLDD2 | M18™ BRUSHLESS DRILL DRIVER

- New brushless motor design delivers 40% more torque than previous model - up to 82 Nm
- Compact design (180 mm in length) provides excellent balance and control, ideal for overhead applications or work in tight spaces
- Advanced 13 mm heavy duty metal chuck for quick bit changes and superior bit retention
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Optimised speed for faster drilling & fastening (0 - 550 / 0 - 1800 rpm)
- On board fuel gauge and LED light
- All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 BLDD2-0X	M18 BLDD2-402X	M18 BLDD2-502X
Battery pack capacity (Ah)	–	4.0	5.0
No. of batteries supplied	0	2	2
Charger supplied	–	47 min	59 min
No load speed gear 1 (rpm)	0 - 550	0 - 550	0 - 550
No load speed gear 2 (rpm)	0 - 1800	0 - 1800	0 - 1800
Chuck capacity (mm)	13	13	13
Max. drilling wood (mm)	76	76	76
Max. drilling steel (mm)	13	13	13
Max. torque (Nm)	82	82	82
Weight with battery pack (kg)	–	2.0	2.0
Supplied in	HD Box	HD Box	HD Box
Article Number	4933464514	4933464559	4933464515

M18 CBLDD

M18™ COMPACT BRUSHLESS DRILL DRIVER

- Compact brushless drill driver measuring 165 mm in length for access into tight spaces
- Advanced 13 mm heavy duty metal chuck for quick bit changes and superior bit retention
- 60 Nm of torque - best power to size ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- All metal reversible belt clip to hang your tool quickly and easily
- On board fuel gauge and LED light
- Flexible battery system: works with all Milwaukee® M18™ batteries



Measuring 165 mm in length



Advanced 13 mm heavy duty metal chuck



All metal reversible belt clip

	M18 CBLDD-0	M18 CBLDD-202C	M18 CBLDD-402C
Battery pack capacity (Ah)	–	2.0	4.0
No. of batteries supplied	0	2	2
Charger supplied	–	40 min	80 min
No load speed gear 1 (rpm)	0 - 500	0 - 500	0 - 500
No load speed gear 2 (rpm)	0 - 1800	0 - 1800	0 - 1800
Chuck capacity (mm)	13	13	13
Max. drilling wood (mm)	52	52	52
Max. drilling steel (mm)	13	13	13
Max. torque (Nm)	60	60	60
Weight with battery pack (kg)	–	1.5	1.8
Supplied in	–	Kitbox	Kitbox
Article Number	4933464316	4933464317	4933464539

M18 CBLPD | M18™ COMPACT BRUSHLESS PERCUSSION DRILL

- Compact brushless percussion drill measuring 165 mm in length for access into tight spaces
- Advanced 13 mm heavy duty metal chuck for quick bit changes and superior bit retention
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 60 Nm of torque - best power to size ratio
- All metal reversible belt clip to hang your tool quickly and easily
- On board fuel gauge and LED light
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 CBLPD-0	M18 CBLPD-202C	M18 CBLPD-402C
Battery pack capacity (Ah)	–	2.0	4.0
No. of batteries supplied	0	2	2
Charger supplied	–	40 min	80 min
No load speed gear 1 (rpm)	0 - 500	0 - 500	0 - 500
No load speed gear 2 (rpm)	0 - 1800	0 - 1800	0 - 1800
Chuck capacity (mm)	13	13	13
Max. drilling wood (mm)	52	52	52
Max. drilling steel (mm)	13	13	13
Max. drilling masonry (mm)	16	16	16
Max. percussion rate (bpm)	0 - 27,000	0 - 27,000	0 - 27,000
Max. torque (Nm)	60	60	60
Weight with battery pack (kg)	–	1.5	1.8
Supplied in	–	Kitbox	Kitbox
Article Number	4933464319	4933464320	4933464537

HD18 PD | M18™ PERCUSSION DRILL

- With its Milwaukee® 4-pole frameless motor it delivers 85 Nm of torque, ideal for powering through the toughest of applications
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal gear box delivers maximum performance and long life
- Heavy Duty 13 mm full metal chuck delivers optimum bit retention
- Hammer mechanism delivers 28,000 bpm for highly effective masonry drilling
- 24 stage torque adjustment delivers optimum control for the user
- 3 stage mode selector allows the user to switch between rotary, screw drive and percussion modes quickly and easily
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	HD18 PD-0	
Battery pack capacity (Ah)	–	
No. of batteries supplied	0	
Charger supplied	–	
No load speed gear 1 (rpm)	0 - 450	
No load speed gear 2 (rpm)	0 - 1800	
Chuck capacity (mm)	13	
Max. drilling wood (mm)	55	
Max. drilling steel (mm)	13	
Max. drilling masonry (mm)	16	
Max. percussion rate (bpm)	28,000	
Max. torque (Nm)	85	
Weight with battery pack (kg)	2.5	
Supplied in	–	
Article Number	4933446925	

M18 BPD | M18™ COMPACT PERCUSSION DRILL

- Compact percussion drill measuring only 198 mm in length, making it ideal for working in confined spaces
- Milwaukee®'s high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal gear box delivers maximum performance and long life
- 13 mm metal chuck for quick bit changes and bit retention
- 18 stage torque adjustment for maximum flexibility
- 3 stage mode selector allows the user to switch between rotary, screw drive and percussion modes quickly and easily
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 BPD-0	M18 BPD-202C	M18 BPD-402C
Battery pack capacity (Ah)	–	2.0	4.0
No. of batteries supplied	0	2	2
Charger supplied	–	40 min	80 min
No load speed gear 1 (rpm)	0 - 450	0 - 450	0 - 450
No load speed gear 2 (rpm)	0 - 1800	0 - 1800	0 - 1800
Chuck capacity (mm)	13	13	13
Max. drilling wood (mm)	38	38	38
Max. drilling steel (mm)	13	13	13
Max. drilling masonry (mm)	16	16	16
Max. percussion rate (bpm)	0 - 28,800	0 - 28,800	0 - 28,800
Max. torque (Nm)	50	50	60
Weight with battery pack (kg)	–	1.9	2.1
Supplied in	–	Kitbox	Kitbox
Article Number	4933443500	4933443515	4933443520

M18 BDD | M18™ COMPACT DRILL DRIVER

- Compact drill driver measuring only 185 mm in length, making it ideal for working in confined spaces
- Milwaukee®'s high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal gear box delivers maximum performance and long life
- 13 mm metal chuck for quick bit changes and bit retention
- 17 stage torque adjustment plus additional drilling for maximum flexibility
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Brightest LED workspace illumination
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 BDD-0	M18 BDD-202C	M18 BDD-402C
Battery pack capacity (Ah)	–	2.0	4.0
No. of batteries supplied	0	2	2
Charger supplied	–	40 min	80 min
No load speed gear 1 (rpm)	0 - 450	0 - 450	0 - 450
No load speed gear 2 (rpm)	0 - 1800	0 - 1800	0 - 1800
Chuck capacity (mm)	13	13	13
Max. drilling wood (mm)	38	38	38
Max. drilling steel (mm)	13	13	13
Max. torque (Nm)	50	50	60
Weight with battery pack (kg)	–	1.8	2.0
Supplied in	–	Kitbox	Kitbox
Article Number	4933443530	4933443555	4933443565

M18 FRAD | M18 FUEL™ SUPER HAWG® 2-SPEED RIGHT ANGLE DRILL DRIVER



- POWERSTATE™ brushless motor provides constant power under load to power through 152 mm holes
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Extreme long runtime up to 75 holes with a 65 mm auger bit into wood
- Mechanical clutch protects the tool in the event of a stall
- All metal gear case and 13 mm keyed chuck for high durability
- On board fuel gauge and LED light
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 FRAD-0	
Battery pack capacity (Ah)	–	
No. of batteries supplied	0	
Charger supplied	–	
No load speed gear 1 (rpm)	0 - 350	
No load speed gear 2 (rpm)	0 - 950	
Chuck capacity (mm)	13	
Max. drilling wood with auger bit (mm)	40	
Max. drilling wood with selffeed bit (mm)	117	
Max. drilling wood with holesaw (mm)	152	
Max. drilling steel (mm)	13	
Weight with battery pack (kg)	6.4	
Supplied in	–	
Article Number	4933451289	

BIG HAWG™ MULTI MATERIAL SET (10 PC)

Article Number 4932464939



M18 FRADH | M18 FUEL™ SUPER HAWG® 2-SPEED RIGHT ANGLE DRILL DRIVER WITH QUIK-LOK™



- POWERSTATE™ brushless motor provides constant power under load to power through 152 mm holes
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Extreme long runtime up to 75 holes with a 65 mm auger bit into wood
- Mechanical clutch protects the tool in the event of a stall
- All metal gear case and 7/16" QUIK-LOK™ chuck for high durability
- On board fuel gauge and LED light
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 FRADH-0	
Battery pack capacity (Ah)	–	
No. of batteries supplied	0	
Charger supplied	–	
No load speed gear 1 (rpm)	0 - 350	
No load speed gear 2 (rpm)	0 - 950	
Tool reception	7/16" Hex	
Max. drilling wood with auger bit (mm)	40	
Max. drilling wood with selffeed bit (mm)	117	
Max. drilling wood with holesaw (mm)	152	
Max. drilling steel (mm)	13	
Weight with battery pack (kg)	6.2	
Supplied in	–	
Article Number	4933451290	

SWITCHBLADE™ SELFEEED BITS SET (5PC): Ø 35 / 38 / 54 / 65 MM, QUIK-LOK EXTENSION 140 MM LENGTH

Article Number 49225100



M18 CRAD | M18 FUEL™ RIGHT ANGLE DRILL



- Delivers corded power and speed (1200 rpm) in wood drilling applications
- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 10x longer motor life and up to 25% more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- All metal gear case and 13 mm keyed chuck
- Extreme long runtime up to 150 holes with a 22 mm auger bit into 50 x 100 mm wood
- Up to 10% lighter and smaller than leading AC competitive tools
- On board fuel gauge and LED light
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 CRAD-0	
Battery pack capacity (Ah)	–	
No. of batteries supplied	0	
Charger supplied	–	
No load speed (rpm)	0 - 1200	
Chuck capacity (mm)	13	
Max. drilling wood with auger bit (mm)	26	
Max. drilling wood with selffeed bit (mm)	51	
Max. drilling wood with holesaw (mm)	102	
Max. drilling steel (mm)	8	
Weight with battery pack (kg)	4.1	
Supplied in	–	
Article Number	4933447730	

C18 RAD | M18™ COMPACT RIGHT ANGLE DRILL

- Optimised performance: 1500 rpm at 20 Nm
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Perfect speed to power ratio for fast application completion
- 10 mm single sleeve ratcheting chuck provides maximum versatility and grip
- 100 mm compact head designed to fit in the tightest work areas
- Multi-position handle design allows for multiple hand positions and maximum comfort
- 10 + 1 electronic clutch enables complete control while fastening
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Built in LED light illuminates the work surface
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	C18 RAD-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	0 - 1500
Chuck capacity (mm)	10
Max. torque (Nm)	20
Max. drilling wood (mm)	28
Max. drilling steel (mm)	10
Weight with battery pack (kg)	1.9
Supplied in	–
Article Number	4933427189

M18 FID2 | M18 FUEL™ 1/4" HEX IMPACT DRIVER

- Higher power efficiency under load - outstanding torque of 226 Nm
- Faster driving speed vs. previous model - up to 3600 rpm and 4300 ipm
- Extreme compact design - total length of just 117 mm for access into tight spaces
- The Milwaukee® DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility
- Mode 1 for precision work
- Mode 2 helps prevent damage to fasteners and material
- Mode 3 delivers maximum performance for the toughest applications
- Mode 4 is the optimum between precision work and maximum performance and automatically adjusts speed, impacts and torque
- Milwaukee® designed and built brushless POWERSTATE™ motor for heavy application under load
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 1/4" Hex chuck for quick and easy bit change



	M18 FID2-0X	M18 FID2-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	1900/2800/3600/0-3600	1900/2800/3600/0-3600
Impact rate (ipm)	1200/3400/4300/0-4300	1200/3400/4300/0-4300
Max. fastening torque (Nm)	226	226
Max. torque (Nm)	119/176/226/0-226	119/176/226/0-226
Tool reception	1/4" Hex	1/4" Hex
Weight with battery pack (kg)	–	1.7
Supplied in	HD Box	HD Box
Article Number	4933464087	4933464088

M18 ONEID2

M18 FUEL™ ONE-KEY™ 1/4" HEX IMPACT DRIVER

- Higher power efficiency under load - outstanding torque of 226 Nm
- Faster driving speed vs. previous model - up to 3600 rpm and 4300 ipm
- Extreme compact design - total length of just 117 mm for access into tight spaces
- Connect via Bluetooth® with the Milwaukee® ONE-KEY™ app
- ONE-KEY™ app provides inventory function for total management of your complete tool/equipment fleet
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite
- Configure to any application choosing optimum tool settings for repeatable precision
- Control speed, torque, start and end speeds and LED
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 ONEID2-0X	M18 ONEID2-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	1900/2800/3600/0-3600	1900/2800/3600/0-3600
Impact rate (ipm)	1200/ 3400/4300/0-4300	1200/ 3400/4300/0-4300
Max. fastening torque (Nm)	226	226
Max. torque (Nm)	119/176/226/0-226	119/176/226/0-226
Tool reception	1/4" Hex	1/4" Hex
Weight with battery pack (kg)	–	1.7
Supplied in	HD Box	HD Box
Article Number	4933464090	4933464091



M18 FUEL



Complete tool customisation via ONE-KEY™ app



Save profiles for application specific repeatable precision



Inventory functionality for total fleet management

M18 FQID

M18 FUEL™ SURGE™ 1/4" HEX HYDRAULIC IMPACT DRIVER

- The M18 FUEL™ SURGE™ 1/4" Hex hydraulic driver is Milwaukee's® quietest impact driver
- FLUID-DRIVE™ hydraulic powertrain reduces metal on metal contact within the tool, delivering quieter operation, smoother performance and increased durability over a standard impact
- Delivers same performance in wood fastening as standard brushless impact drivers
- POWERSTATE™ brushless motor delivers up to 0 - 3.000 RPM with constant power output to drive screws faster
- REDLINK PLUS™ intelligence system delivers the most advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- The Milwaukee® DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility
- Self-tapping screw mode is designed to reduce walking when starting self-tapping screws as well as reduce overdriving, breaking and stripping out screws
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 1/4" Hex chuck for quick and easy bit change
- On board fuel gauge and LED light



	M18 FQID-0X	M18 FQID-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	900/2100/3000/3000	900/2100/3000/3000
Impact rate (ipm)	1800/2900/4000/4000	1800/2900/4000/4000
Max. torque (Nm)	50	50
Tool reception	1/4" Hex	1/4" Hex
Max. bolt diameter	M14	M14
Weight with battery pack (kg)	–	1.7
Supplied in	HD Box	HD Box
Article Number	4933459187	4933451790

M18 FUEL



FLUID-DRIVE™ hydraulic powertrain reduces metal on metal contact within the tool, delivering quieter operation, smoother performance



4 mode DRIVE CONTROL™



1/4" Hex chuck for quick and easy bit change

M18 BLID2 | M18™ BRUSHLESS 1/4" HEX IMPACT DRIVER

- Brushless impact driver measures only 130 mm in length making it ideal for working within confined spaces
- Brushless motor technology delivers 180 Nm of torque, 3400 rpm and 4200 ipm
- The Milwaukee® DRIVE CONTROL™ allows the user to shift into three different speed and torque settings to maximise application versatility
- One-handed bit insert with retention lock, for faster, easier changing of bits
- Heavy duty full metal gearbox and gears for superior durability and maximum torque
- On board fuel gauge and LED light
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 BLID2-0X	M18 BLID2-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	1700/2600/0-3400	1700/2600/0-3400
Impact rate (ipm)	1500/3400/0-4200	1500/3400/0-4200
Max. torque (Nm)	180	180
Tool reception	1/4" Hex	1/4" Hex
Weight with battery pack (kg)	–	1.7
Supplied in	HD Box	HD Box
Article Number	4933464519	4933464520

MAGNETIC BIT HOLDER 152 MM - LONG SERIES WITH 1/4" HEX RECEPTION

Article Number 48324511


M18 CBLID | M18™ COMPACT BRUSHLESS 1/4" HEX IMPACT DRIVER

- Compact impact driver measures only 130 mm in length making it ideal for working within confined spaces
- Brushless motor technology delivers 180 Nm of torque, 3400 rpm and 4200 ipm
- Heavy duty full metal gearbox and gears for superior durability and maximum torque
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- On board fuel gauge and LED light
- All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 CBLID-0	M18 CBLID-402C
Battery pack capacity (Ah)	–	4.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
No load speed (rpm)	0 - 3400	0 - 3400
Impact rate (ipm)	0 - 4200	0 - 4200
Max. torque (Nm)	180	180
Tool reception	1/4" Hex	1/4" Hex
Weight with battery pack (kg)	–	1.7
Supplied in	–	Kitbox
Article Number	4933464476	4933464534

SHOCKWAVE IMPACT DUTY™ BIT SET (24 PC)

Article Number 4932464169


M18 BID | M18™ COMPACT 1/4" HEX IMPACT DRIVER

- Compact impact driver measures 140 mm in length making it ideal for working within confined spaces
- Milwaukee® high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Heavy duty full metal gearbox and gears for superior durability and maximum torque
- 1/4" Hex drive with click lock for single hand loading of bit
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 BID-0	M18 BID-202C	M18 BID-402C
Battery pack capacity (Ah)	–	2.0	4.0
No. of batteries supplied	0	2	2
Charger supplied	–	40 min	80 min
No load speed (rpm)	0 - 2000/0 - 2750	0 - 2000/0 - 2750	0 - 2000/0 - 2750
Impact rate (ipm)	0 - 2450/0 - 3450	0 - 2450/0 - 3450	0 - 2450/0 - 3450
Tool reception	1/4" Hex	1/4" Hex	1/4" Hex
Max. torque (Nm)	180	180	180
Weight with battery pack (kg)	–	1.4	1.7
Supplied in	–	Kitbox	Kitbox
Article Number	4933443570	4933443585	4933443580

SHOCKWAVE IMPACT DUTY™ BIT SET (32 PC)

Article Number 4932464240


M18 BRAID | M18™ RIGHT ANGLE IMPACT DRIVER

- Compact right angle impact driver measures 307 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal gearbox and gears for superior durability and maximum torque
- Compact 53 mm head design
- Multi-handle design for multiple hand positions and maximum comfort
- 1/4" Hex chuck for quick easy one handed bit change
- 2 speed settings for wider range of applications
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 BRAID-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	0 - 1500 / 0 - 2250
Impact rate (ipm)	0 - 2400 / 0 - 3400
Tool reception	1/4" Hex
Max. torque (Nm)	41 / 81
Weight with battery pack (kg)	1.8
Supplied in	–
Article Number	4933447891

M18 FSGC | M18 FUEL™ SCREW GUN WITH A COLLATED ATTACHMENT

- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 10x longer motor life and up to 60% more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- AUTO-START™ technology: When activated the power only engages when the screw gun is pushed into the material during application, delivering unmatched run time
- Quick release 1/4" Hex chuck allows for easy bit change
- Fine adjustment nose cone for setting desired countersink levels in single screw applications
- Removable collated attachment allows the user to use the gun as a stand alone screwdriver or a collaged screw gun
- Intuitive design of collated attachment to allow for easy cleaning of drywall dust
- Reinforced collated attachment to protect against dropping of tool
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability



	M18 FSGC-202X
Battery pack capacity (Ah)	2.0
No. of batteries supplied	2
Charger supplied	26 min
No load speed (rpm)	0 - 4500
Wood screws to (mm)	6
Max. static stalling torque (Nm)	13
Tool reception	1/4" Hex
Weight with battery pack (kg)	2.0
Supplied in	HD Box
Article Number	4933459199

M18 FSG | M18 FUEL™ SCREW GUN

- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 10x longer motor life and up to 60% more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- AUTO-START™ technology: When activated the power only engages when the screw gun is pushed into the material during application, delivering unmatched run time
- Quick release 1/4" Hex chuck allows for easy bit change
- Fine adjustment nose cone for setting desired countersink levels in single screw applications
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Brightest LED workspace illumination
- All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 FSG-0X
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	0 - 4500
Wood screws to (mm)	6
Max. static stalling torque (Nm)	13
Tool reception	1/4" Hex
Weight with battery pack (kg)	1.6
Supplied in	HD Box
Article Number	4933459201

M18 ONEFHIWF34

M18 FUEL™ ONE-KEY™ 3/4" HIGH TORQUE IMPACT WRENCH WITH FRICTION RING

- The M18 FUEL™ high torque impact wrench with ONE-KEY™ technology delivers 1627 Nm of fastening torque in a compact size of 213 mm, which gives more access in tight spaces
- The 4 -Mode DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility
- Mode 4 bolt removal, provides a maximum nut-busting torque of 2034 Nm then shifts to 750 rpm for unmatched control when removing fasteners
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting
- ONE-KEY™ tool customisation allows the user to optimise their tool for specific applications
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- 3/4" friction ring reception
- Flexible battery system: works with all Milwaukee® M18™ batteries

	M18 ONEFHIWF34-0X	M18 ONEFHIWF34-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	0-800/0-1300/0-1800/0-1800	0-800/0-1300/0-1800/0-1800
Impact rate (ipm)	0-850/0-1850/0-2400/0-2400	0-850/0-1850/0-2400/0-2400
Tool reception	3/4" square	3/4" square
Max. fastening torque (Nm)	1627	1627
Nut-busting torque (Nm)	2034	2034
Weight with battery pack (kg)	–	3.5
Supplied in	HD Box	HD Box
Article Number	4933459729	4933459730



Complete tool customisation via ONE-KEY™ app



Save profiles for application specific repeatable precision



Inventory functionality for total fleet management

M18 FUEL

M18 ONEFHIWF12 | M18 FUEL™ ONE-KEY™ 1/2" HIGH TORQUE IMPACT WRENCH WITH FRICTION RING

- The M18 FUEL™ high torque impact wrench with ONE-KEY™ technology delivers 1356 Nm of fastening torque in a compact size of 213 mm, which gives more access in tight spaces
- The 4 -Mode DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility
- Mode 4 bolt removal, provides a maximum nut-busting torque of 1898 Nm then shifts to 750 rpm for unmatched control when removing fasteners
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting
- ONE-KEY™ tool customisation allows the user to optimise their tool for specific applications
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- 1/2" friction ring reception

10 PC SHOCKWAVE IMPACT DUTY™ 1/2" SOCKET SET

Article Number 4932352861



	M18 ONEFHIWF12-0X	M18 ONEFHIWF12-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	0-550/0-1400/0-1750/0-1750	0-550/0-1400/0-1750/0-1750
Impact rate (ipm)	0-950/0-1750/0-2100/0-2100	0-950/0-1750/0-2100/0-2100
Tool reception	1/2" square	1/2" square
Max. fastening torque (Nm)	130/400/1356/1356	130/400/1356/1356
Nut-busting torque (Nm)	1898	1898
Weight with battery pack (kg)	–	3.3
Supplied in	HD Box	HD Box
Article Number	4933459726	4933459727

M18 ONEFHIWP12 | M18 FUEL™ ONE-KEY™ 1/2" HIGH TORQUE IMPACT WRENCH WITH PIN DETENT

- The M18 FUEL™ high torque impact wrench with ONE-KEY™ technology delivers 1017 Nm of fastening torque in a compact size of 206 mm, which gives more access in tight spaces
- The 4 -Mode DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility
- Mode 4 bolt removal, provides a maximum nut-busting torque of 1491 Nm then shifts to 750 rpm for unmatched control when removing fasteners
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting
- ONE-KEY™ tool customisation allows the user to optimise their tool for specific applications
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- 1/2" pin detent for maximum socket retention

10 PC SHOCKWAVE IMPACT DUTY™ 1/2" SOCKET SET

Article Number 4932352861



	M18 ONEFHIWP12-0X	M18 ONEFHIWP12-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	0-950/0-1500/0-1800/0-1800	0-950/0-1500/0-1800/0-1800
Impact rate (ipm)	0-1150/0-2100/0-2400/0-2400	0-1150/0-2100/0-2400/0-2400
Tool reception	1/2" square	1/2" square
Max. fastening torque (Nm)	190/400/1017/1017	190/400/1017/1017
Nut-busting torque (Nm)	1491	1491
Weight with battery pack (kg)	–	3.2
Supplied in	HD Box	HD Box
Article Number	4933459724	4933459725

M18 FHIWF12 | M18 FUEL™ 1/2" HIGH TORQUE IMPACT WRENCH WITH FRICTION RING

- The M18 FUEL™ high torque impact wrench delivers 1356 Nm fastening torque in a compact size of 213 mm, which gives more access in tight spaces
- 4-Mode DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility
- Mode 4 bolt removal, provides maximum nut-busting of 1898 Nm then shifts to 750 rpm for unmatched control when removing fasteners
- 1/2" friction ring reception
- New LED light is 40 percent brighter than previous model
- The Milwaukee® POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics, and fade-free performance to deliver more run time and more work over pack life
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 FHIWF12-0X	M18 FHIWF12-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	0-550/0-1400/0-1750/0-1750	0-550/0-1400/0-1750/0-1750
Impact rate (ipm)	0-950/0-1750/0-2100/0-2100	0-950/0-1750/0-2100/0-2100
Tool reception	1/2" square	1/2" square
Max. fastening torque (Nm)	130/400/1356/1356	130/400/1356/1356
Nut-busting torque (Nm)	1898	1898
Weight with battery pack (kg)	–	3.3
Supplied in	HD Box	HD Box
Article Number	4933459695	4933459696

M18 FHIWP12 | M18 FUEL™ 1/2" HIGH TORQUE IMPACT WRENCH WITH PIN DETENT

- The M18 FUEL™ high torque impact wrench delivers 1017 Nm fastening torque in a compact size of 206 mm, which gives more access in tight spaces
- 4-Mode DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility
- Mode 4 bolt removal, provides maximum nut-busting of 1491 Nm then shifts to 750 rpm for unmatched control when removing fasteners
- 1/2" pin detent for maximum socket retention
- New LED light is 40 percent brighter than previous model
- The Milwaukee® POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics, and fade-free performance to deliver more run time and more work over pack life
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 FHIWP12-0X	M18 FHIWP12-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	0-950/0-1500/0-1800/0-1800	0-950/0-1500/0-1800/0-1800
Impact rate (ipm)	0-1150/0-2100/0-2400/0-2400	0-1150/0-2100/0-2400/0-2400
Tool reception	1/2" square	1/2" square
Max. fastening torque (Nm)	190/400/1017/1017	190/400/1017/1017
Nut-busting torque (Nm)	1491	1491
Weight with battery pack (kg)	–	3.2
Supplied in	HD Box	HD Box
Article Number	4933459692	4933459693

HD18 HIWF | M18™ IMPACT WRENCH WITH FRICTION RING

- Engineered for heavy use, the M18™ impact wrench with friction ring delivers maximum cordless power on the jobsite
- With its Milwaukee® 4-pole frameless motor it delivers a staggering 610 Nm of torque, ideal for powering through the toughest of applications
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- 1/2" square friction ring
- Ideal for heavy applications such as steel fabrication, mechanical fastening, industrial construction and automotive work
- Light weight and ergonomically designed
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life



	HD18 HIWF-0	HD18 HIWF-402C
Battery pack capacity (Ah)	–	4.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
No load speed (rpm)	0 - 1900	0 - 1900
Tool reception	1/2" square	1/2" square
Impact rate (ipm)	0 - 2200	0 - 2200
Max. torque (Nm)	610	610
Weight with battery pack (kg)	–	3.0
Supplied in	–	Kitbox
Article Number	4933441794	4933441789

10 PC SHOCKWAVE IMPACT DUTY™ 1/2" SOCKET SET

Article Number 4932352861


M18 FMTIWF12 | M18 FUEL™ 1/2" MID TORQUE IMPACT WRENCH WITH FRICTION RING

- The M18 FUEL™ mid torque impact wrench delivers 610 Nm in a compact size of only 170 mm
- The Milwaukee® DRIVE CONTROL™ allows the user to shift into three different speed and torque settings to maximise application versatility
- Milwaukee® designed and built brushless POWERSTATE™ motor for longer motor life and more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 1/2" square friction ring
- On board fuel gauge and LED light
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 FMTIWF12-0X	M18 FMTIWF12-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	510/2100/2400	510/2100/2400
Impact rate (ipm)	420/2700/3000	420/2700/3000
Tool reception	1/2" square	1/2" square
Max. torque (Nm)	130/550/610	130/550/610
Weight with battery pack (kg)	–	2.4
Supplied in	HD Box	HD Box
Article Number	4933459189	4933459185

HD18 HIW | M18™ IMPACT WRENCH WITH PIN DETENT

- Engineered for heavy use, the M18™ impact wrench delivers maximum cordless power on the jobsite
- With its Milwaukee® 4-pole frameless motor it delivers a staggering 610 Nm of torque, ideal for powering through the toughest of applications
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- 1/2" square drive with detent pin for secure socket retention
- Ideal for heavy applications such as steel fabrication, mechanical fastening, industrial construction and automotive work
- Light weight and ergonomically designed
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life



	HD18 HIW-0	HD18 HIW-402C
Battery pack capacity (Ah)	–	4.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
No load speed (rpm)	0 - 1900	0 - 1900
Tool reception	1/2" square	1/2" square
Impact rate (ipm)	0 - 2200	0 - 2200
Max. torque (Nm)	610	610
Weight with battery pack (kg)	–	3.0
Supplied in	–	Kitbox
Article Number	4933416195	4933441260

10 PC SHOCKWAVE IMPACT DUTY™ 1/2" SOCKET SET

Article Number 4932352861


M18 FMTIWP12 | M18 FUEL™ 1/2" MID TORQUE IMPACT WRENCH WITH PIN DETENT

- The M18 FUEL™ mid torque impact wrench delivers 610 Nm in a compact size of only 170 mm
- The Milwaukee® DRIVE CONTROL™ allows the user to shift into three different speed and torque settings to maximise application versatility
- Milwaukee® designed and built brushless POWERSTATE™ motor for longer motor life and more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 1/2" square detent pin
- On board fuel gauge and LED light
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 FMTIWP12-0X	M18 FMTIWP12-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	1700/2100/2400	1700/2100/2400
Impact rate (ipm)	2300/2700/3000	2300/2700/3000
Tool reception	1/2" square	1/2" square
Max. torque (Nm)	430/550/610	430/550/610
Weight with battery pack (kg)	–	2.4
Supplied in	HD Box	HD Box
Article Number	4933459188	4933459183

M18 ONEIWF12 | M18 FUEL™ ONE-KEY™ 1/2" IMPACT WRENCH WITH FRICTION RING

- M18 FIWF12 but with ONE-KEY™ technology
- Connect via Bluetooth® with the Milwaukee® ONE-KEY™ app
- Complete tool customisation via ONE-KEY™ app to tune the tool to your needs
- Control speed, torque, start and end speeds and LED
- Configure to any application choosing optimum tool settings for repeatable precision
- Program/save profiles for unmatched control
- Select from a range of application profiles or quickly create your own for perfect results on every trigger pull
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite
- ONE-KEY™ app also provides inventory function for total management of your complete tool/equipment fleet
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 ONEIWF12-0X	M18 ONEIWF12-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	900/1400/1900/2500	900/1400/1900/2500
Impact rate (ipm)	1300/2100/2550/3200	1300/2100/2550/3200
Tool reception	1/2" square	1/2" square
Max. fastening torque (Nm)	300	300
Max. torque (Nm)	40/120/220/300	40/120/220/300
Weight with battery pack (kg)	–	1.8
Supplied in	HD Box	HD Box
Article Number	4933459198	4933451374

10 PC SHOCKWAVE IMPACT DUTY™ 1/2" SOCKET SET

Article Number 4932352861



M18 ONEIWP12 | M18 FUEL™ ONE-KEY™ 1/2" IMPACT WRENCH WITH PIN DETENT

- M18 FIWP12 but with ONE-KEY™ technology
- Connect via Bluetooth® with the Milwaukee® ONE-KEY™ app
- Complete tool customisation via ONE-KEY™ app to tune the tool to your needs
- Control speed, torque, start and end speeds and LED
- Configure to any application choosing optimum tool settings for repeatable precision
- Program/save profiles for unmatched control
- Select from a range of application profiles or quickly create your own for perfect results on every trigger pull
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite
- ONE-KEY™ app also provides inventory function for total management of your complete tool/equipment fleet



	M18 ONEIWP12-0X	M18 ONEIWP12-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	900/1400/1900/2500	900/1400/1900/2500
Impact rate (ipm)	1300/2100/2550/3200	1300/2100/2550/3200
Tool reception	1/2" square	1/2" square
Max. fastening torque (Nm)	300	300
Max. torque (Nm)	40/120/220/300	40/120/220/300
Weight with battery pack (kg)	–	1.8
Supplied in	HD Box	HD Box
Article Number	4933459197	4933451372

10 PC SHOCKWAVE IMPACT DUTY™ 1/2" SOCKET SET

Article Number **4932352861**



M18 FIWF12 | M18 FUEL™ 1/2" IMPACT WRENCH WITH FRICTION RING

- Milwaukee® designed and built brushless POWERSTATE™ motor for longer motor life and up to 20% more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- The Milwaukee® DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility
- Mode 1 for precision work
- Mode 2 helps prevent damage to fasteners and material
- Mode 3 delivers maximum performance for the toughest applications
- Mode 4 intelligently detects when the tool has impacted on a fastener for one second automatically shutting the tool down, reducing overdriving and damaging materials
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- All metal reversible belt clip – quickly and easily hang tool



	M18 FIWF12-0X	M18 FIWF12-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	1700/2000/2500/2000	1700/2000/2500/2000
Impact rate (ipm)	2400/2600/3100/2600	2400/2600/3100/2600
Tool reception	1/2" square	1/2" square
Max. fastening torque (Nm)	300	300
Max. torque (Nm)	40/120/300/120	40/120/300/120
Weight with battery pack (kg)	–	1.8
Supplied in	HD Box	HD Box
Article Number	4933451448	4933451071

M18 FIWP12 | M18 FUEL™ 1/2" IMPACT WRENCH WITH PIN DETENT

- Milwaukee® designed and built brushless POWERSTATE™ motor for longer motor life and up to 20% more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- The Milwaukee® DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility
- Mode 1 for precision work
- Mode 2 helps prevent damage to fasteners and material
- Mode 3 delivers maximum performance for the toughest applications
- Mode 4 intelligently detects when the tool has impacted on a fastener for one second automatically shutting the tool down, reducing overdriving and damaging materials
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- All metal reversible belt clip – quickly and easily hang tool



	M18 FIWP12-0X	M18 FIWP12-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	1700/2000/2500/2000	1700/2000/2500/2000
Impact rate (ipm)	2400/2600/3100/2600	2400/2600/3100/2600
Tool reception	1/2" square	1/2" square
Max. fastening torque (Nm)	300	300
Max. torque (Nm)	40/120/300/120	40/120/300/120
Weight with battery pack (kg)	–	1.8
Supplied in	HD Box	HD Box
Article Number	4933451449	4933451068

M18 BIW12 | M18™ 1/2" IMPACT WRENCH

- Compact 1/2" impact wrench measures 155 mm in length making it ideal for working within confined spaces
- Milwaukee® high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Heavy duty full metal gearbox and gears for superior durability and maximum torque
- 1/2" square drive for use with universal sockets
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 BIW12-0	M18 BIW12-402C
Battery pack capacity (Ah)	–	4.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
No load speed (rpm)	0 - 2450	0 - 2450
Tool reception	1/2" square	1/2" square
Impact rate (ipm)	0 - 3350	0 - 3350
Max. torque (Nm)	240	240
Weight with battery pack (kg)	–	1.9
Supplied in	–	Kitbox
Article Number	4933443590	4933443607

10 PC SHOCKWAVE IMPACT DUTY™ 1/2" SOCKET SET

Article Number **4932352861**



M18 BIW38 | M18™ 3/8" IMPACT WRENCH

- Compact 3/8" impact wrench measures 152 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Heavy duty full metal gearbox and gears for superior durability and maximum torque
- 3/8" square drive for use with universal sockets
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 BIW38-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	0 - 2450
Tool reception	3/8" square
Impact rate (ipm)	0 - 3350
Max. torque (Nm)	210
Weight with battery pack (kg)	1.9
Supplied in	–
Article Number	4933443600

M18 BRAIW | M18™ 3/8" RIGHT ANGLE IMPACT WRENCH

- Compact right angle impact wrench measures 307 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal gearbox and gears for superior durability and maximum torque
- Compact 53 mm head design
- Multi-handle design for multiple hand positions and maximum comfort
- 3/8" square drive for use with universal sockets
- 2 speed settings for wider range of applications
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 BRAIW-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	0 - 1500 / 0 - 2250
Tool reception	3/8" square
Impact rate (ipm)	0 - 2400 / 0 - 3400
Max. torque (Nm)	40 / 76
Weight with battery pack (kg)	1.8
Supplied in	–
Article Number	4933447899

M18 FPM | M18 FUEL™ PADDLE MIXER

- Thanks to the POWERSTATE™ brushless motor it has the power to mix heavy compounds, such as concrete and mortar
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Ultimate speed control: 3 different ways of controlling speed for clean and consistent mixes (8-speed setting dial, variable speed trigger and a lock on button)
- 180° adjustable handle with 16 adjustable settings for user to optimise the handle position based on preference and comfort
- M14 tool reception
- On board fuel gauge and LED light
- Flexible battery system: works with all Milwaukee® M18™ batteries
- Kitted with 150 mm paddle extension (M14)


M18 FUEL

M18 FPM-0X	
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	0 - 550
Tool reception	M14
Max. stirrer paddle diameter (mm)	120
Max. recommended mixing capacities (l)	20
Weight with battery pack (kg)	3.0
Supplied in	HD Box
Article Number	4933459719

M18 FMDP | M18 FUEL™ MAGNETIC DRILLING PRESS WITH PERMANENT MAGNET

- Milwaukee® designed and built brushless POWERSTATE™ motor provides corded drilling performance with strongest magnet holding force on 1/4" steel and 40 x 18 mm holes per battery charge
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- AUTOSTOP™ lift-off detection: Detects excess rotation and automatically cuts power to the drill for best user protection
- Self-powered permanent magnet with 8,890 N of holding force prevents accidental magnet deactivation for improved user protection and easy alignment
- 2 speed gear box for optimised drilling speed with 400 and 690 RPM's when using annual cutters or twist drill bits
- Maximum drilling capacity of 38 mm with use of annual cutters and 13 mm straight shank twist drill bits
- Keyless 19 mm Weldon reception for fast and easy accessory change
- On board magnet lubrication tank for fixing on the machine or on the material, especially when drilling in vertical positions


AUTO STOP
M18 FUEL

	M18 FMDP-0C	M18 FMDP-502C
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	400 / 690	400 / 690
Max. diameter broaching capacity (mm)	38	38
Max. depth broaching capacity (mm)	50	50
Max. drilling solid bit (mm)	13	13
Magn. holding power (at drill point pressure) (N)	8890	8890
Stroke length (mm)	146	146
Weight with battery pack (kg)	–	13.0
Supplied in	Kitbox	Kitbox
Article Number	4933451636	4933451012

M18 CAG125XPDB | M18 FUEL™ 125 MM BRAKING GRINDER WITH PADDLE SWITCH

- Milwaukee® designed and built brushless POWERSTATE™ motor with the power to grind and up to 10x more tool life
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- RAPIDSTOP™ for fastest disc brake in less than 2 seconds and best user protection
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- Premium gearing system - same system as used at high performance corded grinders
- Slim handle design with paddle switch
- Removable dust screen to prevent debris entrance, prolonging motor life
- 125 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner
- FIXTEC nut for tool-free disc change
- Anti-vibration side handle for lower vibration


RAPID STOP
M18 FUEL

	M18 CAG125X-PDB-0X	M18 CAG125X-PDB-502X	M18 CAG125X-PDB-902X
Battery pack capacity (Ah)	–	5.0	9.0
No. of batteries supplied	0	2	2
Charger supplied	–	59 min	95 min
No load speed (rpm)	8500	8500	8500
Disc diameter (mm)	125	125	125
Max. cutting depth (mm)	33	33	33
Spindle size	M 14	M 14	M 14
Weight with battery pack (kg)	–	2.7	3.0
Switch type	Paddle switch	Paddle switch	Paddle switch
Braking time (s)	< 2	< 2	< 2
FIXTEC flange nut	Yes	Yes	Yes
Line lock out function	Yes	Yes	Yes
Supplied in	HD Box	HD Box	HD Box
Article Number	4933451427	4933451544	4933451471

M18 FLAG230XPDB
M18 FUEL™ 230 MM LARGE BRAKING GRINDER WITH PADDLE SWITCH

- The world's first single 18V battery operated large angle grinder that delivers the power to grind, lighter than corded tools and makes up to 68 cuts per charge in 42 mm stainless steel pipe
- Next generation POWERSTATE™ brushless motor: This is Milwaukee's most powerful motor utilising higher grade magnets and 175% more copper vs previous motors
- Next generation REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- New REDLITHIUM-ION™ High Output™ 12.0 Ah battery pack provides superior pack construction, electronics and fade-free performance to deliver the most work per charge than any other Milwaukee® battery pack
- Disc brake slows the disc down faster for improved user protection
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- Keyless guard for great cutting capacity and fast guard adjustment without using a key
- FIXTEC nut for tool-free disc change
- Anti-vibration side handle for lower vibration
- Removable dust screen to prevent debris entrance, prolonging motor life


RED LITHIUM-ION™
HO
HIGH OUTPUT
BATTERY TECHNOLOGY


FIXTEC nut for tool-free disc change



Removable dust screen to prevent debris entrance



Non-lockable safety paddle switch

	M18 FLAG180X-PDB-0	M18 FLAG230XP-DB-0C	M18 FLAG230XP-DB-121C
Battery pack capacity (Ah)	–	–	12.0
No. of batteries supplied	0	0	1
Charger supplied	–	–	130 min
No load speed (rpm)	6600	6600	6600
Disc diameter (mm)	180	230	230
Max. cutting depth (mm)	40	65	65
Spindle size	M14	M14	M14
Weight with battery pack (kg)	–	–	5.3
Switch type	Paddle switch	Paddle switch	Paddle switch
FIXTEC flange nut	Yes	Yes	Yes
Anti-kickback protection	Yes	Yes	Yes
Line lock out function	Yes	Yes	Yes
Supplied in	–	Kitbox	Kitbox
Article Number	4933464112	4933464114	4933464115

DUST GUARD FOR CUTTING, DELIVERED WITH 2 KEYLESS GUARD RECEPTIONS AND QUICK DUST CONNECTOR. DOES NOT FIT TO LAG'S EQUIPPED WITH AUTOBALANCER.

 Article Number **4932459341**

M18 CAG115XPDB | M18 FUEL™ 115 MM BRAKING GRINDER WITH PADDLE SWITCH

- Milwaukee® designed and built brushless POWERSTATE™ motor with the power to grind and up to 10x more tool life
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- RAPIDSTOP™ for fastest disc brake in less than 2 seconds and best user protection
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- Premium gearing system - same system as used at high performance corded grinders
- Slim handle design with paddle switch
- Removable dust screen to prevent debris entrance, prolonging motor life
- 115 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner
- FIXTEC nut for tool-free disc change
- Anti-vibration side handle for lower vibration


RAPID STOP

	M18 CAG115XPDB-0X	M18 CAG115XPDB-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	8500	8500
Disc diameter (mm)	115	115
Max. cutting depth (mm)	28	28
Spindle size	M 14	M 14
Weight with battery pack (kg)	–	2.7
Switch type	Paddle switch	Paddle switch
Braking time (s)	< 2	< 2
FIXTEC flange nut	Yes	Yes
Line lock out function	Yes	Yes
Supplied in	HD Box	HD Box
Article Number	4933451426	4933451010

M18 CAG125XPD | M18 FUEL™ 125 MM ANGLE GRINDER WITH PADDLE SWITCH



- Milwaukee® designed and built brushless POWERSTATE™ motor with the power to grind and up to 10x more motor life
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Premium gearing system - same system as used at high performance corded grinders
- 125 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner
- 100% tool-free wheel change thanks to integrated FIXTEC system
- Slim handle design with paddle switch
- Removable dust screen to prevent debris entrance, prolonging motor life
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge



	M18 CAG125XPD-0X	M18 CAG125XPD-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	8500	8500
Disc diameter (mm)	125	125
Max. cutting depth (mm)	33	33
Spindle size	M 14	M 14
Weight with battery pack (kg)	–	2.5
Switch type	Paddle switch	Paddle switch
FIXTEC	Yes	Yes
Line lock out function	Yes	Yes
Supplied in	HD Box	HD Box
Article Number	4933451441	4933448864

M18 CAG115XPD | M18 FUEL™ 115 MM ANGLE GRINDER WITH PADDLE SWITCH



- Milwaukee® designed and built brushless POWERSTATE™ motor with the power to grind and up to 10x more motor life
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Premium gearing system - same system as used at high performance corded grinders
- 115 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner
- 100% tool-free wheel change thanks to integrated FIXTEC system
- Slim handle design with paddle switch
- Removable dust screen to prevent debris entrance, prolonging motor life
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge



	M18 CAG115XPD-0X
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	8500
Disc diameter (mm)	115
Max. cutting depth (mm)	28
Spindle size	M 14
Weight with battery pack (kg)	2.5
Switch type	Paddle switch
FIXTEC	Yes
Line lock out function	Yes
Supplied in	HD Box
Article Number	4933451440

M18 CAG125X | M18 FUEL™ 125 MM ANGLE GRINDER WITH SLIDE SWITCH



- Milwaukee® designed and built brushless POWERSTATE™ motor with the power to grind and up to 10x more motor life
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Premium gearing system - same system as used at high performance corded grinders
- 125 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner
- 100% tool-free wheel change thanks to integrated FIXTEC system
- Slim handle design
- Removable dust screen to prevent debris entrance, prolonging motor life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 CAG125X-0X	M18 CAG125X-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	8500	8500
Disc diameter (mm)	125	125
Max. cutting depth (mm)	33	33
Spindle size	M 14	M 14
Weight with battery pack (kg)	–	2.5
Switch type	Slide switch	Slide switch
FIXTEC	Yes	Yes
Line lock out function	Yes	Yes
Supplied in	HD Box	HD Box
Article Number	4933451439	4933448866

M18 CAG115X | M18 FUEL™ 115 MM ANGLE GRINDER WITH SLIDE SWITCH



- Milwaukee® designed and built brushless POWERSTATE™ motor with the power to grind and up to 10x more motor life
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Premium gearing system - same system as used at high performance corded grinders
- 115 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner
- 100% tool-free wheel change thanks to integrated FIXTEC system
- Slim handle design
- Removable dust screen to prevent debris entrance, prolonging motor life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 CAG115X-0X	M18 CAG115X-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	8500	8500
Disc diameter (mm)	115	115
Max. cutting depth (mm)	28	28
Spindle size	M 14	M 14
Weight with battery pack (kg)	–	2.5
Switch type	Slide switch	Slide switch
FIXTEC	Yes	Yes
Line lock out function	Yes	Yes
Supplied in	HD Box	HD Box
Article Number	4933451438	4933448861

HD18 AG-125 | M18™ 125 MM ANGLE GRINDER WITH PADDLE SWITCH

- Milwaukee®'s high performance 4-pole motor delivers maximum power whilst (optimising) maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal gear case delivers heavy duty durability
- Reduced height of gear box and slim girth design deliver optimum ergonomics
- Non-lockable switch for best user protection and preventing automatic start up
- Burst resistant and tool-free safety guard for best user protection and fast adjustment
- Multi position side handle for ease of use
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	HD18 AG-125-0	HD18 AG-125-402C
Battery pack capacity (Ah)	–	4.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
No load speed (rpm)	9000	9000
Disc diameter (mm)	125	125
Max. cutting depth (mm)	33	33
Spindle size	M 14	M 14
Weight with battery pack (kg)	–	2.2
Switch type	Paddle switch	Paddle switch
FIXTEC	No	No
Line lock out function	No	No
Supplied in	–	Kitbox
Article Number	4933441502	4933441507

HD18 AG-115 | M18™ 115 MM ANGLE GRINDER WITH PADDLE SWITCH

- Milwaukee®'s high performance 4-pole motor delivers maximum power whilst (optimising) maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal gear case delivers heavy duty durability
- Reduced height of gear box and slim girth design deliver optimum ergonomics
- Non-lockable switch for best user protection and preventing automatic start up
- Burst resistant and tool-free safety guard for best user protection and fast adjustment
- Multi position side handle for ease of use
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	HD18 AG-115-0	HD18 AG-115-402C
Battery pack capacity (Ah)	–	4.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
No load speed (rpm)	9000	9000
Disc diameter (mm)	115	115
Max. cutting depth (mm)	28	28
Spindle size	M 14	M 14
Weight with battery pack (kg)	–	2.4
Switch type	Paddle switch	Paddle switch
FIXTEC	No	No
Line lock out function	No	No
Supplied in	–	Kitbox
Article Number	4933411210	4933441300

M18 BMS12 | M18™ METAL SHEAR

- Accurate cuts with maximum cutting depth of 1.2 mm in steel
- Unique 360° tool-free rotating head with 12 locking positions to access tight spaces and increasing user comfort
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- In-Line wrist design for increased control during cutting
- Variable speed trigger for extra control during cutting
- Belt clip for secure mobility
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



M18 BMS12-0	
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	0 - 2500
Max. cutting capacity steel (mm)	1.2
Max. cutting capacity aluminium (mm)	2.0
Minimum cutting radius (mm)	180
Weight with battery pack (kg)	2.3
Supplied in	–
Article Number	4933447925

M18 BMS20 | M18™ METAL SHEAR

- Accurate cuts with maximum cutting depth of 2.0 mm in steel
- Unique 360° tool-free rotating head with 12 locking positions to access tight spaces and increasing user comfort
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- In-Line wrist design for increased control during cutting
- Variable speed trigger for extra control during cutting
- Belt clip for secure mobility
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



M18 BMS20-0	
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	0 - 2500
Max. cutting capacity steel (mm)	2.0
Max. cutting capacity aluminium (mm)	3.2
Minimum cutting radius (mm)	180
Weight with battery pack (kg)	2.6
Supplied in	–
Article Number	4933447935

M18 CBS125 | M18 FUEL™ DEEP CUT BAND SAW

- Milwaukee® designed and built brushless POWERSTATE™ motor provides corded cutting performance with up to 10x more motor life and up to 2x more run time compared to other cordless solutions
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Largest cutting capacity up to 125 x 125 mm material diameter
- 5 step variable speed selection from 0 - 116 m/min
- Tool-free blade locking mechanism for quick and easy saw blade changes
- Solid metal rafter hook for quick and easy jobsite storage
- Slim full metal motor housing design and LED work surface illumination for best cut visibility
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 CBS125-0	M18 CBS125-502C
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (m/min)	0 - 116	0 - 116
Cutting capacity rect. stock (mm)	125 x 125	125 x 125
Blade length (mm)	1139.83	1139.83
Weight with battery pack (kg)	–	7.3
Supplied in	–	Kitbox
Article Number	4933447150	4933448195

HD18 BS | M18™ METAL BANDSAW

- 4.8 kg compact light weight design for cutting overhead and in tight places
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- 85 mm cut capacity – cuts most common materials
- Tool-free adjustable material shoe – quickly adjusts the shoe and allows flush cuts when working with installed materials against walls and ceilings
- Blade ejection system – quickly change the blade by moving the material guide into the up position and depressing the blade ejection button
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	HD18 BS-0	HD18 BS-402C
Battery pack capacity (Ah)	–	4.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
No load speed (rpm)	146	146
Cutting capacity rect. stock (mm)	85 x 85	85 x 85
Blade length (mm)	898.52	898.52
Weight with battery pack (kg)	–	4.8
Supplied in	–	Kitbox
Article Number	4933419122	4933441415

**900 MM 14 TPI BANDSAW BLADE
3 PCS. 1.8 MM TOOTH PITCH,
IDEAL FOR MATERIALS 5-8 MM IN
THICKNESS**

Article Number **48390519**

M18 FAP | M18 FUEL™ POLISHER

- Milwaukee® designed and built brushless POWERSTATE™ motor to deliver the ultimate mobility in car polishing
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- World's first cordless polisher with 8 position variable speed selection ranging from 360 - 2200 RPM
- Outstanding run time to polish one full size car per battery charge*
- Constant speed electronics with soft start for smooth start up
- Maximum polishing accessory diameter of 180 mm
- Removable dust screen to prevent debris ingress, prolonging motor life
- Rubber overmold gear case for increased comfort, especially when working with the tool vertically
- Lock-on function provides more comfortable use when polishing for longer periods
- 3 position bale handle for improved tool control
- Line-lock-out function to prevent automatic start up after battery change
- *on moderate to good paint, light scratches



	M18 FAP180-0	M18 FAP180-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	360 - 2200	360 - 2200
Disc diameter (mm)	180	180
Spindle size	M 14	M 14
Standard equipment	Polishing backing pad, dust screen, bale handle, AVS side handle	Polishing backing pad, polishing sponge white, polishing sponge orange, lambswool, dust screen, bale handle, AVS side handle
Weight with battery pack (kg)	–	2.2
Variable speed	Yes	Yes
Line lock out function	Yes	Yes
Soft start function	Yes	Yes
Supplied in	–	HD Box
Article Number	4933451549	4933451550

M18 FDG | M18 FUEL™ DIE GRINDER

- Milwaukee® designed and built brushless POWERSTATE™ motor with corded performance, up to 20 min of grinding on a 5.0 Ah battery and up to 10x more tool life
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Universal reception to fit both, 6 and 8 mm accessories
- Slim handle design
- Removable dust screen to prevent debris entrance, prolonging motor life
- Rubber front provides most comfortable handling
- Line-lock out function to prevent automatic start up
- Fuel gauge displays remaining charge
- Flexible battery system: works with all Milwaukee® M18™ batteries
- Supplied with 6 mm & 8 mm collet, 15 mm & 17 mm open ended spanner, 2 x dust screens



	M18 FDG-0X	M18 FDG-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	27,000	27,000
Collet capacity (mm)	6 / 8	6 / 8
Max. grinding accessories diameter (mm)	50	50
Weight with battery pack (kg)	–	2.1
Supplied in	HD Box	HD Box
Article Number	4933459190	4933459107

M18 FMCS | M18 FUEL™ METAL SAW

- Milwaukee® designed and built brushless POWERSTATE™ motor for fast cutting, longest tool life and up to 370 cuts in 3/4" EMT
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Cold cuts - reduces sparks for increased jobsite safety
- Tool-free depth adjustment, quickly and easily adjusts cutting depth from 0 to 57 mm
- Compact and light weight design for most comfortable use
- Integrated rafter hook for easy storage between uses
- On board allen key storage for easy access and preventing losing the key
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Flexible battery system: works with all Milwaukee® M18™ batteries
- Supplied with 150 mm 34 teeth metal cutting blade



M18 FUEL

	M18 FMCS-0X	M18 FMCS-502X
Battery pack capacity (Ah)	-	5.0
No. of batteries supplied	0	2
Charger supplied	-	59 min
No load speed (rpm)	3900	3900
Blade diameter (mm)	150	150
Bore size (mm)	20	20
Max. cutting depth (mm)	57	57
Weight with battery pack (kg)	-	2.8
Supplied in	HD Box	HD Box
Article Number	4933459192	4933459193

METAL CUTTING CIRCULAR SAW BLADE FOR 18 V FUEL™ METAL SAW

Article Number 48404080



M18 BMT | M18™ MULTI-TOOL

- Up to 50% faster and versatile cordless solution for cutting and removal applications with corded performance
- REDLINK™ overload protection and constant speed electronics in tool deliver best in class durability and performance
- 12 variable speed settings from 12,000 - 18,000 orbits per minute and 3.4° oscillation movement allows quick completion of professional applications into materials such as metal, wood and plastic
- Productivity enhancing FIXTEC tool free blade change with universal blade change adaptor included to accept all competitor blades
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Unique cutting depth stop adaptor to prevent over-cutting in material
- Unique dust extraction kit to keep the work space dust-free when connected to an AC or DC extraction system
- Brightest LED workspace illumination
- Flexible battery system: works with all Milwaukee® M18™ batteries



M18 BMT-0 M18 BMT-421C

	M18 BMT-0	M18 BMT-421C
Battery pack capacity (Ah)	-	1 x 2.0 + 1 x 4.0
No. of batteries supplied	0	2
Charger supplied	-	80 min
Oscillation angle left/ right (°)	1.7	1.7
No load speed (rpm)	12,000 - 18,000	12,000 - 18,000
Weight with battery pack (kg)	-	1.7
Supplied in	-	Kitbox
Article Number	4933446203	4933446210

MULTITool BLADE SET (9PCS)

Article Number 48901009



M18 FMS254 | M18 FUEL™ 254 MM MITRE SAW

- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 2x longer motor life and up to 25% more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 254 mm blade delivers large and accurate cut capacities
- Quick release bevel setting with detents allows the simple setting of bevel angles to the left and right
- Large sliding fences gives maximum support to the material being cut providing stability and accuracy
- Trenching cut with depth adjustment allows the user to make trenching and rebate cuts
- Up to 307 cuts in 38 mm x 89 mm soft wood with a 9.0 Ah battery gives the ability to work a full day without recharging the battery
- Integrated carry handle allows easy transportation on and off the jobsite
- Steel detent plate with preset angles gives repeatable accurate cuts
- LED light to illuminate the work piece and cut line in low light conditions



M18 FUEL

	M18 FMS254-0
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
No load speed (rpm)	4000
Blade diameter (mm)	254
Bevel capacity left (°)	48
Bevel capacity right (°)	48
Mitre capacity left (°)	50
Mitre capacity right (°)	60
Max. cutting capacity 45° mitre/ 45° bevel (mm)	205.23 x 51.3
Max. cutting capacity 45° mitre/ 90° bevel (mm)	205.23 x 91.2
Max. cutting capacity 90° mitre/ 45° bevel (mm)	289.3 x 51.3
Max. cutting capacity 90° mitre/ 90° bevel (mm)	289.3 x 91.2
Bore size (mm)	30
Weight with battery pack (kg)	20.0
Supplied in	-
Article Number	4933451729

M18 FMS190 | M18 FUEL™ 190 MM MITRE SAW

- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 2x longer motor life and up to 25% more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 190 mm blade delivers accurate cut capacities
- Quick release bevel setting allows the simple setting of bevel angles to the left and right
- Large sliding fences gives maximum support to the material being cut providing stability and accuracy
- Up to 299 cuts in 38 mm 89 mm soft wood with a 5.0 Ah battery gives the ability to work a full day without recharging the battery
- Light weight and portable at only 12.7 kg
- Integrated carry handle allows easy transportation on and off the jobsite
- Steel detent plate with preset angles gives repeatable accurate cuts
- LED light to illuminate the work piece and cut line in low light conditions
- Flexible battery system: works with all Milwaukee® M18™ batteries



M18 FUEL

	M18 FMS190-0
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
No load speed (rpm)	5000
Blade diameter (mm)	190
Bevel capacity left (°)	48
Bevel capacity right (°)	48
Mitre capacity left (°)	48
Mitre capacity right (°)	48
Max. cutting capacity 45° mitre/ 45° bevel (mm)	39.3 x 152.7
Max. cutting capacity 45° mitre/ 90° bevel (mm)	55.4 x 152.7
Max. cutting capacity 90° mitre/ 45° bevel (mm)	39.3 x 215.5
Max. cutting capacity 90° mitre/ 90° bevel (mm)	55.4 x 215.5
Max. cutting capacity at fence 0° mitre/0° bevel (mm)	90.9 x 21.8
Max. cutting capacity at fence L45° mitre/0° bevel (mm)	90.9 x 20.3
Max. cutting capacity at fence R45° mitre/0° bevel (mm)	90.9 x 17.8
Bore size (mm)	30
Weight with battery pack (kg)	12.7
Supplied in	-
Article Number	4933459619

M18 SMS216 | M18™ 216 MM MITRE SAW

- Milwaukee® powerful frameless motor delivers 2700 rpm for fast cutting
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Accuracy and durability are achieved with dual vertical steel rails with linear bearings which deliver smooth sliding action
- Rail lock - the saw head locks in the back position automatically
- Adjustable laser - for perfect and quick alignment to cut line
- Steel detent plate with preset angles - gives repeatable accurate cuts
- Lock lever/handle over mold - allows the user to make repeated cuts comfortably and without fatigue
- Mitre release system - for quick and smooth change of the cutting orientation
- Integral LED jobsite light illuminates the work area
- Spindle lock - for quick and easy blade change
- Heavy duty cast base and fence ensures durability and accuracy
- 48°/-2° bevel capacity
- Supplied with saw blade (48 teeth), blade spanner and work clamp
- Flexible battery system: works with all Milwaukee® M18™ batteries



M18 SMS216-0

	M18 SMS216-0
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
No load speed (rpm)	2700
Blade diameter (mm)	216
Bevel capacity left (°)	48
Bevel capacity right (°)	-2
Mitre capacity left (°)	50
Mitre capacity right (°)	50
Max. cutting capacity 45° mitre/ 45° bevel (mm)	190 x 48
Max. cutting capacity 45° mitre/ 90° bevel (mm)	190 x 60
Max. cutting capacity 90° mitre/ 45° bevel (mm)	270 x 48
Max. cutting capacity 90° mitre/ 90° bevel (mm)	270 x 60
Bore size (mm)	30
Weight with battery pack (kg)	14.5
Supplied in	-
Article Number	4933446780

M18 FCS66 | M18 FUEL™ 66 MM CIRCULAR SAW FOR WOOD AND PLASTICS

- The M18 FUEL™ circular saw delivers the power to rip cut at the same feed rate of an equivalent AC circular saw - with the ability to cut 750 pieces of 90 mm x 45 mm pine stud on one 12.0 Ah battery charge
- Next generation POWERSTATE™ brushless motor: This is Milwaukee®'s most powerful motor utilising higher grade magnets and 175% more copper vs previous motors
- Next generation REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- New REDLITHIUM-ION™ High Output™ 12.0 Ah battery pack provides superior pack construction, electronics and fade-free performance to deliver the most work per charge than any other Milwaukee® battery pack
- 190 mm blade which gives a 66 mm depth of cut, enabling the saw to cut three stacked OSB boards
- Durable metal rafter hang hook for work space management and safety
- Vacuum adaptor supplied fits directly to all Milwaukee® dust extractors
- Magnesium shoe reduces weight and maximises durability
- Integrated LED light for workspace illumination
- 56° bevel capacity



M18 FUEL

	M18 FCS66-121C
Battery pack capacity (Ah)	12
No. of batteries supplied	1
No load speed (rpm)	5800
Max. cutting depth 90° (mm)	66
Max. cutting depth 45° (mm)	48
Blade diameter (mm)	190
Bore size (mm)	30
Weight with battery pack (kg)	5.4
Supplied in	Kitbox
Article Number	4933464586

M18 CCS55 | M18 FUEL™ 55 MM CIRCULAR SAW FOR WOOD AND PLASTICS


- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 3x longer motor life and up to 2x more cuts per charge
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 50° bevel capacity
- Magnesium upper and lower guards provide best in class durability for impact resistance
- Magnesium shoe reduces weight and maximises durability
- Integrated dust blower keeps cut line clear
- Hang hook allows safe storage of the tool
- Integrated battery fuel gauge & LED light
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 CCS55-0X	M18 CCS55-502X	M18 CCS55-902X
Battery pack capacity (Ah)	–	5.0	9.0
No. of batteries supplied	0	2	2
Charger supplied	–	59 min	95 min
No load speed (rpm)	5000	5000	5000
Max. cutting depth 90° (mm)	55	55	55
Max. cutting depth 45° (mm)	41	41	41
Blade diameter (mm)	165	165	165
Bore size (mm)	15.87	15.87	15.87
Weight with battery pack (kg)	–	3.2	3.5
Supplied in	HD Box	HD Box	HD Box
Article Number	4933451429	4933451376	4933451468

M18 BLCS66 | M18™ BRUSHLESS 66 MM CIRCULAR SAW FOR WOOD AND PLASTICS

- M18™ brushless circular saw with a 190 mm blade giving a 66 mm depth of cut which enables the saw to cut three stacked 19 mm OSB boards
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Durable metal rafter hang hook for work space management and safety
- Vacuum adaptor supplied fits directly to all Milwaukee® dust extractors
- Pressed aluminum shoe for maximum durability
- Integrated LED light for workspace illumination
- 50° bevel capacity with a 46 mm depth of cut
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 BLCS66-0X	M18 BLCS66-502X
Battery pack capacity (Ah)	–	5
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	5000	5000
Max. cutting depth 90° (mm)	66	66
Max. cutting depth 45° (mm)	48	48
Blade diameter (mm)	190	190
Bore size (mm)	30	30
Weight with battery pack (kg)	–	4.0
Supplied in	HD Box	HD Box
Article Number	4933464589	4933464590

HD18 CS | M18™ 55 MM CIRCULAR SAW FOR WOOD AND PLASTIC

- Milwaukee® powerful 3500 rpm motor easily cuts most timber construction materials
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Large 50° bevel facility
- Magnesium upper and lower guards provide best in class durability for impact resistance
- Excellent visibility of cutting line
- Electronic motor brake, saw blade stops within seconds
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries
- Supplied with 24 tooth saw blade, parallel guide, dust port and allen key



	HD18 CS-0	HD18 CS-402B
Battery pack capacity (Ah)	–	4.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
No load speed (rpm)	3500	3500
Max. cutting depth 90° (mm)	55	55
Max. cutting depth 45° (mm)	39	39
Blade diameter (mm)	165	165
Bore size (mm)	15.87	15.87
Weight with battery pack (kg)	–	3.8
Supplied in	–	Tool bag
Article Number	4933419134	4933441400

M18 FTS210
M18 FUEL™ ONE-KEY™ TABLE SAW


- The ONE-KEY™ M18 FUEL™ table saw delivers the power to rip cut at the same feed rate of an equivalent AC saw, with the ability to cut 190 m of 19 mm OSB board on one 12.0 Ah battery charge
- Next generation POWERSTATE™ brushless motor: This is Milwaukee®'s most powerful motor utilising higher grade magnets and 175% more copper vs previous motors
- Next generation REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- New REDLITHIUM-ION™ High Output™ 12.0 Ah battery pack provides superior pack construction, electronics and fade-free performance to deliver the most work per charge than any other Milwaukee® battery pack
- Rack and pinion sliding fence allows the fence to be adjusted accurately and easily from the front of the saw giving 622 mm of rip capacity
- 210 mm blade allows 63 mm depth of cut at 90 degrees
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- Quick change guard and riving knife allows the user to remove and adjust the riving knife and guard without the need to remove the throat plate
- Integrated carry handle allows easy transportation on and off the jobsite

	M18 FTS210-0	M18 FTS210-121B
Battery pack capacity (Ah)	–	12.0
No. of batteries supplied	0	1
Charger supplied	–	130 min
No load speed (rpm)	6300	6300
Blade diameter (mm)	210	210
Bevel capacity (°)	47	47
Rip capacity (mm)	622	622
Depth of cut capacity (mm)	63.5	63.5
Weight with battery pack (kg)	–	22.3
Supplied in	–	–
Article Number	4933464722	4933464225



TABLE SAW STAND TO BE USED WITH M18 FTS210 M18 FUEL™ ONE-KEY™ TABLE SAW. LIGHTWEIGHT, ONLY 6.6 KG AND WILL HOLD UP TO 82 KG. IT FEATURES A QUICK RELEASE BRACKET AND ONE POINT LEG ADJUSTMENT.



Article Number **4933464227**



Anti-kick-back pawls stops material kicking back at the operator



Rack and pinion sliding fence allows the fence to be adjusted accurately and easily from the front of the saw



On fence push stick storage

M18 ONESX | M18 FUEL™ ONE-KEY™ SAWZALL®

- M18 CSX but with ONE-KEY™ technology
- Connect via Bluetooth® with the Milwaukee® ONE-KEY™ app
- ONE-KEY™ tool customisation allows the user to optimise their tool for specific applications
- Custom cut control provides advanced control over cutting speeds
- Adjustable soft start provides more accurate cut-starts in various materials minimising blade chatter and assisting in cleaner faster cuts
- Cut optimisation gives longer blade life and easier cutting in a wide range of materials
- Automatic brake allows the saw to stop the blade after it breaks through a material preventing accidental cuts in adjacent materials
- Plunge cut allows the blade to penetrate the material at a slower speed and then automatically ramp to full speed, sensing an increase in force from the user
- Save up to four custom settings to the tools memory allowing fast and easy selection of the most used configurations
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- Flexible battery system: works with all Milwaukee® M18™ batteries


M18 ONESX-0X M18 ONESX-502X M18 ONESX-902X

	M18 ONESX-0X	M18 ONESX-502X	M18 ONESX-902X
Battery pack capacity (Ah)	–	5.0	9.0
No. of batteries supplied	0	2	2
Charger supplied	–	59 min	95 min
Max. cutting depth in soft-wood (mm)	300	300	300
Max. cutting depth in steel (mm)	20	20	20
Max. cutting depth in aluminium (mm)	25	25	25
Max. cutting depth in non-ferrous metal (mm)	25	25	25
Max. cutting depth in metal pipe (mm)	150	150	150
No load stroke rate (spm)	0 - 3000	0 - 3000	0 - 3000
Stroke length (mm)	28.6	28.6	28.6
Weight with battery pack (kg)	–	4.0	4.3
Supplied in	HD Box	HD Box	HD Box
Article Number	4933459203	4933451666	4933459220

M18 FSX | M18 FUEL™ SUPER SAWZALL®

- The M18 FUEL™ Super Sawzall® delivers the power to cut at the same speed as an equivalent AC reciprocating saw - with the ability to cut 150 pieces of 290 mm x 45 mm pine on one 12.0 Ah battery charge
- Next generation POWERSTATE™ brushless motor: This is Milwaukee®'s most powerful motor utilising higher grade magnets and 175% more copper vs previous motors
- Next generation REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- New REDLITHIUM-ION™ High Output™ 12.0 Ah battery pack provides superior pack construction, electronics and fade-free performance to deliver the most work per charge than any other Milwaukee® battery pack
- Orbital action allows the saw to clear the cut of debris giving a faster cut in wood materials
- 3000 SPM with a 32 mm stroke length delivers fast and effortless cutting in a wide range of materials
- 5 variable speed settings from 1500 SPM to 3000 SPM to allow the correct speed to be set for the material being cut
- FIXTEC blade clamp for fast and easy blade changes without any key
- Durable metal rafter hang hook for work space management and safety



	M18 FSX-0C	M18 FSX-121C
Battery pack capacity (Ah)	–	12.0
No. of batteries supplied	0	1
Charger supplied	–	130 min
Max. cutting depth in soft-wood (mm)	300	300
Max. cutting depth in steel (mm)	20	20
Max. cutting depth in aluminium (mm)	25	25
Max. cutting depth in non-ferrous metal (mm)	25	25
Max. cutting depth in metal pipe (mm)	150	150
No load stroke rate (spm)	0 - 3000	0 - 3000
Stroke length (mm)	32	32
Weight with battery pack (kg)	–	5.5
Supplied in	Kitbox	Kitbox
Article Number	4933464724	4933464484

M18 CSX | M18 FUEL™ SAWZALL®

- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 5x longer motor life and up to 30% faster cutting
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups
- FIXTEC blade clamp for fast and easy blade changes without any key
- Adjustable shoe for optimised use of saw blades
- Integrated battery fuel gauge & LED light
- Durable metal rafter hang hook for work space management and safety
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 CSX-0X	M18 CSX-502X	M18 CSX-902X
Battery pack capacity (Ah)	–	5.0	9.0
No. of batteries supplied	0	2	2
Charger supplied	–	59 min	95 min
Max. cutting depth in soft-wood (mm)	300	300	300
Max. cutting depth in steel (mm)	20	20	20
Max. cutting depth in aluminium (mm)	25	25	25
Max. cutting depth in non-ferrous metal (mm)	25	25	25
Max. cutting depth in metal pipe (mm)	150	150	150
No load stroke rate (spm)	0 - 3000	0 - 3000	0 - 3000
Stroke length (mm)	28.6	28.6	28.6
Weight with battery pack (kg)	–	4.1	4.4
Supplied in	HD Box	HD Box	HD Box
Article Number	4933451428	4933451378	4933451470

M18 BSX | M18™ SAWZALL®

- Milwaukee®'s high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Milwaukee® patented FIXTEC clamp for fast and easy keyless blade change
- Counter balance mechanism to reduce vibrations 15.2 m/s² in wooden beams
- 28.6 mm stroke length & 3000 strokes per minute for extremely fast cutting
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life



	M18 BSX-0	M18 BSX-402C
Battery pack capacity (Ah)	–	4.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
Max. cutting depth in soft-wood (mm)	300	300
Max. cutting depth in steel (mm)	20	20
Max. cutting depth in aluminium (mm)	25	25
Max. cutting depth in non-ferrous metal (mm)	25	25
Max. cutting depth in metal pipe (mm)	150	150
No load stroke rate (spm)	3000	3000
Stroke length (mm)	28.6	28.6
Weight with battery pack (kg)	–	4.0
Supplied in	–	Kitbox
Article Number	4933447275	4933447285

SAWZALL® BLADE SET

 Article Number **49222229**

M18 FHZ | M18 FUEL™ HACKZALL™

- The Milwaukee® POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 22 mm stroke length for controlled cutting with a no load stroke rate of 3000 spm
- Pivoting shoe allows the user to optimise his cutting position
- Built in LED light improves visibility in low light cutting applications
- Milwaukee® patented FIXTEC clamp for quick and efficient blade change
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 FHZ-0X	M18 FHZ-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load stroke rate (spm)	0 - 3000	0 - 3000
Stroke length (mm)	22	22
Weight with battery pack (kg)	–	2.6
Supplied in	HD Box	HD Box
Article Number	4933459887	4933459885

**HACKZALL™ BLADE SET (10 PCS);
2 X 49005460, 3 X 49005614, 3
X 49005424, 2 X 49005418**

 Article Number **49220220**

C18 HZ | M18™ HACKZALL™

- Milwaukee® high performance compact one handed use HACKZALL™, measuring only 375mm in length, makes it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Dual gear counter balance reduces vibration and increases tool life
- Milwaukee® patented FIXTEC clamp for fast keyless blade change
- 20 mm stroke length for controlled cutting with a no load stroke rate of 3000 spm
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Built in LED light illuminates the work surface
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	C18 HZ-0	C18 HZ-402B
Battery pack capacity (Ah)	–	4.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
No load stroke rate (spm)	0 - 3000	0 - 3000
Stroke length (mm)	20	20
Weight with battery pack (kg)	–	2.5
Supplied in	–	Tool bag
Article Number	4933416785	4933441340

**HACKZALL™ BLADE SET (10 PCS);
2 X 49005460, 3 X 49005614, 3
X 49005424, 2 X 49005418**

 Article Number **49220220**

M18 FBJS | M18 FUEL™ BODY GRIP JIGSAW

- Milwaukee® designed and built brushless POWERSTATE™ motor for fast cutting, long tool life and up to 32 m in 19 mm OSB (on a 5.0 Ah pack)
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Milwaukee® patented FIXTEC blade clamp for fast and easy blade change
- Five stage pendulum action for increased cutting performance
- Ambidextrous on / off switch allows user to turn the tool on in any position
- 6-speed settings with auto controlled start mode allows the tool to start slow and ramp up to full speed when load is detected for smooth and accurate cut starts
- 3500 spm delivers smooth cuts, minimised chipping and vibration
- Dust blower keeps the cut line free of wood dust
- Integrated LED light for workspace illumination
- Detachable soft shoe avoids marks and scratches when cutting soft materials



	M18 FBJS-0X	M18 FBJS-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load stroke rate (spm)	800 - 3500	800 - 3500
Max. cutting capacity wood (mm)	100	100
Max. cutting capacity steel (mm)	10	10
Bevel capacity (°)	45	45
Stroke length (mm)	25	25
Weight with battery pack (kg)	–	2.8
Supplied in	HD Box	HD Box
Article Number	4933464799	4933464800

M18 FJS | M18 FUEL™ TOP HANDLE JIGSAW

- Milwaukee® designed and built brushless POWERSTATE™ motor for fast cutting, long tool life and up to 32 m in 19 mm OSB (on a 5.0 Ah pack)
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Milwaukee® patented FIXTEC blade clamp for fast and easy blade change
- Keyless bevel facility on the base plate allows for adjustment between 0 - 45°
- Five stage pendulum action for increased cutting performance
- Dust blower keeps the cut line free of wood dust
- Integrated LED light for workspace illumination
- Detachable soft shoe avoids marks and scratches when cutting soft materials
- Flexible battery system: works with all Milwaukee® M18™ batteries



M18 FUEL

	M18 FJS-0X	M18 FJS-502X
Battery pack capacity (Ah)	-	5.0
No. of batteries supplied	0	2
Charger supplied	-	59 min
No load stroke rate (spm)	0 - 3500	0 - 3500
Max. cutting capacity wood (mm)	135	135
Max. cutting capacity steel (mm)	10	10
Bevel capacity (°)	45	45
Stroke length (mm)	25	25
Weight with battery pack (kg)	-	2.9
Supplied in	HD Box	HD Box
Article Number	4933464726	4933464727

M18 BJS | M18™ TOP HANDLE JIGSAW

- Milwaukee® high performance motor delivers 2800 spm for fast cutting
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Milwaukee® patented FIXTEC blade clamp for fast and easy blade change
- Keyless bevel facility on the base plate allows for adjustment between 0 - 45°
- Five stage pendulum action for increased cutting performance
- LED light to illuminate the work piece
- Dust blower keeps the cut line free of wood dust
- Detachable soft shoe avoids marks and scratches when cutting soft materials
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 BJS-0	M18 BJS-402C
Battery pack capacity (Ah)	-	4.0
No. of batteries supplied	0	2
Charger supplied	-	80 min
No load stroke rate (spm)	0 - 2800	0 - 2800
Max. cutting capacity wood (mm)	135	135
Max. cutting capacity steel (mm)	10	10
Stroke length (mm)	25	25
Weight with battery pack (kg)	-	2.5
Supplied in	-	Kitbox
Article Number	4933451391	4933451389

75 X 2.5 MM T 101 B JIGSAW BLADE, 5 PCS

Article Number 4932254061



M18 BP | M18™ PLANER

- Milwaukee®'s high performance 4-pole motor delivers 14,000 rpm to achieve optimum surface finish
- REDLINK™ overload protection and constant speed electronics in tool deliver best in class durability and performance
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Faster material removal with two double edged carbide blades over a planing width of 82 mm
- Adjustable depth of cut from 0 to 2 mm with twenty locking positions allows the user to accurately set the amount of material to be removed in one pass
- Up to 10.7 mm of rebate depth
- Left or right chip ejection allows the user to keep the chips away from his face when planing
- Extended front shoe allows the tool to be placed on the work piece accurately and quickly
- A kick stand located on the base protects the work piece from accidental damage



	M18 BP-0	M18 BP-402C
Battery pack capacity (Ah)	-	4.0
No. of batteries supplied	0	2
Charger supplied	-	80 min
No load speed (rpm)	14,000	14,000
Cutting width (mm)	82	82
Max. cutting depth (mm)	2	2
Rebate depth (mm)	10.7	10.7
Weight with battery pack (kg)	-	2.7
Supplied in	-	Kitbox
Article Number	4933451113	4933451114

2 X TUNGSTEN CARBIDE REVERSIBLE BLADES

Article Number 4932273484



M18 BOS125 | M18™ 125 MM RANDOM ORBITAL SANDER

- Milwaukee® high performance motor delivers 14,000 to 24,000 sanding strokes per minute for faster material removal
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Variable speed wheel with six speed settings allows the correct speed to be set for different types of material
- Dust extraction box with internal filter keeps dust contained and managed
- Universal hook and loop sanding pad allows easy changing of sanding discs
- Lightweight - 1.6 kg
- Vacuum adaptor supplied fits directly to all Milwaukee® dust extractors
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 BOS125-0	M18 BOS125-502B
Battery pack capacity (Ah)	-	5.0
No. of batteries supplied	0	2
Charger supplied	-	80 min
No load speed (rpm)	12,000	12,000
Oscillation rate (opm)	14,000 - 24,000	14,000 - 24,000
Oscillation diameter (mm)	2.4	2.4
Sanding pad size (mm)	125	125
Weight with battery pack (kg)	-	1.6
Supplied in	-	Tool bag
Article Number	4933464228	4933464229

M18 CN15GA | M18 FUEL™ 15 GA ANGLED NAIL FINISH NAILER

- Best-in-class power to consistently seat nails sub-flush to the surface in hardwoods
- Ready to Fire Nail Technology eliminates ramp-up time between each nail discharge
- No gas cartridges and no cleaning required, designed to deliver durability and reliability to the most demanding users with very little maintenance
- Two mode selection allows for sequential fire for precision or bump fire for speed
- Tool-free, quick and easy depth adjustment to assure nails are driven sub-flush
- Dry-Fire lockout stops the tool being fired when there are no nails left in the magazine
- Fires up to 700 nails per charge on a REDLITHIUM-ION™ 2.0 Ah battery pack for maximum productivity
- Quick access and easy clearing of jams
- LED work light illuminates the work surface for better placement of nails
- Flexible battery system: works with all Milwaukee® M18™ batteries



M18 FUEL

	M18 CN15GA-0X
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
Collation angle (°)	34
Nail diameter (mm)	1.8
Nail type (mm)	32 / 63
Magazine capacity nails	110
Cycle rate (h)	900
Weight with battery pack (kg)	3.3
Supplied in	HD Box
Article Number	4933459633

M18 CN16GA | M18 FUEL™ 16 GA ANGLED NAIL FINISH NAILER

- Best-in-class power to consistently seat nails sub-flush to the surface in hardwoods
- Ready to Fire Nail Technology eliminates ramp-up time between each nail discharge
- No gas cartridges and no cleaning required, designed to deliver durability and reliability to the most demanding users with very little maintenance
- Two mode selection allows for sequential fire for precision or bump fire for speed
- Tool-free, quick and easy depth adjustment to assure nails are driven sub-flush
- Dry-Fire lockout stops the tool being fired when there are no nails left in the magazine
- Fires up to 800 nails per charge on a REDLITHIUM-ION™ 2.0 Ah battery pack for maximum productivity
- Quick access and easy clearing of jams
- LED work light illuminates the work surface for better placement of nails
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 CN16GA-0X	M18 CN16GA-202X
Battery pack capacity (Ah)	-	2.0
No. of batteries supplied	0	2
Charger supplied	-	40 min
Collation angle (°)	20	20
Nail diameter (mm)	1.6	1.6
Nail type (mm)	32 / 63	32 / 63
Magazine capacity nails	110	110
Cycle rate (h)	900	900
Weight with battery pack (kg)	-	3.3
Supplied in	HD Box	HD Box
Article Number	4933451958	4933451570

M18 CN18GS | M18 FUEL™ 18 GA BRAD NAIL FINISH NAILER

- Best-in-class power to consistently seat nails sub-flush to the surface in hardwoods
- Ready to Fire Nail Technology eliminates ramp-up time between each nail discharge
- No gas cartridges and no cleaning required, designed to deliver durability and reliability to the most demanding users with very little maintenance
- Two mode selection allows for sequential fire for precision or bump fire for speed
- Tool-free, quick and easy depth adjustment to assure nails are driven sub-flush
- Dry-Fire lockout stops the tool being fired when there are no nails left in the magazine
- Fires up to 1200 nails per charge on a REDLITHIUM-ION™ 2.0 Ah battery pack for maximum productivity
- Quick access and easy clearing of jams
- LED work light illuminates the work surface for better placement of nails
- Flexible battery system: works with all Milwaukee® M18™ batteries


M18 FUEL

	M18 CN18GS-0X	M18 CN18GS-202X
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	2
Charger supplied	–	40 min
Collation angle (°)	0	0
Nail diameter (mm)	1.2	1.2
Nail type (mm)	16 / 54	16 / 54
Magazine capacity nails	110	110
Cycle rate (h)	900	900
Weight with battery pack (kg)	–	3.1
Supplied in	HD Box	HD Box
Article Number	4933451959	4933451573

M18 FBPV | M18 FUEL™ BACKPACK VACUUM

- Milwaukee® designed and built brushless POWERSTATE™ motor for advanced suction power and longer motor life
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Dust class L. Standard MAK-factor > 1 mg/m³
- HEPA filter will collect 99.97% of airborne particles down to 0.3 microns
- DEK 26 compatible allows the vacuum to be easily connected to a powertool
- Low noise of only 76 db (operating sound level)
- Cyclonic technology for longer filter life, extended peak performance and bag-less debris collection
- Integrated hanging hook for ladders and scaffolding
- Removable harness transforms the vacuum into a canister style vacuum
- Supplied with 1 x floor tool, 1 x crevice tool, 1 x telescopic extension wand, 1 x flexible hose, 1 x dust extraction adaptor


M18 FUEL

	M18 FBPV-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Capacity (l)	3.8
Hose diameter (mm)	36
Max. vacuum (mbar)	189
Air volume (l/min)	1557.43
Filter type	HEPA
Sealed suction (mm)	1905 in H2O
Weight with battery pack (kg)	8.5
Supplied in	–
Article Number	4933464483

M18 VC2 | M18™ WET/DRY VACUUM

- Powerful 18 V motor with a maximum air flow of 1300 l/min / 80 bar provides excellent suction power for both wet and dry clean up applications
- HEPA filter will collect 99.97% of airborne particles down to 0.03 microns for fine dust collection
- Up to 30 minutes run time with M18™ 9.0 Ah battery pack
- Internal accessory and hose storage allows all attachments to be carried with the tool avoiding loss of equipment
- DEK 26 compatible allows the vacuum to be easily connected to a powertool
- Stackable tool box design for added portability and easier storage
- On board blower for moving debris away from the work area
- Waterproof switch prevents switch damage over the life time of the tool
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 VC2-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Capacity solids (l)	9.79
Capacity liquids (l)	7.5
Hose diameter (mm)	41
Hose length (m)	0.47
Max. vacuum (mbar)	80
Air volume (l/min)	1300
Filter type	Wet/Dry
Weight with battery pack (kg)	5.3
Supplied in	–
Article Number	4933464029

M18 CV | M18™ HAND VAC

- Excellent suction power for wood, metal and common debris
- HEPA filter will collect 99.97% of airborne particles down to 0.3 microns
- Lock on switch reduces fatigue during sustained use
- Versatile accessories for small or large clean up areas
- Secure canister lock guards against unwanted spillage
- Clear viewing window gives the user the ability to see debris build up
- Up to 23 minutes continuous run time on a 5.0 Ah battery
- Flexible battery system: works with all Milwaukee® M18™ batteries


M18 CV-0

Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Capacity solids (l)	2.5
Hose diameter (mm)	32
Hose length (m)	1.2
Max. vacuum (mbar)	84.8
Air volume (l/min)	1019.33
Filter type	Dry
Weight with battery pack (kg)	1.9
Supplied in	–
Article Number	4933459204

M18 BBL | M18™ BATTERY BLOWER

- Compact body - clears dirt and debris in tight spaces
- Power control - 3 speed settings with variable speed trigger
- Versatile attachments - nozzle extension (228.6 mm), universal inflator/deflator attachment
- Removable nozzle for easy, convenient storage
- Lock-on switch
- Flexible battery system: works with all Milwaukee® M18™ batteries


M18 BBL-0

Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Air volume (m³/min)	0 - 2.9
Airflow speed (km/h)	0 - 42.8
Fan speed (rpm)	0 - 18,700
Length without nozzle (mm)	375
Weight with battery pack (kg)	1.2
Supplied in	–
Article Number	4933446216

M18 AF | M18™ AIR FAN

- AC/DC, allows the user to run on M18™ REDLITHIUM-ION™ or AC power when available
- Three speed settings for optimised air flow up to 1290 meters per hour
- Efficient air circulation circulates the air within a 3.6 m x 4 m room
- Adjustable head allows the user to utilise the fan in various heights and positions over a range of 120°
- Three hours run time on speed three with a M18™ REDLITHIUM-ION™ 4.0 Ah battery pack
- Compact design with integrated carry handle to maximise portability
- Rubber feet provide stability and no surface scratches
- Fixing points gives the user the option to wall mount the fan if needed
- AC adaptor supplied
- Flexible battery system: works with all Milwaukee® M18™ batteries


M18 AF-0

Voltage (DC) (V)	18
Voltage (AC) (V)	220 - 240
Battery type	Li-ion
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Airflow speed 1 (m³/h)	760
Airflow speed 2 (m³/h)	1000
Airflow speed 3 (m³/h)	1290
Weight with battery pack (kg)	2.7
Supplied in	–
Article Number	4933451022

M18 BHG | M18™ HEAT GUN

- High performance heat coil allows the tool to reach 470 °C
- Reaches operational temperature in six seconds allowing the user to quickly complete his application
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Durable ladder hook for work space management and safety
- Integrated LED light to illuminate the work area
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 BHG-0	M18 BHG-502C
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
Temperature range (°C)	470	470
Air volume (l/min)	170	170
Recommended ambient operating temperature (°C)	-18 - +52	-18 - +52
Weight with battery pack (kg)	–	1.4
Supplied in	–	Kitbox
Article Number	4933459771	4933459772

C18 PCG/600 | M18™ CAULK GUN WITH 600 ML TUBE

- Up to 4500 N of force. Min 40% higher than previous Milwaukee® caulk gun
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	C18 PCG/600A-201B	C18 PCG/600T-201B
Battery pack capacity (Ah)	2.0	2.0
No. of batteries supplied	1	1
Charger supplied	40 min	40 min
Max. pushing force (N)	4500	4500
Speed settings	6	6
Standard equipment	600 ml alum. tube	600 ml transp. tube
Weight with battery pack (kg)	2.3	2.3
Supplied in	Tool bag	Tool bag
Article Number	4933441305	4933441808

C18 PCG/400 | M18™ CAULK GUN WITH 400 ML TUBE

- Up to 4500 N of force. Min 40% higher than previous Milwaukee® caulk gun
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	C18 PCG/400T-201B
Battery pack capacity (Ah)	2.0
No. of batteries supplied	1
Charger supplied	40 min
Max. pushing force (N)	4500
Speed settings	6
Standard equipment	400 ml transparent tube
Weight with battery pack (kg)	2.3
Supplied in	Tool bag
Article Number	4933441812

C18 PCG/310 | M18™ CAULK GUN WITH 310 ML CANISTER

- Up to 4500 N of force. Min 40% higher than previous Milwaukee® caulk gun
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability



	C18 PCG/310C-0B	C18 PCG/310C-201B
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	1
Charger supplied	–	40 min
Max. pushing force (N)	4500	4500
Speed settings	6	6
Standard equipment	310 ml canister cartridge holder	310 ml canister cartridge holder
Weight with battery pack (kg)	–	2.3
Supplied in	–	Tool bag
Article Number	4933459637	4933441310

310 ML STANDARD CARRIAGE. INCLUDES PLUNGER ROD ASSEMBLY (4932352937), PISTON FOR CARRIAGE ASSEMBLIES AND A FEED SCREW (44700330)



Article Number 49081076

M18 GG | M18™ GREASE GUN

- Powerful 18V motor delivers over 562 bar max. operating pressure
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Best in class run time - dispenses up to 7 cartridges per charge
- Superior handle balance and ergonomics - only 355 mm long and 3.9 kg
- Air bleeder valve - priming mechanism for quick flow
- Integrated hose storage, shoulder strap loop and LED fuel gauge - added user convenience and less down time
- Three way loading - bulk, cartridge and suction capable
- Grease capacity 400 ml cartridge, 473 ml bulk
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries
- Supplied with 1219 mm high pressure flex hose with spring guard



	M18 GG-0	M18 GG-201C
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	1
Charger supplied	–	40 min
Weight with battery pack (kg)	–	3.9
Supplied in	–	Kitbox
Article Number	4933440493	4933440490

M18 RC | M18™ JOBSITE RADIO/CHARGER WITH BLUETOOTH®

- Built in charger function allows for quick, convenient charging of any M18™ battery or electronic devices via USB port
- Digital Bluetooth® receiver: play music up to 30 m away from your smartphone, computer, or tablet
- AC/DC versatility: powered by Milwaukee® M18™ batteries, or 230 V mains supply
- Exclusive AM/FM tuner with digital processor delivers highest reception accuracy and signal clarity
- Premium speaker and 40 W amplifier produce rich, full sound
- Weather sealed auxiliary compartment protects Mp3 players and other audio devices
- Reinforced roll cage and metal handles protects against abusive jobsite conditions
- Customisable equalizer and 10-station preset
- Protected 2.1 Amp USB power outlet charges devices in both AC and DC mode
- Supplied with auxiliary input cord, 2 x AAA batteries. Milwaukee® batteries sold separately
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 RC-0
Voltage (DC) (V)	18
Voltage (AC) (V)	220 - 240
Battery type	Li-ion
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Dimensions (mm)	300 x 307 x 370
Speaker output (W)	40
Weight (kg)	7.7
Supplied in	–
Article Number	4933446639

M12-18 JSSP | M12™ - M18™ BLUETOOTH® SPEAKER

- Advanced technology Bluetooth® jobsite speaker
- Bluetooth® wireless range of up to 30 m
- Flexible battery system: works with all Milwaukee® M12™ & M18™ batteries
- IP54 rated, water and debris resistant to withstand tough conditions on and off the jobsite
- Loud, clear sounds at all volumes
- 2.1A USB charger, charges phones, tablets and media players
- Premium speaker with bass port


M12-18 JSSP-0

Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
Dimensions (mm)	360 x 165 x 165
Speaker output (W)	40
Weight with battery pack (kg)	2.3
Supplied in	-
Article Number	4933459275

M18 JSR DAB+ | M18™ JOBSITE RADIO DAB+

- High performance audio system - DAB+/FM tuner with digital processor delivers highest reception accuracy and signal clarity
- DAB+ gives best sound quality and additional information like: song, artist and accurate time
- Dual speaker with passive radiators - deliver loud, clear sound with deep, accurate bass
- Customisable equalizer for enhanced sound quality and 10-station preset
- Shock absorbing end caps and metal speaker grills - protect from drops, water and debris on the jobsite
- Integrated handles - allow for easy transport and storage
- Powered by Milwaukee® M18™ batteries or AC outlet. Up to 12 hours of runtime with an M18™ REDLITHIUM-ION™ 5.0 Ah battery pack
- Weather sealed device compartment protects mobile devices
- Protected 2.1 A USB power outlet - charges electronic devices in both AC and DC mode
- Supplied with auxiliary input cord, 2 x AAA batteries. Milwaukee® batteries sold separately


M18 JSR DAB+-0

Voltage (DC) (V)	18
Voltage (AC) (V)	220 - 240
Battery type	Li-ion
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
Tuning range AM (kHz)	-
Tuning range FM (MHz)	87.50 - 108
Tuning range DAB+ (MHz)	174.928 - 239.20
Dimensions (mm)	402 x 197 x 197
Weight with battery pack (kg)	4.9
Supplied in	-
Article Number	4933451251

M18 JSR | M18™ JOBSITE RADIO

- High performance audio system - AM/FM tuner with digital processor delivers highest reception accuracy and signal clarity
- Dual speaker with passive radiators - deliver loud, clear sound with deep, accurate bass
- Customisable equalizer for enhanced sound quality and 10-station preset
- Shock absorbing end caps and metal speaker grills - protect from drops, water and debris on the jobsite
- Integrated handles - allow for easy transport and storage
- Powered by Milwaukee® M18™ batteries or AC outlet. Up to 12 hours of runtime with an M18™ REDLITHIUM-ION™ 5.0 Ah battery pack
- Weather sealed device compartment protects mobile devices
- Protected 2.1 A USB power outlet - charges electronic devices in both AC and DC mode


M18 JSR-0

Voltage (DC) (V)	18
Voltage (AC) (V)	220 - 240
Battery type	Li-ion
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
Tuning range AM (kHz)	522 - 1629
Tuning range FM (MHz)	87.50 - 108.00
Dimensions (mm)	402 x 197 x 197
Weight with battery pack (kg)	4.9
Supplied in	-
Article Number	4933451250

M18 FHPP3A | M18™ HIGH PERFORMANCE POWERPACK

- M18 FLAG230XPDB - M18 FUEL™ 230 mm large braking grinder with paddle switch
- M18 FSX - M18 FUEL™ Super SAWZALL®
- M18 FCS66 - M18 FUEL™ 66 mm circular saw for wood and plastics


M18 FHPP3A-122B

Battery pack capacity (Ah)	12.0
No. of batteries supplied	2
Charger supplied	130 min
Supplied in	Tool bag
Article Number	4933464831

M18 ONEPP2B2 | M18 FUEL™ ONE-KEY™ POWERPACK

- M18 ONEPD2 - M18 FUEL™ ONE-KEY™ percussion drill
- M18 ONEIWF12 - M18 FUEL™ ONE-KEY™ 1/2" impact wrench with friction ring


M18 ONEPP2B2-502X

Battery pack capacity (Ah)	5.0
No. of batteries supplied	2
Charger supplied	59 min
Supplied in	HD Box
Article Number	4933464595

M18 ONEPP2A2 | M18 FUEL™ ONE-KEY™ POWERPACK

- M18 ONEPD2 - M18 FUEL™ ONE-KEY™ percussion drill
- M18 ONEID2 - M18 FUEL™ ONE-KEY™ 1/4" Hex impact driver


M18 ONEPP2A2-502X

Battery pack capacity (Ah)	5.0
No. of batteries supplied	2
Charger supplied	59 min
Supplied in	HD Box
Article Number	4933464529

M18 FPP2A2 | M18 FUEL™ POWERPACK

- M18 FPD2 - M18 FUEL™ percussion drill
- M18 FID2 - M18 FUEL™ 1/4" Hex impact driver


M18 FPP2A2-502X

Battery pack capacity (Ah)	5.0
No. of batteries supplied	2
Charger supplied	59 min
Supplied in	HD Box
Article Number	4933464268

M18 FPP2C2 | M18 FUEL™ POWERPACK

- M18 FPD2 - M18 FUEL™ percussion drill
- M18 FIWF12 - M18 FUEL™ 1/2" impact wrench with friction ring

FUEL



M18 FPP2C2-502X

Battery pack capacity (Ah)	5.0
No. of batteries supplied	2
Charger supplied	59 min
Supplied in	HD Box
Article Number	4933464270

M18 FPP6C2 | M18 FUEL™ POWERPACK

- M18 FPD2 - M18 FUEL™ percussion drill
- M18 FID2 - M18 FUEL™ 1/4" Hex impact driver
- M18 CSX - M18 FUEL™ SAWZALL®
- M18 CAG125X - M18 FUEL™ 125 mm angle grinder with slide switch
- M18 CCS55 - M18 FUEL™ 55 mm circular saw for wood and plastics
- M18 TLED - M18™ LED torch

FUEL



M18 FPP6C2-502B

Battery pack capacity (Ah)	5.0
No. of batteries supplied	2
Charger supplied	59 min
Supplied in	Tool bag
Article Number	4933464592

M18 CBLPP2A | M18™ COMPACT BRUSHLESS POWERPACK

- M18 CBLPD - M18™ compact brushless percussion drill
- M18 CBLID - M18™ compact brushless 1/4" Hex impact driver



M18 CBLPP2A-402C

Battery pack capacity (Ah)	4.0
No. of batteries supplied	2
Charger supplied	80 min
Supplied in	Kitbox
Article Number	4933464536

M18 BLPP2B2 | M18™ BRUSHLESS POWERPACK

- M18 BLDD2 - M18™ brushless drill driver
- M18 BLID2 - M18™ brushless 1/4" Hex impact driver



M18 BLPP2B2-502X

Battery pack capacity (Ah)	5.0
No. of batteries supplied	2
Charger supplied	59 min
Supplied in	HD Box
Article Number	4933464594

M18 BLPP2A2 | M18™ BRUSHLESS POWERPACK

- M18 BLPD2 - M18™ brushless percussion drill
- M18 BLID2 - M18™ brushless 1/4" Hex impact driver



M18 BLPP2A2-502X

Battery pack capacity (Ah)	5.0
No. of batteries supplied	2
Charger supplied	59 min
Supplied in	HD Box
Article Number	4933464522

M18 CBLPP2B | M18™ COMPACT BRUSHLESS POWERPACK

- M18 CBLDD - M18™ compact brushless drill driver
- M18 CBLID - M18™ compact brushless 1/4" Hex impact driver



M18 CBLPP2B-402C M18 CBLPP2B-502C

Battery pack capacity (Ah)	4.0	5.0
No. of batteries supplied	2	2
Charger supplied	80 min	80 min
Supplied in	Kitbox	Kitbox
Article Number	4933464593	4933464718

M18 BPP2C | M18™ POWERPACK

- M18 BPD - M18™ percussion drill
- M18 BID - M18™ 1/4" Hex impact driver



M18 BPP2C-402C

Battery pack capacity (Ah)	4.0
No. of batteries supplied	2
Charger supplied	80 min
Supplied in	Kitbox
Article Number	4933443552

M18 FPP4F2 | M18 FUEL™ POWERPACK

- M18 FPD2 - M18 FUEL™ percussion drill
- M18 FID2 - M18 FUEL™ 1/4" Hex impact driver
- M18 FBJS - M18 FUEL™ body grip jigsaw
- M18 BMT - M18™ multi-tool
- 5 m slim tape measure

FUEL



M18 FPP4F2-502B

Battery pack capacity (Ah)	5.0
No. of batteries supplied	2
Charger supplied	59 min
Supplied in	Tool bag
Article Number	4933471208

M12

**UPGRADE.
OUTWORK.
OUTLAST.**



**ONE SYSTEM
OVER
75
TOOLS**

**PORTABLE PRODUCTIVITY.
TRADE FOCUSED.
SYSTEM WIDE.**



M12 FUEL

RED LITHIUM-ION™

DRIVEN TO OUTPERFORM.™

M12 FUEL™ is engineered for the most demanding tradesmen in the world. M12 FUEL™ delivers extreme performance in a compact structure and features three Milwaukee® exclusive innovations - the POWERSTATE™ brushless motor, REDLITHIUM-ION™ battery pack and REDLINK PLUS™ intelligence hardware and software - that deliver incredible power, run time and durability.

Simply put, M12 FUEL™ offers the best, full circle technology that drives, protects and powers your cordless tools.


NEW
MORE CAPABLE*

LIGHT WEIGHT*

MORE COMPACT*

1 POWERSTATE™ BRUSHLESS MOTOR

- Milwaukee® designed and built brushless motor
- Provides increased efficiency
- Lasts longer and delivers maximum power*



M12 FUEL™

DRIVEN TO OUTPERFORM.™



2 REDLINK PLUS™ INTELLIGENCE

- Individual cell monitoring to optimise tool run time and ensure long term pack durability
- Advanced system electronics with unique digital performance enhancement
- Total system communication with overload protection increases tool life

3 REDLITHIUM-ION™ BATTERY PACKS

- Total system communication with overload protection increases tool life
- Fade-free performance to deliver more run time and more work over pack life
- Fuel gauge displays remaining charge
- Operates down to -20°C



REDLITHIUM-ION™ 2.0 / 3.0 / 4.0 / 6.0Ah



M12

75 **M12**
TOOLS

* Compared with previous Milwaukee® technology. Results dependent on voltage, tool and application.

M12 CH

M12 FUEL™ SUB COMPACT SDS-PLUS HAMMER

- Industry's first brushless compact 12V rotary hammer with 1.1 Joules (EPTA), 0 - 6575 bpm & 0 - 900 rpm
- Exceptionally low vibration value 4.4 m/s² can be used for 8 hours in a day
- Will drill over 60 50 mm x 6 mm holes per battery charge
- Superior power to weight ratio in its class with Milwaukee® designed and built brushless POWERSTATE™ motor for up to 3x longer motor life and up to 2x more run time
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 2-mode operation: choose rotary hammer or rotation only for maximum versatility
- Optimised hammer drilling up to 6 - 10 mm (max 13 mm)
- 43 mm neck size - compatible with M12 DE dust extractor
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 CH-0	M12 CH-202C	M12 CH-602X
Battery pack capacity (Ah)	–	2.0	6.0
No. of batteries supplied	0	2	2
Charger supplied	–	40 min	90 min
Tool reception	SDS-Plus	SDS-Plus	SDS-Plus
Blow energy (EPTA)(J)	1.1	1.1	1.1
Max. drilling wood (mm)	13	13	13
Max. drilling steel (mm)	10	10	10
Max. drilling concrete (mm)	13	13	13
Vibration drilling (m/s ²)	4.4	4.4	4.4
Weight with battery pack (kg)	–	1.7	1.9
Supplied in	–	Kitbox	HD Box
Article Number	4933441947	4933441997	4933451510

SET OF 5 SDS-PLUS DRILL BITS, Ø 5 / 6 X 110 MM AND Ø 6 / 8 / 10 X 160 MM

Article Number **4932352338**


M12 FUEL


2 mode SDS-plus hammer


 Exceptionally low vibration value 4.4 m/s²


LED light

M12 DE | M12™ UNIVERSAL HAMMER VAC

- Fits all Milwaukee® SDS-plus and the majority of competitor's drills between 43-59 mm neck size, supplied with side handle and 3 neck collars
- Will extract 65 x Ø6 mm by 50 mm deep holes per charge
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Multi functionality - can be used as a dedicated dust extraction as well as a hand held vac, right or left mounting
- HEPA filter: 99.7 % efficient
- Automatic 5 sec switch off time delay to ensure dust from drilled hole is completely cleaned
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 DE-0C	M12 DE-201C
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	1
Charger supplied	–	40 min
Max. drill bit diameter (mm)	4 - 16	4 - 16
Max. drilling depth (mm)	120	120
Weight with battery pack (kg)	–	1.7
Supplied in	Kitbox	Kitbox
Article Number	4933440510	4933440500

M12 FPD

M12 FUEL™ SUB COMPACT PERCUSSION DRILL

- Milwaukee® designed and built brushless POWERSTATE™ motor delivers more power in a more compact size
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 13 mm metal chuck for quick bit changes and bit retention
- Electronic clutch with 16 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer
- Fuel gauge displays remaining charge
- Bright LED workspace illumination
- Flexible battery system: works with all Milwaukee® M12™ batteries



More power, more compact



13 mm metal chuck



Electronic clutch with 16 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer

M12 H | M12™ SUB COMPACT SDS-PLUS HAMMER

- Ergonomically designed, compact and light weight allows for work in tight spaces and reduces fatigue during all day use
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- L-shape, 2 mode hammer drill for hammer & rotary drilling for maximum versatility
- Low vibration at 6.7 m/s²
- Optimised hammer drilling up to 4 - 8 mm (max 13 mm)
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 H-0	M12 H-202C	M12 H-402C
Battery pack capacity (Ah)	–	2.0	4.0
No. of batteries supplied	0	2	2
Charger supplied	–	40 min	80 min
Tool reception	SDS-Plus	SDS-Plus	SDS-Plus
Blow energy (EPTA)(J)	0.9	0.9	0.9
Max. drilling wood (mm)	10	10	10
Max. drilling steel (mm)	8	8	8
Max. drilling concrete (mm)	13	13	13
Vibration drilling (m/s ²)	6.7	6.7	6.7
Weight with battery pack (kg)	–	1.6	1.8
Supplied in	–	Kitbox	Kitbox
Article Number	4933431355	4933431340	4933441164

	M12 FPD-0	M12 FPD-202X	M12 FPD-602X
Battery pack capacity (Ah)	–	2.0	6.0
No. of batteries supplied	0	2	2
Charger supplied	–	40 min	90 min
No load speed gear 1 (rpm)	0 - 450	0 - 450	0 - 450
No load speed gear 2 (rpm)	0 - 1700	0 - 1700	0 - 1700
Chuck capacity (mm)	13	13	13
Max. drilling wood (mm)	35	35	35
Max. drilling steel (mm)	13	13	13
Max. drilling masonry (mm)	13	13	13
Max. percussion rate (bpm)	0 - 25,500	0 - 25,500	0 - 25,500
Max. torque (Nm)	44	37	44
Weight with battery pack (kg)	–	1.2	1.5
Supplied in	–	HD Box	HD Box
Article Number	4933459801	4933459802	4933459806

M12 FDD | M12 FUEL™ SUB COMPACT DRILL DRIVER

- Milwaukee® designed and built brushless POWERSTATE™ motor delivers more power in a more compact size
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 13 mm metal chuck for quick bit changes and bit retention
- Electronic clutch with 16 torque settings and plus 1 for locked clutch drilling
- Fuel gauge displays remaining charge
- Bright LED workspace illumination
- Flexible battery system: works with all Milwaukee® M12™ batteries



M12 FUEL

	M12 FDD-0	M12 FDD-202X	M12 FDD-602X
Battery pack capacity (Ah)	–	2.0	6.0
No. of batteries supplied	0	2	2
Charger supplied	–	40 min	90 min
No load speed gear 1 (rpm)	0 - 450	0 - 450	0 - 450
No load speed gear 2 (rpm)	0 - 1700	0 - 1700	0 - 1700
Chuck capacity (mm)	13	13	13
Max. drilling wood (mm)	35	35	35
Max. drilling steel (mm)	13	13	13
Max. torque (Nm)	44	37	44
Weight with battery pack (kg)	–	1.2	1.5
Supplied in	–	HD Box	HD Box
Article Number	4933459815	4933459816	4933459820

M12 BPD | M12™ SUB COMPACT PERCUSSION DRILL

- Milwaukee® high performance sub compact percussion drill measures 190 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- 10 mm metal chuck for quick bit changes and bit retention
- Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 BPD-0	M12 BPD-202C	M12 BPD-402C
Battery pack capacity (Ah)	–	2.0	4.0
No. of batteries supplied	0	2	2
Charger supplied	–	40 min	80 min
No load speed gear 1 (rpm)	0 - 400	0 - 400	0 - 400
No load speed gear 2 (rpm)	0 - 1500	0 - 1500	0 - 1500
Chuck capacity (mm)	10	10	10
Max. drilling wood (mm)	22	22	22
Max. drilling steel (mm)	10	10	10
Max. drilling masonry (mm)	10	10	10
Max. percussion rate (bpm)	22,500	22,500	22,500
Max. torque (Nm)	30	30	38
Weight with battery pack (kg)	–	1.2	1.5
Supplied in	–	Kitbox	Kitbox
Article Number	4933441950	4933441940	4933441935

M12 FPDX | M12 FUEL™ SUB COMPACT PERCUSSION DRILL WITH REMOVABLE CHUCK

- Milwaukee® high performance compact 6-in-1 percussion drill system for extreme versatility
- Removable chuck system with 3 different heads for multiples of applications
- Milwaukee® designed and built brushless POWERSTATE™ motor
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 13 mm keyless chuck, full metal right angle 1/4" hex drive head and full metal offset 1/4" hex drive head
- 1/4" hex drive behind chuck fitting, reduces drill length to 138 mm when required
- Full metal planetary gearbox transmission for extreme durability
- LED light for workspace illumination
- Flexible battery system: works with all Milwaukee® M12™ batteries



M12 FUEL

	M12 FPDX-0	M12 FPDX-202XM12 FPDXKIT-202X
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	2
Charger supplied	–	40 min
No load speed gear 1 (rpm)	0 - 450	0 - 450
No load speed gear 2 (rpm)	0 - 1700	0 - 1700
Chuck capacity (mm)	13	13
Max. drilling wood (mm)	35	35
Max. drilling steel (mm)	13	13
Max. drilling masonry (mm)	13	13
Max. percussion rate (bpm)	0 - 25,500	0 - 25,500
Max. torque (Nm)	44	37
Weight with battery pack (kg)	–	1.2
Standard equipment	Removable chuck	Removable chuck, offset attachment, right angle attachment
Supplied in	–	HD Box
Article Number	4933464135	4933464136

M12 BDD | M12™ SUB COMPACT DRILL DRIVER

- Milwaukee® high performance sub compact drill driver measures 187 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- 10 mm metal chuck for quick bit changes and bit retention
- Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 BDD-0	M12 BDD-202C	M12 BDD-402C
Battery pack capacity (Ah)	–	2.0	4.0
No. of batteries supplied	0	2	2
Charger supplied	–	40 min	80 min
No load speed gear 1 (rpm)	0 - 400	0 - 400	0 - 400
No load speed gear 2 (rpm)	0 - 1500	0 - 1500	0 - 1500
Chuck capacity (mm)	10	10	10
Max. drilling wood (mm)	22	22	22
Max. drilling steel (mm)	10	10	10
Max. torque (Nm)	30	30	38
Weight with battery pack (kg)	–	1.2	1.4
Supplied in	–	Kitbox	Kitbox
Article Number	4933441930	4933441915	4933441925

M12 BDDX | M12™ SUB COMPACT DRILL DRIVER WITH REMOVABLE CHUCK

- Milwaukee® high performance sub compact 5-in-1 drill driver system for extreme versatility
- Removable chuck system with 3 different heads for multiples of applications
- Standard 10 mm keyless chuck, full metal right angle 1/4" hex drive head and full metal offset 1/4" hex drive head
- 1/4" hex drive behind chuck fitting, reduces drill length to 153 mm when required
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal planetary gearbox transmission for extreme durability
- LED light for workspace illumination
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 BDDX-202C	M12 BDDXKIT-202C
Battery pack capacity (Ah)	2.0	2.0
No. of batteries supplied	2	2
Charger supplied	40 min	40 min
No load speed gear 1 (rpm)	0 - 400	0 - 400
No load speed gear 2 (rpm)	0 - 1500	0 - 1500
Chuck capacity (mm)	10	10
Max. drilling wood (mm)	25	25
Max. drilling steel (mm)	10	10
Max. torque (Nm)	32	32
Weight with battery pack (kg)	1.2	1.2
Standard equipment	Removable FIXTEC chuck, belt clip, 25 mm P22 bit	Removable FIXTEC chuck, offset attachment, right angle drill attachment, belt clip, 25 mm P22 bit
Supplied in	Kitbox	Kitbox
Article Number	4933447830	4933447836

C12 RAD | M12™ SUB COMPACT RIGHT ANGLE DRILL

- Heavy Duty full metal gearbox and gears for superior durability and maximum torque
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Variable speed paddle switch trigger for comfortable working in any situation
- 10 mm chuck for quick bit changes and bit retention
- Electronic clutch with indicator light for complete control
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	C12 RAD-0	C12 RAD-202B
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	2
Charger supplied	–	40 min
No load speed (rpm)	0 - 800	0 - 800
Chuck capacity (mm)	10	10
Max. drilling wood (mm)	22	22
Max. drilling steel (mm)	10	10
Max. torque (Nm)	12	12
Weight with battery pack (kg)	–	1.1
Supplied in	–	Tool bag
Article Number	4933416900	4933441215

M12 CD | M12 FUEL™ SUB COMPACT DRIVER

- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 10x longer motor life, up to 2x more power and up to 2x more run time
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 1/4" Hex chuck for quick easy one handed bit change
- Fuel gauge displays remaining charge
- Bright LED workspace illumination
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 CD-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed gear 1 (rpm)	0 - 450
No load speed gear 2 (rpm)	0 - 1700
Tool reception	1/4" Hex
Max. drilling wood (mm)	25
Max. drilling steel (mm)	10
Max. torque (Nm)	37
Weight with battery pack (kg)	1.2
Supplied in	–
Article Number	4933440450

M12 BD | M12™ SUB COMPACT DRIVER

- Milwaukee® high performance sub compact screw driver measures 175 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- 1/4" Hex chuck for quick easy one handed bit change
- Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 BD-0	M12 BD-202C
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	2
Charger supplied	–	40 min
No load speed gear 1 (rpm)	0 - 400	0 - 400
No load speed gear 2 (rpm)	0 - 1500	0 - 1500
Tool reception	1/4" Hex	1/4" Hex
Max. drilling wood (mm)	22	22
Max. drilling steel (mm)	10	10
Wood screws to (mm)	6	6
Max. torque (Nm)	30	30
Weight with battery pack (kg)	–	1.0
Supplied in	–	Kitbox
Article Number	4933441910	4933441900

M12 BSD | M12™ SUB COMPACT SINGLE SPEED DRIVER

- Milwaukee® high performance compact screw driver measures 169 mm in length making it ideal for working within confined spaces
- Metal planetary gears for superior durability and maximum torque up to 20 Nm
- 1/4" Hex chuck for quick easy one handed bit change
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- 15 stage torque adjustment plus additional drilling for maximum flexibility
- Slimline soft grip handle
- Built in LED light illuminates the work surface
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 BSD-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	0 - 500
Max. drilling wood (mm)	16
Max. drilling steel (mm)	10
Max. torque (Nm)	20
Tool reception	1/4" Hex
Weight with battery pack (kg)	0.9
Supplied in	–
Article Number	4933447135

M12 FID

M12 FUEL™ SUB COMPACT 1/4" HEX IMPACT DRIVER

- Milwaukee® designed and built brushless POWERSTATE™ motor with faster speed in a more compact size of 130 mm
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- The Milwaukee® DRIVE CONTROL™ allows the user to shift to three different speed and torque settings, as well as a self-tapping mode to maximise application versatility
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 1/4" Hex chuck for quick and easy bit change
- On board fuel gauge and LED light
- Flexible battery system: works with all Milwaukee® M12™ batteries




Compact, lightweight design



DRIVE CONTROL™ allows the user to shift into 4 different modes to best suit application



One handed bit insertion

	M12 FID-0	M12 FID-202X
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	2
Charger supplied	–	40 min
No load speed (rpm)	0-1300 / 0-2400 / 0-3300 / 0-3300	0-1300 / 0-2400 / 0-3300 / 0-3300
Tool reception	1/4" Hex	1/4" Hex
Impact rate (ipm)	0 - 4000	0 - 4000
Max. torque (Nm)	147	147
Weight with battery pack (kg)	–	1.1
Supplied in	–	HD Box
Article Number	4933459822	4933459823

40 PC SHOCKWAVE IMPACT DUTY™ DRILL & DRIVER SET

Article Number **4932430908**



M12 BID | M12™ SUB COMPACT 1/4" HEX IMPACT DRIVER

- Milwaukee® high performance sub compact impact driver measures 165 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Heavy duty full metal gearbox and gears for superior durability and maximum torque
- 1/4" Hex chuck for quick and easy bit change
- Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 BID-0	M12 BID-202C
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	2
Charger supplied	–	40 min
No load speed (rpm)	0 - 2500	0 - 2500
Impact rate (ipm)	0 - 3300	0 - 3300
Tool reception	1/4" Hex	1/4" Hex
Max. torque (Nm)	112	112
Weight with battery pack (kg)	–	1.0
Supplied in	–	Kitbox
Article Number	4933441955	4933441960

M12 BRAID | M12™ SUB COMPACT RIGHT ANGLE IMPACT DRIVER

- Compact right angle impact driver measures 287 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics delivers best in class system durability
- Full metal gearbox and gears for superior durability and maximum torque of 68 Nm
- Compact head design with diameter of 35.6 mm
- Multi-handle design for multiple hand positions and maximum comfort
- 1/4" Hex chuck for quick easy one handed bit change
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 BRAID-0
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
No load speed (rpm)	0 - 2425
Impact rate (ipm)	0 - 3300
Tool reception	1/4" Hex
Max. torque (Nm)	68
Weight with battery pack (kg)	1.2
Supplied in	-
Article Number	4933451247

M12 FIWF12

M12 FUEL™ SUB COMPACT 1/2" IMPACT WRENCH

- More power, more compact, more control
- Up to 339 Nm of maximum torque
- 1/2" anvil with friction ring for quick and easy socket changes
- Milwaukee® designed and built brushless POWERSTATE™ motor delivers more power in a more compact size
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Better access in tight spaces with an overall length of only 124.5 mm
- 4-Mode DRIVE CONTROL™ with auto-shut off mode, offers the user precise control
- Bright LED workspace illumination
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 FIWF12-0	M12 FIWF12-422X
Battery pack capacity (Ah)	-	1x 2.0/1x 4.0
No. of batteries supplied	0	2
Charger supplied	-	80 min
No load speed (rpm)	1200/1800/2700/2700	1200/1800/2700/2700
Tool reception	1/2" square	1/2" square
Impact rate (ipm)	1100/2100/3200	1100/2100/3200
Max. torque (Nm)	339	339
Max. bolt diameter	M16	M16
Weight with battery pack (kg)	-	1.1
Supplied in	-	HD Box
Article Number	4933464615	4933464616

1/2" SHOCKWAVE IMPACT DUTY™ SOCKETS SET (10 PC)

Article Number **4932352861**



M12 FUEL



1/2" anvil with friction ring



Better access in tight spaces with an overall length of only 124.5 mm



4-Mode DRIVE CONTROL™ with auto-shut off mode

M12 FIW38 | M12 FUEL™ SUB COMPACT 3/8" IMPACT WRENCH

- More power, more compact, more control
- Up to 339 Nm of maximum torque
- 3/8" anvil with friction ring for quick and easy socket changes
- Milwaukee® designed and built brushless POWERSTATE™ motor delivers more power in a more compact size
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Better access in tight spaces with an overall length of only 121.9 mm
- 4-Mode DRIVE CONTROL™ with auto-shut off mode, offers the user precise control
- Bright LED workspace illumination
- Flexible battery system: works with all Milwaukee® M12™ batteries



M12 FUEL

	M12 FIW38-0	M12 FIW38-422X
Battery pack capacity (Ah)	-	1x 2.0/1x 4.0
No. of batteries supplied	0	2
Charger supplied	-	80 min
No load speed (rpm)	1200/1800/2700/2700	1200/1800/2700/2700
Tool reception	3/8" square	3/8" square
Impact rate (ipm)	1100/2100/3200	1100/2100/3200
Max. torque (Nm)	339	339
Max. bolt diameter	M16	M16
Weight with battery pack (kg)	-	1.1
Supplied in	-	HD Box
Article Number	4933464612	4933464613

M12 FIW14 | M12 FUEL™ SUB COMPACT 1/4" IMPACT WRENCH

- More power, more compact, more control
- Up to 115 Nm of maximum fastening torque
- Up to 136 Nm of maximum nut busting torque
- 1/4" anvil with friction ring for quick and easy socket changes
- Milwaukee® designed and built brushless POWERSTATE™ motor delivers more power in a more compact size
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Better access in tight spaces with an overall length of only 129.5 mm
- 4-Mode DRIVE CONTROL™ with auto-shut off mode, offers the user precise control
- Bright LED workspace illumination
- Flexible battery system: works with all Milwaukee® M12™ batteries



M12 FUEL

	M12 FIW14-0
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
No load speed (rpm)	1300/1900/3200/3200
Tool reception	1/4" square
Impact rate (ipm)	1300/2000/4300
Max. torque (Nm)	136
Max. bolt diameter	M12
Weight with battery pack (kg)	0.9
Supplied in	-
Article Number	4933464611

M12 BIW12 | M12™ SUB COMPACT 1/2" IMPACT WRENCH

- Milwaukee® high performance sub compact impact wrench measures 171 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Heavy duty full metal gearbox and gears for superior durability and maximum torque
- 1/2" square drive with pin detent for use with universal sockets
- Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 BIW12-0	M12 BIW12-202C
Battery pack capacity (Ah)	-	2.0
No. of batteries supplied	0	2
Charger supplied	-	40 min
No load speed (rpm)	0 - 2550	0 - 2550
Tool reception	1/2" square	1/2" square
Impact rate (ipm)	0 - 3400	0 - 3400
Max. torque (Nm)	138	138
Weight with battery pack (kg)	-	1.0
Supplied in	-	Kitbox
Article Number	4933447134	4933447133

M12 BIW38 | M12™ SUB COMPACT 3/8" IMPACT WRENCH

- Milwaukee® high performance sub compact impact wrench measures 165 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Heavy duty full metal gearbox and gears for superior durability and maximum torque
- 3/8" square drive with friction ring for use with universal sockets
- Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 BIW38-0	M12 BIW38-202C
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	2
Charger supplied	–	40 min
No load speed (rpm)	0 - 2500	0 - 2500
Tool reception	3/8" square	3/8" square
Impact rate (ipm)	0 - 3300	0 - 3300
Max. torque (Nm)	135	135
Weight with battery pack (kg)	–	1.0
Supplied in	–	Kitbox
Article Number	4933441985	4933441990

M12 FIR12 | M12 FUEL™ SUB COMPACT 1/2" RATCHET

- With up to 81 Nm of max torque and 175 rpm's, this tool is the ideal fastening solution for automotive mechanics, maintenance and repair professionals
- Low profile head design allows users better access in tight spaces
- The industry leading FUEL™ technology combined with a reinforced mechanism and Investment cast steel yoke housing provides greater durability for the professional user
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Variable speed metal trigger provides ultimate control of the tool
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- The LED light illuminates the work area while the on-board fuel gauge displays remaining run time
- Supplied with 3/8" adaptor
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 FIR12-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Tool reception	1/2" square
Max. torque (Nm)	81
No load speed (rpm)	0 - 175
Length (mm)	324
Weight with battery pack (kg)	1.5
Supplied in	–
Article Number	4933459800

M12 FIR38 | M12 FUEL™ SUB COMPACT 3/8" RATCHET

- With up to 75 Nm of max torque and 200 rpm's, this tool is the ideal fastening solution for automotive mechanics, maintenance and repair professionals
- Low profile head design allows users better access in tight spaces
- The industry leading FUEL™ technology combined with a reinforced mechanism and Investment cast steel yoke housing provides greater durability for the professional user
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Variable speed metal trigger provides ultimate control of the tool
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- The LED light illuminates the work area while the on-board fuel gauge displays remaining run time
- Supplied with 1/4" adaptor
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 FIR38-0	M12 FIR38-201B
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	1
Charger supplied	–	40 min
Tool reception	3/8" square	3/8" square
Max. torque (Nm)	75	75
No load speed (rpm)	0 - 200	0 - 200
Length (mm)	307	307
Weight with battery pack (kg)	–	1.4
Supplied in	–	Tool bag
Article Number	4933459797	4933459798

M12 FIR14 | M12 FUEL™ SUB COMPACT 1/4" RATCHET

- With up to 54 Nm of max torque and 250 rpm's, this tool is the ideal fastening solution for automotive mechanics, maintenance and repair professionals
- Low profile head design allows users better access in tight spaces
- The industry leading FUEL™ technology combined with a reinforced mechanism and Investment cast steel yoke housing provides greater durability for the professional user
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Variable speed metal trigger provides ultimate control of the tool
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- The LED light illuminates the work area while the on-board fuel gauge displays remaining run time
- Supplied with 3/8" adaptor
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 FIR14-0	M12 FIR14-201B
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	1
Charger supplied	–	40 min
Tool reception	1/4" square	1/4" square
Max. torque (Nm)	54	54
No load speed (rpm)	0 - 250	0 - 250
Length (mm)	291	291
Weight with battery pack (kg)	–	1.1
Supplied in	–	Tool bag
Article Number	4933459795	4933459796

M12 IR | M12™ SUB COMPACT RATCHET

- Pneumatic performance with cordless convenience, 47 Nm of torque and no load speed of 250 rpm
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Reinforced housing - provides high durability similar to steel ratchets
- Compact design - ideal for tight spaces and small engine bays
- Variable speed metal paddle switch trigger - provides greater user control during application
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 IR-201B 1/4	M12 IR-201B 3/8
Battery pack capacity (Ah)	2.0	2.0
No. of batteries supplied	1	1
Charger supplied	40 min	40 min
Tool reception	1/4" square	3/8" square
Max. torque (Nm)	40	47
No load speed (rpm)	0 - 250	0 - 250
Length (mm)	274	274
Weight with battery pack (kg)	0.9	0.9
Supplied in	Tool bag	Tool bag
Article Number	4933441725	4933441720

M12 SI | M12™ SUB COMPACT SOLDERING IRON

- Quick heat up time, the tool is ready to use in 20 - 30 seconds
- 3 locking head positions to work in multiple orientations - 0°, 45°, 90°
- Tool free replaceable tips
- Dual color LED lights to notify user: flashing green when tool is heating up, solid green when the tool is ready for operation and solid red when the tool is off but the tip is hot to touch until the red LED turns off
- Temperature monitoring to maintain heat throughout tough applications
- Bright LED light for increased visibility of soldering application
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 SI-0	M12 SI-201C
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	1
Charger supplied	–	40 min
Heater power (W)	90	90
Temperature range (°C)	400	400
Weight with battery pack (kg)	–	0.5
Supplied in	–	Kitbox
Article Number	4933459760	4933459761

M12 BI | M12™ SUB COMPACT INFLATOR

- Compact lightweight design for fast inflation of car, light truck and compact equipment tires
- High efficiency motor & pump
- Anti-vibration stand with all rubber feet for no movement while inflating
- Auto shut-off technology inflates to users pre-selected pressure for highly accurate inflation
- Illuminated LCD display with a digital pressure and fuel gauge that displays remaining charge
- Nozzle & hose storage, easily stores 66 cm hose and attachments, with an all-brass schrader chuck
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life (Battery sold separately)
- Flexible battery system: works with all Milwaukee® M12™ batteries
- Supplied with a ball inflation needle, presta chuck, inflator nozzle and schrader chuck



	M12 BI-0
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
Hose length (mm)	660
Max. pressure (bar / PSI)	8.27 / 120
No load air delivery (l/min)	24.9
Duty cycle	50% at 10 min On and 10 min Off
Gauge accuracy (%)	± 3%
Weight with battery pack (kg)	1.6
Supplied in	-
Article Number	4933464124

M12 CHZ | M12 FUEL™ SUB COMPACT HACKZALL™

- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 6x longer motor life and up to 70% faster cutting in certain applications
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Milwaukee® patented FIXTEC clamp for fast and easy keyless blade change
- Counter balance mechanism lowers vibration to 6.5 m/s² allowing the operator to work safely for longer periods of time reducing fatigue
- Sealed gearbox prevents water and debris entering the housing
- LED light illuminates the cutline in low light conditions
- Compact and light weight allows users to complete applications in restricted areas
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 CHZ-0	M12 CHZ-402C	M12 CHZ-602X
Battery pack capacity (Ah)	-	4.0	6.0
No. of batteries supplied	0	2	2
Charger supplied	-	80 min	90 min
No load stroke rate (spm)	0 - 3000	0 - 3000	0 - 3000
Stroke length (mm)	15.9	15.9	15.9
Weight with battery pack (kg)	-	1.6	1.6
Supplied in	-	Kitbox	HD Box
Article Number	4933446960	4933446950	4933451511

10 PC SET; 2 X 49005460, 3 X 49005614, 3 X 49005424, 2 X 49005418

Article Number **49220220**

C12 HZ | M12™ SUB COMPACT HACKZALL™

- Milwaukee® high performance compact one handed use HACKZALL™, measuring only 280 mm in length, making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Milwaukee® patented FIXTEC clamp for fast and easy keyless blade change
- Low vibration at 10.5 m/s²
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	C12 HZ-0	C12 HZ-202C
Battery pack capacity (Ah)	-	2.0
No. of batteries supplied	0	2
Charger supplied	-	40 min
No load stroke rate (spm)	0 - 3000	0 - 3000
Stroke length (mm)	13	13
Weight with battery pack (kg)	-	1.2
Supplied in	-	Kitbox
Article Number	4933411925	4933441195

10 PC SET; 2 X 49005460, 3 X 49005614, 3 X 49005424, 2 X 49005418

Article Number **49220220**

M12 CCS44 | M12 FUEL™ SUB COMPACT CIRCULAR SAW

- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 2x longer motor life and up to 2x more cuts per charge
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 50° bevel capacity
- Magnesium upper and lower guards provide best in class durability for impact resistance
- Magnesium shoe reduces weight and maximises durability
- Integrated dust blower keeps cut line clear
- LED light illuminates the cut line
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 CCS44-0	M12 CCS44-402C	M12 CCS44-602X
Battery pack capacity (Ah)	-	4.0	6.0
No. of batteries supplied	0	2	2
Charger supplied	-	80 min	90 min
No load speed (rpm)	3600	3600	3600
Max. cutting depth 90° (mm)	44	44	44
Max. cutting depth 45° (mm)	33	33	33
Blade diameter (mm)	140	140	140
Bore size (mm)	20	20	20
Weight with battery pack (kg)	-	2.7	2.7
Supplied in	-	Kitbox	HD Box
Article Number	4933448225	4933448235	4933451512

M12 JS | M12™ SUB COMPACT JIGSAW

- New grip design combines the best features from both top handle and barrel grip jigsaw design
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Variable speed - electronic trigger provides user flexibility and control
- Smooth cut - minimal vibration during cutting provides ultra smooth performance
- Precision roller guide increases user control and reduces blade deviation
- Line of sight - the compact tool design improves cut line visibility
- Tool free bevel facility - quick and easy bevel adjustment up to 45°
- QUIK-LOK™ T-Shank blade clamp
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries
- Non marking shoe comes as standard to protect work surfaces from scratching



	M12 JS-0	M12 JS-402B
Battery pack capacity (Ah)	-	4.0
No. of batteries supplied	0	2
Charger supplied	-	80 min
No load stroke rate (spm)	0 - 2800	0 - 2800
Stroke length (mm)	19	19
Weight with battery pack (kg)	-	2.1
Supplied in	-	Tool bag
Article Number	4933431305	4933441700

75 X 2.5 MM T 101 B JIGSAW BLADE, 5 PCS

Article Number **4932254061**

M12 BST | M12™ SUB COMPACT STAPLER

- Breakthrough performance limits user fatigue by eliminating the repetitive motion of hand tools
- Ready to Fire Technology eliminates ramp-up time between each staple discharge
- Bump fire and sequential fire operation allows the user to fire quickly and accurately
- 2000 staples fired with one 2.0 Ah battery pack
- Fires standard T50 staples from 6 to 14 mm
- Dry-Fire lock out stops the stapler from being fired when empty
- Compact length, height and width for easier access to compact spaces
- Adjustable belt hook for user convenience
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 BST-0	M12 BST-202X
Battery pack capacity (Ah)	-	2.0
No. of batteries supplied	0	2
Charger supplied	-	40 min
Staple strip	T50	T50
Staple strip width (mm)	11.4	11.4
Staple strip length (mm)	6 - 14	6 - 14
Magazine capacity	89	89
Cycle rate (min)	140	140
Weight with battery pack (kg)	-	1.6
Supplied in	-	HD Box
Article Number	4933459634	4933459635

T50 0.5 X 1.27 MM STAPLES, 6 MM TOTAL LENGTH

Article Number **4932459145**

M12 BPRT | M12™ SUB COMPACT RIVET TOOL


- Up to 325 x 4.8 mm stainless steel rivets on a single charge with a 2.0 Ah battery pack
- Suitable for all aluminium, steel, stainless steel and copper rivets up to 4.8 mm
- Rivets in one stroke with a 20.32 mm stroke length
- Retention nose pieces hold rivets in any orientation
- Tool-free access to easily clean jaws. On-board nose piece storage and removal tool for user convenience
- On board fuel gauge and LED light for added user convenience and illumination in low lit working conditions
- Ergonomic design with 273 mm H x 66.8 mm W - 165 mm in length without mandrel collector
- Integrated belt hook and lanyard tie off point
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries
- Supplied with 4 x retaining tips



	M12 BPRT-0	M12 BPRT-201X
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	1
Charger supplied	–	40 min
Max. pulling force (N)	9000	9000
Max. rivets popped with M12 B2 battery (mm)	325 x 4.8	325 x 4.8
Rivet diameter range (mm)	2.4 - 4.8	2.4 - 4.8
Stroke length (mm)	20.32	20.32
Dimensions (mm)	273 x 66 x 8 x 230	273 x 66 x 8 x 230
Weight with battery pack (kg)	–	2.1
Supplied in	–	HD Box
Article Number	4933464404	4933464405

152 MM NOSE EXTENSION KIT FOR M12™ RIVET TOOL

Article Number 48950100



C12 PN | M12™ SUB COMPACT PALM NAILER

- Professional power effectively drives 100 mm framing nails in less than 3 seconds
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Superior ergonomics – user-preferred palm style grip provides outstanding comfort and control
- Fits into locations where a hammer cannot be swung
- Increased run time: drives up to 100 x 90 mm nails on a single charge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Flexible battery system: works with all Milwaukee® M12™ batteries



	C12 PN-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Max. percussion rate (bpm)	2700
Max. nail size (mm)	90
Blow energy (EPTA)(J)	2.9
Weight with battery pack (kg)	1.6
Supplied in	–
Article Number	4933427182

C12 MT | M12™ SUB COMPACT MULTI-TOOL

- Versatile cordless solution for cutting and removal applications
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Variable speed (5000 - 20,000 rpm) and 1.5° left/right oscillation movement allows quick completion of professional applications into materials such as metal, wood and plastic
- Will accept competitor accessories
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries
- Supplied with an adapter, plunge cut blade OSC 112, sanding backing pad, 5 x sanding sheets



	C12 MT-0	C12 MT-202B	C12 MT-402B
Battery pack capacity (Ah)	–	2.0	4.0
No. of batteries supplied	0	2	2
Charger supplied	–	40 min	80 min
Oscillation angle left/ right (°)	1.5	1.5	1.5
No load speed (rpm)	5000 - 20,000	5000 - 20,000	5000 - 20,000
Weight with battery pack (kg)	–	1.0	1.2
Supplied in	–	Tool bag	Tool bag
Article Number	4933427180	4933441710	4933441705

32 MM PLUNGE CUT BLADE. PLUNGE / RECESS / FLUSH CUTTING IN WOOD AND PVC

Article Number 48900030



C12 RT | M12™ SUB COMPACT ROTARY TOOL

- Versatile cordless solution for cutting and removal applications
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Variable speed (5000 - 32,000 rpm)
- 3.2 mm collet fits most current accessories in the market
- Spindle lock mechanism for easy accessory changes
- Superior ergonomics and lightweight
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Flexible battery system: works with all Milwaukee® M12™ batteries



	C12 RT-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	5000 - 32,000
Collet capacity (mm)	3.2
Weight with battery pack (kg)	0.6
Supplied in	–
Article Number	4933427183

M12 BS | M12™ SUB COMPACT BANDSAW


- Compact light weight design for cutting with one hand overhead in existing installations and in tight spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Cuts a multitude of materials: steel, stainless steel, copper, plastic, aluminium
- Cold cutting - spark and burr free
- Clean cut - balanced handle design combined with 8-large ball bearing blade supports provide best in class cut quality
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries
- Supplied with a 18 Tpi blade



	M12 BS-0	M12 BS-402C
Battery pack capacity (Ah)	–	4.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
No load speed (rpm)	0 - 85	0 - 85
Max. cutting capacity (mm)	41 x 41	41 x 41
Blade length (mm)	687.57	687.57
Weight with battery pack (kg)	–	3.2
Supplied in	–	Kitbox
Article Number	4933431310	4933441805

3 PC BANDSAW BLADE SET 687.57 MM LENGTH, 2.5 MM TO 8 MM MATERIAL WALL THICKNESS, 18 TEETH PER INCH WITH 1.4 MM TOOTH PITCH

Article Number 48390572



M12 FCOT | M12 FUEL™ SUB COMPACT MULTI-MATERIAL CUT-OFF TOOL

- Fast accurate cutting with up to 20,000 RPM
- Optimised ergonomic design for best control and one-handed use. Only 1.1 kg and 226 mm in length
- Multi-material cutting capability with variety of blades available (metal cut-off wheel, carbide abrasive blade and diamond tile blade)
- A very capable problem solving tool for cutting steel, stainless steel, non-ferrous materials, drywall, fibre cement, plastic and ceramics
- Easily adjustable guard and unique forward/reverse selectable blade rotation direction to protect user from debris in various cutting positions
- Quick release dust shoe with depth adjustment and optional dust extraction port
- Milwaukee® designed and built brushless POWERSTATE™ motor delivers more power in a more compact size
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life



	M12 FCOT-0	M12 FCOT-422X
Battery pack capacity (Ah)	–	1x 2.0 + 1x 4.0
No. of batteries supplied	0	2
Charger supplied	–	80 min
No load speed (rpm)	20,000	20,000
Max. cutting depth (mm)	16.3	16.3
Disc diameter (mm)	76	76
Bore size (mm)	10	10
Weight with battery pack (kg)	–	1.1
Supplied in	–	HD Box
Article Number	4933464618	4933464619

M12 BPS | M12™ SUB COMPACT POLISHER / SANDER

- Variable two speed selection (0-2800 / 0-8300 RPM) for both polishing and sanding applications
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Large capacity of 76 mm polishing sponge and 50 mm sanding pad size for fast job completion
- Long run time allows frequent task completion with one battery charge
- Compact design with only 130 mm allows access to hard areas
- Spindle lock allows fast, tool free accessory change
- Detachable 2 position side handle
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 BPS-0	M12 BPS-421X
Battery pack capacity (Ah)	–	1 x 2.0 + 1 x 4.0
No. of batteries supplied	0	2
Charger supplied	–	40 min
No load speed gear 1 (rpm)	0 - 2800	0 - 2800
No load speed gear 2 (rpm)	0 - 8300	0 - 8300
Disc diameter (mm)	76	76
Spindle size	M9 x 0.75	M9 x 0.75
Weight with battery pack (kg)	–	1.0
Supplied in	–	HD Box
Article Number	4933447791	4933447799

LAMBS WOOL POLISHING PAD, HOOK AND LOOP FIXATION. FOR USE WITH POLISHING/SANDING BACKING PAD

Article Number 4932430838



M12 HV | M12™ SUB COMPACT STICK VAC

- Excellent suction power for wood, metal and common debris
- Clear viewing window gives the user the ability to see debris build up
- Lock on switch reduces fatigue during sustained use
- Versatile accessories for small or large clean up areas
- Compact design makes it easy to clean in tight spaces
- Secure canister lock guards against unwanted spillage
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 HV-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Air volume (l/min)	934
Airflow speed (m³/h)	56
Max. vacuum (mbar)	31.1
Capacity solids (l)	0.6
Hose diameter (mm)	22.5
Weight with battery pack (kg)	1.2
Supplied in	–
Article Number	4933448390

M12 GG | M12™ SUB COMPACT GREASE GUN

- Powerful 12 V motor delivers over 562 bar max operating pressure
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Best in class run time - dispenses up to 7 cartridges per charge
- Superior handle balance and ergonomics - only 355 mm long and 3.2 kg
- Air bleeder valve - priming mechanism for quick flow
- Integrated hose storage & shoulder strap loop - added user convenience and less down time
- Three way loading - bulk, cartridge and suction capable
- Grease capacity 400 ml cartridge, 473 ml bulk
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries
- Supplied with 914 mm x 14.4 mm high pressure flex hose with spring guard and grease coupler



	M12 GG-0	M12 GG-401B
Battery pack capacity (Ah)	–	4.0
No. of batteries supplied	0	1
Charger supplied	–	80 min
Pressure (bar)	562	562
Weight with battery pack (kg)	–	3.2
Supplied in	–	Tool bag
Article Number	4933440435	4933441675

M12 PCG/310 | M12™ SUB COMPACT CAULK GUN WITH 310 ML CARTRIDGE HOLDER

- Up to 1780 N of force
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all construction adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 PCG/310C-0	M12 PCG/310C-201B
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	1
Charger supplied	–	40 min
Max. pushing force (N)	1780	1780
Speed settings	6	6
Standard equipment	310 ml cart. holder	310 ml cart. holder
Weight with battery pack (kg)	–	1.9
Supplied in	–	Tool bag
Article Number	4933441783	4933441655

310 ML STANDARD CARRIAGE. ACCEPTS ALL STANDARD 250 ML AND 310 ML TUBES/CARTRIDGES

Article Number 48080900



M12 PCG/400 | M12™ SUB COMPACT CAULK GUN WITH 400 ML TUBE

- Up to 1780 N of force
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all construction adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 PCG/400A-0	M12 PCG/400A-201B
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	1
Charger supplied	–	40 min
Max. pushing force (N)	1780	1780
Speed settings	6	6
Standard equipment	400 ml alum. tube	400 ml alum. tube
Weight with battery pack (kg)	–	1.9
Supplied in	–	Tool bag
Article Number	4933441780	4933441655

400 ML ALUMINIUM SAUSAGE TUBE BARREL. REQUIRES PLUNGER ROD (48091090) AND PISTON (44700375)

Article Number 4932352844



M12 PCG/600 | M12™ SUB COMPACT CAULK GUN WITH 600 ML TUBE

- Up to 1780 N of force
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all construction adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 PCG/600A-0	M12 PCG/600A-201B
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	1
Charger supplied	–	40 min
Max. pushing force (N)	1780	1780
Speed settings	6	6
Standard equipment	600 ml alum. tube	600 ml alum. tube
Weight with battery pack (kg)	–	1.9
Supplied in	–	Tool bag
Article Number	4933441786	4933441670

600 ML ALUMINIUM SAUSAGE TUBE BARREL. REQUIRES PLUNGER ROD (48091091) AND PISTON (44700375)

Article Number 4932352845



C12 PC | M12™ SUB COMPACT COPPER PIPE CUTTER

- Milwaukee® high performance 500 rpm motor cuts 12 mm copper pipe in less than 3 seconds
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Auto locking cut mechanism cuts installed copper tubing with as little as 37 mm clearance
- Auto adjusting jaws – automatically adjust to pipe size
- All metal sealed front end – rust and corrosion resistant cut head
- Slimline soft grip handle
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- Flexible battery system: works with all Milwaukee® M12™ batteries



	C12 PC-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Copper tubes (mm)	12, 15, 18, 22, 25, 28
Minimum space for tube cutting (mm)	80
Length (mm)	360
Weight with battery pack (kg)	1.5
Supplied in	–
Article Number	4933411920

PIPE CUTTER WHEELS. SUITABLE FOR COPPER PIPE. NOT SUITABLE FOR PLASTIC OR STAINLESS STEEL PIPE



Article Number 48380010

C12 PPC | M12™ SUB COMPACT PEX CUTTER

- Massive cutting pressure of 175 kg/cm²
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Powerful mechanism cuts up to 50 mm PVC pipe in 3 seconds
- Heavy Duty full metal gearbox and gears for superior durability and maximum torque
- Variable speed trigger for complete cut out control
- Super sharp blade for blur free cuts
- Highly efficient mechanism delivers over 200 cuts per charge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- Flexible battery system: works with all Milwaukee® M12™ batteries



	C12 PPC-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Max. cutting capacity (mm)	50
No load speed (rpm)	0 - 500
Weight with battery pack (kg)	1.9
Supplied in	–
Article Number	4933416550

M12 CC | M12™ SUB COMPACT CABLE CUTTER

- Professional capacity Ø32 mm - powerful jaws cut effortlessly through large cable
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Extended run time - delivers up to 60 cuts of 4 x 35 mm² copper per charge
- Compact front end - goes straight to the cable in panels or electrical cabinets without long handles looping or ratcheting
- Superior cut quality - Milwaukee® designed blade geometry delivers a flat, round and installation ready cut
- Auto-release lever - provides the ability to cut, reload and quickly repeat
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 CC-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Max. cutting diameter (mm)	32
Cutting force (kN)	32
Speed settings	2
Weight with battery pack (kg)	3.0
Supplied in	–
Article Number	4933431600

C12 JSR | M12™ SUB COMPACT RADIO WITH MP3 PLAYER CONNECTION

- Advanced technology tuner for high reception and clarity
- Powers from either M12™ battery or 230 V mains supply
- At least 8 hour run time on a M12™ Milwaukee® battery
- Weather sealed auxiliary compartment protects Mp3 players and other audio devices
- Digital display tuner for accurate signal selection
- Mute button for instant volume kill
- 220 - 240 V power adapter, 3.5 mm jack plug for auxiliary connection, i.e. iPods
- Flexible battery system: works with all Milwaukee® M12™ batteries



	C12 JSR-0
Voltage (DC) (V)	12
Voltage (AC) (V)	220-240
Battery type	Li-ion
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Dimensions (mm)	267 x 102 x 178
Weight (kg)	1.8
Supplied in	–
Article Number	4933416365

M12 JSSP | M12™ JOBSITE BLUETOOTH® SPEAKER

- Advanced technology Bluetooth® jobsite speaker
- Connect wirelessly with portable electronic devices from up to 10 m away
- Loud, clear sound at all volumes
- Premium speaker with bass port
- Drop, water and debris resistant to withstand tough conditions on and off the jobsite
- Rugged over mould, metal speaker grill
- 2.1 A USB charger, charges phones, tablets and media players
- Up to 25 hrs run time per charge with M12™ 4.0 Ah battery
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 JSSP-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Dimensions (mm)	105.5 x 153
Speaker output (W)	5
Weight (kg)	0.5
Supplied in	–
Article Number	4933448380

M12-18 JSSP | M12™ - M18™ BLUETOOTH® SPEAKER

- Advanced technology Bluetooth® jobsite speaker
- Bluetooth® wireless range of up to 30 m
- Flexible battery system: works with all Milwaukee® M12™ & M18™ batteries
- IP54 rated, water and debris resistant to withstand tough conditions on and off the jobsite
- Loud, clear sounds at all volumes
- 2.1A USB charger, charges phones, tablets and media players
- Premium speaker with bass port



	M12-18 JSSP-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Dimensions (mm)	360 x 165 x 165
Speaker output (W)	40
Weight with battery pack (kg)	2.3
Supplied in	–
Article Number	4933459275

M12 FPP2A | M12 FUEL™ POWERPACK

- M12 FPD - M12 FUEL™ sub compact percussion drill
- M12 FID - M12 FUEL™ sub compact 1/4" Hex impact driver

M12 FUEL



	M12 FPP2A-402X	M12 FPP2A-602X
Battery pack capacity (Ah)	4.0	6.0
No. of batteries supplied	2	2
Charger supplied	80 min	90 min
Supplied in	HD Box	HD Box
Article Number	4933459808	4933459810

M12 FPP2B | M12 FUEL™ POWERPACK

- M12 FPD - M12 FUEL™ sub compact percussion drill
- M12 CH - M12 FUEL™ sub compact SDS-Plus hammer

M12 FUEL



	M12 FPP2B-402X	M12 FPP2B-602X
Battery pack capacity (Ah)	4.0	6.0
No. of batteries supplied	2	2
Charger supplied	80 min	90 min
Supplied in	HD Box	HD Box
Article Number	4933459812	4933459813

M12 BPP2D | M12™ POWERPACK

- M12 BDD - M12™ sub compact drill driver
- C12 MT - M12™ sub compact multi-tool



	M12 BPP2D-402B
Battery pack capacity (Ah)	4.0
No. of batteries supplied	2
Charger supplied	80 min
Supplied in	Tool bag
Article Number	4933441250

M12 BPP3A | M12™ POWERPACK

- M12 BDD - M12™ sub compact drill driver
- M12 BID - M12™ sub compact 1/4" Hex impact driver
- M12 TLED - M12™ LED torch



	M12 BPP3A-202B
Battery pack capacity (Ah)	2.0
No. of batteries supplied	2
Charger supplied	40 min
Supplied in	Tool bag
Article Number	4933441225

M12 BPP2B | M12™ POWERPACK

- M12 BPD - M12™ sub compact percussion drill
- M12 BID - M12™ sub compact 1/4" Hex impact driver



	M12 BPP2B-421C
Battery pack capacity (Ah)	1 x 2.0 & 1 x 4.0
No. of batteries supplied	2
Charger supplied	80 min
Supplied in	Kitbox
Article Number	4933443497

M12 BPP2C | M12™ POWERPACK

- M12 BDD - M12™ sub compact drill driver
- C12 HZ - M12™ sub compact HACKZALL™



	M12 BPP2C-402B
Battery pack capacity (Ah)	4.0
No. of batteries supplied	2
Charger supplied	80 min
Supplied in	Tool bag
Article Number	4933441230

M12 BPP4A | M12™ POWERPACK

- M12 BDD - M12™ sub compact drill driver
- M12 BID - M12™ sub compact impact driver
- C12 HZ - M12™ sub compact HACKZALL™
- M12 TLED - M12™ LED torch



	M12 BPP4A-202B
Battery pack capacity (Ah)	2.0
No. of batteries supplied	2
Charger supplied	40 min
Supplied in	Tool bag
Article Number	4933441240

TEST & MEASUREMENT



M12 IC | M12™ SUB COMPACT M-SPECTOR™ 360° CAMERA



- Rotating screen: screen rotates 270 degrees providing the user fluid image control
- Optimised 68.6 mm LCD: digital image and larger screen delivers crisp, clear picture
- 9 mm 640 x 480 digital image sensor: superior image quality in nearly half the size
- 4 surround LED lights: best in class brightness without shadow or glare
- Enhanced cable: aluminium head and improved flexibility deliver unmatched durability and pipe manoeuvrability
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries
- Accessories: hook, magnet, and mirror attachments help to inspect and solve



	M12 IC-0 (S)	M12 IC-201C (S)
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	1
Charger supplied	–	40 min
Display size (mm)	68	68
Display resolution (pixels)	320 x 240	320 x 240
Camera head diameter (mm)	9	9
Camera cable length (mm)	914	914
Weight with battery pack (kg)	–	0.6
Supplied in	–	Kitbox
Article Number	4933431615	4933441680

M12 IC AV3 | M12™ DIGITAL INSPECTION CAMERA



- Removable screen, screen can be removed from console and works within a range of 10 m
- M12™ digital inspection camera 4x zoom and screen rotation
- Optimised 85 mm LCD, digital image and larger screen delivers crisp, clear picture
- 12 mm 320 x 240 digital image sensor, superior image quality in improved larger screen
- 4 surround LED lights, for best in class brightness without shadow or glare
- Supplied with 8 GB SD memory card and 2.7 m digital cable
- Enhanced cable, aluminium head and improved flexibility delivers unmatched durability and manoeuvrability
- Articulating head attachment available as an accessory
- Flexible battery system, works with all Milwaukee® M12™ batteries



	M12 IC AV3-201C
Battery pack capacity (Ah)	2.0
No. of batteries supplied	1
Charger supplied	40 min
Display size (mm)	85
Display resolution (pixels)	320 x 240
Camera head diameter (mm)	12
Cable length (m)	2.7
Image zoom	4x
Weight with battery pack (kg)	0.7
Supplied in	Kitbox
Article Number	4933451367

2309-60 | ALKALINE INSPECTION CAMERA



- Optimised 65.8 mm LCD screen, digital image and large screen delivers crisp clear picture
- 9 mm 320 x 240 digital image sensor, superior image quality in nearly half the size
- Light weight sub 0.5 kg design
- Anti glare function allowing better screen visibility
- Supplied with 9V alkaline battery for over an hour continuous run time



	2309-60
Battery type	2 x AA
Display size (mm)	65.8
Display resolution (pixels)	320 x 240
Camera head diameter (mm)	9
Cable length (m)	0.914
Weight with battery pack (kg)	0.5
Supplied in	Kitbox
Article Number	4933451526

2205-40 | FORK METER FOR ELECTRICIANS

- TRMS always guarantees accurate readings
- High contrast, easy to read display provides clearer readings
- Built-in non-contact voltage detector
- CAT III 1000 V/CAT IV 600 V for increased safety
- Rugged over-moulding for increased durability and grip
- Built-in LED work light – lights the work area
- Side mounted dial for one-handed use
- Simplified user interface and feature set specifically tailored to the electrician
- Supplied with electrical test lead set and 2 x AA batteries



2205-40	
Fork opening (mm)	16
Current AC (amps)	200
Voltage (AC) (V)	1000
Voltage (DC) (V)	1000
Lo-Z measurement	Yes
Resistance (kΩ)	40
Continuity	Yes
Battery type	2 x AA
Weight with battery pack (kg)	0.3
Supplied in	Tool bag
Article Number	4933416972



2217-40 | DIGITAL MULTIMETER

- TRMS always guarantees accurate readings
- High contrast, easy to read display provides clearer readings
- Cat III 600 V for increased safety
- Side mounted dial for one-handed use
- Feature set tailored to electrician – for intuitive use
- Lo-Z. – always guaranteed accurate readings
- Versatile contact temperature measurement
- Slide rail for accessory mount
- Supplied with electrical test lead set, thermocouple (dual banana) and 2 x AA batteries



2217-40	
Current AC/ DC (amps)	10
Voltage AC/DC (V)	600
Lo-Z measurement	Yes
Resistance (kΩ)	40,000
Continuity	Yes
Capacitance (µF)	1000
Contact temperature (°C)	-40 - +538
Frequency (Hz)	2.00 Hz - 50.00 kHz
Battery type	2 x AA
Weight with battery pack (kg)	0.4
Supplied in	Tool bag
Article Number	4933416976



2212-20 | AUTO VOLTAGE / CONTINUITY TESTER

- Provides measurements down to decimals and displays them on an easy-to-read backlit LCD
- Automatically determines the need for voltage or continuity tests and display all measurements with proper resolution
- Compatible with accessories for carrying or mounting
- LED worklight for low lit areas
- Dual LED and audible indicators for fast and convenient test results
- Replaceable test leads for greater flexibility
- Rugged over-moulding protects your meter in any environment



2212-20	
Voltage AC/DC (V)	600
Temperature range (°C)	0 - 50
Safety rating	CAT IV 600 V
Continuity	Yes
Battery type	2 x AAA
Weight with battery pack (kg)	0.3
Supplied in	-
Article Number	4933447776



2235-40 | LIGHT COMMERCIAL CLAMP METER

- TRMS always guarantees accurate readings
- CAT III 600 V for increased safety
- Rugged over-moulding increases durability and user grip
- Built-in LED work light – lights the work area
- Side mounted dial for one-handed use
- Thin jaw profile for easier wire measurement in panels or in bundles
- Supplied with electrical test lead set and 2 x AA batteries



2235-40	
Jaw size (mm)	25
AC Amps (A)	400
Voltage AC/DC (V)	600
Lo-Z measurement	No
Resistance (kΩ)	0.4
Continuity	Yes
Battery type	2 x AA
Weight with battery pack (kg)	0.3
Supplied in	-
Article Number	4933427315



2216-40 | LIGHT COMMERCIAL MULTIMETER

- TRMS always guarantees accurate readings
- CAT III 600 V for increased safety
- Rugged over-moulding increases durability and user grip
- Side mounted dial for one-handed use
- Feature set tailored to electrician – for intuitive use
- Auto range to mV
- Supplied with electrical test lead set and 2 x AA batteries



2216-40	
Current AC/ DC (amps)	10
Voltage (AC) (V)	6.00 mV - 600
Voltage (DC) (V)	600
Lo-Z measurement	No
Resistance (kΩ)	40,000
Continuity	Yes
Frequency (Hz)	10 kHz - 50 kHz
Battery type	2 x AA
Weight with battery pack (kg)	0.4
Supplied in	-
Article Number	4933427309



2267-40 | 10:1 INFRARED TEMP-GUN™

- 10:1 distance to spot ratio, a 1 m spot from 10 m away
- Up to -30°C to 400°C temperature range
- Premium LCD display for superior readability
- Simplified buttons and setup for faster scanning
- Raised overmolding protects lens and screen from direct impact



2267-40	
Temperature range (°C)	-30 - 400
Basic accuracy (%)	± 2
Repeatability (%)	± 0.08
Emissivity	0.95
Battery type	2 x AA
Weight with battery pack (kg)	0.3
Supplied in	-
Article Number	4933451906



2200-40 | VOLTAGE DETECTOR

- Wide 50 - 1000 AC voltage range
- CAT IV 1000 V for highest safety rating
- Tip for checking outlets
- Green light indicates tool is on
- Loud beeper indicates voltage
- Blinking red light indicates voltage
- On/Off button
- Pocket clip for easy storage



	2200-40
Voltage (AC) (V)	50 - 1000
Safety rating	CAT IV 1000 V
Battery type	2 x AAA
Weight with battery pack (kg)	0.4
Supplied in	-
Article Number	4932352561



LDM 30 | 30 M LASER DISTANCE METER

- Easy to use one person point and shoot system
- IP54 water & dust protection
- Auto shut off and low power indication
- Metric & Imperial units of measurement
- Very slim housing design with belt clip for easy transport
- Two easy to touch measure buttons on the front and side of the housing
- Enables user to perform single measurements & continuous tracking
- Large 3 line LCD graphical display with automatic white backlight
- Display shows last three measurements



	LDM 30
Max. measurement range (m)	30
Accuracy	± 2
Display	LCD
Display size (mm)	25 x 25
Laser classification	Class 2
Dimensions (mm)	101 x 38 x 28
Range (m)	0.15 - 30
Battery type	2 x AAA
Weight with battery pack (kg)	0.1
Auto-level measurements	No
Pythagoras function	No
Inclination sensor	No
Height tracking	No
Supplied in	Blister
Article Number	4933459276



LDM 45 | 45 M LASER DISTANCE METER

- Easy to use one person point and shoot system
- IP54 water & dust protection
- Metric & Imperial units of measurement
- Easy to touch measure buttons on the front and side of the housing
- Enables user to perform single measurements & continuous tracking
- Offers several different measurement functions that allow users to add and subtract values, calculate linear distance, surface area, total area and volume
- Large 3 line 50 mm diameter multi-color LCD graphical display for optimised visibility
- Display shows last three measurements and history menu shows the last 30 calculations
- Built-in 2-position auto-reference fold out pin for easy in corner measurements
- Auto shut off and low power indication
- Slim housing for easy handling and nylon carry pouch for safe transport



	LDM 45
Max. measurement range (m)	45
Accuracy	± 1.5
Display	LCD
Display size (mm)	31.5 x 40
Laser classification	Class 2
Dimensions (mm)	105 x 48 x 24
Range (m)	0.15 - 45
Battery type	2 x AAA
Weight with battery pack (kg)	0.11
Auto-level measurements	No
Pythagoras function	No
Inclination sensor	No
Height tracking	No
Supplied in	-
Article Number	4933459277



LDM 50 | 50 M LASER DISTANCE METER

- Easy to use one person point and shoot system
- Very slim housing design with belt clip for easy transport
- Area/volume/indirect height and patent pending surface measurement
- Min/Max sweep & continuous tracking
- Distance addition & subtraction for layouting
- Indirect height measurements (Pythagoras 2-point, 3-point, partial height)
- Large 3 line LCD graphical display with automatic white backlight
- Fold-out end piece for diagonal corner measurements
- Memory recall for the last 20 measurements
- IP54 water & dust protection
- Auto shut off and low power indication
- Metric units of measurement only



	LDM 50
Max. measurement range (m)	50
Accuracy	± 1.5
Display	LCD
Display size (mm)	26 x 37
Laser classification	Class 2
Dimensions (mm)	119 x 40 x 32
Range (m)	0.05 - 50
Battery type	2 x AAA
Weight with battery pack (kg)	0.1
Pythagoras function	2-point, 3-point, partial height
Inclination sensor	No
Height tracking	No
Supplied in	-
Article Number	4933447700



LDM 100 100 M LASER DISTANCE METER

- Easy to use one person point and shoot system
- IP54 water & dust protection
- Metric & Imperial units of measurement
- Easy to touch measure buttons on the front and side of the housing to perform single measurements & continuous tracking
- Offers several different measurement functions that allow users to add and subtract values, calculate linear distance, surface area, total area and volume
- Digital auto-level feature allows for a measurement to be automatically taken when the meter reaches a level position (0°), increasing accuracy when measuring long distances
- Easy indirect height and length measurement using the auto-level feature to enhance user convenience in difficult measurement situations
- Large 3 line 50 mm diameter multi-color LCD graphical display for optimised visibility
- Display shows last three measurements and history menu shows the last 30 calculations
- Built-in 3-position auto-reference fold out pin for easy in corner/edge measurements

	LDM 100
Max. measurement range (m)	100
Accuracy	± 1.5
Display	LCD
Display size (mm)	31.5 x 40
Laser classification	Class 2
Dimensions (mm)	113 x 48 x 31
Range (m)	0.15 - 100
Battery type	2 x AAA
Weight with battery pack (kg)	0.14
Auto-level measurements	Yes
Pythagoras function	Yes
Inclination sensor	Yes
Height tracking	Yes
Supplied in	-
Article Number	4933459278



Easy to use one person point and shoot system



Auto level function



3-position auto-reference fold out pin



WORKGEAR



M12 HJP | M12™ HEATED HYBRID PUFFER JACKET

- Powered by M12™ 12V REDLITHIUM-ION™ battery technology, Milwaukee®'s hybrid puffer jackets uses carbon fibre heating elements to create and distribute heat to the chest, back and shoulders
- A one-touch LED controller allows the user to select from 3 heat settings, delivering ideal heat for any environment
- Superior run time – up to 8 hours of heat on a single battery charge (2.0 Ah)
- The Ripstop Polyester provides a lightweight design that can be used as an outer-shell or as a mid-layer (100% Polyester outer and inner shell)
- Water and wind resistant - provides comfort and durability in harsh environments
- Machine washable and dryable
- Reinforced high-wear zones protect from abrasion and tears
- M12™ battery holder - concealed battery pocket for minimal user interference
- Flexible battery system: works with all Milwaukee® M12™ batteries

	M12 HJP-0 (S)	M12 HJP-0 (M)	M12 HJP-0 (L)	M12 HJP-0 (XL)	M12 HJP-0 (2XL)
No. of batteries supplied	0	0	0	0	0
Charger supplied	–	–	–	–	–
Weight with battery pack (kg)	0.9	0.9	1.0	1.0	1.1
Article Number	4933464364	4933464365	4933464366	4933464367	4933464368



M12 HJP LADIES | M12™ HEATED HYBRID LADIES PUFFER JACKET

- Powered by M12™ 12V REDLITHIUM-ION™ battery technology, Milwaukee®'s hybrid ladies puffer jackets uses carbon fibre heating elements to create and distribute heat to the chest, back and shoulders
- A one-touch LED controller allows the user to select from 3 heat settings, delivering ideal heat for any environment
- Superior run time – up to 8 hours of heat on a single battery charge (2.0 Ah)
- The Ripstop Polyester provides a lightweight design that can be used as an outer-shell or as a mid-layer (100% Polyester outer and inner shell)
- Water and wind resistant - provides comfort and durability in harsh environments
- Machine washable and dryable
- Reinforced high-wear zones protect from abrasion and tears
- M12™ battery holder - concealed battery pocket for minimal user interference
- Flexible battery system: works with all Milwaukee® M12™ batteries

	M12 HJP LADIES-0 (S)	M12 HJP LADIES-0 (M)	M12 HJP LADIES-0 (L)	M12 HJP LADIES-0 (XL)	M12 HJP LADIES-0 (2XL)
No. of batteries supplied	0	0	0	0	0
Charger supplied	–	–	–	–	–
Weight with battery pack (kg)	0.8	0.8	0.9	0.9	1.0
Article Number	4933464340	4933464341	4933464342	4933464343	4933464344



M12 HBWP | M12™ HEATED HYBRID PUFFER VEST

- Powered by M12™ 12V REDLITHIUM-ION™ battery technology, Milwaukee®'s hybrid puffer vests uses carbon fibre heating elements to create and distribute heat to the chest and back
- A one-touch LED controller allows the user to select from 3 heat settings, delivering ideal heat for any environment
- Superior run time – up to 6 hours of heat on a single battery charge (2.0 Ah)
- The Ripstop Polyester provides a lightweight design that can be used as an outer-shell or as a mid-layer (100% Polyester outer and inner shell)
- Water and wind resistant - provides comfort and durability in harsh environments
- Machine washable and dryable
- Reinforced high-wear zones protect from abrasion and tears
- M12™ battery holder - concealed battery pocket for minimal user interference
- Flexible battery system: works with all Milwaukee® M12™ batteries

	M12 HBWP-0 (S)	M12 HBWP-0 (M)	M12 HBWP-0 (L)	M12 HBWP-0 (XL)	M12 HBWP-0 (2XL)
No. of batteries supplied	0	0	0	0	0
Charger supplied	–	–	–	–	–
Weight with battery pack (kg)	0.7	0.7	0.7	0.8	0.8
Article Number	4933464370	4933464371	4933464372	4933464373	4933464374



M12 HBWP LADIES | M12™ HEATED HYBRID LADIES PUFFER VEST

- Powered by M12™ 12V REDLITHIUM-ION™ battery technology, Milwaukee®'s hybrid puffer ladies vests uses carbon fibre heating elements to create and distribute heat to the chest and back
- A one-touch LED controller allows the user to select from 3 heat settings, delivering ideal heat for any environment
- Superior run time – up to 6 hours of heat on a single battery charge (2.0 Ah)
- The Ripstop Polyester provides a lightweight design that can be used as an outer-shell or as a mid-layer (100% Polyester outer and inner shell)
- Water and wind resistant - provides comfort and durability in harsh environments
- Machine washable and dryable
- Reinforced high-wear zones protect from abrasion and tears
- M12™ battery holder - concealed battery pocket for minimal user interference
- Flexible battery system: works with all Milwaukee® M12™ batteries

	M12 HBWP LADIES-0 (S)	M12 HBWP LADIES-0 (M)	M12 HBWP LADIES-0 (L)	M12 HBWP LADIES-0 (XL)
No. of batteries supplied	0	0	0	0
Charger supplied	–	–	–	–
Weight with battery pack (kg)	0.6	0.6	0.7	0.7
Article Number	4933464803	4933464804	4933464805	4933464806



M12 HJ CAMO5 | M12™ PREMIUM HEATED CAMOUFLAGE JACKET

- Realtree Xtra® Camo pattern blends perfectly year round in a variety of habitats
- Quiet-Shell stretch 100% polyester material to reduce noise during movement
- Heat on Demand - 5 sewn in carbon fibre heating zones distribute heat to core body areas and to the front pockets
- Superior run time, up to 8 hours of heat on a single battery charge of an M12™ REDLITHIUM-ION™ 2.0 Ah battery pack
- Easy touch heat controller concealed inside the lapel - 3 heat settings: High, Medium, Low
- Free Flex™ mobility - additional material under the arms increases range of movement for working overhead
- Water and wind resistant, provides comfort and durability in harsh environments
- Improved design with extended back and adjustable waist prevents heat loss and keeps the user warm
- M12™ battery controller with 2.1A USB port, to charge mobile devices stored in concealed battery pocket
- Machine washable and dryable
- Big hand & chest pocket, ideal for storing mobile devices
- Flexible battery system: works with all Milwaukee® M12™ batteries

	M12 HJ CAMO5-0 (S)	M12 HJ CAMO5-0 (M)	M12 HJ CAMO5-0 (L)	M12 HJ CAMO5-0 (XL)	M12 HJ CAMO5-0 (2XL)
No. of batteries supplied	0	0	0	0	0
Charger supplied	–	–	–	–	–
Weight with battery pack (kg)	1.3	1.3	1.4	1.4	1.5
Article Number	4933464334	4933464335	4933464336	4933464337	4933464338



M12 HJ GREY4 | M12™ PREMIUM HEATED JACKET

- Heat on Demand - 5 sewn in carbon fibre heating zones distribute heat to core body areas and to the front pockets
- Superior run time, up to 8 hours of heat on a single battery charge of an M12™ REDLITHIUM-ION™ 2.0 Ah battery pack
- Easy touch heat controller - 3 heat settings: High, Medium, Low
- ToughShell™ stretch 100% polyester material to withstand harsh working conditions and up to 5x longer life
- Free Flex™ mobility - additional material under the arms increases range of movement for working overhead
- Water and wind resistant, provides comfort and durability in harsh environments
- Improved design with extended back and adjustable waist prevents heat loss and keeps the user warm
- M12™ battery controller with 2.1A USB port, to charge mobile devices stored in concealed battery pocket
- Machine washable and dryable
- Big hand & chest pocket, ideal for storing mobile devices
- Flexible battery system: works with all Milwaukee® M12™ batteries

	M12 HJ GREY4-0 (S)	M12 HJ GREY4-0 (M)	M12 HJ GREY4-0 (L)	M12 HJ GREY4-0 (XL)	M12 HJ GREY4-0 (2XL)
No. of batteries supplied	0	0	0	0	0
Charger supplied	–	–	–	–	–
Weight with battery pack (kg)	1.5	1.5	1.6	1.7	1.8
Article Number	4933464328	4933464329	4933464330	4933464331	4933464332



M12 HJ BL4 | M12™ PREMIUM HEATED JACKET

- Heat on Demand - 5 sewn in carbon fibre heating zones, distributes heat to core body areas and to the front pockets
- Superior run time, up to 8 hours of heat on a single battery charge of an M12™ REDLITHIUM-ION™ 2.0 Ah battery pack
- Easy touch heat controller - 3 heat settings: High, Medium, Low
- ToughShell™ stretch 100% polyester material to withstand harsh working conditions and up to 5x longer life
- Free Flex™ mobility - additional material under the arms increases range of movement for working overhead
- Water and wind resistant, provides comfort and durability in harsh environments
- Improved design with extended back and adjustable waist prevents heat loss and keeps the user warm
- M12™ battery controller with 2.1A USB port, to charge mobile devices stored in concealed battery pocket
- Machine washable and dryable
- Big hand & chest pocket, ideal for storing mobile devices
- Flexible battery system: works with all Milwaukee® M12™ batteries

	M12 HJ BL4-0 (S)	M12 HJ BL4-0 (M)	M12 HJ BL4-0 (L)	M12 HJ BL4-0 (XL)	M12 HJ BL4-0 (2XL)
No. of batteries supplied	0	0	0	0	0
Charger supplied	–	–	–	–	–
Weight with battery pack (kg)	1.5	1.5	1.6	1.7	1.8
Article Number	4933464322	4933464323	4933464324	4933464325	4933464326



M12 HJ LADIES2 | M12™ LADIES HEATED JACKET

- Heat on Demand - 4 sewn in carbon fibre heating zones distribute heat to core body areas, the collar and to the front pockets
- Superior run time, up to 8 hours of heat on a single battery charge of an M12™ REDLITHIUM-ION™ 2.0 Ah battery pack
- Easy touch heat controller - 3 heat settings: High, Medium, Low
- Rugged construction, wind and water resistant (100% Polyester) shell and thermal fleece lining keep elements out and hold heat close to the body
- Women's cut, stitch lines positioned for a less baggy fit to hold heat zones closer to the body
- M12™ battery controller with 2.1A USB port, to charge mobile devices stored in a concealed battery pocket
- Machine washable and dryable
- Flexible battery system: works with all Milwaukee® M12™ batteries

	M12 HJ LADIES2-0 (S)	M12 HJ LADIES2-0 (M)	M12 HJ LADIES2-0 (L)	M12 HJ LADIES2-0 (XL)	M12 HJ LADIES2-0 (2XL)
No. of batteries supplied	0	0	0	0	0
Charger supplied	–	–	–	–	–
Weight with battery pack (kg)	1.1	1.1	1.2	1.3	1.4
Article Number	4933464839	4933464840	4933464841	4933464842	4933464843



M12 HH GREY3 | M12™ GREY HEATED HOODIE

- Rugged heated hoodie made from durable cotton (53%) exterior with durable reinforced utility pockets and waffle-weave polyester (47%) lining to withstand tough outdoor conditions
- In autumn and spring the hoodie can be worn as a rugged outer layer. In winter, it is best as a base layer that allows to shed bulky undergarments while generating and holding heat close to the body
- Superior run time, up to 8 hours of heat on a single battery charge of an M12™ REDLITHIUM-ION™ battery pack
- Multiple heating zones - 3 sewn in carbon fibre heating zones distribute heat to core body areas
- Easy touch heat controller - 3 heat settings: High, Medium, Low
- M12™ battery holder is stored in a concealed battery pocket for increased comfort and convenience
- Hood fits easily under hard hat
- Integrated cell phone pocket
- Machine washable and dryable
- Flexible battery system: works with all Milwaukee® M12™ batteries

	M12 HH GREY3-0 (S)	M12 HH GREY3-0 (M)	M12 HH GREY3-0 (L)	M12 HH GREY3-0 (XL)	M12 HH GREY3-0 (2XL)
No. of batteries supplied	0	0	0	0	0
Charger supplied	–	–	–	–	–
Weight with battery pack (kg)	1.1	1.1	1.3	1.4	1.5
Article Number	4933464352	4933464353	4933464354	4933464355	4933464356



M12 HH BL3 | M12™ BLACK HEATED HOODIE



- Rugged heated hoodie made from durable cotton (53%) exterior with durable reinforced utility pockets and waffle-weave polyester (47%) lining to withstand tough outdoor conditions
- In autumn and spring the hoodie can be worn as a rugged outer layer. In winter, it is best as a base layer that allows to shed bulky undergarments while generating and holding heat close to the body
- Superior run time, up to 8 hours of heat on a single battery charge of an M12™ REDLITHIUM-ION™ 2.0 Ah battery pack
- Multiple heating zones - 3 sewn in carbon fibre heating zones distribute heat to core body areas
- Easy touch heat controller - 3 heat settings: High, Medium, Low
- M12™ battery holder is stored in a concealed battery pocket for increased comfort and convenience
- Hood fits easily under hard hat
- Integrated cell phone pocket
- Machine washable and dryable
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 HH BL3-0 (S)	M12 HH BL3-0 (M)	M12 HH BL3-0 (L)	M12 HH BL3-0 (XL)	M12 HH BL3-0 (2XL)
No. of batteries supplied	0	0	0	0	0
Charger supplied	-	-	-	-	-
Weight with battery pack (kg)	1.1	1.1	1.2	1.3	1.4
Article Number	4933464346	4933464347	4933464348	4933464349	4933464350

WGT-R | GRIDIRON™ WORK GEAR TROUSERS



- GRIDIRON™ work gear trousers have up to 3x longer lifetime than a traditional 340 g cotton fabric to withstand the harshest working conditions
- Free Flex™ mobility stretch panels for an easier range of movement
- Engineered with reinforced high-wear areas, tarnish resistant metal zippers and durable metal buckles that won't bend or break
- All weather protection provides resistance against wind and water
- Utility chest pocket provides quick access to commonly used items
- 2 x front hand pockets, 2 x large back pockets, 3 x side leg pockets
- Machine washable and dryable
- 100% Polyester inner and outer material



	WGT-RS	WGT-RM	WGT-RL	WGT-RXL	WGT-R2XL
Weight (kg)	1.4	1.5	1.5	1.6	1.7
Article Number	4933464386	4933464387	4933464388	4933464389	4933464390

WWLSG | WORKSKIN™ LIGHT WEIGHT PERFORMANCE LONG SLEEVE SHIRT - GREY



- COOLCORE® performance fabrics use patented three-yarn construction to wick moisture away from the body and keep the garment up to 30% cooler when working in the heat
- Fast wicking sweat zones extend down the back and under the arms to accelerate drying in high-sweat body areas
- Chemical free moisture wicking allows shirt to dry faster, reduces saturation and doesn't wash out over time
- UV protection helps block harmful rays from reaching the skin
- Durable pilling-resistant fabrics extend product life
- Drop tail extended back provides extra coverage when working overhead
- Seamless shoulders reduce discomfort from straps and harnesses
- 100% Polyester material (single Jersey)



	WWLSG (S)	WWLSG (M)	WWLSG (L)	WWLSG (XL)	WWLSG (XXL)
Weight (kg)	0.1	0.1	0.1	0.1	0.1
Article Number	4933464108	4933464194	4933464195	4933464196	4933464197

WWLSY | WORKSKIN™ LIGHT WEIGHT PERFORMANCE LONG SLEEVE SHIRT - HI-VIS



- COOLCORE® performance fabrics use patented three-yarn construction to wick moisture away from the body and keep the garment up to 30% cooler when working in the heat
- Fast wicking sweat zones extend down the back and under the arms to accelerate drying in high-sweat body areas
- Chemical free moisture wicking allows shirt to dry faster, reduces saturation and doesn't wash out over time
- UV protection helps block harmful rays from reaching the skin
- Durable pilling-resistant fabrics extend product life
- Drop tail extended back provides extra coverage when working overhead
- Seamless shoulders reduce discomfort from straps and harnesses
- 100% Polyester material (single Jersey)



	WWLSY (S)	WWLSY (M)	WWLSY (L)	WWLSY (XL)	WWLSY (XXL)
Weight (kg)	0.1	0.1	0.1	0.1	0.1
Article Number	4933464109	4933464198	4933464199	4933464200	4933464201

WWSSG | WORKSKIN™ LIGHT WEIGHT PERFORMANCE SHORT SLEEVE SHIRT - GREY



- COOLCORE® performance fabrics use patented three-yarn construction to wick moisture away from the body and keep the garment up to 30% cooler when working in the heat
- Fast wicking sweat zones extend down the back and under the arms to accelerate drying in high-sweat body areas
- Chemical free moisture wicking allows shirt to dry faster, reduces saturation and doesn't wash out over time
- UV protection helps block harmful rays from reaching the skin
- Durable pilling-resistant fabrics extend product life
- Drop tail extended back provides extra coverage when working overhead
- Seamless shoulders reduce discomfort from straps and harnesses
- 100% Polyester material (pique mesh)



	WWSSG (S)	WWSSG (M)	WWSSG (L)	WWSSG (XL)	WWSSG (XXL)
Weight (kg)	0.1	0.1	0.1	0.1	0.1
Article Number	4933464110	4933464202	4933464203	4933464204	4933464205

WWSSY | WORKSKIN™ LIGHT WEIGHT PERFORMANCE SHORT SLEEVE SHIRT - HI-VIS



- COOLCORE® performance fabrics use patented three-yarn construction to wick moisture away from the body and keep the garment up to 30% cooler when working in the heat
- Fast wicking sweat zones extend down the back and under the arms to accelerate drying in high-sweat body areas
- Chemical free moisture wicking allows shirt to dry faster, reduces saturation and doesn't wash out over time
- UV protection helps block harmful rays from reaching the skin
- Durable pilling-resistant fabrics extend product life
- Drop tail extended back provides extra coverage when working overhead
- Seamless shoulders reduce discomfort from straps and harnesses
- 100% Polyester material (pique mesh)



	WWSSY (S)	WWSSY (M)	WWSSY (L)	WWSSY (XL)	WWSSY (XXL)
Weight (kg)	0.1	0.1	0.1	0.1	0.1
Article Number	4933464111	4933464206	4933464207	4933464208	4933464209

WGJHBL | GRIDIRON™ HOODED JACKET BLACK

- Engineered to battle the jobsite and survive the elements and is built for tradesmen who can't let cold slow them down
- Gridiron™ ripstop 100% polyester outlasts up to 3 x against abrasion and tearing when compared to the most common 340 g cotton textile
- FreeFlex™ mobility gussets provide enhanced mobility when working overhead
- Wind and water resistant polyester materials don't get wet and do not freeze in cold weather
- 100 g of high-loft insulation
- Riveted and reinforced pocket edges, and tarnish resistant metal zippers
- Fitted hood provides full range of vision
- Rib knit cuffs and waist keep cold air out
- (2) large outer pockets, (1) quick-access sleeve pocket, (1) inner zip pocket



GRIDIRON
RIPSTOP POLYESTER

	WGJHBL (S)	WGJHBL (M)	WGJHBL (L)	WGJHBL (XL)	WGJHBL (XXL)
Weight (kg)	1.1	1.2	1.2	1.2	1.3
Article Number	4933459435	4933459436	4933459437	4933459438	4933459439

WGJCBL | GRIDIRON™ TRADESMAN JACKET

- Engineered to battle the jobsite and survive the elements and is built for tradesmen who can't let cold slow them down
- Gridiron™ ripstop 100% polyester outlasts up to 3 x against abrasion and tearing when compared to the most common 340 g cotton textile
- FreeFlex™ mobility gussets provide enhanced mobility when working overhead
- Wind and water resistant polyester materials don't get wet and do not freeze in cold weather
- 100 g of high-loft insulation
- Riveted and reinforced pocket edges, and tarnish resistant metal zippers
- Drop tail extended back provides extra protection
- Dual cuff with rib knit inner
- (4) large outer pockets, (1) quick-access pencil pocket, (1) inner zip pocket



GRIDIRON
RIPSTOP POLYESTER

	WGJCBL (S)	WGJCBL (M)	WGJCBL (L)	WGJCBL (XL)	WGJCBL (2XL)
Weight (kg)	1.1	1.2	1.2	1.2	1.3
Article Number	4933459699	4933459700	4933459701	4933459702	4933459703

WORK GLOVES

		Size	Article Number	
Fingerless gloves	<ul style="list-style-type: none"> ◦ Designed to provide ultimate dexterity when handling small objects. ◦ Reinforced palm and thumb seam. ◦ Lightweight, breathable backing. ◦ Moisture wicking lining provides all day comfort. ◦ Built-in sweat wipe. 	M	48229741	
		L	48229742	
		XL	48229743	
		XXL	48229744	
FREE-FLEX work gloves	<ul style="list-style-type: none"> ◦ SMARTWIPE™ knuckle, palm and fingertips. ◦ Flexible and elastic gloves. ◦ Lightweight, breathable backing. ◦ Reinforced thumb seam. ◦ High dexterity finger tips. 	M	48229711	
		L	48229712	
		XL	48229713	
		XXL	48229714	
Demolition gloves	<ul style="list-style-type: none"> ◦ Armortex® reinforced palms and finger tips: Increased durability and hand protection. ◦ SMARTWIPE™ Knuckle: Capacitive knuckle allows to use touch screen devices without removing gloves or using dirty fingertips. ◦ Breathable tri-cot lining: Provides ultimate comfort and breathability. ◦ Knuckle protection: TPR pad provides knuckle protection. 	M	48229731	
		L	48229732	
		XL	48229733	
		XXL	48229734	

EQUIPMENT

		Article Number	
Electricians pouch	<ul style="list-style-type: none"> ◦ Robust construction, made from 1680D ballistic nylon. ◦ Solid base allows bag to stand-up, even when fully loaded. ◦ Integrated belt loops allow bag to be worn on a tool belt. 	48228112	
Electricians belt	<ul style="list-style-type: none"> ◦ Robust construction, made from 1680D ballistic nylon. ◦ Padded, breathable belt for ultimate comfort and jobsite performance. ◦ Metal suspender attachments allow suspenders to be added. 	48228110	
Contractor rig	<ul style="list-style-type: none"> ◦ Robust construction, made from 1680D ballistic nylon. ◦ Padded 4-point harness distributes weight for all day comfort. ◦ Padded, breathable belt for ultimate comfort and jobsite performance. 	48228120	
Jobsite backpack	<ul style="list-style-type: none"> ◦ Hard moulded base allows bag to stand-up and provides ultimate all-weather protection. ◦ Vertical tool wall maximises storage space while allowing for bulk storage space. ◦ Laptop pocket allows protected storage for laptops/tablets and personal goods. 	48228200	
Tradesman backpack	<ul style="list-style-type: none"> ◦ Durable construction, made from 1680D ballistic nylon. ◦ Laptop pocket allows protected storage for laptops/tablets and personal goods. ◦ 18 organiser pockets allow variety of options. 	4932464252	
Low profile backpack	<ul style="list-style-type: none"> ◦ Reinforced base protects the backpack from being damaged by abusive jobsite conditions. ◦ Padded and breathable load-bearing harness evenly distributes the weight for more comfort and jobsite performance. ◦ 22 pockets including a padded electronic sleeve to provide ultimate organisation. 	4932464834	
Ultimate jobsite backpack	<ul style="list-style-type: none"> ◦ Hard molded base allows backpack to stand up and reduces ingress of dirt and water. ◦ Padded and breathable load-bearing harness evenly distributes the weight for more comfort and jobsite performance. ◦ 48 total pockets including 2 hardshell pockets to protect electronics and equipment from impact. 	4932464833	

PACKOUT™



**VERSATILE.
DURABLE.**

Milwaukee® Tool revolutionises tool transportation, organisation, and storage for the trades with the new PACKOUT™ Modular Storage System. Designed to provide users with the ability to interchange and interlock a wide assortment of heavy duty tool boxes, organisers and storage totes in multiple different configurations.

PACKOUT™ COMPONENTS

BUILD YOUR SYSTEM



NEW

NEW

NEW

NEW

NEW



NEW

NEW

PACKOUT™ TROLLEY BOX

- Part of the PACKOUT™ modular storage system.
- Constructed with impact resistant polymers for jobsite durability.
- 113 kg weight capacity.
- Industrial grade extension handle.
- Oversized Ø 228 mm all terrain wheels.
- IP65 rated weather seal to keep out rain and jobsite debris.
- Metal reinforced corners.
- Metal reinforced locking point.
- Interior organiser tray.
- Mounting location for the ONE-KEY™ TICK™.



PACKOUT™ trolley box

Dimensions (mm)	560 x 410 x 480
Loading capacity (kg)	113
Article Number	4932464078

PACKOUT™ ADAPTOR HD BOX

Article Number	4932464081
----------------	------------



PACKOUT™ BOXES

- Part of the PACKOUT™ modular storage system.
- Constructed with impact resistant polymers for jobsite durability.
- IP65 rated weather seal to keep out rain and jobsite debris.
- Metal reinforced corners.
- Metal reinforced locking point.
- Interior organiser trays.
- Mounting location for the ONE-KEY™ TICK™.
- Metal reinforced top handle for easier carrying (only on the large box).



PACKOUT™ large box

PACKOUT™ box

Dimensions (mm)	560 x 410 x 290	560 x 410 x 170
Article Number	4932464079	4932464080

PACKOUT™ ORGANISER

- Part of the PACKOUT™ modular storage system.
- Constructed with impact resistant polymers for jobsite durability.
- The interior features 10 removable & mountable bins that can be mounted onto common jobsite materials for easy access.
- IP65 rated weather seal to keep out rain and jobsite debris.
- No-travel bins seals to prevent the bins contents from migrating between bins during transport.



PACKOUT™ organiser

Dimensions (mm)	500 x 380 x 120
Article Number	4932464082

PACKOUT™ COMPACT ORGANISER

- Part of the PACKOUT™ modular storage system.
- Constructed with impact resistant polymers for jobsite durability.
- The interior features 5 removable & mountable bins that can be mounted onto common jobsite materials for easy access.
- IP65 rated weather seal to keep out rain and jobsite debris.
- No-travel bins seals to prevent the bins contents from migrating between bins during transport.



PACKOUT™ compact organiser

Dimensions (mm)	250 x 380 x 120
Article Number	4932464083

PACKOUT™ SLIM ORGANISER

- Part of the PACKOUT™ modular storage system.
- Constructed with impact resistant polymers for jobsite durability.
- Interior features 2 large bins and 8 small bins. All bins contain dividers.
- No travel bin seals to prevent the bins contents from migrating between bins during transportation.
- IP 65 rated weather seal to keep out rain and jobsite debris.



PACKOUT™ slim organiser	
Dimensions (mm)	500 x 380 x 65
Article Number	4932471064

PACKOUT™ COMPACT SLIM ORGANISER

- Part of the PACKOUT™ modular storage system.
- Constructed with impact resistant polymers for jobsite durability.
- Interior features 1 large bin and 4 small bins. All bins contain dividers.
- No travel bin seals to prevent the bins contents from migrating between bins during transportation.
- IP 65 rated weather seal to keep out rain and jobsite debris.



PACKOUT™ compact slim organiser	
Dimensions (mm)	250 x 380 x 65
Article Number	4932471065

PACKOUT™ TOTE TOOLBAG

- Part of the PACKOUT™ modular storage system.
- 1680 ballistic material construction.
- Impact resistant molded base.
- All metal hardware.
- Durable overmolded handle.



	25 cm tote toolbag	40 cm tote toolbag	50 cm tote toolbag
Dimensions (mm)	250 x 280 x 320	250 x 400 x 320	250 x 500 x 320
No. of pockets	28	31	32
Article Number	4932464084	4932464085	4932464086

PACKOUT™ DUFFEL BAG

- Part of the PACKOUT™ modular storage system.
- Made from 1680 ballistic material for jobsite durability.
- Impact resistant polymer base protects contents from water and dirt.
- Cushioned shoulder strap, top and side handles for flexible carry.



	38 cm PACKOUT™ duffel bag	50 cm PACKOUT™ duffel bag
Dimensions (mm)	395 x 295 x 341	530 x 310 x 350
Article Number	4932471066	4932471067

PACKOUT™ TECH BAG

- Part of the PACKOUT™ modular storage system.
- Made from 1680 ballistic material for jobsite durability.
- Impact resistant polymer base protects contents from water and dirt.
- 58 total pockets. Hardshell protected instrument pocket.
- Secure, protected storage for laptops and tablets.



PACKOUT™ tech bag	
Article Number	4932471130

PACKOUT™ BACKPACK

- Part of the PACKOUT™ modular storage system.
- Made from 1680 ballistic material for jobsite durability.
- 48 total pockets. Hardshell protected instrument pocket.
- Impact resistant polymer base protects contents from water and dirt and also allows backpack to stand up.
- Extra back padding, chest strap, attachment strap for rolling bags and heavy duty harness for ultimate jobsite comfort.



PACKOUT™ backpack	
Article Number	4932471131

PACKOUT™ JOBSITE COOLER

- Part of the PACKOUT™ modular storage system.
- Impact resistant polymer base protects contents from water and dirt and also allows backpack to stand up.
- Extra insulation keeps contents cold for up to 24 hours.
- Food grade leak proof liner.
- Shoulder strap for easy transport.



PACKOUT™ jobsite cooler	
Article Number	4932471132

OUTDOOR EQUIPMENT



M18

#MILWAUKEETOOL f @ WWW.MILWAUKEETOOL.EU

M18 FCHS M18 FUEL™ CHAINSAW

M18 FUEL

- The M18 FUEL™ chainsaw delivers the power to outperform on the most demanding chainsaw applications vs. petrol chainsaws
- FUEL™ technology allows the saw to maintain speed in tough application without bogging down, giving it the ability to outperform petrol chainsaws up to 40cc
- Next generation POWERSTATE™ brushless motor: This is Milwaukee®'s most powerful motor utilising higher grade magnets and 175% more copper vs previous motors
- Next generation REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- New REDLITHIUM-ION™ High Output™ 12.0 Ah battery pack provides superior pack construction, electronics and fade-free performance to deliver the most work per charge than any other Milwaukee® battery pack
- Provides extremely high work per charge the saw will cut 150 pieces of 100 mm x 100 mm pine on one full charge of a 12.0 Ah battery pack
- High strength all metal gearing delivers best in class torque
- Variable speed trigger allows the user to have full control over the power curve, giving instantaneous throttle response to reach full speed in under one second
- All metal bucking spikes allows the user increased leverage when cutting
- No-spill oil reservoir with easy to access tank and clear viewing window
- Supplied with 80cc of oil, chain tool and bar cover



	M18 FCHS-0	M18 FCHS-121
Battery pack capacity (Ah)	–	12.0
No. of batteries supplied	0	1
Charger supplied	–	130 min
Chain bar length (cm)	40	40
Chain speed (m/s)	12.4	12.4
Weight with battery pack (kg)	–	6.4
Supplied in	–	–
Article Number	4933464723	4933464223

40 CM SAW CHAIN	
Article Number	4932464873



Variable speed trigger



All metal bucking spikes



No-spill oil reservoir

M18 FBL | M18 FUEL™ BLOWER

- The Milwaukee® POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- Ergonomic inline design clears debris and dirt in tight spaces
- Up to 12.74 m³/min of air volume at 193 km/h to clear debris
- Variable trigger and speed lock for full power control
- Lock-on switch
- Flexible battery system: works with all Milwaukee® M18™ batteries


M18 FUEL

	M18 FBL-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Air volume 1 (m³/min)	8.75
Air volume 2 (m³/min)	12.7
Airflow speed 1 (km/h)	133
Airflow speed 2 (km/h)	193
Fan speed (rpm)	14,000
Weight with battery pack (kg)	4.4
Supplied in	–
Article Number	4933459825

M18 CLT | M18 FUEL™ LINE TRIMMER

- The Milwaukee® POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- Full throttle in under 1 second
- Has the power to clear thick brush
- Up to 1 hour of run time with M18™ 9.0 Ah battery pack
- 2-speed with variable speed trigger
- 135° protection guard
- Flexible battery system: works with all Milwaukee® M18™ batteries


M18 FUEL

	M18 CLT-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Cutting line diameter (mm)	2.4
Cutting path width (cm)	38.6
Weight with battery pack (kg)	5.6
Supplied in	–
Article Number	49334599345

2 MM X 45 M TRIMMER LINE

Article Number 49162712


M18 CHT | M18 FUEL™ HEDGE TRIMMER

- The Milwaukee® POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- Power to cut 20 mm branches
- 600 mm blade trims more material in a single pass, increasing reach and productivity
- Up to 2 hours run time with M18™ 9.0 Ah battery pack
- Cuts up to 30% faster vs. cordless competitor
- Flexible battery system: works with all Milwaukee® M18™ batteries


M18 FUEL

	M18 CHT-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (m/min)	3400
Blade length (mm)	610
Tooth spacing (mm)	20
Cutting capacity (mm)	20
Sharpening angle to horizontal (°)	< 30
Weight with battery pack (kg)	5.0
Supplied in	–
Article Number	49334599346

M18 FUEL™ OPE ATTACHMENTS

STEP 1 CHOOSE YOUR POWER


M18 FOPH-0
M18 FUEL™ OUTDOOR
POWER HEAD
4933464954

FEATURES:

- The Milwaukee® POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- Full throttle in under 1 second
- Compatible with all Milwaukee® outdoor power head system attachments
- 2-speed with variable speed trigger
- Adjustable auxiliary handle, strap and carrying ring help set the tool up for the optimum user comfort and control
- Flexible battery system: works with all Milwaukee® M18™ batteries

STEP 2 CHOOSE YOUR ATTACHMENTS


M18 FOPH-LTA
M18™ LINE TRIMMER
ATTACHMENT
4932464955

M18 FOPH-CSA
M18™ CHAIN SAW
ATTACHMENT
4932464957

M18 FOPH-EA
M18™ EDGER
ATTACHMENT
4932464958

M18 FOPH-HTA
M18™ HEDGE
TRIMMER
ATTACHMENT
4932464959

M18 FOPH-EXA
M18™ EXTENSION
ATTACHMENT
4932464960

M18 FOPHLTKIT-0
M18 FUEL™ OUTDOOR POWER
HEAD KIT – INCL. LINE
TRIMMER ATTACHMENT
4933464956

**ALSO AVAILABLE
AS A SET**

FORCE LOGIC™



M18 HCCT109/42 | M18™ FORCE LOGIC™ HYDRAULIC 109 KN CABLE CRIMPER



- FORCE LOGIC™ hydraulic cable crimper crimps connectors with 109 kN of force
- The Milwaukee® POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power
- Lightest, most balanced tool with ergonomic grip design
- 42 mm jaw opening and 350° head rotation provides easy positioning and access, even for large connectors
- Red alignment marks on the tool jaws aid accuracy in crimp placement
- PFM™ (Predictive Force Monitoring) with auto complete ensures full pressure and provides instant pressure verification with green indicator
- Allows to crimp connectors up to 400 mm²
- Universal die reception to fit most common U-Dies (C shaped dies) on the market
- The tool records & stores every crimp made for professional report building through both ONE-KEY™ app and ONE-KEY™ adaptor
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- Pre-crimp battery check automatically ensures enough charge to complete each crimp
- Sealed electronics resist harsh environments with dirt, dust and moisture
- REDLINK™ individual battery cell monitoring optimises tool run time and ensures long term pack durability
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics, and fade-free performance to deliver more run time and more work over pack life



	M18 HCCT109/42-522C
Battery pack capacity (Ah)	1 x 5.0 & 1 x 2.0
No. of batteries supplied	2
Charger supplied	59 min
Crimping force (kN)	109
Crimping range (mm²)	16 - 400
Jaw opening capacity for pipe (mm)	42
Weight with battery pack (kg)	5.6
Supplied in	Kitbox
Article Number	4933459273

CRIMPING DIE BOX FOR M18 HCCT109/42 CRIMPER (DIES TO BE BOUGHT SEPARATELY)

Article Number 4932464211



M18 HCCT | M18™ FORCE LOGIC™ HYDRAULIC 53 KN CABLE CRIMPER



- FORCE LOGIC™ hydraulic cable crimper crimps connectors in less than 3 seconds with 53 kN of force
- The Milwaukee® POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power
- Best balanced tool and easiest control due to one hand operation
- Compact in-line and slim jaw design with 350° rotatable head allows easy crimps, even in narrow spaces
- Revolutionary jaw holds connector for best alignment of cable and connector
- PFM™ (Predictive Force Monitoring): Automatically modifies output based on connector, ensuring optimal pressure every time and visualises with a green light
- Allows crimping of connectors up to 300 mm²
- Universal die reception to fit most common 60 kN U-Dies (C shaped dies) on the market
- The tool records & stores every crimp made for professional report building through both ONE-KEY™ app and ONE-KEY™ adaptor
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- Pre-crimp battery check automatically ensures enough charge to complete each crimp
- Sealed electronics resist harsh environments with dirt, dust and moisture
- REDLINK™ individual battery cell monitoring optimises tool run time and ensures long term pack durability
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics, and fade-free performance to deliver more run time and more work over pack life



	M18 HCCT-201C
Battery pack capacity (Ah)	2.0
No. of batteries supplied	1
Charger supplied	40 min
Crimping force (kN)	53
Crimping range (mm²)	16 - 300
Crimps per battery	> 250 on a 70 mm² copper connector
Press cycles	30,000
Weight with battery pack (kg)	3.7
Supplied in	Kitbox
Article Number	4933451194

CU/AL STANDARD COPPER & ALUMINIUM CABLE CUTTING BLADES. THE BLADES FIT FOR THE CU/AL CUTTING JAWS FOR M18HCC & ONEHCC CUTTERS + M18 HCCT CRIMPER CUTTING JAW

Article Number 4932464498



CRIMPING DIES

Type	Form	Image	M18 HCCT109/42		M18 HCCT		
			Cable lug size (mm²)	Description	Article Number	Description	Article Number
NF C 20-130 for copper compression cable lugs	Hex		16	NF13 Cu 16	4932459453	NF22 Cu 16	4932451733
			25	NF13 Cu 25	4932459454	NF22 Cu 25	4932451734
			35	NF13 Cu 35	4932459455	NF22 Cu 35	4932451735
			50	NF13 Cu 50	4932459456	NF22 Cu 50	4932451736
			70	NF13 Cu 70	4932459457	NF22 Cu 70	4932451737
			95	NF13 Cu 95	4932459458	NF22 Cu 95	4932451738
			120	NF13 Cu 120	4932459459	NF22 Cu 120	4932451739
			150	NF13 Cu 150	4932459460	NF22 Cu 150	4932451740
			185	NF13 Cu 185	4932459461	NF22 Cu 185	4932451741
			240	NF13 Cu 240	4932459462	NF22 Cu 240	4932451742
			300	NF13 Cu 300	4932459463	NF22 Cu 300	4932451743
			400	NF13 Cu 400	4932459464		
DIN 46235 for copper compression cable lugs and connectors (DIN 46267)	Hex		16	DIN13 Cu 16	4932459465	DIN22 Cu 16	4932451744
			25	DIN13 Cu 25	4932459466	DIN22 Cu 25	4932451745
			35	DIN13 Cu 35	4932459467	DIN22 Cu 35	4932451746
			50	DIN13 Cu 50	4932459468	DIN22 Cu 50	4932451747
			70	DIN13 Cu 70	4932459469	DIN22 Cu 70	4932451748
			95	DIN13 Cu 95	4932459470	DIN22 Cu 95	4932451749
			120	DIN13 Cu 120	4932459471	DIN22 Cu 120	4932451750
			150	DIN13 Cu 150	4932459472	DIN22 Cu 150	4932451751
			185	DIN13 Cu 185	4932459473	DIN22 Cu 185	4932451752
			240	DIN13 Cu 240	4932459474	DIN22 Cu 240	4932451753
			300	DIN13 Cu 300	4932459475	DIN22 Cu 300	4932451754
			400	DIN13 Cu 400	4932459476		
Tubular cable lugs and connectors	Hex		16	R13 Cu 16	4932459494	R22 Cu 16	4932451755
			25	R13 Cu 25	4932459495	R22 Cu 25	4932451756
			35	R13 Cu 35	4932459496	R22 Cu 35	4932451757
			50	R13 Cu 50	4932459497	R22 Cu 50	4932451758
			70	R13 Cu 70	4932459498	R22 Cu 70	4932451759
			95	R13 Cu 95	4932459499	R22 Cu 95	4932451760
			120	R13 Cu 120	4932459500	R22 Cu 120	4932451761
			150	R13 Cu 150	4932459501	R22 Cu 150	4932451762
			185	R13 Cu 185	4932459502	R22 Cu 185	4932451763
			240	R13 Cu 240	4932459503	R22 Cu 240	4932451764
			300	R13 Cu 300	4932459504	R22 Cu 300	4932451765
			400	R13 Cu 400	4932459505		
Copper solderless terminals (DIN 46234, DIN 46230, DIN 46341)	Half round indent		16	Q13 CU 16	4932459477	Q22 CU 16	4932451766
			25	Q13 CU 25	4932459478	Q22 CU 25	4932451767
			35	Q13 CU 35	4932459479	Q22 CU 35	4932451768
			50	Q13 CU 50	4932459480	Q22 CU 50	4932451769
			70	Q13 CU 70	4932459481	Q22 CU 70	4932451770
			95	Q13 CU 95	4932459482	-	-
			16/25	DIN13 AL 16/25	4932459506	DIN22 AL 16/25	4932451771
DIN Aluminium for aluminium compression cable lugs and connectors (DIN 46329, 46267 Part 1 and 2, DIN EN 50182)	Hex		35	DIN13 AL 35	4932459507	DIN22 AL 35	4932451772
			50	DIN13 AL 50	4932459508	DIN22 AL 50	4932451773
			70	DIN13 AL 70	4932459509	DIN22 AL 70	4932451774
			95/120	DIN13 AL 95/120	4932459510	DIN22 AL 95/120	4932451775
			150	DIN13 AL 150	4932459511	DIN22 AL 150	4932451776
			185	DIN13 AL 185	4932459512	DIN22 AL 185	4932451777
			240	DIN13 AL 240	4932459513	DIN22 AL 240	4932451778
			300	DIN13 AL 300	4932459514	DIN22 AL 300	4932451779
			16	RU13 Cu/Al16	4932459483	RU22 Cu/Al 16	4932451780
			35/25	RU13 Cu35/Al25	4932459484	RU22 Cu35/Al25	4932451781
			50/35	RU13 Cu50/Al35	4932459485	RU22 Cu50/Al35	4932451782
			70/50	RU13 Cu70/Al50	4932459486	RU22 Cu70/Al50	4932451783
95/70	RU13 Cu95/Al70	4932459487	RU22 Cu95/Al70	4932451784			
120/95	RU13 Cu120/Al95	4932459488	RU22 Cu120/Al95	4932451785			
150/120	RU13 Cu150/Al120	4932459489	RU22 Cu150/Al120	4932451786			
185/150	RU13 Cu185/Al150	4932459490	RU22 Cu185/Al150	4932451787			
240/185	RU13 Cu240/Al185	4932459491	RU22 Cu240/Al185	4932451788			
300/240	RU13 Cu300/Al240	4932459492	RU22 Cu300/Al240	4932451789			
400/300	RU13 Cu400/Al300	4932459493	-	-			
Ferruls	Trapezoid		16	AEH13 Cu 16	4932459515	-	-
			25	AEH13 Cu 25	4932459516	-	-
			35	AEH13 Cu 35	4932459517	-	-
			50	AEH13 Cu 50	4932459518	-	-
			70	AEH13 Cu 70	4932459519	-	-
			95	AEH13 Cu 95	4932459520	-	-
			120	AEH13 Cu 120	4932459521	-	-
			150	AEH13 Cu 150	4932459522	-	-
			185	AEH13 Cu 185	4932459523	-	-
			240	AEH13 Cu 240	4932459524	-	-
			16	C13 Cu 16	4932459525	-	-
			25	C13 Cu 25	4932459526	-	-
35	C13 Cu 35	4932459527	-	-			
50	C13 Cu 50	4932459528	-	-			
70	C13 Cu 70	4932459529	-	-			
10	C13 Cu 10	4932459530	-	-			
10-35	C13 Cu 10-35	4932459531	-	-			
25-50	C13 Cu 25-50	4932459532	-	-			
35-70	C13 Cu 35-70	4932459533	-	-			
70	HAH13 Cu 70	4932459534	-	-			
95	HAH13 Cu 95	4932459535	-	-			
120	HAH13 Cu 120	4932459536	-	-			
2x50	DP13 Cu 2x50	4932459537	-	-			
2x70	DP13 Cu 2x70	4932459538	-	-			
2x95	DP13 Cu 2x95	4932459539	-	-			
Double press cable shoes	Oval		16	DP13 Cu 16	4932459540	-	-
			25	DP13 Cu 25	4932459541	-	-

M18 HCC75R

M18™ FORCE LOGIC™ HYDRAULIC REMOTE UNDERGROUND CABLE CUTTER

- o FORCE LOGIC™ hydraulic remote underground cable cutter cuts cables in less than 10 seconds with 77.8 kN of force
- o The Milwaukee® POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power
- o Cuts aluminium & copper cables up to 75 mm
- o Wireless remote communicates with the tool via a mutually exclusive Bluetooth® connection, removing any physical connection to the tool and allowing Linemen to make remote cuts WIRELESSLY
- o Green LED light on wireless remote gives positive indication that the tool is done cutting
- o Converts from Local to Remote cutting mode easily
- o Balanced design, handle and hang hook enable easiest set-up in vaults
- o Open jaw design provides easiest access in trenches
- o Milwaukee® ONE-KEY™ technology allows linemen to view tool usage, receive notifications for recommended maintenance, and sync information wirelessly to the cloud
- o ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- o REDLINK™ individual battery cell monitoring optimises tool run time and ensures long term pack durability
- o REDLITHIUM-ION™ battery pack provides superior pack construction, electronics, and fade-free performance to deliver more run time and more work over pack life
- o Flexible battery system: works with all Milwaukee® M18™ batteries

M18 FORCE LOGIC™

UNLOCKING THE DIGITAL JOBSITE.



UNDERGROUND CUTTER BLADE M18 HCC75	
Article Number	49162774


M18 HCC75R-502C

Battery pack capacity (Ah)	5.0
No. of batteries supplied	2
Charger supplied	59 min
Cutting force (kN)	77.8
Max. cutting diameter (mm)	75
Cutting time (s)	<10
Weight with battery pack (kg)	7.9
Supplied in	Kitbox
Article Number	4933459271



Allowing Linemen to make remote cuts WIRELESSLY by removing any physical connection to the tool



Balanced design, handle and hang hook enable easiest set-up in vaults



Open jaw design provides easiest access in trenches

M18 HCC75 | M18™ FORCE LOGIC™ HYDRAULIC UNDERGROUND CABLE CUTTER

M18 FORCE LOGIC™

- o FORCE LOGIC™ hydraulic underground cable cutter cuts cables in less than 10 seconds with 77.8 kN of force
- o Milwaukee® designed and built brushless POWERSTATE™ motor provides more power, more run time and longer life
- o Cuts aluminium and copper cables up to 75 mm
- o In-line design delivers easiest access in trenches and a secure stand during cable cuts
- o Versatile top-handle can also be used as a stand and provides balanced cut alignment
- o 340° rotatable head powered by a 77.8 kN hydraulic pump delivers best in class cut speed
- o Milwaukee® ONE-KEY™ technology allows linemen to view tool usage, receive notifications for recommended maintenance, and sync information wirelessly to the cloud
- o ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- o REDLINK™ individual battery cell monitoring optimises tool run time and ensures long term pack durability
- o REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- o Flexible battery system: works with all Milwaukee® M18™ batteries

UNLOCKING THE DIGITAL JOBSITE.



	M18 HCC75-0C	M18 HCC75-502C
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
Cutting force (kN)	77.8	77.8
Max. cutting diameter (mm)	75	75
Cutting time (s)	<10	<10
Weight with battery pack (kg)	–	7.9
Supplied in	Kitbox	Kitbox
Article Number	4933459268	4933459269

UNDERGROUND CUTTER BLADE M18 HCC75	
Article Number	49162774



M18 HCC45 | M18™ FORCE LOGIC™ HYDRAULIC 44 MM CABLE CUTTER

M18 FORCE LOGIC™

- o FORCE LOGIC™ hydraulic cable cutter cuts ACSR/ACSS cables in less than 9 seconds with 77.8 kN of force
- o Milwaukee® designed and built brushless POWERSTATE™ motor provides more power, more run time and longer life
- o Cuts ACSR and ACSS transmission line cables up to 44 mm
- o Patent pending jaw design enables opening with just two fingers, enhancing alignment while delivering easiest operation with Class 3 gloves
- o Wire automatically closes the jaw, providing hands-free jaw closure and the easiest mid-span cuts. Fully balanced design delivers the best control
- o 340° rotatable head powered by a 77.8 kN hydraulic pump delivers the fastest transmission wire cuts for enhanced productivity
- o Milwaukee® ONE-KEY™ technology allows linemen to view tool usage, receive notifications for recommended maintenance, and sync information wirelessly to the cloud
- o ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- o REDLINK™ individual battery cell monitoring optimises tool run time and ensures long term pack durability
- o REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- o Flexible battery system: works with all Milwaukee® M18™ batteries

UNLOCKING THE DIGITAL JOBSITE.



	M18 HCC45-0C	M18 HCC45-522C
Battery pack capacity (Ah)	–	1 x 5.0 + 1 x 2.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
Cutting force (kN)	77.8	77.8
Max. cutting diameter (mm)	44	44
Cutting time (s)	<9	<9
Weight with battery pack (kg)	–	6.0
Supplied in	Kitbox	Kitbox
Article Number	4933459265	4933459266


ACSR BLADE FOR M18 HCC45	
Article Number	49162775



M18 ONEHCC

M18™ FORCE LOGIC™ HYDRAULIC 35 MM CABLE CUTTER

- o FORCE LOGIC™ hydraulic cable cutter cuts cables in less than 3 seconds with 53 kN of force
- o Milwaukee® designed and built brushless POWERSTATE™ motor provides more power, more run-time and longer life
- o Fully balanced tool provides secure control during one hand operation
- o One tool provides cutting solutions for ACSR wire, steel guy wire, fine stranded or standard copper and aluminium cable
- o Quick jaw reception enables user to retool for a complete new application in less than 15 seconds
- o Compact in-line and slim jaw design with 350° rotatable head allows easy cuts, even in narrow spaces
- o Milwaukee® ONE-KEY™ technology allows linemen to view tool usage, receive notifications for recommended maintenance and sync information wirelessly to the Cloud
- o Sealed electronics resist harsh environments with dirt, dust and moisture

M18 FORCE LOGIC™
ONE-KEY™
 UNLOCKING THE DIGITAL JOBSITE.™


		Description	Article Number	
1.	Cu/Al standard copper & aluminium cable cutting jaw including blades	Cable cutter jaw and blade set for cutting copper/aluminium. Copper/aluminium standard stranded cable up to 4 x 50 mm², 1 x 500 mm² in aluminium and 1 x 400 mm² in copper. Not suitable for fine stranded/highly flexible cable. Max. cutting Ø35 mm	4932430839	
	Cu/Al standard copper & aluminium cable cutting blades	Cu/Al standard copper & aluminium cable cutting blades. The blades fit for the Cu/Al cutting jaws for M18HCC & ONEHCC cutters + M18 HCCT crimper cutting jaw	4932464498	
2.	ACSR Aluminium steel reinforced cable cutting jaw including blades	Cable cutter jaw and blade set for cutting aluminium-steel transmission cable. ACSR-aluminium conductor steel supported cable and ACSR-aluminium conductor steel reinforced cable i.e. 94-AL1 / 15-ST1A (EN 50182). Not suitable for armoured cable or steel rods. Max. cutting Ø22.5 mm	49162773	
	ACSR Aluminium steel reinforced cable cutting blades	Replacement cable cutter blades for ACSR-jaw. Not suitable for armoured cable or steel rods.	48440412	
3.	EHS guy wire/steel wire cutting jaw including blades	Cutting jaw and blades for EHS grade guy wire, stay wire & steel wire according to DIN48201/3 guy wire of grade ST1/ST2/ST3. Not suitable for fine stranded steel ropes. Max. cutting Ø15 mm	49162777	
	EHS guy wire/steel wire cutting blades	EHS guy wire/steel wire cutting blades	48442777	
4.	FSW fine stranded wire cutting jaw including blades	Cable cutter jaw and blades for class 5 fine stranded wire and class 6 finest stranded wire according to IEC 60228/DIN VDE 0295 standards. Also suitable for high flexible data- and telecable. Not suitable for thick stranded cables. Max. cutting Ø35 mm	49162778	
	FSW fine stranded wire cutting blades	FSW fine stranded wire cutting blade	48442778	

	M18 ONEHCC-0C CU/AL-SET	M18 ONEHCC-201C CU/AL-SET	M18 ONEHCC-0C ACSR SET	M18 ONEHCC-201C ACSR SET	M18 ONEHCC-0C FSW SET	M18 ONEHCC-201C FSW SET
Battery pack capacity (Ah)	–	2.0	–	2.0	–	2.0
No. of batteries supplied	0	1	0	1	0	1
Charger supplied	–	40 min	–	40 min	–	40 min
Cutting force (kN)	53	53	53	53	53	53
Max. cutting diameter (mm)	35	35	22.5	22.5	35	35
Cutting time (s)	<3	<3	<3	<3	<3	<3
Weight with battery pack (kg)	–	3.7	–	3.7	–	3.7
Standard equipment	Cu/AL jaw	Cu/AL jaw	ACSR jaw	ACSR jaw	FSW jaw	FSW jaw
Supplied in	Kitbox	Kitbox	Kitbox	Kitbox	Kitbox	Kitbox
Article Number	4933464300	4933464301	4933464303	4933464304	4933464308	4933464309

M18 HKP

M18™ FORCE LOGIC™ HYDRAULIC KNOCKOUT PUNCH

- o FORCE LOGIC™ hydraulic knockout punch is the most compact and lightweight tool on the market with 60 kN of force
- o The easiest way to punch - for fast, accurate, round, and burr free holes
- o Highest accuracy due to industry's finest exact alignment system for dies
- o Best balanced tool and easiest control due to one hand operation
- o Quick connector allows easy set-up of punch and die without carrying the weight of the tool
- o Tool punches up to Ø100 mm holes into 3.0 mm mild steel or 2.5 mm stainless steel
- o Compatible with most common punches and dies available on market
- o Easiest, less strenuous and nonexpedable way of making holes into sheet metal
- o On board fuel gauge and LED light
- o REDLINK™ individual battery cell monitoring optimises tool run time and ensures long term pack durability
- o REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- o Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 HKP-201C	M18 HKP-201CA
Battery pack capacity (Ah)	2.0	2.0
No. of batteries supplied	1	1
Charger supplied	40 min	40 min
Punching force (kN)	60	60
Max. punching diameter (mm)	100	100
Max. material thickness (mm)	2.5 in stainless and 3.0 in mild steel	2.5 in stainless and 3.0 in mild steel
Standard equipment	11.1mm (7/16") draw stud, 19mm (3/4") draw stud, quick connector, ball pull, adaptor	11.1mm (7/16") draw stud, 19mm (3/4") draw stud, quick connector, ball pull, adaptor, punches and dies: M16, M20, M25, M32, M40
Weight with battery pack (kg)	2.3	2.3
Supplied in	Kitbox	Kitbox
Article Number	4933451202	4933451204

Description	Diameter (mm)	Article Number		Description	Diameter (mm)	Article Number	
Punch M16	16.2	4932430841		Die M16	16.2	4932430913	
Punch PG16	22.5	4932430843		Die PG16	22.5	4932430915	
Punch M20	20.4	4932430842		Die M20	20.4	4932430914	
Punch PG21	28.3	4932430845		Die PG21	28.3	4932430917	
Punch M25	25.4	4932430844		Die M25	25.4	4932430916	
Punch M32	32.5	4932430846		Die M32	32.5	4932430918	
Punch M40	40.5	4932430847	Die M40	40.5	4932430919		
Punch M50	50.5	4932430848	Die M50	50.5	4932430920		
Punch M63	63.5	4932430849	Die M63	63.5	4932430921		
Draw bolt 11.1 mm (7/16")		49162680					
Draw bolt 19 mm (3/4")		49162681					

M18 FORCE LOGIC™


SET UP - bold crosshairs and a clear view of the work surface make alignment fast and easy



CONNECT - grab the tool and snap it on to the quick connect



PUNCH - just pull the trigger to punch the hole with ease



REPEAT - release from tool, drop out the slug with ease, and reset

M18 BLHPT | M18™ FORCE LOGIC™ BRUSHLESS PRESSTOOL

- New compact brushless motor in FORCE LOGIC™ press tools delivers up to 10% faster connections and 20% more runtime
- Most compact in-line design with 13% less weight for easy operation
- One hand operated tool for over head applications and working in narrow spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Battery-tool communication: press operation doesn't start to prevent incomplete pressing in case of low charged battery. Pre-press battery check ensures enough charge to complete each press
- FORCE LOGIC™ press indicator: provides visual confirmation of a quality connection
- FORCE LOGIC™ long life reliability: No press cycle limitation within the 3 year maintenance interval
- Allows to press system related up to 108 mm metal pipes and 110 mm composite pipes
- Universal jaw reception to fit most common jaws available on the market
- REDLINK™ individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries


M18 FORCE LOGIC™

	M18 BLHPT-202C	M18 BLHPT-202C M-SET	M18 BLHPT-202C V-SET	M18 BLHPT-202C TH-SET	M18 BLHPT-202C U-SET
Battery pack capacity (Ah)	2.0	2.0	2.0	2.0	2.0
No. of batteries supplied	2	2	2	2	2
Charger supplied	40 min	40 min	40 min	40 min	40 min
Press cycles	40,000	40,000	40,000	40,000	40,000
Press force (kN)	32	32	32	32	32
Max. press size in metal (mm)	108	108	108	108	108
Max. press size in plastic (mm)	110	110	110	110	110
Weight with battery pack (kg)	2.9	2.9	2.9	2.9	2.9
Standard equipment	-	3 x M-profile jaws (15/22/28 mm)	3 x V-profile jaws (15/22/28 mm)	3 x TH-profile jaws (16/20/32 mm)	3 x U-profile jaws (16/20/25 mm)
Supplied in	Kitbox	Kitbox	Kitbox	Kitbox	Kitbox
Article Number	4933451132	4933451133	4933451134	4933451135	4933451136

M12 HPT | M12™ SUB COMPACT FORCE LOGIC™ HYDRAULIC PRESS TOOL

- The industry's smallest, lightest press tool: weighs only 1.8 kg for greater user comfort
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Patented one hand operation allows to work in restricted areas
- Battery-tool communication: press operation doesn't start to prevent incomplete pressing in case of low charged battery. Pre-press battery check ensures enough charge to complete each press
- Service intervals: advanced electronics count cycles and notify users when tool reaches calibration intervals
- 4-step and precise battery status indicator
- Press indicator: provides visual confirmation of a quality connection
- Long-term reliability: goes an industry-leading 40,000 cycles between calibration inspections - the tool will not stop working after reaching 40,000 cycles
- Outstanding pressing range up to 35 mm metal- and 40 mm composite pipes
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries


M12 FORCE LOGIC™

	M12 HPT-202C	M12 HPT-202C M-KIT	M12 HPT-202C V-KIT	M12 HPT-202C V-KIT2	M12 HPT-202C TH-KIT	M12 HPT-202C U-KIT
Battery pack capacity (Ah)	2.0	2.0	2.0	2.0	2.0	2.0
No. of batteries supplied	2	2	2	2	2	2
Charger supplied	40 min	40 min	40 min	40 min	40 min	40 min
Press cycles	40,000	40,000	40,000	40,000	40,000	40,000
Press force (kN)	19	19	19	19	19	19
Max. press size in metal (mm)	35	35	35	35	35	35
Max. press size in plastic (mm)	40	40	40	40	40	40
Weight with battery pack (kg)	1.8	1.8	1.8	1.8	1.8	1.8
Standard equipment	-	3 x M-profile jaws (15/22/28 mm)	3 x V-profile jaws (15/22/28 mm)	3 x V-profile jaws (14/16/22 mm)	3 x TH-profile jaws (16/20/32 mm)	3 x U-profile jaws (16/20/25 mm)
Supplied in	Kitbox	Kitbox	Kitbox	Kitbox	Kitbox	Kitbox
Article Number	4933443085	4933443095	4933443100	4933459382	4933443105	4933443110

PRESS JAWS

Jaw profile	Fits to following pipe system suppliers	Nominal size	M12 HPT		M18 BLHPT		Image
			Description	Article Number	Description	Article Number	
M	Geberit: Mapress VSH: X-Press Eurotubi Raccorderie Metallique Rubinetteria Bresciane Sanha: Nirosoan Pegler Yorkshire	12	J12-M12	4932430243	J18-M12	4932430244	
		15	J12-M15	4932430245	J18-M15	4932430246	
		18	J12-M18	4932430247	J18-M18	4932430248	
		22	J12-M22	4932430249	J18-M22	4932430250	
		28	J12-M28	4932430251	J18-M28	4932430252	
		35	J12-M35	4932430253	J18-M35	4932430254	
V	Vioga Comap IBP Sanha: Nirosoan	42	-	-	RJ18-M42 (requires ring jaw adaptor RJA-1)	4932430255	
		54	-	-	RJ18-M54 (requires ring jaw adaptor RJA-1)	4932430256	
		12	J12-V12	4932430260	J18-V12	4932430261	
		14	J12-V14	4932451660	J18-V14	4932471086	
		15	J12-V15	4932430262	J18-V15	4932430263	
		16	J12-V16	4932451661	J18-V16	4932471087	
		18	J12-V18	4932430264	J18-V18	4932430265	
		22	J12-V22	4932430266	J18-V22	4932430267	
		28	J12-V28	4932430268	J18-V28	4932430269	
		35	J12-V35	4932430270	J18-V35	4932430271	
		42	-	-	RJ18-V42 (requires ring jaw adaptor RJA-1)	4932430272	
		54	-	-	RJ18-V54 (requires ring jaw adaptor RJA-1)	4932430273	
TH	ALB Comap Frankische Henco (TH14 - TH25 only) IPA Sanha Tiemme	14	J12-TH14	4932430274	J18-TH14	4932430275	
		16	J12-TH16	4932430276	J18-TH16	4932430277	
		18	J12-TH18	4932430278	J18-TH18	4932430279	
		20	J12-TH20	4932430280	J18-TH20	4932430281	
		25	J12-TH25	4932430282	J18-TH25	4932430355	
		26	J12-TH26	4932430283	J18-TH26	4932430284	
		32	J12-TH32	4932430285	J18-TH32	4932430286	
		40	J12-TH40	4932430287	RJ18-TH40 (requires ring jaw adaptor RJA-1)	4932430288	
		50	-	-	RJ18-TH50 (requires ring jaw adaptor RJA-1)	4932430289	
		63	-	-	RJ18-TH63 (requires ring jaw adaptor RJA-1)	4932430290	
U	ALB Uponor: Unipipe, Airpipe Kan: Kan-therm Wavin: Press-Systeme Frankische: Alplex F50 Profi DW Verbundrohr Multitubo IBP->B-Flex KE Kelit: Kelit Kelox Jupiter: Heizsystem	14	J12-U14	4932430291	J18-U14	4932430292	
		16	J12-U16	4932430293	J18-U16	4932430294	
		18	J12-U18	4932430295	J18-U18	4932430296	
		20	J12-U20	4932430297	J18-U20	4932430298	
		25	J12-U25	4932430299	J18-U25	4932430300	
		32	J12-U32	4932430301	J18-U32	4932430302	
		40	J12-U40	4932430303	RJ18-U40 (requires ring jaw adaptor RJA-1)	4932430304	
		50	-	-	RJ18-U50 (requires ring jaw adaptor RJA-1)	4932430305	
63	-	-	RJ18-U63	4932430306			
ACz	ACOME MT	12	J12-ACz 12	4932459388	-	-	
		16	J12-ACz 16	4932459389	-	-	
		20	J12-ACz 20	4932459390	-	-	
		25	J12-ACz 25	4932459391	-	-	
G	Geberit: Mepla & Mepla Therm	16	J12-G16	4932464217	J18-G16	4932464544	
		20	J12-G20	4932464218	J18-G20	4932464545	
		26	J12-G26	4932464219	J18-G26	4932464546	
		32	J12-G32	4932464220	J18-G32	4932464547	
		40	J12-G40	4932464221	J18-G40	4932464548	
50	-	-	J18-G50	4932464549			
a Ring jaw adaptor (RJA - 1).					RJA-1	4932430307	

M18 ONEBLPXPL

M18™ ONE-KEY™ FORCE LOGIC™ UPONOR® Q&E HYDRAULIC PIPE EXPANDING TOOL

- The ONE-KEY™ FORCE LOGIC™ hydraulic expander is the world's first cordless expander for Uponor® Q&E PE-Xa pipe sizes up to DN75
- Milwaukee® designed and built brushless POWERSTATE™ motor delivers outstanding run time and quick expansions
- Expands dimensions DN40, DN50, DN63 and DN75 of 6 and 10 bar pipes
- Intelligent design delivers optimum balance for overhead connections, and flips over for extended use on table-tops
- Auto-rotating head expands PEX pipe quickly and evenly
- Auto-cycle rotates, expands and resets automatically simplifying installation process
- Expander resets automatically after every expansion to speed up repetitive connections
- Side handle and integrated tethering point for improved jobsite safety
- ONE-KEY™ technology allows the operator to view tool usage, receive notifications for recommended maintenance, and sync information wirelessly to the Cloud
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



ONE-KEY
UNLOCKING THE DIGITAL JOBSITE™

M18 FORCELOGIC™



Delivers optimum balance for overhead connections



Flips over for extended use on table-tops



Side handle and integrated tethering point for improved jobsite safety

M18 ONEBLPXPL-502C

Battery pack capacity (Ah)	5.0
No. of batteries supplied	2
Charger supplied	100 min
Stroke length (mm)	55.5
Head type	Auto-rotating
Weight with battery pack (kg)	10.1
Supplied in	Kitbox
Article Number	4933464299

HD18 PXP | M18™ UPONOR® Q&E EXPANSION TOOL

- Auto rotating head 12 mm to 40 mm (6 bar) and to 32 mm (10 bar) provides accurate, one-handed expansion
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Quick cam mechanism - single pull continuous action installs Q&E up to 4x faster
- Steel gears and integrated magnesium frame
- Robust D-handle design for easy installation of Q&E fittings
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M18™ batteries



	HD18 PXP-H06202C	HD18 PXP-H10202C
Battery pack capacity (Ah)	2.0	2.0
No. of batteries supplied	2	2
Charger supplied	40 min	40 min
Stroke length (mm)	14	25
Speed (spm)	45	45
Included heads	16/20/25/32 mm	16/20/25/H32 mm
Head type	Auto-rotating	Auto-rotating
Weight with battery pack (kg)	3.5	3.5
Supplied in	Kitbox	Kitbox
Article Number	4933441771	4933441774

C12 PXP | M12™ SUB COMPACT UPONOR® Q&E EXPANSION TOOL

- Auto-rotating head 12 mm to 32 mm (6 bar) and to 25 mm (10 bar) provides accurate, one-handed expansion
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Quick cam mechanism - single pull, continuous action installs Q&E up to 4x faster
- Steel gears and integrated frame
- Right angle design for easy installation of Q&E fittings
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	C12 PXP-I06202C	C12 PXP-I10202C	C12 PXP-N202C
Battery pack capacity (Ah)	2.0	2.0	2.0
No. of batteries supplied	2	2	2
Charger supplied	40 min	40 min	40 min
Stroke length (mm)	14	14	14
Speed (spm)	60	60	60
Included heads	16/ 20/ 25 mm	16/ 20/ 25 mm	15/18/22 mm
Weight with battery pack (kg)	1.9	1.9	1.9
Supplied in	Kitbox	Kitbox	Kitbox
Article Number	4933441715	4933441730	4933441740

EXPANDER HEADS

	Pipe diameter (mm)	Pipe wall thickness (mm)	Pipe pressure (bar)	Suitable	Article Number
PXPH9-144/8	9.9	1.1	4/8	M12, M18	4932430102
PXPH12-14	12	1.7/ 1.8/ 2	6-10	M12, M18	4932352716
PXPH15N-14	14 / 15	2.5	6-10	M12, M18	4932352727
PXPH16-1406	16	1.5/ 1.8	6	M12, M18	4932430103
PXPH16-1410	16	1.8/ 2.0/ 2.2	10	M12, M18	4932352717
PXPH18N-14	17 / 18	2.5	6-10	M12, M18	4932352728
PXPH20I-1406	20	1.9/ 2.0/ 2.3	6, (8 bar - Ø 2.3 mm)	M12, M18	4932352718
PXPH20I-1410	20	2.8	10	M12, M18	4932352719
PXPH20I-2506	20	1.9/ 2.0/ 2.3	6, (8 bar - Ø 2.3 mm)	M18	4932352733
PXPH20I-2510	20	2.8	10	M18	4932352748
PXPH22N-14	22	3	6-10	M12, M18	4932352729
PXPH25I-1406	25	2.3	6	M12, M18	4932352720
PXPH25I-1410	25	3.5	10	M12, M18	4932352721
PXPH25I-2506	25	2.3	6	M18	4932352722
PXPH25I-2510	25	3.5	10	M18	4932352749
PXPH28N-14	28	4	6-10	M12, M18	4932352730
PXPH32I-1406	32	2.9	6	M12, M18	4932352723
PXPH32I-25	32	2.9/ 4.4	6-10	M18	4932352724
PXPH40I-2506	40	3.7	6	M18	4932352725
PXPH 40I - 5606	40	3.7	6-10	M18 BLPXPL	4932451396
PXPH 50I - 5606	50	4.6	6-10	M18 BLPXPL	4932451397
PXPH 63I - 5606	63	5.8	6-10	M18 BLPXPL	4932451398
PXPH 75I - 5606	75	6.8	6-10	M18 BLPXPL	4932451399



Grease

Tube contents 50 g. For lubrication of cone and expander heads.

4932352726

DRAIN CLEANERS



M12 BDC6 | M12™ SUB COMPACT DRAIN CLEANER WITH SPIRAL DIAMETER 6 MM

- Lightest professional drain cleaner on the market
- Versatile design, provides benefits of both handheld and floor based drain cleaners in one machine
- Best user flexibility and manoeuvrability due to the independence of electric power supply
- Tool includes a highly flexible 6 mm spiral for easy access in drainpipes up to 50 mm, also all standard Ø 6 & 8 mm spirals can be used with the tool
- Robust drum shield protects user & fixtures from spinning drum during use
- Easy removable inner drum helps to prevent spiral bind up and contains dirt inside the drum
- Quick cable lock mechanism for manual feeding and releasing the spiral
- Integrated LED light illuminates work area underneath sinks and other dark spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 BDC6-0	M12 BDC6-202C
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	2
Charger supplied	–	40 min
No load speed (rpm)	0 - 500	0 - 500
Max. drain diameter (mm)	50	50
Spiral diameter (mm)	6	6
Cable length (m)	7.6	7.6
Bucket capacity (l)	22.5	22.5
Weight with battery pack (kg)	–	4.2
Supplied in	Bucket	Bucket
Article Number	4933451634	4933451635

M12 BDC8 | M12™ SUB COMPACT DRAIN CLEANER WITH SPIRAL DIAMETER 8 MM

- Lightest professional drain cleaner on the market
- Versatile design, provides benefits of both handheld and floor based drain cleaners in one machine
- Best user flexibility and manoeuvrability due to the independence of electric power supply
- Tool includes a tough 8 mm spiral for strong blockages in pipes up to 60 mm, also all standard Ø 6 & 8 mm spirals can be used with the tool
- Robust drum shield protects user & fixtures from spinning drum during use
- Easy removable inner drum helps to prevent spiral bind up and contains dirt inside the drum
- Quick cable lock mechanism for manual feeding and releasing the spiral
- Integrated LED light illuminates work area underneath sinks and other dark spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 BDC8-0	M12 BDC8-202C
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	2
Charger supplied	–	40 min
No load speed (rpm)	0 - 500	0 - 500
Max. drain diameter (mm)	60	60
Spiral diameter (mm)	8	8
Cable length (m)	7.6	7.6
Bucket capacity (l)	22.5	22.5
Weight with battery pack (kg)	–	4.8
Supplied in	Bucket	Bucket
Article Number	4933451632	4933451633

M12™ DRAIN CLEANER ACCESSORIES


	Article Number
1. Ø 8 mm x 7.6 m spiral, bulb auger	48532571
2. Ø 8 mm x 7.6 m pivot bulb auger spiral	48532572
1. Ø 6 mm x 7.6 m spiral, bulb auger	48532573
2. Ø 6 mm x 7.6 m pivot bulb auger spiral	48532574
3. Ø 8 mm x 7.6 m spiral, bulb auger with drum	48532581
4. Ø 8 mm x 7.6 m spiral, pivot bulb auger with drum	48532582
3. Ø 6 mm x 7.6 m spiral, bulb auger with drum	48532583
4. Ø 6 mm x 7.6 m spiral, pivot bulb auger with drum	48532584

M18 FDCPF8 | M18 FUEL™ DRAIN CLEANER - POWER FEED 8 MM

- Milwaukee® designed and built brushless POWERSTATE™ motor delivers maximum power 15 m down the line
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- CABLE-DRIVE locking feed system maintains selected feed speed, and auto-adjusts to compatible cable sizes for the best cable grip when feeding and working the clog
- Fully enclosed drum for best protection and mess containment
- LED light illuminates work area underneath sinks and other dark spaces
- Accepts other brand cables
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 FDCPF8-0C
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	0 - 600
Max. drain diameter (mm)	64
Spiral diameter (mm)	8
Cable length (m)	10.6
Bucket capacity (l)	23
Standard equipment	8 mm x 10.6 m cable (48532673)
Weight with battery pack (kg)	6.9
Supplied in	Bucket
Article Number	4933459683

M18 FDCPF10 | M18 FUEL™ DRAIN CLEANER - POWER FEED 10 MM

- Milwaukee® designed and built brushless POWERSTATE™ motor delivers maximum power 15 m down the line
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- CABLE-DRIVE locking feed system maintains selected feed speed, and auto-adjusts to compatible cable sizes for the best cable grip when feeding and working the clog
- Fully enclosed drum for best protection and mess containment
- LED light illuminates work area underneath sinks and other dark spaces
- Accepts other brand cables
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 FDCPF10-0C	M18 FDCPF10-201C
Battery pack capacity (Ah)	–	2.0
No. of batteries supplied	0	1
Charger supplied	–	40 min
No load speed (rpm)	0 - 600	0 - 600
Max. drain diameter (mm)	75	75
Spiral diameter (mm)	10	10
Cable length (m)	10.6	10.6
Bucket capacity (l)	23	23
Standard equipment	1 x 10 mm x 10.6 m cable (48532675), retriever bulb, removal pin	1 x 10 mm x 10.6 m cable (48532675), 5 pc cutter set (48532685), removal pin
Weight with battery pack (kg)	6.9	6.9
Supplied in	Bucket	Bucket
Article Number	4933459684	4933459685

M18™ POWER SPEED DRAIN CLEANER ACCESSORIES


	Article Number
1. 6 mm x 10.5 m spiral bulb auger	48532671
1. 8 mm x 10.5 m spiral bulb auger.	48532673
1. 6 mm x 15 m spiral bulb auger	48532672
1. 10 mm x 10.5 m spiral.	48532675
1. 8 mm x 15 m spiral bulb auger.	48532674
2. Retriever bulb.	48532681
3. Down retriever bulb.	48532682
4. 25 mm spade bit.	48532683
5. 25 mm grease cutter.	48532684
6. M18 Small 5 pcs attachment set	48532685

M18 FFSDC16

M18 FUEL™ FREE STANDING DRAIN CLEANER 16 MM

- Milwaukee® designed and built brushless POWERSTATE™ motor delivers maximum power 30 m down the line
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- M18 FUEL™ SWITCH PACK™ tool-free drum connection system allows users to quickly interchange between cable sizes, or add a second drum to reach 30 m down the line
- Built-in backpack straps for the easiest transport to any roof, drain, crawl space, or clean out
- Integrated drum brake electronically slows drum super-fast for end user control and safety
- Electronic foot pedal with non-slip grip for maximum durability
- Fully enclosed drum for best protection and mess containment
- SWITCH PACK™ drum capacity 8 mm x 23 m inner core cable
- On-tool accessory attachment storage
- Supplied with 1 x backpack assembly, 2 x drum assembly's, 2 x 16 mm x 15 m cables, 1 x cutter set & removal tool
- Accepts other brand cables
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 FFSDC16-0	M18 FFSDC16-502
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	59 min
No load speed (rpm)	0 - 250	0 - 250
Max. drain diameter (mm)	75	75
Spiral diameter (mm)	16	16
Cable length (m)	15	15
Weight with battery pack (kg)	13.4	13.4
Supplied in	–	–
Article Number	4933459709	4933459710



M18 FUEL™ SWITCH PACK™ tool-free drum connection system



Built-in backpack straps for the easiest transport



Electronic foot pedal with non-slip grip

M18 FFSDC13 | M18 FUEL™ FREE STANDING DRAIN CLEANER 13 MM

- Milwaukee® designed and built brushless POWERSTATE™ motor delivers maximum power 30 m down the line
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- M18 FUEL™ SWITCH PACK™ tool-free drum connection system allows users to quickly interchange between cable sizes, or add a second drum to reach 30 m down the line
- Built-in backpack straps for the easiest transport to any roof, drain, crawl space, or clean out
- Integrated drum brake electronically slows drum super-fast for end user control and safety
- Electronic foot pedal with non-slip grip for maximum durability
- Fully enclosed drum for best protection and mess containment
- SWITCH PACK™ drum capacity 8 mm x 23 m inner core cable
- On-tool accessory attachment storage
- Supplied with 1 x backpack assembly, 2 x drum assembly's, 2 x 13 mm x 15 m cables, 1 x cutter set & removal tool



	M18 FFSDC13-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	0 - 250
Max. drain diameter (mm)	100
Spiral diameter (mm)	13
Cable length (m)	15
Weight with battery pack (kg)	7.8
Supplied in	–
Article Number	4933459708


M18 FFSDC10 | M18 FUEL™ FREE STANDING DRAIN CLEANER 10 MM

- Milwaukee® designed and built brushless POWERSTATE™ motor delivers maximum power 30 m down the line
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- M18 FUEL™ SWITCH PACK™ tool-free drum connection system allows users to quickly interchange between cable sizes, or add a second drum to reach 30 m down the line
- Built-in backpack straps for the easiest transport to any roof, drain, crawl space, or clean out
- Integrated drum brake electronically slows drum super-fast for end user control and safety
- Electronic foot pedal with non-slip grip for maximum durability
- Fully enclosed drum for best protection and mess containment
- SWITCH PACK™ drum capacity 8 mm x 23 m inner core cable
- On-tool accessory attachment storage
- Supplied with 1 x backpack assembly, 1 x drum assembly, 1 x 10 mm x 15 m cable, 1 x cutter set & removal tool



	M18 FFSDC10-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	0 - 250
Max. drain diameter (mm)	75
Spiral diameter (mm)	10
Cable length (m)	15
Weight with battery pack (kg)	13.4
Supplied in	–
Article Number	4933459707

M18™ FREESTANDING DRAIN CLEANER ACCESSORIES



	Article Number
1. Drain cleaner drum only	4932464277
2. 8 mm x 23 m spiral bulb auger.	48532772
2. 10 mm x 15 m spiral.	48532773
2. 13 mm x 15 m spiral.	48532774
2. 16 mm x 15 m spiral.	48532775
3. Funnel retriever.	48532786
4. Drop head.	48532787
5. 36 mm spade bit.	48532788
6. 40 mm grease cutter.	48532789
7. M18 Medium 5 pcs attachment set	48532790

TRUEVIEW™ HIGH DEFINITION LIGHTING



M18

M18 ONESLDP

M18™ ONE-KEY™ LED COMPACT SITE LIGHT CHARGER

M18

- Optimise brightness and run time by adjusting the light output from 0 - 9000 Lumens
- ONE-KEY™ tool customisation allows user to control brightness and set light settings remotely
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- Program automatic schedules to decide during which days/times the light is running
- Integrated M18™ charger - charges up to 2 batteries sequentially
- Dual power source, powered by either M18™ REDLITHIUM-ION™ battery packs or use of 2.5 m hardwired cord
- AC outlet gives the possibility to string multiple lights together
- Highly durable and impact resistant polycarbonate lens to protect the light from rough jobsite conditions
- IP54 rating in battery mode - light is protected from dust and splashing water
- TRUEVIEW™ high definition light output delivers consistent beam, optimised colour temperature and true representation of colours and detail
- Securable battery door helps to protect batteries from theft (lock not included)

	M18 ONESLDP-0
Voltage (AC) (V)	100 - 240
Voltage (DC) (V)	18
Battery type	Li-ion
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
System	M18
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	9000/ 4800/ 2500/ -
Max. run time with M18 B9 battery (h)	3.5/ 7/ 14/ -
Weight with battery pack (kg)	12.1
Supplied in	-
Article Number	4933459160

ONE-KEY™
UNLOCKING THE DIGITAL JOBSITE.™



ONE-KEY™ technology enables advanced light customisation and to control the light remotely



Integrated M18™ charger - charges up to 2 batteries sequentially



Highly durable and impact resistant polycarbonate lens

M18 ONESLSP | M18™ ONE-KEY™ LED COMPACT SITE LIGHT

M18

- ONE-KEY™ tool customisation allows user to control brightness and set light settings remotely
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- Optimise brightness and run time by adjusting the light output between 0 - 4400 Lumens
- Program automatic schedules to decide during which days/times the light is running
- TRUEVIEW™ high definition lighting solutions combine the most advanced LED technology
- 180° and 360° electronic light control for large area and task lighting
- Self-centering metal hook designed for hanging the light from studs or pipes
- Dual power source, powered by either M18™ REDLITHIUM-ION™ battery packs or use of 2.5 m hardwired cord
- AC outlet gives the possibility to string multiple lights together
- Up to 8 hours of run time on low setting when powered by an M18™ REDLITHIUM-ION™ 5.0 Ah battery pack



ONE-KEY™
UNLOCKING THE DIGITAL JOBSITE.™

	M18 ONESLSP-0
Voltage (AC) (V)	220 - 240
Voltage (DC) (V)	18
Battery type	Li-ion
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
System	M18
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	4400 / 2100 / 1000 / -
Max. run time with M18 B5 battery (h)	2 / 4 / 8 / -
Weight with battery pack (kg)	5.4
Supplied in	-
Article Number	4933459157

M18 SLSP | M18™ LED COMPACT SITE LIGHT

- TRUEVIEW™ high definition lighting
- Most versatile light on site, can be used for task, area and overhead lighting
- 180° and 360° electronic light control for large area and task lighting
- High performance LEDs and 3 light settings provide up to 4400 Lumens for full workspace coverage
- Reinforced hang hole as well as self-centering metal hook designed for hanging the light from studs or pipes
- Dual power source, powered by either M18™ REDLITHIUM-ION™ battery packs or use of 2.5 m included extension cord
- Up to 8 hours of run time on Low setting when powered by an M18™ REDLITHIUM-ION™ 5.0 Ah battery pack
- Highly durable and impact resistant polycarbonate lens to protect the light from rough jobsite conditions
- IP54 rating, the light is protected from dust and splashing water
- Carry handle with rubber overmould for easy one-handed transport
- Security cable included


M18

M18 SLSP-0	
Voltage (AC) (V)	220 - 240
Voltage (DC) (V)	18
Battery type	Li-ion
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
System	M18
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	4400 / 2100 / 1000 / -
Max. run time with M18 B5 battery (h)	2 / 4 / 8 / -
Weight with battery pack (kg)	5.4
Supplied in	–
Article Number	4933451514

M18 HSAL | M18™ HIGH PERFORMANCE LED STAND LIGHT CHARGER

- TRUEVIEW™ high definition lighting
- Twelve high performance LEDs and 3 light settings provide up to 3000 Lumens on High mode which is brighter than a 500 Watt halogen light
- 3 impact resistant adjustable heads with highly durable polycarbonate lens can be rotated 180° vertically and pivoted 240° horizontally to have the perfect workplace illumination
- Integrated M18™ charger
- Dual power source, powered by either M18™ REDLITHIUM-ION™ battery packs or use of 2.5 m hardwired cord
- Protective guard secures the head and lens when the light is collapsed for storage or transport
- Extendable mast which reaches from 1.10 m to over 2.15 m to light up work spaces from top without casting shadows
- Compact footprint with low center of gravity and impact resistant reinforced nylon legs to protect against abusive jobsite conditions
- Carry handles with rubber overmould on two positions for easy one-handed transport, weight is evenly balanced when compressed
- Low battery indicator, light flashes when battery pack is low on charge


M18

	M18 HSAL-0	M18 HSAL-502B
Voltage (AC) (V)	220 - 240	220 - 240
Voltage (DC) (V)	18	18
Battery type	Li-ion	Li-ion
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	100 min
System	M18	M18
Battery compatibility	All Milwaukee® M18™ batteries	All Milwaukee® M18™ batteries
Bulb type	LED	LED
Max. light output High/Medium/Low/Strobe (Lumens)	3000 / 1700 / 900 / -	3000 / 1700 / 900 / -
Max. run time with M18 B5 battery (h)	2.25 / 4.25 / 8 / -	2.25 / 4.25 / 8 / -
Weight with battery pack (kg)	–	8.5
Supplied in	–	Tool bag
Article Number	4933451392	4933451898

M18 TAL | M18™ TRADESMAN AREA LIGHT

- TRUEVIEW™ high definition lighting with 2,200 Lumens of light output in Area mode and 1,000 Lumens in Flood mode
- Advanced LED technology provides 360° of area light, while an independent array of LEDs on the side provide 90° of task lighting
- Compact design allowing for one-handed transport on the jobsite, with a built-in carry handle
- Impact polycarbonate lens design that is impact and chemical resistant, delivering superior impact durability
- Equipped with a 10.8 cm self-centering metal hook, users can hang the light overhead on studs and piping
- Low battery indicator, light flashes when battery pack is low on charge
- Flexible battery system: works with all Milwaukee® M18™ batteries


M18

M18 TAL-0	
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
System	M18
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output Area Mode High/Medium/Low (Lumens)	2200 / 1100 / 550
Max. light output Flood Mode High/Medium/Low (Lumens)	1000 / 500 / 250
Max. run time with M18 B5 battery (h)	4 / 8 / 16
Weight with battery pack (kg)	2.5
Supplied in	–
Article Number	4933464134

M18 ONERSAL | M18™ ONE-KEY™ LED REMOTE STAND LIGHT

- Optimise brightness and run time by adjusting the light output from 0 - 5400 Lumens
- ONE-KEY™ tool customisation allows user to control brightness and set light settings remotely
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- IP67 allows use in all weather conditions (heavy rain, snow, dusty environments)
- Reinforced leg design with 3 different leg deployment options for best durability and stability
- Highly durable and impact resistant polycarbonate lens and all aluminium cam design to protect the light from rough working conditions
- TRUEVIEW™ high definition light output delivers consistent beam, optimised colour temperature and true representation of colours and detail
- Sealed battery compartment for up to 2 packs to extend run time
- Change height from 0.5 m to 1.65 m to cast light from overhead to limit shadows
- Collapsible to only 55 cm for easy storage and transportation


M18

M18 ONERSAL-0	
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
System	M18
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	5400/3000/1550/-
Max. run time with M18 B9 battery (h)	7/12.5/26/-
Weight with battery pack (kg)	9.1
Supplied in	–
Article Number	4933459431

HOBL 7000 | HIGH OUTPUT BAY LIGHT

- TRUEVIEW™ high definition lighting - 7700 Lumens of even light output for best jobsite illumination (110 Lumens / Watt)
- Impact resistant polycarbonate lens withstands drops from up to 2.7 m
- Integrated wiring terminal accepts voltages from 90 -277 V, allows easy wiring and stringing of multiple lights
- Wire strain relief accepts cables up to H07RNF 3 x 2.5 mm²
- Spring-loaded cable retention allows easy adjustment of installation height with 1.2 m steel hanging cable
- 4 m AC power cord for out of the box operation
- Conical lens design and small footprint allow simple storage and safe stacking of up to 3 units


HOBL 7000

Voltage (AC) (V)	90 - 277
Bulb type	LED
Weight (kg)	3.7
Supplied in	–
Article Number	4933464126

M18 SAL | M18™ LED STAND LIGHT

- TRUEVIEW™ high definition lighting
- Twelve high performance LEDs provide 2000 Lumens on high light output which is brighter than 250 Watt halogen
- Impact resistant adjustable head with highly durable polycarbonate lens can be rotated 230° vertically and pivoted 240° horizontally
- Protective guard secures the head and lens when the light is collapsed for storage or transport
- Extendable mast which reaches from 1.10 m to over 2.20 m to light up work spaces from top without casting shadows
- IP54 - protected from dust and splashing water
- Compact footprint with low center of gravity and impact resistant reinforced nylon legs to protect against abusive jobsite conditions
- Carry handles on two positions for easy one handed transport: weight is evenly balanced when compressed
- Low battery indicator - light flashes when battery pack is low


M18

	M18 SAL-0	M18 SAL-502B
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	100 min
System	M18	M18
Battery compatibility	All Milwaukee® M18™ batteries	All Milwaukee® M18™ batteries
Bulb type	LED	LED
Max. light output High/Medium/Low/Strobe (Lumens)	2000 / 1300 / 850 / -	2000 / 1300 / 850 / -
Max. run time with M18 B5 battery (h)	4 / 6 / 10 / -	4 / 6 / 10 / -
Weight with battery pack (kg)	–	7.3
Supplied in	–	Tool bag
Article Number	4933451246	4933451896

M12 SAL | M12™ STAND LIGHT
M12

- TRUEVIEW™ high definition lighting
- Twelve high performance LEDs provide 1400 Lumens on high light output
- Impact resistant adjustable head with highly durable polycarbonate lens to withstand drops up to 3 m
- Head can be rotated 210° vertically and pivoted 270° horizontally to have the best perfect workplace illumination
- Protective guard secures the head and lens when the light is collapsed for storage or transport
- Extendable mast which reaches from 0.91 m to over 1.72 m to light up work spaces
- Compact footprint with low center of gravity and impact resistant reinforced nylon legs to protect against abusive jobsite conditions
- Carry handles on two positions for easy one handed transport: weight is evenly balanced when compressed
- Low battery indicator - light flashes when battery pack is low



	M12 SAL-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
System	M12
Battery compatibility	All Milwaukee® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	1400 / - / 700 / -
Max. run time with M12 B4 battery (h)	4 / - / 10 / -
Weight with battery pack (kg)	3.4
Supplied in	–
Article Number	4933464823

M18 AL | M18™ LED AREA LIGHT
M18

- TRUEVIEW™ high definition lighting
- Eight high performance LEDs provide 1500 Lumens of light output - up to 30% brighter than 250 W halogen lights
- Compact roll cage design provides superior durability
- Convenient built-in handle - ability to hang vertically or horizontally
- Flexibility to mount vertically on a max. 13 mm diameter pipe, threaded rod or rebar to maximise hands-free operation
- Flexible battery system: works with all Milwaukee® M18 batteries™



	M18 AL-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
System	M18
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	1500 / - / 780
Max. run time with M18 B5 battery (h)	5 / 10
Weight with battery pack (kg)	2.1
Supplied in	–
Article Number	4932430392

M18 PAL | M18™ PIVOTING AREA LIGHT
M18

- TRUEVIEW™ high definition lighting with up to 1500 Lumens and up to 20 hours of run time, allows replacement of 500 W halogen
- Two powerful magnets, a spring loaded clamp and a folding rotating light head design provide multiple mounting options and illumination possibilities from any angle
- Highly durable and impact resistant polycarbonate lens to withstand drops up to 2.7 metres
- Most compact M18™ flood light designed for the on-the-go needs of service and maintenance trades
- IP54 rating, the light is protected from dust and splashing water
- Integrated handle/tie off zone, designed to be carried or tethered while used on a scissor lift
- Low battery indicator, light flashes when battery pack is low on charge
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 PAL-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
System	M18
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	1500 / 600 / 300
Max. run time with M18 B5 battery (h)	4.5 / 10 / 20
Weight with battery pack (kg)	2.1
Supplied in	–
Article Number	4933464105

M12 AL | M12™ LED AREA LIGHT
M12

- TRUEVIEW™ high definition lighting
- Five high performance LEDs provide 1000 Lumens of light output replacing 250 W halogen lights
- Highly durable and impact resistant polycarbonate lens to withstand drops up to 2.7 metres
- Integrated magnets, clamping mechanism, and key hole for screws / nails provide multiple mounting options for different surfaces
- Most compact flood light designed for the on-the-go needs of service and maintenance trades
- IP54 rating, the light is protected from dust and splashing water
- Low battery indicator, light flashes when battery pack is low on charge
- Flexible battery system: works with all Milwaukee® M12™ batteries



	M12 AL-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
System	M12
Battery compatibility	All Milwaukee® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	1000 / 500 / 250
Max. run time with M12 B4 battery (h)	3.5 / 7.5 / 15
Weight with battery pack (kg)	1.3
Supplied in	Blister
Article Number	4933451394

M18 HAL | M18™ HIGH PERFORMANCE LED AREA LIGHT
M18

- TRUEVIEW™ high definition lighting
- Twelve high performance LEDs and 3 light settings provide up to 3000 Lumens on high - up to 30% brighter than a 500 Watt halogen light
- 240° rotatable light head and integrated key holes for horizontal and vertical hanging
- Impact resistant polycarbonate lens and durable roll cage to protect the light from rough jobsite conditions
- Dual power source, powered by either M18™ REDLITHIUM-ION™ battery packs or by 2.5 m included extension cord
- Easy one-handed transport with built-in carry handles
- Low battery indicator, light flashes when battery pack is low on charge
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 HAL-0
Voltage (AC) (V)	220 - 240
Voltage (DC) (V)	18
Battery type	Li-ion
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
System	M18
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	3000 / 1500 / 650 / -
Max. run time with M18 B5 battery (h)	2 / 4 / 9 / -
Weight with battery pack (kg)	3.4
Supplied in	–
Article Number	4933451262

M18 SLED | M18™ LED SEARCH LIGHT
M18

- TRUEVIEW™ high definition lighting
- Pivoting head provides 1250 Lumens with up to 650 m beam distance
- 4 output modes: Spot, Flood, Spot/Flood, Strobe delivering multiple options in work space illumination
- Spot mode for long range identification: utility pole/high voltage cable inspection, inspection of long runs of conduit, cast or copper pipe, under ground work, bridge work...
- Flood mode for illuminating close work spaces
- IP54 rating, the light is protected from dust and splashing water
- Ergonomic grip with rubber overmould enhances user comfort and grip during use
- Key hole for hanging function
- Flexible battery system: works with all Milwaukee® M18™ batteries



	M18 SLED-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
System	M18
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output Spot-flood/Flood/Spot/Strobe (Lumens)	1250 / 1200 / 600 / 1200
Max. run time with M18 B5 battery (h)	4 / 4 / 7 / 5
Beam distance (m)	650
Weight with battery pack (kg)	1.4
Supplied in	–
Article Number	4933459159

M12 SLED | M12™ LED SPOT LIGHT
M12

- TRUEVIEW™ high definition lighting
- Up to 35% longer beam distance than competition - 650 m intense and highly focused beam of light with 750 Lumens
- Especially useful for long range identification - utility pole/high voltage cable inspection, inspection of long runs of conduit, cast or copper pipe, under ground work, bridge work
- Metal housing and impact resistant polycarbonate lens with gasketed rubber cap which protects from moisture for harsh jobsite conditions
- Milwaukee® designed reflector - produces narrow centre beam with wide peripheral beam
- Ergonomic grip with rubber overmold - enhances user comfort and grip during use
- 45° rubber overmold stand for aiming beam upward during prolonged use when the light is equipped with a compact battery pack
- Up to 8 hours of runtime with an M12™ REDLITHIUM-ION™ 4.0 Ah battery pack
- Dual function trigger allows momentary or lock-on use
- Battery fuel gauge displays battery status
- Hand wrist lanyard to keep the light safe and handy
- Flexible battery system: works with all Milwaukee® M12™ batteries



M12 SLED-0	
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
System	M12
Battery compatibility	All Milwaukee® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	750 / - / 400 / 750
Max. run time with M12 B4 battery (h)	4 / - / 8 / 8
Beam distance (m)	650
Weight with battery pack (kg)	0.8
Supplied in	Blister
Article Number	4933451261

M12 SL | M12™ LED STICK LIGHT
M12

- TRUEVIEW™ high definition lighting
- Powerful three LED design provides 220 Lumens
- Adjustable metal hook allows for light to be hung in multiple orientations when being used
- Compact design - operates in locations other lights cannot
- Flexible battery system: works with all Milwaukee® M12™ batteries



M12 SL-0	
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
System	M12
Battery compatibility	All Milwaukee® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	220 / - / - / -
Max. run time with M12 B4 battery (h)	11 / - / - / -
Weight with battery pack (kg)	0.5
Supplied in	-
Article Number	4932430178

M12 UHL | M12™ LED UNDERHOOD LIGHT
M12

- TRUEVIEW™ high definition light output delivers consistent beam, optimised colour temperature and true representation of colours and detail
- Two light output settings with 1350 and 600 Lumens to maximise run time and to optimise lighting output
- M12™ 4.0 Ah battery provides 4 hours of run time in high and 8 hours of run time in low setting
- Mounting hooks extend 119 cm - 196 cm (47" - 77") covering wide cars and trucks
- Flexible and versatile light bar to rotate vertically, adjust position and remove from the carrier to suit user needs
- Rubber gripping surface for maximum hold
- Milwaukee®'s FINISHGUARD™ hooks provide lasting protection against scratches to a vehicle's finish
- Stainless hook allows to hang the light bar independently from the carrier
- Aircraft grade aluminium frame ensures maximum durability
- Impact and chemical resistant polycarbonate lens to withstand common automotive fluids
- IP54 - protected from dust and splashing water
- Flexible battery system: works with all Milwaukee® M12™ batteries



M12 UHL-0	
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
System	M12
Battery compatibility	All Milwaukee® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	1350 / - / 600 / -
Max. run time with M12 B4 battery (h)	4 / - / 8 / -
Weight with battery pack (kg)	1.1
Supplied in	-
Article Number	4933459432

M18 LL | M18™ LED LANTERN LIGHT
M18

- TRUEVIEW™ high definition lighting
- 180° - 360° adjustable beam - versatile design, allows the user to select between area lighting and task lighting
- Best-in-class performance - unmatched light output 700 Lumens, designed to illuminate large areas
- High powered USB charger charges tablets, smart phones, MP3 players and other electronic devices
- Job site durability - rugged designed with impact resistant lens to withstand abusive job site conditions
- 4 light settings - provides 700 Lumens on High & Strobe (100%), 350 Lumens on Medium (50%), 70 Lumens on Low (10%)
- 2 hooks for hanging
- Protected against splashing water at all angles (IP24)
- Flexible battery system: works with all Milwaukee® M18™ batteries



M18 LL-0	
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
System	M18
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	700 / 350 / 70 / 700
Max. run time with M18 B5 battery (h)	10 / 20 / 100 / 16
Beam distance (m)	29
Weight with battery pack (kg)	1.4
Supplied in	-
Article Number	4932430563

M18 IL | M18™ LED INSPECTION LIGHT
M18

- TRUEVIEW™ high definition lighting
- Three LED design with 2 light settings provides 300 Lumens on High and 130 Lumens on Low setting
- Pivoting 45° forward & backward head allows for 180° coverage
- 2 adjustable metal hooks for hanging in vertical and horizontal position
- Thanks to its compact design it operates in locations other lights cannot
- Protected against splashing water at all angles (IP24)
- Flexible battery system: works with all Milwaukee® M18™ batteries



M18 IL-0	
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
System	M18
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	300 / - / 130 / -
Max. run time with M18 B5 battery (h)	17 / - / 36 / -
Weight with battery pack (kg)	1.2
Supplied in	-
Article Number	4932430564

M12 LL | M12™ LED LANTERN LIGHT
M12

- TRUEVIEW™ high definition lighting
- 180° - 360° adjustable beam - versatile design, allows the user to select between area lighting and task lighting
- Best-in-class performance - unmatched light output 400+ Lumens, designed to illuminate large areas
- High powered 2.1A USB charger charges tablets, smart phones, MP3 players and other electronic devices
- Job site durability - rugged designed with impact resistant lens to withstand abusive job site conditions
- 2 hooks for hanging
- Protected against splashing water at all angles (IP24)
- Flexible battery system: works with all Milwaukee® M12™ batteries



M12 LL-0	
Battery pack capacity (Ah)	-
No. of batteries supplied	0
Charger supplied	-
System	M12
Battery compatibility	All Milwaukee® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	400 / 200 / 40 / 400
Max. run time with M12 B4 battery (h)	8 / 15 / 67 / 16
Beam distance (m)	23
Weight with battery pack (kg)	0.9
Supplied in	-
Article Number	4932430562

M12 MLED | M12™ LED HIGH PERFORMANCE FLASHLIGHT

- TRUEVIEW™ high definition lighting
- Sliding head allows adjustment of beam pattern from flooding to spotting
- Milwaukee® designed optic maximises performance, powerful LED can cast 350 m intense and highly focused beam of light with up to 800 Lumens
- Machined 6000 series aluminium with a type II anodized finish body, highly durable and impact resistant polycarbonate lens for extreme durability
- Ergonomic contoured grip with knurled texture ensures perfect handle
- IP54 rating, light is protected from dust and splashing water
- M12™ fuel gauge with low battery indication
- Hand wrist lanyard to keep the light safe and handy
- Flexible battery system: works with all Milwaukee® M12™ batteries


M12

M12 MLED-0	
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
System	M12
Battery compatibility	All Milwaukee® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	800 / - / 325 / 800
Max. run time with M12 B4 battery (h)	5 / - / 7 / 7
Beam distance (m)	350
Weight with battery pack (kg)	0.7
Supplied in	Blister
Article Number	4933451899

M18 TLED | M18™ LED TORCH

- The 120 Lumen LED light is 2x brighter and whiter than conventional incandescent bulbs
- M18™ LED electronics deliver 2x longer run time on a single charge with less heat than conventional removable light bulbs
- Sealed aluminium head is designed for impact- and weather-resistant durability
- 135° rotating head allows the user to easily direct the light beam at the desired work area
- Integrated hook for hands-free use
- Flexible battery system: works with all Milwaukee® M18™ batteries


M18

M18 TLED-0	
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
System	M18
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	120 / - / - / -
Max. run time with M18 B5 battery (h)	29
Weight with battery pack (kg)	0.7
Supplied in	–
Article Number	4932430361

M12 TLED | M12™ LED TORCH

- The 120 Lumen LED light is 2x brighter and whiter than conventional incandescent bulbs
- M12™ LED electronics deliver 2x longer run time on a single charge with less heat
- Sealed aluminium head is designed for impact- and weather-resistant durability
- 90° rotating head allows the user to easily direct the light beam at the desired work area
- Magnetic back for hands-free use
- Flexible battery system: works with all Milwaukee® M12™ batteries


M12

M12 TLED-0	
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
System	M12
Battery compatibility	All Milwaukee® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	120 / - / - / -
Max. run time with M12 B4 battery (h)	15 / - / - / -
Weight with battery pack (kg)	0.5
Supplied in	–
Article Number	4932430360

L4 FL | USB RECHARGEABLE POCKET FLOOD LIGHT

- 445 Lumens of TRUEVIEW™ high definition output
- Can be mounted with double magnet and clipped on pockets
- Compact size allows easy storage in pocket
- IP54 rating, light is protected from dust and splashing water
- Impact and chemical resistant lens
- Fuel gauge allows fast checking of REDLITHIUM™ USB battery charge
- Conveniently charge REDLITHIUM™ USB battery internally with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable


REDLITHIUM
LITHIUM ION

L4 FL-201	
Battery pack capacity (Ah)	2.5
No. of batteries supplied	1
Charger supplied	–
System	REDLITHIUM™ USB
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	445 / - / 100 / -
Max. run time with L4 B2 battery (h)	2 / - / 11 / -
Weight with battery pack (kg)	0.2
Supplied in	–
Article Number	4933459442

L4 FFL | USB RECHARGEABLE FOLDING FLOOD LIGHT

- 550 Lumens of TRUEVIEW™ high definition output
- Can be mounted with double magnet or you can hang the light with an integrated carabiner hook
- Compact size allows easy storage in pocket
- IP54 rating, light is protected from dust and splashing water
- Impact and chemical resistant lens
- Fuel gauge allows fast checking of REDLITHIUM™ USB battery charge
- Conveniently charge REDLITHIUM™ USB battery internally with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable


REDLITHIUM
LITHIUM ION

L4 FFL-201	
Battery pack capacity (Ah)	2.5
No. of batteries supplied	1
Charger supplied	–
System	REDLITHIUM™ USB
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	550 / 250 / 100 / -
Max. run time with L4 B2 battery (h)	2 / 4.5 / 11.5 / -
Weight with battery pack (kg)	0.2
Supplied in	–
Article Number	4933464821

L4 PWL | USB RECHARGEABLE PIVOTING WORK LIGHT

- 500 Lumens Spot & Flood beam with TRUEVIEW™ high definition output
- Flood and Spot beam options in different output modes for optimal brightness and up to 10 hrs. run time
- Light head can be maneuvered up to 45° to help users direct light where it's needed most
- Impact and chemical resistant lens
- Fuel gauge allows fast checking of REDLITHIUM™ USB battery charge
- Conveniently charge REDLITHIUM™ USB battery internally with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable


REDLITHIUM
LITHIUM ION

L4 PWL-201	
Battery pack capacity (Ah)	2.5
No. of batteries supplied	1
Charger supplied	–
System	REDLITHIUM™ USB
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output Flood (High/Medium/Low)/Spot Mode (Lumens)	400 / - / 100 / 500
Max. run time with L4 B2 battery (h)	3 / - / 10 / 3
Weight with battery pack (kg)	0.2
Supplied in	–
Article Number	4933464822

L4 HL | USB RECHARGEABLE HEADLAMP

- 475 Lumens Spot & Flood beam with TRUEVIEW™ high definition output
- Flood, Spot and Spot/Flood beam options in different output modes for optimal brightness and up to 31 hrs. run time
- 4 mounting clips for securing to helmets and adjustable strap with rubber grip
- Light can be maneuvered in (7) different positions and features 216° tilting motion to help users direct light where it's needed most
- Removable strap connector allows for handheld use
- IP53 rating, light is protected from dust and falling water
- Impact and chemical resistant lens
- Fuel gauge allows fast checking of REDLITHIUM™ USB battery charge
- Conveniently charge REDLITHIUM™ USB battery internally with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable



L4 HL-201	
Battery pack capacity (Ah)	2.5
No. of batteries supplied	1
Charger supplied	-
System	REDLITHIUM™ USB
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output Spot-flood/Flood/Spot/Strobe (Lumens)	475 / 25, 150, 300 / 300 / -
Max. run time with L4 B2 battery (h)	2 / 31, 8.5, 4.5 / 4 / -
Weight with battery pack (kg)	0.2
Supplied in	-
Article Number	4933459443



HL-LED | ALKALINE SLIM HEADLAMP

- 300 Lumens of TRUEVIEW™ high definition output
- Washable micro fiber sweat-absorbing strap for all day comfort on the head
- Ultra compact and lightweight product
- 6-position tilt adjustment for directing light
- 4 mounting clips for securing to helmets
- Light is protected from impact as well as from weather and dust
- Includes (3) AAA batteries



HL-LED	
Battery type	3 x AAA
Battery compatibility	Alkaline
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	300 / 150 / 25/ -
Max. run time (h)	4 / 8.5 / 31/ -
Weight with battery pack (kg)	0.1
Supplied in	-
Article Number	4933459441



L4 MLED | USB RECHARGEABLE COMPACT FLASHLIGHT

- 700 Lumens of TRUEVIEW™ high definition output with up to 155 m beam distance
- Sliding head allows adjustment of beam pattern from flooding to spotting
- Aircraft aluminium "AL 6000 Series" with premium knurling grip and polycarbonate lens withstand drops from up to 4m and deliver outstanding durability
- IP67 rated for submersion in up to 1 meter of water and protection from dust
- Momentary & constant power on button
- Removable belt clip
- Fuel gauge allows fast checking of REDLITHIUM™ USB battery charge
- Conveniently charge REDLITHIUM™ USB battery internally with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable



L4 MLED-201	
Battery pack capacity (Ah)	2.5
No. of batteries supplied	1
Charger supplied	-
System	REDLITHIUM™ USB
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	700 / - / 100 / 700
Max. run time with L4 B2 battery (h)	4.5 / - / 16 / 9
Beam distance (m)	155
Weight with battery pack (kg)	0.3
Supplied in	-
Article Number	4933459444



FL-LED | ALKALINE FLOOD LIGHT

- 300 Lumens of TRUEVIEW™ high definition output delivers consistent beam, optimised colour temperature and true representation of colours and details
- Can be mounted with double magnet and clipped on pockets
- Compact size and lightweight construction allows easy storage in pocket
- IP54 rating, light is protected from dust and splashing water
- Impact and chemical resistant lens for more durability
- Includes (2) AA alkaline batteries



FL-LED	
Battery type	2 x AA
Battery compatibility	Alkaline
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	300 / - / 100/ -
Max. run time (h)	5 / - / 16/ -
Weight with battery pack (kg)	0.1
Supplied in	-
Article Number	4933464824



IPL-LED | ALKALINE PEN LIGHT

- 100 Lumens of TRUEVIEW™ high definition light output deliver up to 30 m beam distance for inspection tasks
- Impact and corrosion resistant aircraft aluminium body with knurling grip for best durability
- IP67 rated for submersion in up to 1 meter of water and protection from dust
- Features a protective rubber bite zone for occasional hands-free use
- Removable metal pocket clip
- On/off and momentary-on button
- Includes (2) AAA batteries



IPL-LED	
Battery type	2 x AAA
Battery compatibility	Alkaline
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	100
Max. run time (h)	3
Beam distance (m)	30
Weight with battery pack (kg)	0.1
Supplied in	-
Article Number	4933459440



ML-LED | ALKALINE FLASHLIGHT

- 325 Lumens of TRUEVIEW™ high definition light output deliver up to 50 m beam distance for inspection tasks
- Impact and corrosion resistant aircraft aluminium body with knurling grip for best durability
- IP67 rated for submersion in up to 1 meter of water and protection from dust
- Removable metal pocket clip
- Impact and chemical resistant lens
- Includes (3) AAA batteries



ML-LED	
Battery type	3 x AAA
Battery compatibility	Alkaline
Bulb type	LED
Max. light output High/Medium/Low/Strobe (Lumens)	325 / - / 25/ -
Max. run time (h)	5 / - / 18/ -
Beam distance (m)	50
Weight with battery pack (kg)	0.13
Supplied in	-
Article Number	4933464825





M28 CHPX | M28 FUEL™ 4-MODE SDS-PLUS HAMMER WITH FIXTEC CHUCK

- Milwaukee® designed and built brushless POWERSTATE™ motor
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- High powered motor gives corded tool performance
- Hardest hitting cordless SDS hammer in its class. Powerful hammer mechanism: delivers 4.1 J of impact energy at low 8.1 m/s² vibrations thanks to the new dual rail anti-vibration system
- All metal gear case - optimum seating of the gears for enhanced service life
- 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility
- FIXTEC system - keyless chuck changing
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining battery charge
- Compatible with M18-28 CPDEX dust extractor



M28 FUEL

	M28 CHPX-0X	M28 CHPX-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	90 min
Tool reception	SDS-Plus	SDS-Plus
Blow energy (EPTA)(J)	4.1	4.1
Max. drilling wood (mm)	30	30
Max. drilling steel (mm)	13	13
Max. drilling concrete (mm)	28	28
Max. percussion rate (bpm)	0 - 5000	0 - 5000
Vibration drilling (m/s ²)	8.1	8.1
Vibration chiseling (m/s ²)	8.1	8.1
Weight with battery pack (kg)	–	4.7
Supplied in	HD Box	HD Box
Article Number	4933451029	4933451025

M18-28 CPDEX | M18-28 FUEL™ DUST EXTRACTOR

- Designed to collect dust effectively with automatic operation from the tools on/off trigger switch
- HEPA filter: widely regarded as the ultimate filter that traps all sizes of particles with an efficiency rating of 99.75%
- Large dust collection box
- Dust extraction aluminium tube is adjustable according to the size of the drill bit and length 16 mm max and 90 mm depth
- Compatible with M18 CHPX & M28 CHPX



M28 FUEL

	M18-28 CPDEX-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
Max. drill bit diameter (mm)	16
Max. drilling depth (mm)	90
Max. drill bit length (mm)	160
Stroke length (mm)	100
Weight without battery pack (kg)	1.6
Supplied in	–
Article Number	4933446810

M28 CHPXDE | M28 FUEL™ 4-MODE SDS-PLUS HAMMER WITH FIXTEC CHUCK AND DEDICATED DUST EXTRACTOR

- M28 CHPX - M28 FUEL™ 4-mode SDS-Plus hammer with FIXTEC chuck
- M18-28 CPDEX - M18-28 FUEL™ dust extractor



M28 FUEL

	M28 CHPXDE-502C
Battery pack capacity (Ah)	5.0
No. of batteries supplied	2
Charger supplied	90 min
Supplied in	Kitbox
Article Number	4933448015

HD28 PD | M28™ PERCUSSION DRILL

- With its Milwaukee® high powered motor it delivers a staggering 90 Nm of torque, ideal for powering through the toughest of applications
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- All metal gear case provides maximum durability
- Compact size of only 237 mm overall length
- 13 mm Röhm chuck provides maximum durability
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Built in LED light illuminates the work surface
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life



	HD28 PD-0X	HD28 PD-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	90 min
No load speed gear 1 (rpm)	0 - 450	0 - 450
No load speed gear 2 (rpm)	0 - 1800	0 - 1800
Chuck capacity (mm)	13	13
Max. drilling wood (mm)	65	65
Max. drilling steel (mm)	16	16
Max. drilling concrete (mm)	20	20
Max. torque (Nm)	90	90
Weight with battery pack (kg)	–	2.5
Supplied in	HD Box	HD Box
Article Number	4933431646	4933448544


HD28 IW | M28™ 1/2" DRIVE IMPACT WRENCH WITH PIN DETENT

- With its Milwaukee® 4-pole frameless motor it delivers a staggering 440 Nm of torque, ideal for powering through the toughest of applications
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Durable, lightweight magnesium gear case for extended life and comfort
- Variable speed trigger for enhanced control and accuracy
- 1/2" square drive with detent pin for secure socket retention
- Non-slip gripping surfaces for maximum comfort and control
- Exclusive reversible battery pack design for optimal tool balance
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life



	HD28 IW-0X	HD28 IW-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	90 min
No load speed (rpm)	0 - 1450	0 - 1450
Impact rate (ipm)	0 - 2450	0 - 2450
Tool reception	1/2" square	1/2" square
Max. torque (Nm)	440	440
Weight with battery pack (kg)	–	4.1
Supplied in	HD Box	HD Box
Article Number	4933431642	4933448545


10 PC SHOCKWAVE IMPACT DUTY™ 1/2" SOCKET SET

Article Number 4932352861


HD28 AG125 | M28™ 125 MM ANGLE GRINDER

- Milwaukee®'s high performance motor delivers maximum power whilst (optimising) maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal gear case delivers heavy duty durability
- Reduced height of gear box and slim girth design deliver optimum ergonomics
- Fast and easy wheel change with patented FIXTEC nut
- Burst resistant and tool-free safety guard for best user protection and fast adjustment
- AVS side handle for most compatible work and less strain to the user
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life



	HD28 AG125-0X	HD28 AG125-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	90 min
No load speed (rpm)	9000	9000
Disc diameter (mm)	125	125
Max. cutting depth (mm)	36	36
Spindle size	M 14	M 14
Weight with battery pack (kg)	–	2.8
FIXTEC flange nut	Yes	Yes
Line lock out function	Yes	Yes
AVS side handle	Yes	Yes
Supplied in	HD Box	HD Box
Article Number	4933432225	4933448541


HD28 MS | M28™ METAL DRY CUT SAW

- Milwaukee®'s high performance motor delivers 3200 rpm for fast cutting
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Large cutting depth of 61 mm
- Compact, ergonomic design provides superior control over standard metal saws, reciprocating saws and band saws
- Ergonomic soft grip handle design for more comfortable use
- Electronic motor brake, saw blade stops within seconds
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Built in LED light illuminates the work surface
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Premium 174 mm carbide blade
- Supplied with 36 tooth blade



	HD28 MS-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	3200
Blade diameter (mm)	174
Bore size (mm)	20
Max. cut cap. in steel plate (mm)	5
Max. cutting capacity metal pipe Ø (mm)	61
Max. cutting capacity sections (mm)	61
Weight with battery pack (kg)	4.2
Supplied in	–
Article Number	4933416880


HD28 AG115 | M28™ 115 MM ANGLE GRINDER

- Milwaukee®'s high performance motor delivers maximum power whilst (optimising) maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal gear case delivers heavy duty durability
- Reduced height of gear box and slim girth design deliver optimum ergonomics
- Fast and easy wheel change with patented FIXTEC nut
- Burst resistant and tool-free safety guard for best user protection and fast adjustment
- AVS side handle for most compatible work and less strain to the user
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life



	HD28 AG115-0X	HD28 AG115-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	90 min
No load speed (rpm)	9000	9000
Disc diameter (mm)	115	115
Max. cutting depth (mm)	28	28
Spindle size	M 14	M 14
Weight with battery pack (kg)	–	2.8
FIXTEC flange nut	Yes	Yes
Line lock out function	Yes	Yes
AVS side handle	Yes	Yes
Supplied in	HD Box	HD Box
Article Number	4933432146	4933448540


HD28 SG | M28™ STRAIGHT GRINDER

- Long slender spindle neck for better access to awkward spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Digital electronic 2-speed for optimum use of consumables
- Battery lock out function to prevent unintended start up
- Full metal gear case for maximum durability
- Maximised airflow for cool running for extended periods
- 6 mm collet for use with common accessories
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge



	HD28 SG-0
Battery pack capacity (Ah)	–
No. of batteries supplied	0
Charger supplied	–
No load speed (rpm)	22,500 / 19,500
Collet capacity (mm)	6
Weight with battery pack (kg)	3.1
Supplied in	–
Article Number	4933415615



HD28 CS | M28™ 54 MM CIRCULAR SAW

- Milwaukee® powerful 4200 rpm motor easily cuts most timber construction materials
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Versatile 54 mm cutting depth, 50° bevel cut capacity
- Heavy Duty construction with all metal lower / upper blade guards and aluminium shoe
- Left-blade design for optimal cut-line visibility and control
- Electronic motor brake, saw blade stops within seconds
- Ergonomic soft grip handle design for more comfortable use
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Supplied with 24 tooth saw blade, parallel guide, dust port and allen key


M28

	HD28 CS-0	HD28 CS-502C
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	90 min
No load speed (rpm)	4200	4200
Max. cutting depth 90° (mm)	54	54
Max. cutting depth 45° (mm)	39	39
Blade diameter (mm)	165	165
Arbor size (mm)	15.87	15.87
Weight with battery pack (kg)	–	3.6
Supplied in	–	Kitbox
Article Number	4933419022	4933448538

HD28 SX | M28™ SAWZALL®

- Milwaukee®'s high performance motor delivers maximum power whilst (optimising) maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Milwaukee® patented FIXTEC clamp for fast and easy keyless blade change
- Gear protection clutch - protects the gearbox in case of blade lock ups
- Counter balance mechanism to reduce vibrations
- 28.6 mm stroke length, 3000 spm for extremely fast cutting
- Tool free, adjustable shoe quickly adjusts blade depth
- Convenient two-speed selection for best cut control in different materials
- Soft grip gripping surfaces for maximum comfort and control
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life


M28

	HD28 SX-0	HD28 SX-502C
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	90 min
No load stroke rate (spm)	0-2000/0-3000	0-2000/0-3000
Stroke length (mm)	28.6	28.6
Weight with battery pack (kg)	–	4.1
Supplied in	–	Kitbox
Article Number	4933416860	4933448537

HD28 JSB | M28™ BODY GRIP JIGSAW

- Milwaukee® high performance motor delivers 2800 spm for fast cutting
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Soft start
- 2-speed selector switch for ideal speed in different materials
- Patented FIXTEC system for fast keyless blade change and bevel adjustment with snap-in at 0° and 45°
- Four-stage adjustment of the pendulum action for increased cutting performance and longer saw blade life
- Adjustable saw dust blower
- Exact saw blade guidance with large blade support roller on needle bearings fitted in a very low position
- Die-cast base plate for high durability
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life


M28

	HD28 JSB-0X	HD28 JSB-502X
Battery pack capacity (Ah)	–	5.0
No. of batteries supplied	0	2
Charger supplied	–	90 min
No load stroke rate (spm)	2100 / 2800	2100 / 2800
Max. cutting capacity wood (mm)	135	135
Max. cutting capacity steel (mm)	10	10
Stroke length (mm)	26	26
Weight with battery pack (kg)	–	3.5
Supplied in	HD Box	HD Box
Article Number	4933432090	4933448542

M28 PACK D | M28™ POWERPACK

- HD28 PD - M28™ percussion drill
- HD28 SX - M28™ SAWZALL®
- M28 WL - M28™ lamp


M28

M28 Pack D-502B	
Battery pack capacity (Ah)	5.0
No. of batteries supplied	2
Charger supplied	90 min
Supplied in	Tool bag
Article Number	4933448547

M4 D
M4™ DRILL DRIVER

- Compact 244 mm screwdriver
- Best in class high accuracy electronic clutch with 8% tolerance
- 2 speed gearbox for screwdriving and drilling
- Electronic switch for variable speed
- 1/4" Hex chuck for quick and easy bit change
- 2 position handle for best balance and minimum reaction force
- Fuel gauge displays remaining charge


M4

M4 D-202B	
Battery pack capacity (Ah)	2.0
No. of batteries supplied	2
Charger supplied	30 min
No load speed gear 1 (rpm)	0 - 200
No load speed gear 2 (rpm)	0 - 600
Tool reception	1/4" Hex
Max. torque (Nm)	5
Weight with battery pack (kg)	0.5
Supplied in	Kitbox
Article Number	4933440475



2 speed gearbox



1/4" Hex chuck



2 position handle

M12™ BATTERIES



M12

	System	Battery type	Battery pack capacity (Ah)	Voltage (V)	Article Number	
1.	M12 B6	M12	Li-ion	6.0	12	4932451395
2.	M12 B4	M12	Li-ion	4.0	12	4932430065
3.	M12 B3	M12	Li-ion	3.0	12	4932451388
4.	M12 B2	M12	Li-ion	2.0	12	4932430064

M18™ BATTERIES



REDLITHIUM-ION
BATTERY TECHNOLOGY **M18**

	System	Battery type	Battery pack capacity (Ah)	Voltage (V)	Article Number	
1.	M18 HB12	M18	Li-ion	12.0	18	4932464260
2.	M18 HB8	M18	Li-ion	8.0	18	4932471070
3.	M18 HB5.5	M18	Li-ion	5.5	18	4932464712
4.	M18 HB3	M18	Li-ion	3.0	18	4932471069
5.	M18 B9	M18	Li-ion	9.0	18	4932451245
6.	M18 B6	M18	Li-ion	6.0	18	4932451244
7.	M18 B5	M18	Li-ion	5.0	18	4932430483
8.	M18 B4	M18	Li-ion	4.0	18	4932430063
9.	M18 B2	M18	Li-ion	2.0	18	4932430062

OTHER BATTERIES



	System	Battery type	Battery pack capacity (Ah)	Voltage (V)	Article Number	
1.	M28 B5	M28	Li-ion	5.0	28	4932430484
2.	M28 BX	M28	Li-ion	3.0	28	4932352732
3.	M14 B4	M14	Li-ion	4.0	14.4	4932430323
4.	M14 B	M14	Li-ion	1.5	14.4	4932352665
5.	L4 B2	REDLITHIUM™ USB	Li-ion	2.5	4	4932459445
6.	M4 B2	M4	Li-ion	2.0	4	4932430098

CHARGERS



	System	Charging range	Charging time (min)	Battery pack capacity (Ah)	For battery type Li-Ion	Article Number	
1.	M28 C	M28	28 V	60/90	3.0, 5.0	Yes	4932352524
2.	M1418 C6	M14, M18	14.4 V - 18 V	40/80/100/124/180/70/125/190/270	2.0, 4.0, 5.0, 6.0, 9.0, 3.0, 5.5, 8.0, 12.0	Yes	4932430086
3.	M12-18 AC	M12, M14, M18	12 - 18 V	40/80/100/124/180/75/130/190/285	2.0, 4.0, 5.0, 6.0, 9.0, 3.0, 5.5, 8.0, 12.0	Yes	4932459205
4.	M12 18 FC	M12, M14, M18	12 - 18 V	26/47/59/68/95/35/60/87/130	2.0, 4.0, 5.0, 6.0, 9.0, 3.0, 5.5, 8.0, 12.0	Yes	4932451079
5.	M12-18C	M12, M14, M18	12 - 18 V	40/80/100/124/180/65/115/167/250	2.0, 4.0, 5.0, 6.0, 9.0, 3.0, 5.5, 8.0, 12.0	Yes	4932352959
6.	M12 C4	M12	12 V	40/70/80/130	2.0, 3.0, 4.0, 6.0	Yes	4932430554
7.	M12 TC	M12	12 V	40/70/80/130	2.0, 3.0, 4.0, 6.0	Yes	4932459450
8.	C12 C	M12	12 V	40/70/80/130	2.0, 3.0, 4.0, 6.0	Yes	4932352000
9.	L4 C	REDLITHIUM™ USB	4 V	120	2.5	Yes	4932459446
10.	M4 C	M4	4 V	30	2.0	Yes	4932352958

BUY AN M18™ BATTERY & CHARGER KIT AND RECEIVE A FREE M12™ BATTERY.

FREE M12™



REDLITHIUM-ION™



M12-18 FC

TWO SYSTEMS

ONE CHARGER

DUAL M12 + M18 COMPATIBILITY
CHARGES ALL M12™ & M18™ BATTERIES

PROMOTION VALID UNTIL 31.12.2019

BATTERIES AND CHARGER KITS



		Voltage (V)	Battery type	Battery pack capacity (Ah)	No. of batteries supplied	Charger supplied	Charger supplied	Article Number
1.	M18 NRG-903	18	Li-ion	9.0	3	100 min	M12-18 FC	4933459219
2.	M18 NRG-902	18	Li-ion	9.0	2	95 min	M12-18 FC	4933451422
3.	M18 NRG-603	18	Li-ion	6.0	3	68 min	M12-18 FC	4933464026
4.	M18 NRG-503	18	Li-ion	5.0	3	59 min	M12-18 FC	4933451423
5.	M18 NRG-502	18	Li-ion	5.0	2	59 min	M12-18 FC	4933459217

	System	Voltage (V)	Battery type	Battery pack capacity (Ah)	No. of batteries supplied	Charger supplied	Charger supplied	Article Number	
1.	M18 HNRG-122	M18	18	Li-ion	12.0	2	130 min	M12-18 FC	4933464261
2.	M18 HNRG-802	M18	18	Li-ion	8.0	2	-	M12-18 FC	4933471073
3.	M18 HNRG-552	M18	18	Li-ion	5.5	2	59 min	M12-18 FC	4933464713
4.	M18 HNRG-302	M18	18	Li-ion	3.0	2	35 min	M12-18 FC	4933471071
5.	M18 NRG-402	M18	18	Li-ion	4.0	2	47 min	M12-18 FC	4933459215
6.	M18 NRG-202	M18	18	Li-ion	2.0	2	40 min	M12-18 C	4933459213
7.	M12 NRG-603	M12	12	Li-ion	6.0	3	130 min	C12 C	4933459208
8.	M12 NRG-602	M12	12	Li-ion	6.0	2	130 min	C12 C	4933451903
9.	M12 NRG-402	M12	12	Li-ion	4.0	2	80 min	C12 C	4933459211
10.	M12 NRG-303	M12	12	Li-ion	3.0	3	70 min	C12 C	4933459207
11.	M12 NRG-302	M12	12	Li-ion	3.0	2	70 min	C12 C	4933451902
12.	M12 NRG-202	M12	12	Li-ion	2.0	2	40 min	C12 C	4933459209
13.	M12 NRG-201	M12	12	Li-ion	2.0	1	40 min	C12 C	4933451900
14.	L4 NRG-201	REDLITHIUM™ USB	4	Li-ion	2.5	1	120 min	L4 C	4932459448

CONSTRUCTION



K 2500 H | 25 KG CLASS 28 MM HEX BREAKING HAMMER

- Heavy Duty breaker provides 64 blow Joules of impact energy for toughest demolition applications
- Floating body anti-vibration technologies allows the user to work all day without reaching dangerous exposure levels
- Additional third handle gives maximum control when lifting the breaker between applications
- 1300 BPM provides maximum productivity in all applications
- Brushless motor allows for maximum run time in-between service intervals
- 10 m cable allows for a working area of up to 314 m²
- 28 mm Hex reception
- Separately available trolley with 4 chisel location and cable management makes it easy to transport breaker on the jobsite



K 2500 H	
Power input (W)	2200
Blow energy (EPTA)(J)	64
Full load hammer action (bpm)	1300
Tool reception	K-Hex
Vibration chiseling (m/s ²)	4.9
Weight (kg)	27.4
Supplied in	-
Article Number	4933459602

28 MM HEX POINTED CHISEL

Article Number **4932459774**



K 2000 H | 20 KG CLASS 28 MM HEX BREAKING HAMMER

- Compact and powerful breaker provides 42 blow Joules of impact energy for toughest demolition applications
- Floating body anti-vibration technologies allows the user to work all day without reaching dangerous exposure levels
- Additional third handle gives maximum control when lifting the breaker between applications
- 1300 BPM provides maximum productivity in all applications
- 10 m cable allows for a working area of up to 314 m²
- 28 mm Hex reception
- Separately available trolley with 4 chisel location and cable management makes it easy to transport breaker on the jobsite



K 2000 H	
Power input (W)	2200
Blow energy (EPTA)(J)	42
Full load hammer action (bpm)	1300
Tool reception	K-Hex
Vibration chiseling (m/s ²)	4.7
Weight (kg)	24.2
Supplied in	-
Article Number	4933459604

28 MM HEX POINTED CHISEL

Article Number **4932459774**



BRT | BREAKER TROLLEY

- Breaker trolley with 4 chisel location and cable management makes it easy to transport breaker on the jobsite
- 100 kg loading capacity
- Powder coated finish protects against jobsite abuse
- Compatible with K 2000 H and K 2500 H



BRT	
Loading capacity (kg)	100
Weight (kg)	14.3
Supplied in	-
Article Number	4933459794

K 1530 H 15 KG CLASS 30 MM HEX BREAKING HAMMER

- Powerful and compact breaker delivering up to 39 blow Joules of impact energy for challenging applications
- Floating body anti-vibration technologies allows the user to work all day without reaching dangerous exposure levels
- 1560 BPM provides maximum productivity in all applications
- 6 m cable allows for working area over 110 m²
- Dedicated brush window for easy maintenance
- 30 mm Hex reception
- Service reminder light to indicate when service will be needed
- BMC with wheels for ease of transport on site



K 1530 H	
Power input (W)	2100
Blow energy (EPTA)(J)	39
Full load hammer action (bpm)	1560
Tool reception	K-Hex
Vibration chiseling (m/s ²)	8.4
Weight (kg)	16.8
Supplied in	Plastic case
Article Number	4933464117

30 MM HEX POINTED CHISEL

Article Number **4932464162**



Milwaukee® floating body AVS system enables to lean the tool against the body without feeling the vibrations



Additional third handle gives maximum control when lifting



30 mm Hex reception

K 1528 H | 15 KG CLASS 28 MM HEX BREAKING HAMMER

- Powerful and compact breaker delivering up to 39 blow Joules of impact energy for challenging applications
- Floating body anti-vibration technologies allows the user to work all day without reaching dangerous exposure levels
- 1560 BPM provides maximum productivity in all applications
- 6 m cable allows for working area over 110 m²
- Dedicated brush window for easy maintenance
- 28 mm Hex reception
- Service reminder light to indicate when service will be needed
- BMC with wheels for ease of transport on site



K 1528 H	
Power input (W)	2100
Blow energy (EPTA)(J)	39
Full load hammer action (bpm)	1560
Tool reception	K-Hex
Vibration chiseling (m/s ²)	8.8
Weight (kg)	17.2
Supplied in	Plastic case
Article Number	4933464118

28 MM HEX 400 X 35 MM FLAT CHISEL

Article Number **4932459775**



K 1000 S 10 KG CLASS BREAKING HAMMER

- o Compact chiseling hammer delivering up to 26 blow Joules of impact energy for a wide variety of applications
- o Floating body anti-vibration technologies allows the user to work all day without reaching dangerous exposure levels
- o 1400 – 1950 BPM provides maximum productivity in all applications
- o 6 m cable allows for working area over 110 m²
- o Variolock (12 positions) for selecting the most appropriate chisel angle
- o SDS-Max tool reception
- o Service reminder light to indicate when service will be needed
- o Dedicated brush window for easy maintenance
- o BMC with wheels for ease of transport on site



K 1000 S	
Power input (W)	1750
Blow energy (EPTA)(J)	26
Full load hammer action (bpm)	1400 - 1950
Tool reception	SDS-Max
Vibration chiseling (m/s ²)	6.7
Weight (kg)	12.7
Supplied in	Plastic case
Article Number	4933464120

PCHDE DUST EXTRACTOR WITH 400 MM LONG SDS-MAX POINTED CHISEL

Article Number **4932455280**



Floating body anti-vibration technologies allows the user to work all day without reaching dangerous exposure levels



Variolock (12 positions) for selecting the most appropriate chisel angle



Service reminder light to indicate when service will be needed

K 850 8 KG CLASS DRILLING AND BREAKING HAMMER

- o Powerful SDS max rotary hammer with AUTOSTOP™ delivering 11 Joules of blow energy whilst maximising user safety
- o AUTOSTOP™ shuts down the tool to protect the user after 45 degrees of sharp movement in bind up situations
- o Redesigned electronic package delivers constant power and maximum productivity in the most challenging of applications
- o Trigger lock on for to prevent user having to hold trigger during long periods of chipping applications
- o Large AVS back handle supports two handed drilling applications whilst minimising vibration exposure
- o Service light indicator illuminates when tool requires servicing
- o Anti-vibration side handle minimising user exposure
- o 6 m cable for 110m² working area



AUTOSTOP



AUTOSTOP™ - maximum control, advanced safety



Trigger lock on



Large AVS back and side handle minimises vibration exposure

K 850 S	
Power input (W)	1400
No load speed (rpm)	380
Blow energy (EPTA)(J)	11
Full load hammer action (bpm)	1600 - 2900
Full load speed (soft hammer) (rpm)	210 - 380
Max. drilling solid bit (mm)	50
Max. drilling tunnel bit (mm)	80
Max. drilling core bit (mm)	150
Tool reception	SDS-Max
Vibration drilling (m/s ²)	9.4
Vibration chiseling (m/s ²)	7.8
Weight (kg)	9.6
Supplied in	Kitbox
Article Number	4933464896

K 950 | 10 KG CLASS DRILLING AND BREAKING HAMMER

- o 20 J blow energy for hard hitting performance
- o 1700 watt motor - best in class with plenty in reserve for the toughest applications
- o DIGITRONIC® - fullwave electronics for precise power adjustment to application
- o 3 handles - all with AVS (Anti-Vibration-System) and soft grip for comfortable and less tiring use
- o All metal gearcase - optimum seating of the gears for enhanced service life
- o Service indicator light
- o Automatic lubrication system for longer life time
- o In-Line motor design for more comfort in below waist applications
- o Ideal for usage with generators
- o Variolock (12 positions) for selecting the most appropriate chisel angle
- o 6 m cable



K 950 S	
Power input (W)	1700
No load speed (rpm)	125 - 250
Blow energy (EPTA)(J)	20
Full load hammer action (bpm)	975 - 1950
Full load speed (soft hammer) (rpm)	125 - 250
Max. drilling solid bit (mm)	50
Max. drilling tunnel bit (mm)	80
Max. drilling core bit (mm)	150
Tool reception	SDS-Max
Vibration drilling (m/s ²)	12.5
Vibration chiseling (m/s ²)	11
Weight (kg)	11.8
Supplied in	Kitbox
Article Number	4933375710

K 900 | 10 KG CLASS BREAKING HAMMER

- o 20 J blow energy for hard hitting performance
- o 1600 watt motor - best in class with plenty in reserve for the toughest applications
- o DIGITRONIC® - fullwave electronics for precise power adjustment to application
- o 3 handles - all with AVS (Anti-Vibration-System) and soft grip for comfortable and less tiring use
- o Service indicator light
- o Automatic lubrication system for longer life time
- o In-Line motor design for more comfort in below waist applications
- o Ideal for usage with generators
- o Variolock (12 positions) for selecting the most appropriate chisel angle
- o 6 m cable



	K 900 S	K 900 K
Power input (W)	1600	1600
Blow energy (EPTA)(J)	20	20
Full load hammer action (bpm)	975 - 1950	975 - 1950
Tool reception	SDS-Max	K-Hex
Vibration chiseling (m/s ²)	11	11
Weight (kg)	11.0	11.0
Supplied in	Kitbox	Kitbox
Article Number	4933375720	4933375650

PCHDE DUST EXTRACTOR WITH 400 MM LONG SDS-MAX POINTED CHISEL

Article Number **4932455280**



K 750 S | 7 KG CLASS DRILLING AND BREAKING HAMMER

- Large, heavy weight striker delivers maximum 11.9 J impact energy
- Powerful 1550 watt ensures maximum power yet due to better heat dissipation, guarantees maximum possible durability
- Fullwave electronics for precise power adjustment to application
- Soft start for precise start of drilling/chiselling
- AVS (Anti-Vibration-System) and soft grip on front and back handle
- Additional handle can be fixed in 3 different positions
- Soft hammer mode reduces blow energy for chiselling in sensitive materials
- Roto-stop and multi-position chisel function
- Service indicator light
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



K 750 S	
Power input (W)	1550
No load speed (rpm)	300
Blow energy (EPTA)(J)	11.9
Full load hammer action (bpm)	2740
Full load speed (soft hammer) (rpm)	240
Max. drilling solid bit (mm)	50
Max. drilling tunnel bit (mm)	80
Max. drilling core bit (mm)	150
Tool reception	SDS-Max
Vibration drilling (m/s ²)	9.5
Vibration chiseling (m/s ²)	9.1
Weight (kg)	8.2
Supplied in	Kitbox
Article Number	4933398600

K 500 ST | 5 KG CLASS TRADESMAN BREAKING HAMMER

- Best power to weight ratio in its class - 7.5 J and 5.9 kg
- Powerful 1100 watt ensures maximum power, guarantees maximum possible durability
- Soft start for precise start of chiselling
- Low vibration construction enhances usage time per day
- Robust magnesium gear housing for tough environments, exact seat fitting of gear components and better cooling
- Roto-stop and multi position chisel function gives 12 different positions to optimise working angle
- Safety clutch protects operator and machine if drill bit jams
- Soft grip main side handle
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 4 m cable



K 500 ST	
Power input (W)	1100
Blow energy (EPTA)(J)	7.5
Full load hammer action (bpm)	3000
Tool reception	SDS-Max
Vibration chiseling (m/s ²)	16.7
Weight (kg)	5.9
Supplied in	Kitbox
Article Number	4933443180

K 545 S | 5 KG CLASS DRILLING AND BREAKING HAMMER

- Large, heavy weight striker delivers maximum 8.5 J impact energy
- Powerful 1300 watt ensures maximum power yet due to better heat dissipation, guarantees maximum possible durability
- Constant electronic for keeping the speed uniform even under load
- Soft start for precise start of drilling/chiselling
- AVS (Anti-Vibration-System) and soft grip on front and back handle
- Additional handle can be fixed in 3 different positions
- Soft hammer mode reduces blow energy for drilling/chiselling in sensitive materials
- Roto-stop and multi-position chisel function
- Service indicator light
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



K 545 S	
Power input (W)	1300
No load speed (rpm)	450
Blow energy (EPTA)(J)	8.5
Full load hammer action (bpm)	2840
Full load speed (soft hammer) (rpm)	350
Max. drilling solid bit (mm)	45
Max. drilling tunnel bit (mm)	65
Max. drilling core bit (mm)	100
Tool reception	SDS-Max
Vibration drilling (m/s ²)	13
Vibration chiseling (m/s ²)	9
Weight (kg)	6.7
Supplied in	Kitbox
Article Number	4933398200

K 500 S | 5 KG CLASS BREAKING HAMMER

- Large, heavy weight striker delivers maximum 8.5 J impact energy
- Powerful 1300 watt ensures maximum power yet due to better heat dissipation, guarantees maximum possible durability
- Constant electronic for keeping the speed uniform even under load
- Soft start for precise start of chiselling
- AVS (Anti-Vibration-System) and soft grip on front and back handle
- Additional handle can be fixed in 3 different positions
- Soft hammer mode reduces blow energy for chiselling in sensitive materials
- Roto-stop and multi-position chisel function
- Service indicator light
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



K 500 S	
Power input (W)	1300
Blow energy (EPTA)(J)	8.5
Full load hammer action (bpm)	2840
Tool reception	SDS-Max
Vibration chiseling (m/s ²)	11.5
Weight (kg)	6.3
Supplied in	Kitbox
Article Number	4933398220

REPLACEMENT 400 MM LONG SDS-MAX POINTED CHISEL

Article Number **4932455144**



K 540 S | 5 KG CLASS DRILLING AND BREAKING HAMMER

- Best power to weight ratio in its class - 7.5 J and 6.3 kg
- Powerful 1100 watt ensures maximum power, guarantees maximum possible durability
- Soft start for precise start of drilling/chiselling
- Low vibration construction enhances usage time per day
- Robust magnesium gear housing for tough environments, exact seat fitting of gear components and better cooling
- Roto-stop and multi position chisel function gives 12 different positions to optimise working angle
- Safety clutch protects operator and machine if drill bit jams
- Soft grip main side handle
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 4 m cable



K 540 S	
Power input (W)	1100
No load speed (rpm)	450
Blow energy (EPTA)(J)	7.5
Full load hammer action (bpm)	3000
Full load speed (soft hammer) (rpm)	430
Max. drilling concrete (mm)	40
Max. drilling tunnel bit (mm)	65
Max. drilling core bit (mm)	105
Tool reception	SDS-Max
Vibration drilling (m/s ²)	16.8
Vibration chiseling (m/s ²)	16.7
Weight (kg)	6.3
Supplied in	Kitbox
Article Number	4933418100

PCE 3/K | 3 KG SDS-PLUS CHIPPING HAMMER

- Over sized heavy weight striker delivers 3.6 joules of impact energy
- 720 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Electronics with accelerator switch
- Fully insulated metal gearbox for maximum stability
- Lightweight, ergonomic front handle is fully adjustable and can be securely fixed in the best position to suit the required drilling angle
- AVS (Anti-Vibration-System) and soft grip for less tiring operation
- Lock-on switch for more comfortable extended use
- Variolock (35 positions) for setting the face of the chisel
- 4 m cable



PCE 3/K	
Power input (W)	720
Blow energy (EPTA)(J)	3.6
Full load hammer action (bpm)	0 - 3650
Tool reception	SDS-Plus
Weight (kg)	3.7
Supplied in	Kitbox
Article Number	4933384300

PLH 32 | 32 MM SDS-PLUS 3-MODE L-SHAPED HAMMER

- Tough, durable hammer with excellent drilling performance in concrete from the high torque motor and gears and a 3.8 joule single blow energy
- 900 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Electronics with accelerator switch
- Good balance and easy handling from the compact L-shape design with AVS (Anti-Vibration-System) and soft grip handle
- Fast tool changing from the FIXTEC system with keyless chuck
- Heavy Duty magnesium gear casing for optimum seating of gears for a longer operational life
- Reliable safety clutch protects machine and user
- Roto-stop and variolock for maximum control when doing light chiselling work
- 4 m cable



PLH 32 XE	
Power input (W)	900
Blow energy (EPTA)(J)	3.8
Full load hammer action (bpm)	0 - 4500
Full load speed (rpm)	0 - 800
Max. drilling concrete (mm)	32
Max. drilling steel (mm)	16
Max. drilling wood (mm)	40
Tool reception	SDS-Plus
Vibration drilling (m/s ²)	22
Vibration chiseling (m/s ²)	20
FIXTEC	Yes
Weight (kg)	3.6
Supplied in	Kitbox
Article Number	4933400069

PLH 28 | 28 MM SDS-PLUS 3-MODE L-SHAPED HAMMER

- Hardest hitting corded SDS hammer in its class. Tough, durable hammer with excellent drilling performance in concrete from the high torque motor and gears and a 4.1 joule single blow energy
- 800 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Low vibration 10.6 m/s² due to patented dual anti-vibration* handle
- Good balance and easy handling from the compact L-shape design with dual patented AVS (Anti-Vibration-System) and soft grip handle
- Reliable safety clutch protects machine and user
- Roto-stop and variolock for maximum control when doing light chiselling work
- XE version comes with fast changing FIXTEC adaptor and 13 mm keyed chuck
- 4 m durable rubber cable
- *patent pending



	PLH 28 E	PLH 28 XE
Power input (W)	800	800
Blow energy (EPTA)(J)	4.1	4.1
Full load hammer action (bpm)	0 - 4000	0 - 4000
Full load speed (rpm)	0 - 1000	0 - 1000
Max. drilling concrete (mm)	28	28
Max. drilling steel (mm)	13	13
Max. drilling wood (mm)	40	40
Tool reception	SDS-Plus	SDS-Plus
Vibration drilling (m/s ²)	10.6	10.6
Vibration chiseling (m/s ²)	6.8	6.8
FIXTEC	No	Yes
Weight (kg)	3.4	3.6
Supplied in	Kitbox	Kitbox
Article Number	4933446790	4933446800

PH 30 | 30 MM SDS-PLUS 3-MODE HAMMER

- Over sized heavy weight striker delivers 3.6 joules of impact energy
- 1030 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Soft start for precise start of drilling/chiselling
- Low vibration due to ergonomic soft grip on main and side handle
- Soft hammer mode for drilling in sensitive materials
- Fast tool changing from FIXTEC system with keyless chuck
- Greatest durability in class is achieved by utilising integrated metal block technology in the gearing mechanism
- Brush rotation ring (for same power in forward & reverse action)
- Safety clutch protects machine and user if drill bit jams
- 4 m cable



PH 30 POWER X	
Power input (W)	1030
Blow energy (EPTA)(J)	3.6
Full load hammer action (bpm)	0 - 3800
Full load speed (rpm)	0 - 850
Max. drilling concrete (mm)	30
Max. drilling steel (mm)	13
Max. drilling wood (mm)	40
Tool reception	SDS-Plus
Vibration drilling (m/s ²)	22
Vibration chiseling (m/s ²)	14
FIXTEC	Yes
Weight (kg)	2.9
Supplied in	Kitbox
Article Number	4933396420

PH 28 | 28 MM SDS-PLUS 3-MODE HAMMER

- Over sized heavy weight striker delivers 3.4 joules of impact energy
- 820 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Soft start for precise start of drilling/chiselling
- Low vibration due to ergonomic soft grip on main and side handle
- Soft hammer mode for drilling in sensitive materials
- Greatest durability in class is achieved by utilising integrated metal block technology in the gearing mechanism
- Brush rotation ring (for same power in forward & reverse action)
- Safety clutch protects machine and user if drill bit jams
- X version comes with fast changing FIXTEC adaptor with keyless chuck
- 4 m cable



	PH 28	PH 28 X
Full load hammer action (bpm)	0 - 4000	0 - 4000
Full load speed (rpm)	0 - 900	0 - 900
Vibration drilling (m/s ²)	22	22
Vibration chiseling (m/s ²)	16	16
Weight (kg)	2.7	2.9
Supplied in	Kitbox	Kitbox
Article Number	4933396396	4933396392

PH 27 | 26 MM SDS-PLUS 3-MODE HAMMER

- Most compact, slim line hammer available in its class
- 800 watt motor combined with optimized drilling speed results in unsurpassed drilling performance
- Unmatched performance with 2.8 joules of EPTA rated blow energy and 4800 bpm
- Lowest vibration only 11.4 m/s² in class
- Innovative and patented internal weight reduction technology
- Hammer stop function
- Safety clutch protects machine and user if drill bit jams
- X version comes with fast changing FIXTEC adaptor with keyless chuck
- 4 m rubber cable



	PH 27	PH 27 X
Power input (W)	800	800
Blow energy (EPTA)(J)	2.8	2.8
Full load hammer action (bpm)	0 - 4800	0 - 4800
Full load speed (soft hammer) (rpm)	0 - 1300	0 - 1300
Max. drilling concrete (mm)	26	26
Max. drilling steel (mm)	13	13
Max. drilling wood (mm)	30	30
Tool reception	SDS-Plus	SDS-Plus
Vibration drilling (m/s ²)	11.4	11.4
Vibration chiseling (m/s ²)	10.2	10.2
FIXTEC	No	Yes
Weight (kg)	2.8	3.0
Supplied in	Kitbox	Kitbox
Article Number	4933448469	4933448470

PH 26 | 26 MM SDS-PLUS 3-MODE HAMMER

- Most compact, slimline hammer available in its class
- Unmatched performance with 2.4 J blow energy and 4500 bpm
- Lowest vibration only 13.5 m/s²
- Extreme Milwaukee® durability thanks to integrated metal block technology
- Innovative and patented internal weight reduction technology
- Hammer stop function
- Safety clutch protects machine and user if drill bit jams
- X version comes with fast changing FIXTEC adaptor with keyless chuck
- 4 m cable



PH 26 X	
Power input (W)	725
Blow energy (EPTA)(J)	2.4
Full load hammer action (bpm)	0 - 4500
Full load speed (rpm)	0 - 1250
Max. drilling concrete (mm)	26
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Tool reception	SDS-Plus
Vibration drilling (m/s ²)	13.5
Vibration chiseling (m/s ²)	11.2
FIXTEC	Yes
Weight (kg)	2.6
Supplied in	Kitbox
Article Number	4933428250

PH 26 T | 26 MM SDS-PLUS 3-MODE HAMMER

- Tough, durable and compact hammer for drilling applications in masonry and concrete
- 2.4 J of impact energy delivering premium drill rate
- 800 W motor providing power for toughest applications
- Optimised for drilling 6 - 16 mm
- Safety clutch protects user if drill bit jams
- X version comes with FIXTEC adaptor and additional keyless chuck
- 4 m cable



	PH 26 T	PH 26 TX
Power input (W)	800	800
Blow energy (EPTA)(J)	2.4	2.4
Full load hammer action (bpm)	0 - 4500	0 - 4500
Full load speed (rpm)	0 - 1500	0 - 1500
Max. drilling concrete (mm)	26	26
Max. drilling steel (mm)	13	13
Max. drilling wood (mm)	30	30
Tool reception	SDS-Plus	SDS-Plus
Vibration drilling (m/s ²)	13.6	13.6
Vibration chiseling (m/s ²)	11.9	11.9
FIXTEC	No	Yes
Weight (kg)	2.4	2.6
Supplied in	Kitbox	Kitbox
Article Number	4933464580	4933464579

PFH 24 | 24 MM SDS-PLUS 2-MODE FIXING HAMMER

- Variable speed - precise drilling start and perfect adjustment to the application
- Lock-on switch for more comfortable extended use
- Safety clutch protects machine and user if drill bit jams
- Reverse function
- Hammer stop function - turns off the hammering action - for screw driving applications or drilling without percussion in wood/metal
- Service hatch - access hatch for servicing (e.g. worn-out carbon brushes)
- Depth-gauge knob
- Soft grip for user comfort
- 4 m cable



	PFH 24 E
Power input (W)	670
Blow energy (EPTA)(J)	1.9
Full load hammer action (bpm)	0 - 3700
Full load speed (soft hammer) (rpm)	0 - 850
Max. drilling masonry (mm)	24
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Tool reception	SDS-Plus
Vibration drilling (m/s ²)	15.5
FIXTEC	No
Weight (kg)	2.4
Supplied in	Kitbox
Article Number	4933411470

PFH 26 T | 26 MM SDS-PLUS 2-MODE FIXING HAMMER

- Tough, durable and compact hammer for drilling applications in masonry and concrete
- 2.4 J of impact energy delivering premium drill rate
- 800 W motor providing power for toughest applications
- Optimised for drilling 6 - 16 mm
- Safety clutch protects user if drill bit jams
- 4 m cable



	PFH 26 T
Power input (W)	800
Blow energy (EPTA)(J)	2.4
Full load hammer action (bpm)	0 - 4500
Full load speed (rpm)	0 - 1500
Max. drilling concrete (mm)	26
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Tool reception	SDS-Plus
Vibration drilling (m/s ²)	13.6
FIXTEC	No
Weight (kg)	2.4
Supplied in	Kitbox
Article Number	4933464581

PLH 20 | 20 MM SDS-PLUS 2-MODE L-SHAPED FIXING HAMMER

- Best power to weight ratio in its class - 2.0 J and 1.9 kg
- 620 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Motor cooling airflow is designed in a way that blows drilling debris away from user when drilling overhead
- AVS (Anti-Vibration-System) for more comfortable use and less strain on the user
- Optimised hammer drilling 5 - 12 mm
- Safety clutch protects user and machine if drill bit jams
- Forward and reverse mechanism
- Soft grip handle for comfort
- 4 m cable



	PLH 20
Power input (W)	620
Blow energy (EPTA)(J)	2.0
Full load hammer action (bpm)	0 - 4400
Full load speed (soft hammer) (rpm)	0 - 2700
Max. drilling concrete (mm)	20
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Tool reception	SDS-Plus
Vibration drilling (m/s ²)	10.2
FIXTEC	No
Weight (kg)	1.9
Supplied in	Kitbox
Article Number	4933408070

PFH 26 | 26 MM SDS-PLUS 2-MODE FIXING HAMMER

- Most compact, slimline fixing hammer available in its class
- Unmatched performance with 2.4 J blow energy and 4500 bpm
- Lowest vibration at drilling into concrete: only 13.5 m/s²
- Extreme Milwaukee® durability thanks to Integrated metal block technology
- Innovative and patented internal weight reduction technology
- Hammer stop function - turns off the hammering action - for screw driving applications or drilling without percussion in wood/metal
- Brush rotation ring (for same power in forward & reverse action)
- 4 m cable



	PFH 26
Power input (W)	725
Blow energy (EPTA)(J)	2.4
Full load hammer action (bpm)	0 - 4500
Full load speed (rpm)	0 - 1250
Max. drilling concrete (mm)	26
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Tool reception	SDS-Plus
Vibration drilling (m/s ²)	13.5
FIXTEC	No
Weight (kg)	2.4
Supplied in	Kitbox
Article Number	4933428230

SB 2-35 D | 1010 W 2-SPEED PERCUSSION DRILL

- Powerful 1010 W motor
- High torque and lower speed for tough applications
- Variable speed
- Metal gearbox for outstanding durability
- Hammer action stop for rotary drilling only
- 16 mm metal keyed chuck
- 4 m cable



	SB 2-35 D
Power input (W)	1010
No load speed gear 1 (rpm)	0 - 800
No load speed gear 2 (rpm)	0 - 1800
Max. drilling concrete (mm)	35
Max. drilling masonry (mm)	40
Max. drilling steel (mm)	16
Max. drilling wood (mm)	50
Max. static stalling torque (Nm)	57
Chuck capacity (mm)	16
Weight (kg)	4.2
Supplied in	Kitbox
Article Number	4933380507

PD2E 24 R | 1020 W 2-SPEED PERCUSSION DRILL

- Powerful 1020 W motor
- Electronics with variable speed selection and reverse function
- AVS (Anti-Vibration-System) and soft grip for more comfortable use
- Metal gearbox for outstanding durability
- Direct bit reception for reduced length and weight for best visibility during screw driving
- Safety clutch to protect the user
- Keyless chuck 1.5 - 13 mm
- 4 m cable



PD2E 24 R	
Power input (W)	1020
No load speed gear 1 (rpm)	0 - 1000
No load speed gear 2 (rpm)	0 - 3200
Max. drilling concrete (mm)	22
Max. drilling masonry (mm)	24
Max. drilling steel (mm)	16
Max. drilling wood (mm)	40
Max. static stalling torque (Nm)	60
Chuck capacity (mm)	13
Weight (kg)	3.0
Supplied in	Kitbox
Article Number	4933419595

MULTI MATERIAL DRILL BIT SET (7 PC) - Ø 3 / 4 / 5 / 6 / 6 / 8 / 10 MM



Article Number 4932352335

PD2E 24 RS | 1010 W 2-SPEED PERCUSSION DRILL

- Powerful 1010 W motor
- Electronics with variable speed selection and reverse function
- AVS (Anti-Vibration-System) and soft grip for more comfortable use
- Metal synchronmesh gearbox for outstanding durability
- Direct bit reception for reduced length and weight for best visibility during screw driving
- Safety clutch to protect the user
- Keyless chuck 1.5 - 13 mm
- 4 m cable



PD2E 24 RS	
Power input (W)	1010
No load speed gear 1 (rpm)	0 - 1450
No load speed gear 2 (rpm)	0 - 3400
Max. drilling concrete (mm)	20
Max. drilling masonry (mm)	24
Max. drilling steel (mm)	16
Max. drilling wood (mm)	40
Max. static stalling torque (Nm)	54
Chuck capacity (mm)	13
Weight (kg)	3.1
Supplied in	Kitbox
Article Number	4933380462

MULTI MATERIAL DRILL BIT SET (7 PC) - Ø 3 / 4 / 5 / 6 / 6 / 8 / 10 MM



Article Number 4932352335

PD2E 24 RST | 1200 W 2-SPEED PERCUSSION DRILL

- Powerful 1200 W motor
- Electronics with variable speed selection and reverse function
- AVS (Anti-Vibration-System) and soft grip for more comfortable use
- Metal synchronmesh gearbox for outstanding durability
- Torque adjustment
- Direct bit reception for reduced length and weight for best visibility during screw driving
- Safety clutch to protect the user
- Keyless chuck 1.5 - 13 mm
- 4 m cable



PD2E 24 RST	
Power input (W)	1200
No load speed gear 1 (rpm)	0 - 1450
No load speed gear 2 (rpm)	0 - 3400
Max. drilling concrete (mm)	22
Max. drilling masonry (mm)	24
Max. drilling steel (mm)	16
Max. drilling wood (mm)	45
Max. static stalling torque (Nm)	56
Chuck capacity (mm)	13
Weight (kg)	3.1
Supplied in	Kitbox
Article Number	4933380796

PD2E 22 R | 850 W 2-SPEED PERCUSSION DRILL

- Powerful 850 W motor
- Electronics with variable speed selection and reverse function
- AVS (Anti-Vibration-System) and soft grip for more comfortable use
- Metal gearbox for outstanding durability
- Direct bit reception for reduced length and weight for best visibility during screw driving
- Safety clutch to protect the user
- Keyless chuck 1.5 - 13 mm
- 4 m cable



PD2E 22 R	
Power input (W)	850
No load speed gear 1 (rpm)	0 - 1000
No load speed gear 2 (rpm)	0 - 3200
Max. drilling concrete (mm)	20
Max. drilling masonry (mm)	22
Max. drilling steel (mm)	13
Max. drilling wood (mm)	40
Max. static stalling torque (Nm)	56
Chuck capacity (mm)	13
Weight (kg)	2.9
Supplied in	Kitbox
Article Number	4933419570

CONCRETE SUPER DRILL BIT SET (5 PCS) - Ø 4 / 5 / 6 / 8 / 10 MM



Article Number 4932352336

PD-705 | 705 W PERCUSSION DRILL

- Compact and powerful 705 W motor
- Compact ergonomic design with large soft grip areas offers excellent handling
- Variable speed control with forward and reverse mechanism
- Hammer action stop for rotary drilling
- 13 mm metal keyless chuck
- 43 mm gear neck diameter for use in drill stands
- 4 m cable



PD-705	
Power input (W)	705
No load speed (rpm)	0 - 3000
Max. drilling concrete (mm)	15
Max. drilling masonry (mm)	16
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Max. static stalling torque (Nm)	15
Chuck capacity (mm)	13
Weight (kg)	1.9
Supplied in	-
Article Number	4933431955

PDE 16 RP | 630 W SINGLE SPEED PERCUSSION DRILL

- Excellent handling from a compact ergonomic design
- Planetary gearbox for low speed and high torque applications
- Integrated-Metal-Block technology for highest durability and stability
- Electronics: variable preselection of speed for optimum drilling
- Hammer action stop for rotary drilling
- 4 m cable



PDE 16 RP	
Power input (W)	630
No load speed (rpm)	0 - 950
Max. drilling concrete (mm)	16
Max. drilling masonry (mm)	20
Max. drilling steel (mm)	13
Max. drilling wood (mm)	40
Max. static stalling torque (Nm)	59
Chuck capacity (mm)	13
Weight (kg)	2.0
Supplied in	Kitbox
Article Number	4933409206

PDE 13 RX | 630 W SINGLE SPEED PERCUSSION DRILL

- Excellent handling from a compact ergonomic design
- IMB - Integrated-Metal-Block technology for highest durability and stability
- Electronics: variable preselection of speed for optimum drilling
- Hammer action stop for rotary drilling
- Keyless chuck 1,5 - 13 mm with one sleeve
- Easy access and exchange of carbon brushes by removing soft grip
- 4 m cable



PDE 13 RX	
Power input (W)	630
No load speed (rpm)	0 - 2900
Max. drilling concrete (mm)	15
Max. drilling masonry (mm)	18
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Max. static stalling torque (Nm)	21
Chuck capacity (mm)	13
Weight (kg)	1.8
Supplied in	Kitbox
Article Number	4933409200

HDE 13 RQX | 950 W SINGLE SPEED ROTARY DRILL

- Compact and powerful 950 W motor
- Variable speed
- Great performance in low speed and high torque applications
- Industrial metal single sleeve keyless chuck
- Automatic spindle lock
- Reverse operation
- 4 m QUIK-LOK cable



	HDE 13 RQX	HDE 13 RQX KIT
Power input (W)	950	950
No load speed (rpm)	0 - 850	0 - 850
Max. drilling steel (mm)	13	13
Max. drilling wood (mm)	38	38
Max. static stalling torque (Nm)	94	94
Chuck capacity (mm)	13	13
Tool reception	1/2" x 20	1/2" x 20
Weight (kg)	2.0	2.0
Supplied in	-	Kitbox
Article Number	030250	4933428550

B2E 16 RLD | 900 W 2-SPEED ROTARY DRILL

- Powerful 900 W motor
- High torque and lower speed for tough applications
- Variable speed selection
- Metal gearbox for outstanding durability
- 16 mm metal keyed chuck
- 4 m cable



B2E 16 RLD	
Power input (W)	900
No load speed gear 1 (rpm)	0 - 750
No load speed gear 2 (rpm)	0 - 1600
Max. drilling steel (mm)	16
Max. drilling wood (mm)	40
Max. static stalling torque (Nm)	88
Chuck capacity (mm)	16
Tool reception	M18 x 2.5
Weight (kg)	4.2
Supplied in	-
Article Number	4933380482

WOOD AUGER BITS SET (6 PC) - Ø 8 / 10 / 12 / 14 / 16 / 18 MM X 230 MM

Article Number 4932373380

HDE 13 RQD | 825 W SINGLE SPEED ROTARY DRILL

- Compact and powerful 825 W motor
- Variable speed
- Great performance in low speed and high torque applications
- Keyed chuck 1.5 - 13 mm
- Reverse operation
- 4 m QUIK-LOK cable



HDE 13 RQD	
Power input (W)	825
No load speed (rpm)	0 - 500
Max. drilling steel (mm)	13
Max. drilling wood (mm)	38
Max. static stalling torque (Nm)	101
Chuck capacity (mm)	13
Tool reception	1/2" x 20
Weight (kg)	3.2
Supplied in	-
Article Number	110750

RIGHT ANGLE DRILL ATTACHMENT; COUPLING, SLEEVE AND HEAD (45 MM X 95 MM)

Article Number 48062871

HD2E 13 R | 705 W 2-SPEED ROTARY DRILL

- Compact and powerful 705 W motor
- Electronics with variable speed selection and reverse function
- Metal gearbox for outstanding durability
- 13 mm metal keyless chuck
- Soft grip and ergonomic handle design for comfortable handling
- 4 m cable



HD2E 13 R	
Power input (W)	705
No load speed gear 1 (rpm)	0 - 1050
No load speed gear 2 (rpm)	0 - 2200
Max. drilling steel (mm)	13
Max. drilling wood (mm)	40
Max. static stalling torque (Nm)	60
Chuck capacity (mm)	13
Tool reception	1/2" x 20
Weight (kg)	2.7
Supplied in	-
Article Number	4933390186

DE 13 RP | 630 W SINGLE SPEED ROTARY DRILL

- Compact and powerful 630 W motor
- Electronics: variable preselection of speed for optimum drilling
- Integrated metal block technology for highest durability and stability
- Planetary gearbox for low speed and high torque applications
- Metal keyless chuck (1.5 - 13 mm)
- Reversible action
- Easy access and exchange of carbon brushes by removing soft grip
- 4 m cable



DE 13 RP	
Power input (W)	630
No load speed (rpm)	0 - 950
Max. drilling steel (mm)	13
Max. drilling wood (mm)	40
Max. static stalling torque (Nm)	59
Chuck capacity (mm)	13
Tool reception	1/2" x 20
Weight (kg)	2.1
Supplied in	Kitbox
Article Number	4933409194

TKSE 2500 Q | TECH GUN FOR SELF DRILLING SCREWS

- Metal gearbox for exact seating of bearings and gears
- Quiet snap-action clutch
- Very easy to remove "snap-on" depth setting nose
- Soft grip
- Supplied with a belt clip, socket set - 6/8/10 mm (49-66-3004) and 4 m QUIK-LOK cable



TKSE 2500 Q	
Power input (W)	725
No load speed (rpm)	0 - 2500
Wood screws to (mm)	6
Max. static stalling torque (Nm)	25
Tool reception	1/4" Hex
Weight (kg)	1.4
Supplied in	-
Article Number	679050

3 PIECE HEXAGON SOCKET SET; Ø 6 / 8 / 10 MM MAGNETIC SOCKETS

Article Number 49663004



DWSE 4000 Q | DRYWALL SCREWDRIVER

- Metal gearbox for exact seating of bearings and gears
- Quiet snap-action clutch
- Very easy to remove "snap-on" depth setting nose
- Soft grip
- Supplied with a bit holder, Phillips No. 2, belt clip and 4 m QUIK-LOK cable



DWSE 4000 Q	
Power input (W)	725
No load speed (rpm)	0 - 4000
Wood screws to (mm)	4.8
Max. static stalling torque (Nm)	20
Tool reception	1/4" Hex
Weight (kg)	1.3
Supplied in	-
Article Number	674350

IPWE 400 R | 1/2" DRIVE IMPACT WRENCH

- Metal gearbox for exact seating of bearings and gears
- High torque output 400 Nm
- Soft grip and ergonomic handle design
- Variable speed, reversible
- Supplied with 4 m cable



IPWE 400 R	
Power input (W)	725
No load speed (rpm)	0 - 1700
Impact rate (ipm)	1000 - 2600
Max. torque (Nm)	400
Max. bolt diameter	M20
Tool reception	1/2" square
Weight (kg)	2.7
Supplied in	-
Article Number	4933451524

1/2" SHOCKWAVE IMPACT DUTY™ SOCKETS SET (10 PC)

Article Number 4932352861



IPWE 520 R | 3/4" DRIVE IMPACT WRENCH

- Metal gearbox for exact seating of bearings and gears
- High torque output 520 Nm
- Soft grip and ergonomic handle design
- Variable speed, reversible
- Supplied with 4 m cable



IPWE 520 R	
Power input (W)	725
No load speed (rpm)	0 - 1700
Impact rate (ipm)	1000 - 2500
Max. torque (Nm)	520
Max. bolt diameter	M24
Tool reception	3/4" square
Weight (kg)	2.8
Supplied in	-
Article Number	4933451525

DD 3-152 | 3-SPEED COMBI DIAMOND DRILL

- Powerful 1900 watt motor
- Optimum speed range to drive small and large core bits
- Soft start with stepless speed control
- LED thermal motor temperature protection indicator
- Safety clutch
- Quick-in connection - secure motor fixing connection for ease of use and minimum vibration
- L shaped handle for better weight distribution



DD 3-152	
Power input (W)	1900
Full load speed (rpm)	550 / 1250 / 2700
Max. drilling concrete (mm)	152
Max. drilling masonry (mm)	202
Tool reception	1/2" G + 1 1/4" UNC
Weight (kg)	6.5
Supplied in	Kitbox
Article Number	4933428000

WT 10 WATERTANK. 10 LITERS CAPACITY, STEEL, WATER TANK WITH INSIDE AND OUTSIDE POLYESTER COATING. RELIABLE BRASS PUMP WITH A MAX. PRESSURE BAR OF 6 BAR. 2.5 M HOSE WITH QUICK CONNECTION SYSTEM FITS DIRECT TO MILWAUKEE® DIAMOND DRILLS

Article Number 4932399726



DR 152 T | DIAMOND DRILL STAND FOR DD 3-152

- Cast aluminium base for easy transportation
- 45° tilt for angle drilling
- Quick-in connection - precise and quick connection of tool and rig
- Compact base - saves space for drilling in confined spaces
- 4 leveling screws for fast adjustment
- Horizontal and vertical spirit levels
- Transport handle
- Locking knob locks unit at highest position to aid fixing of machine and core bit
- Two spoke wheel feed for left and right hand operation
- Vacuum plate is available as accessory (4932352676)



DR 152 T	
Max. drilling core bit (mm)	152
Base size (mm)	330 x 210
Angle capacity (°)	45
Weight (kg)	10
Supplied in	-
Article Number	4933428020

VACUUM PLATE

Article Number 4932352676



DD 2-160 XE | 2-SPEED DRY DIAMOND DRILL

- Powerful robust motor delivers constant high torque
- Dual protection from the interlinked mechanical and electronic clutches to protect both user and tool
- Robust construction with metal gearbox
- Safe handling from the long AVS side handle and "D- shaped" back handle
- 2-speed gear box
- M16 FIXTEC adaptor for fast core bit changing
- Soft hammer action - when activated allows the core bit to cut faster and easier
- Soft start via accelerator switch for precision and controlled drilling
- FIXTEC Cleanline rotor (additional accessory) the best solution for dust extraction
- 4 m cable
- Supplied with quick change adaptor for M16 diamond cores, SDS-plus pilot drill bit (8 x 140 mm)



DD 2-160 XE	
Power input (W)	1500
No load speed (rpm)	0 - 1500 / 0 - 3000
Full load speed (rpm)	0 - 890 / 0 - 1770
No load hammer stroke (rpm)	24,000 / 48,000
Max. drilling masonry (mm)	162
Max. static stalling torque (Nm)	50
Tool reception	M18 x 2.5
Weight (kg)	4.2
Supplied in	Kitbox
Article Number	4933368690

FIXTEC CLEAN LINE ROTOR (CLR) FITS TO DIAMOND CORES WITH 1 1/2" UNC THREAD. THE ADDED ADVANTAGE OF DUST ABSORPTION ALLOWS DRILLING SPEED TO BE INCREASED AND EXTENDS THE LIFETIME OF THE DIAMOND CORES

Article Number 4932352172



DCM 2-350 C | DIAMOND DRILLING MOTOR

- Two-speed diamond coring motor
- Internal slip clutch
- Triple-reduction gearing
- Soft start switch
- Motor overload protection
- PRCD residual current device
- Built-in water swivel
- Dual-mount switch box
- Supplied with open end wrench, Hex keys and strap with switch box



DCM 2-350 C	
Power input (W)	2800
No load speed gear 1 (rpm)	300
No load speed gear 2 (rpm)	600
Max. drilling core bit (mm)	350
Tool reception	1 1/4" UNC
Weight (kg)	9.0
Supplied in	-
Article Number	40044

DR 350 T | DIAMOND DRILL STAND FOR DCM 2-350 C

- Light weight drilling rig from aluminium
- Tilting (0 - 45°)
- Drill angle and depth display
- Quick-connect motor plate
- Fine adjustment of feed speed
- Vertical and horizontal water level
- Drill hole centering device
- Leveling screws
- Feed handle attachable to both sides of rig
- Transportable handle & wheels
- Supplied with 3/16" Hex key, 6 mm Hex key, 17 x 19 wrench, quick-connect motor plate, 4 pcs. M8 x 25 mm screws, centering device



DR 350 T	
Max. drilling core bit (mm)	350
Stroke length (mm)	610
Height (mm)	1042
Base size (mm)	391 x 523
Angle capacity (°)	45
Weight (kg)	19.5
Supplied in	-
Article Number	4933400600

WATER COLLECTION RING FOR USE WITH DRILL RIG DR 350 T. FOR USE WITH MAX. Ø 300 MM CORE BITS

Article Number 4932399728



DCM 2-250 C | DIAMOND DRILLING MOTOR

- Two-speed diamond coring motor
- Internal slip clutch
- Triple-reduction gearing
- Soft start switch
- Motor overload protection
- PRCD residual current device
- Built-in water swivel
- Dual-mount switch box
- Supplied with open end wrench, Hex keys and strap with switch box



DCM 2-250 C	
Power input (W)	2800
No load speed gear 1 (rpm)	450
No load speed gear 2 (rpm)	900
Max. drilling core bit (mm)	250
Tool reception	1 1/2" UNC
Weight (kg)	9.0
Supplied in	-
Article Number	40964

DR 250 TV | DIAMOND DRILL STAND FOR DCM 2-250 C

- Light weight drilling rig from aluminium
- Tilting (0 - 45°)
- Drill angle and depth display
- Quick-connect motor plate
- Integrated vacuum base plate (use with and without vacuum possible)
- Fine adjustment of feed speed
- Vertical and horizontal water level
- Drill hole centering device
- Leveling screws
- Feed handle attachable to both sides of rig
- Supplied with 3/16" Hex key, 6 mm Hex key, 17 x 19 wrench, quick-connect motor plate, 4 pcs. M8 x 25 mm screws, centering device, vacuum rubber seal



DR 250 TV	
Max. drilling core bit (mm)	250
Stroke length (mm)	520
Height (mm)	834
Base size (mm)	276 x 467
Angle capacity (°)	45
Weight (kg)	10.0
Supplied in	-
Article Number	4933400590

AGV 15 DEC | 1550 W ANGLE GRINDER WITH DUST MANAGEMENT (28 MM DOC)

- Powerful, 1550 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Very compact and slim design for comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Safety clutch to prevent user from "kickback-effect"
- Keyless depth adjustment from 5 - 28 mm
- Keyless opening for easy and fast blade change
- Cutting guide with cutting indication line to prevent twisting and best control during work
- Tool-free quick release guard for fast and easy adjustment
- Dust shroud can be easily mounted to the Milwaukee® M-Class cleaners with unique "click-system" adaptor supplied with the Milwaukee® EMAC vacuum cleaner
- Anti-vibration side handle for reduced user fatigue
- Supplied with 4 m rubber cable, dust extraction cutting shroud, diamond cutting wheel DUH 125 mm



AGV 15-125 XC DEC-SET	
Power input (W)	1550
No load speed (rpm)	11,000
Disc diameter (mm)	125
Max. cutting depth (mm)	28
Spindle size	M 14
Weight (kg)	2.6
Variable speed	No
FIXTEC	Yes
Line lock out function	Yes
AVS side handle	Yes
Supplied in	HD Box
Article Number	4933448025

AGV 15 DEG 1550 W ANGLE GRINDER WITH DUST MANAGEMENT

- Powerful, 1550 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased tool life time and best performance in all applications
- Very compact and slim design for comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Magnetic, tool-free interface for optimum work in corners and closed to walls
- On-board storage of front cover, when removed for work in restricted areas
- Flexible height adjustment allows for complete use of diamond segments on grinding wheel
- Tool-free quick release guard for fast and easy adjustment
- Dust shroud can be easily mounted to the Milwaukee® M-Class cleaners with unique "click-system" adaptor supplied with the Milwaukee® EMAC vacuum cleaner
- Angled bale handle design to allow for more pressure to be applied in all positions
- Brushes are replaceable when worn
- Supplied with 4 m rubber cable, bale handle, dust extraction grinding shroud, diamond cup wheel 125 mm



	AGV 15-125 XC DEG-SET	AGV 15-125 XE DEG-SET
Power input (W)	1550	1550
No load speed (rpm)	11,000	2800 - 11,000
Disc diameter (mm)	125	125
Max. cutting depth (mm)	28	28
Spindle size	M 14	M 14
Weight (kg)	2.6	2.6
Variable speed	No	Yes
FIXTEC	Yes	Yes
Line lock out function	Yes	Yes
Supplied in	HD Box	HD Box
Article Number	4933448035	4933448830

UNIVERSAL WHEEL FOR GRINDING AND LEVELLING APPLICATIONS, HIGH STOCK REMOVAL

Article Number **4932451186**



Magnetic, tool-free interface



Dust shroud can be easily mounted to the Milwaukee® M-Class cleaners with unique "click-system" adaptor



100% keyless

AGV 12 DEC | 1200 W ANGLE GRINDER WITH DUST MANAGEMENT (28 MM DOC)

- Powerful, 1200 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Very compact and slim design for comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Safety clutch to prevent user from "kickback-effect"
- Keyless depth adjustment from 5 - 28 mm
- Keyless opening for easy and fast blade change
- Cutting guide with cutting indication line to prevent twisting and best control during work
- Tool-free quick release guard for fast and easy adjustment
- Dust shroud can be easily mounted to the Milwaukee® M-Class cleaners with unique "click-system" adaptor supplied with the Milwaukee® EMAC vacuum cleaner
- Anti-vibration side handle for reduced user fatigue
- Supplied with 4 m rubber cable, dust extraction cutting shroud, diamond cutting wheel DUH 125 mm



AGV 12-125 X DEC-SET

Power input (W)	1200
No load speed (rpm)	11,000
Disc diameter (mm)	125
Max. cutting depth (mm)	28
Spindle size	M 14
Weight (kg)	2.4
FIXTEC	Yes
Line lock out function	Yes
AVS side handle	Yes
Switch type	Slide switch
Supplied in	HD Box
Article Number	4933448020

AGV 12 DEG | 1200 W ANGLE GRINDER WITH DUST MANAGEMENT

- Powerful, 1200 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Very compact and slim design for comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Magnetic, tool-free interface for optimum work in corners and close to walls
- On-board storage of front cover, when removed for work in restricted areas
- Flexible height adjustment allows for complete use of diamond segments on grinding wheel
- Tool-free quick release guard for fast and easy adjustment
- Dust shroud can be easily mounted to the Milwaukee® M-Class cleaners with unique "click-system" adaptor supplied with the Milwaukee® EMAC vacuum cleaner
- Angled bale handle design to allow for more pressure to be applied in all positions
- Brushes are replaceable when worn
- Supplied with 4 m rubber cable, bale handle, dust extraction grinding shroud, diamond cup wheel 125 mm



AGV 12-125 X DEG-SET

Power input (W)	1200
No load speed (rpm)	11,000
Disc diameter (mm)	125
Max. cutting depth (mm)	28
Spindle size	M 14
Weight (kg)	2.4
FIXTEC	Yes
Line lock out function	Yes
Switch type	Slide switch
Supplied in	HD Box
Article Number	4933448030

WCS 45 | 1900 W 150 MM (45 MM DOC) WALL CHASER

- Powerful 1900 W motor
- Overload protection
- Variable adjustable cutting depth and variable cutting width
- TILT-LOK handle
- Soft grip
- Dust extraction connection
- Supplied with 2 diamond discs, special chisel, keys



WCS 45

Power input (W)	1900
No load speed (rpm)	5800
Disc diameter (mm)	150
Cutting width (mm)	45
Max. cutting depth (mm)	45
Spindle size	M 14
Weight (kg)	6.6
Supplied in	Kitbox
Article Number	4933383350

150 X 22.23 MM DIAMOND BLADE WITH 2.4 MM CUTTING WIDTH, 10 MM SEGMENT HEIGHT IDEAL FOR GENERAL MASONRY

Article Number **4932373148**



WCE 30 | 1500 W 125 MM (30 MM DOC) WALL CHASER

- Powerful 1500 watt motor
- Ideal for the installation of conduit for electrical cables
- High performance electronics with overload protection
- Current limitation for soft start
- Easily adjustable cutting width
- In-Line dust extraction connection
- Supplied with 2 diamond discs, special chisel, keys, bayonet adaptor



WCE 30

Power input (W)	1500
No load speed (rpm)	9500
Disc diameter (mm)	125
Cutting width (mm)	26
Max. cutting depth (mm)	30
Spindle size	M 14
Weight (kg)	4.3
Supplied in	Kitbox
Article Number	4933383855

125 X 22.23 MM DIAMOND BLADE WITH 2.4 MM CUTTING WIDTH, 10 MM SEGMENT HEIGHT, IDEAL FOR GENERAL MASONRY

Article Number **4932373147**



METALWORKING



AGVM 26 | 2600 W ANGLE GRINDER WITH AVS AND KICKBACK PROTECTION

- Milwaukee® B-Guard protects both operator and machine from "kickback effect"
- Powerful, 2600 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Autobalancer for greatly reduced vibration of bad discs
- AVS equipped motor housing and additional AVS side handle for more comfortable handling and less strain of body joints
- Lowest vibration in it's class with only 2.5 m/s²
- 7 position rotatable main handle
- FIXTEC flange nut for fast and easy change of discs
- Burst resistant quick release safety guard for easy adjustment
- Automatic cut-off carbon brushes
- 4 m rubber cable



	AGVM 26-230 GEX	AGVM 26-230 GEX/DMS
Power input (W)	2600	2600
No load speed (rpm)	6600	6600
Disc diameter (mm)	230	230
Max. cutting depth (mm)	68	68
Spindle size	M 14	M 14
Weight (kg)	5.8	5.8
FIXTEC flange nut	Yes	Yes
Deadman switch	No	Yes
Line lock out function	Yes	No
Autobalancer system	Yes	Yes
AVS Anti-Vibration System	Yes	Yes
Rotatable main handle	Yes	Yes
Supplied in	-	-
Article Number	4933402365	4933402495

AGV 26 | 2600 W ANGLE GRINDER WITH AVS

- Powerful, 2600 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Autobalancer for greatly reduced vibration of bad discs
- AVS equipped motor housing and additional AVS side handle for more comfortable handling and less strain of body joints
- Lowest vibration in it's class with only 2.5 m/s²
- 7 position rotatable main handle
- Soft start for smooth start up
- Burst resistant quick release safety guard for easy adjustment
- Automatic cut-off carbon brushes
- 4 m rubber cable



	AGV 26-230 GE	AGV 26-230 GE/DMS
Power input (W)	2600	2600
No load speed (rpm)	6600	6600
Disc diameter (mm)	230	230
Max. cutting depth (mm)	68	68
Spindle size	M 14	M 14
Weight (kg)	5.5	5.5
FIXTEC flange nut	No	No
Deadman switch	No	Yes
Line lock out function	Yes	No
Autobalancer system	Yes	Yes
AVS Anti-Vibration System	Yes	Yes
Rotatable main handle	Yes	Yes
Supplied in	-	-
Article Number	4933402360	4933402490

AGVM 24 | 2400 W ANGLE GRINDER WITH AVS AND KICKBACK PROTECTION

- Milwaukee® B-Guard protects both operator and machine from "kickback" effect
- Powerful, 2400 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Autobalancer for greatly reduced vibration of bad discs
- AVS equipped motor housing and additional AVS side handle for more comfortable handling and less strain of body joints
- Lowest vibration in it's class with only 2.5 m/s²
- 7 position rotatable main handle
- FIXTEC flange nut for fast and easy change of discs
- Burst resistant quick release safety guard for easy adjustment
- Automatic cut-off carbon brushes
- 4 m rubber cable



	AGVM 24-230 GEX	AGVM 24-230 GEX/DMS
Power input (W)	2400	2400
No load speed (rpm)	6600	6600
Disc diameter (mm)	230	230
Max. cutting depth (mm)	68	68
Spindle size	M 14	M 14
Weight (kg)	5.8	5.8
FIXTEC flange nut	Yes	Yes
Deadman switch	No	Yes
Line lock out function	Yes	No
Autobalancer system	Yes	Yes
AVS Anti-Vibration System	Yes	Yes
Rotatable main handle	Yes	Yes
Supplied in	-	-
Article Number	4933402340	4933402475

AGVK 24 | 2400 W ANGLE GRINDER WITH AVS AND KICKBACK PROTECTION

- Powerful, 2400 W motor with powder field coating for increased life time and outstanding performance in all applications
- Line lock out function to prevent automatic start up after power breakdown
- Safety clutch to prevent user from "kickback-effect"
- Overload protection to prevent overheating
- Soft start for smooth start up
- Extremely compact design with an overall length of 485 mm and 5.4 kg for most comfortable handling
- 2-position Anti-vibration side handle for less vibration and more comfortable work



	AGVK 24-230 EK	AGVK 24-230 EK DMS
Power input (W)	2400	2400
No load speed (rpm)	6600	6600
Disc diameter (mm)	230	230
Max. cutting depth (mm)	68	68
Spindle size	M 14	M 14
Weight (kg)	5.4	5.4
FIXTEC flange nut	No	No
Deadman switch	No	Yes
Line lock out function	Yes	Yes
AVS side handle	Yes	Yes
Rotatable main handle	No	No
Supplied in	-	-
Article Number	4933451413	4933451414

DUST GUARD FOR CUTTING, DELIVERED WITH 2 KEYLESS GUARD RECEPTIONS AND QUICK DUST CONNECTOR. DOES NOT FIT TO LAG'S EQUIPPED WITH AUTOBALANCER.



Article Number 4932459341

AGV 24 | 2400 W ANGLE GRINDER WITH AVS

- Powerful, 2400 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Autobalancer for greatly reduced vibration of bad discs
- AVS equipped motor housing and additional AVS side handle for more comfortable handling and less strain of body joints
- Lowest vibration in it's class with only 2.5 m/s²
- Soft start for smooth start up
- Burst resistant quick release safety guard for easy adjustment
- Automatic cut-off carbon brushes
- 4 m rubber cable



	AGV 24-230 E	AGV 24-230 GE	AGV 24-230 GE/DMS
Power input (W)	2400	2400	2400
No load speed (rpm)	6600	6600	6600
Disc diameter (mm)	230	230	230
Max. cutting depth (mm)	68	68	68
Spindle size	M 14	M 14	M 14
Weight (kg)	5.5	5.5	5.5
FIXTEC flange nut	No	No	No
Deadman switch	No	No	Yes
Line lock out function	Yes	Yes	No
Autobalancer system	Yes	Yes	Yes
AVS Anti-Vibration System	Yes	Yes	Yes
Rotatable main handle	No	Yes	Yes
Supplied in	-	-	-
Article Number	4933402335	4933402330	4933402520

AG 24 | 2400 W ANGLE GRINDER

- Powerful, 2400 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Ergonomically designed motor housing for best user comfort
- Soft start for smooth start up
- Burst resistant quick release safety guard for easy adjustment
- Automatic cut-off carbon brushes
- 4 m rubber cable



	AG 24-230 E	AG 24-230 E/DMS
Power input (W)	2400	2400
No load speed (rpm)	6600	6600
Disc diameter (mm)	230	230
Max. cutting depth (mm)	68	68
Spindle size	M 14	M 14
Weight (kg)	5.3	5.3
FIXTEC flange nut	No	No
Deadman switch	No	Yes
Line lock out function	Yes	No
Autobalancer system	No	No
AVS Anti-Vibration System	No	No
Rotatable main handle	No	No
Supplied in	-	-
Article Number	4933402325	4933402450

DUST GUARD FOR CUTTING, DELIVERED WITH 2 KEYLESS GUARD RECEPTIONS AND QUICK DUST CONNECTOR. DOES NOT FIT TO LAG'S EQUIPPED WITH AUTOBALANCER.



Article Number 4932459341

AGV 22 | 2200 W ANGLE GRINDER WITH AVS

- Powerful, 2200 W motor with powder field coating for long life time and outstanding performance in all applications
- Extreme compact design with an overall short length of 485 mm and 5.4 kg for most comfortable handling
- Soft start for smooth start up
- Burst resistant quick release safety guard for easy adjustment
- 2-positions Anti-vibration side handle for less vibrations to the user and more comfortable work
- External brush doors for easy access to the brushes for fast servicing
- 4 m rubber cable



	AGV 22-180 E	AGV 22-230 E	AGV 22-230/DMS
Power input (W)	2200	2200	2200
No load speed (rpm)	8500	6600	6600
Disc diameter (mm)	180	230	230
Max. cutting depth (mm)	43	68	68
Spindle size	M 14	M 14	M 14
Weight (kg)	5.3	5.4	5.4
FIXTEC flange nut	No	No	No
Deadman switch	No	No	Yes
Line lock out function	Yes	Yes	No
Autobalancer system	No	No	No
AVS side handle	Yes	Yes	Yes
Rotatable main handle	No	No	No
Supplied in	-	-	-
Article Number	4933431820	4933431850	4933431860

DUST GUARD FOR CUTTING, DELIVERED WITH 2 KEYLESS GUARD RECEPTIONS AND QUICK DUST CONNECTOR. DOES NOT FIT TO LAG'S EQUIPPED WITH AUTOBALANCER.



Article Number **4932459341**

AG 22 | 2200 W ANGLE GRINDER

- Powerful, 2200 W motor with powder field coating for long life time and outstanding performance in all applications
- Extreme compact design with an overall short length of 485 mm and 5.2 kg for most comfortable handling
- Burst resistant keyed safety guard
- External brush doors for easy access to the brushes for fast servicing



	AG 22-180/DMS	AG 22-230/DMS
Power input (W)	2200	2200
No load speed (rpm)	8500	6600
Disc diameter (mm)	180	230
Max. cutting depth (mm)	43	68
Spindle size	M 14	M 14
Weight (kg)	5.1	5.2
FIXTEC flange nut	No	No
Deadman switch	Yes	Yes
Line lock out function	No	No
Autobalancer system	No	No
AVS side handle	No	No
Rotatable main handle	No	No
Supplied in	-	-
Article Number	4933431830	4933433630

DUST GUARD FOR CUTTING, DELIVERED WITH KEYED GUARD RECEPTION AND QUICK DUST CONNECTOR. FITS MILWAUKEE® AG 22.



Article Number **4932459340**

AGV 21 GEX | 2100 W ANGLE GRINDER WITH AVS

- Powerful, 2100 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Autobalancer for greatly reduced vibration of bad discs
- AVS equipped motor housing and additional AVS side handle for more comfortable handling and less strain on body joints
- 7 position main handle
- Soft start for smooth start up
- FIXTEC flange nut for fast and easy change of discs
- Burst resistant quick release safety guard for easy adjustment
- Automatic cut-off carbon brushes
- 4 m rubber cable



	AGV 21-230 GEX	AGV 21-230 GEX/DMS
Power input (W)	2100	2100
No load speed (rpm)	6600	6600
Disc diameter (mm)	230	230
Max. cutting depth (mm)	68	68
Spindle size	M 14	M 14
Weight (kg)	5.5	5.5
FIXTEC flange nut	Yes	Yes
Deadman switch	No	Yes
Line lock out function	Yes	No
Autobalancer system	Yes	Yes
AVS Anti-Vibration System	Yes	Yes
Rotatable main handle	Yes	Yes
Supplied in	-	-
Article Number	4933402304	4933402525

AGV 17 INOX | 1750 W LOW SPEED GRINDER WITH AVS

- Powerful, 1750 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- 7 position variable speed selection from 2000 - 7600 RPM's for best results on stainless steel
- Constant power electronics with soft start for smooth start up
- Line lock out function to prevent automatic start up after power breakdown
- Thermal overload protection to prevent overheating
- Safety clutch to prevent user from "kickback-effect"
- FIXTEC nut for tool-free disc change
- Burst resistant and tool-free safety guard for best user protection and fast adjustment
- Anti-vibration side handle for lower vibration
- 4 m rubber cable



	AGV 17-125 INOX
Power input (W)	1750
No load speed (rpm)	2000 - 7600
Disc diameter (mm)	125
Max. cutting depth (mm)	33
Spindle size	M 14
Weight (kg)	2.8
Variable speed	Yes
FIXTEC flange nut	Yes
Line lock out function	Yes
Supplied in	-
Article Number	4933449870

AGV 17 | 1750 W ANGLE GRINDER WITH AVS

- Powerful, 1750 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Constant power electronics with soft start for smooth start up
- Line lock out function to prevent automatic start up after power breakdown
- Thermal overload protection to prevent overheating
- Safety clutch to prevent user from "kickback-effect"
- FIXTEC nut for tool-free disc change
- Burst resistant and tool-free safety guard for best user protection and fast adjustment
- Anti-vibration side handle for lower vibration
- 4 m rubber cable



"PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection



Anti-vibration side handle for lower vibration



Electronics

	AGV 17-125 XE	AGV 17-125 XC	AGV 17-125 XC/DMS	AGV 17-150 XC/DMS	AGV 17-180 XC/DMS
Power input (W)	1750	1750	1750	1750	1750
No load speed (rpm)	2600 - 11,000	11,000	11,000	9500	7600
Disc diameter (mm)	125	125	125	150	180
Max. cutting depth (mm)	33	33	33	45	58
Spindle size	M 14	M 14	M 14	M 14	M 14
Weight (kg)	2.8	2.8	2.8	3.0	3.1
Variable speed	Yes	No	No	No	No
FIXTEC flange nut	Yes	Yes	Yes	Yes	Yes
Deadman switch	No	No	Yes	Yes	Yes
Line lock out function	Yes	Yes	Yes	Yes	Yes
AVS side handle	Yes	Yes	Yes	Yes	Yes
Autobalancer system	No	No	No	No	No
Supplied in	-	-	-	-	-
Article Number	4933432230	4933449850	4933455140	4933432250	4933432270

AGV 15 | 1550 W ANGLE GRINDER WITH AVS

- Powerful, 1550 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Very compact and slim design for comfortable handling
- Soft start for smooth start up
- Line lock out function to prevent automatic start up after power breakdown
- Overload protection to prevent overheating
- Safety clutch to prevent user from "kickback-effect"
- New integrated and innovative FIXTEC tool-free disc change system
- Burst resistant and tool-free quick release safety guard for fast adjustment
- Anti-vibration side handle for less fatigue



	AGV 15-125 XC	AGV 15-125 XE	AGV 15-150 XC
Power input (W)	1550	1550	1550
No load speed (rpm)	11,000	2800 - 11,000	9000
Disc diameter (mm)	125	125	150
Max. cutting depth (mm)	33	33	44
Spindle size	M 14	M 14	M 14
Weight (kg)	2.6	2.6	2.6
Variable speed	No	Yes	No
FIXTEC	Yes	Yes	Yes
Line lock out function	Yes	Yes	Yes
Autobalancer system	No	No	No
Supplied in	-	-	-
Article Number	4933428120	4933428127	4933433250

DUST GUARD FOR SURFACE CONDITIONING. 100% TOOL FREE CONNECTION TO Ø125 MM AG(V) 12, AGV 13 AND AGV 15 SERIES GRINDERS.



Article Number **4932430468**

AGV 13 XSPDEB

1250 W BRAKING GRINDER WITH AVS AND PADDLE SWITCH

- Powerful, 1250 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- RAPIDSTOP™ braking system: stops accessories up to 50% faster than grinders without braking function
- Most compact design by Milwaukee® with only 160 mm body size for comfortable handling
- Soft start for smooth start up
- Line lock out function to prevent automatic start up after power breakdown
- Overload protection to prevent overheating
- Safety clutch to prevent user from "kickback-effect"
- FIXTEC nut for tool-free disc change
- Burst resistant and tool-free quick release safety guard for fast adjustment
- Anti-vibration side handle for less user fatigue



Powerful, 1250 W "PROTECTOR-MOTOR"



RAPIDSTOP™ braking system



Safety clutch to prevent user from "kickback-effect"

DUST GUARD FOR CUTTING. 100% TOOL FREE CONNECTION TO Ø115 - 125 MM AG(V) 12, AGV 13, AGV 15 SERIES AND FUEL™ GRINDERS.



Article Number **4932430467**

	AGV 13-125 XSPDEB	AGV 13-125 XSPDEB KIT
Power input (W)	1250	1250
No load speed (rpm)	12,000	12,000
Disc diameter (mm)	125	125
Max. cutting depth (mm)	33	33
Spindle size	M14	M14
Weight (kg)	2.5	2.5
FIXTEC flange nut	Yes	Yes
Deadman switch	Yes	Yes
Line lock out function	Yes	Yes
AVS Anti-Vibration System	Yes	Yes
Anti-kickback protection	Yes	Yes
Switch type	Paddle switch	Paddle switch
Supplied in	-	Kitbox
Article Number	4933464998	4933471194

AGV 13 XSPDE | 1250 W ANGLE GRINDER WITH AVS AND SLIM PADDLE SWITCH

- Powerful, 1250 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Most compact design with only 160 mm body size for comfortable handling
- Soft start for smooth start up
- Line lock out function to prevent automatic start up after power breakdown
- Overload protection to prevent overheating
- Safety clutch to prevent user from "kickback-effect"
- Integrated and innovative FIXTEC tool-free disc change system
- Burst resistant and tool-free quick release safety guard for fast adjustment
- Anti-vibration side handle for less user fatigue



	AGV 13-125 XSPDE
Power input (W)	1250
No load speed (rpm)	12,000
Disc diameter (mm)	125
Max. cutting depth (mm)	33
Spindle size	M 14
Weight (kg)	2.5
FIXTEC	Yes
Deadman switch	Yes
Line lock out function	Yes
AVS side handle	Yes
Switch type	Paddle switch
Supplied in	-
Article Number	4933451578

DUST GUARD FOR CUTTING. 100% TOOL FREE CONNECTION TO Ø115 - 125 MM AG(V) 12, AGV 13, AGV 15 SERIES AND FUEL™ GRINDERS.



Article Number **4932430467**

AG 13 XSPD | 1250 W ANGLE GRINDER WITH SLIM PADDLE SWITCH

- Powerful, 1250 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Most compact design with only 160 mm body size for comfortable handling
- Integrated and innovative FIXTEC tool-free disc change system
- Burst resistant and tool-free quick release safety guard for fast adjustment
- 4 m rubber cable



	AG 13-125 XSPD
Power input (W)	1250
No load speed (rpm)	12,000
Disc diameter (mm)	125
Max. cutting depth (mm)	28
Spindle size	M 14
Weight (kg)	2.3
FIXTEC	Yes
Line lock out function	No
Switch type	Paddle switch
Supplied in	-
Article Number	4933451577

DUST GUARD FOR CUTTING. 100% TOOL FREE CONNECTION TO Ø115 - 125 MM AG(V) 12, AGV 13, AGV 15 SERIES AND FUEL™ GRINDERS.



Article Number **4932430467**

AGV 13 | 1250 W ANGLE GRINDER WITH AVS AND SLIDE SWITCH

- Powerful, 1250 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Very compact and slim design for comfortable handling
- 6 position variable speed selection from 2800 - 11,500 RPM's for work with various materials
- Constant power electronics to provide constant speed under load
- Line lock out function to prevent automatic start up after power breakdown
- Overload protection to prevent overheating
- Safety clutch to prevent user from "kickback-effect"
- Integrated and innovative FIXTEC system for tool-free disc change



	AGV 13-125 XE
Power input (W)	1250
No load speed (rpm)	2,800 - 11,500
Disc diameter (mm)	125
Max. cutting depth (mm)	33
Spindle size	M 14
Weight (kg)	2.4
Variable speed	Yes
FIXTEC	Yes
Line lock out function	Yes
AVS side handle	Yes
Supplied in	-
Article Number	4933451218

DUST GUARD FOR SURFACE CONDITIONING. 100% TOOL FREE CONNECTION TO Ø125 MM AG(V) 12, AGV 13 AND AGV 15 SERIES GRINDERS.



Article Number **4932430468**

AGV 12 | 1200 W ANGLE GRINDER WITH AVS

- Powerful, 1200 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Very compact and slim design for comfortable handling
- Soft start for smooth start up
- Line lock out function to prevent automatic start up after power breakdown
- Overload protection to prevent overheating
- Safety clutch to prevent user from "kickback-effect"
- New integrated and innovative FIXTEC tool-free disc change system
- Burst resistant and tool-free quick release safety guard for fast adjustment
- Anti-vibration side handle for less user fatigue
- 4 m rubber cable



AGV 12-125 X	
Power input (W)	1200
No load speed (rpm)	11,000
Disc diameter (mm)	125
Max. cutting depth (mm)	33
Spindle size	M 14
Weight (kg)	2.4
FIXTEC	Yes
Deadman switch	No
Line lock out function	Yes
Switch type	Slide switch
Supplied in	-
Article Number	4933428085

DUST GUARD FOR CUTTING. 100% TOOL FREE CONNECTION TO Ø115 - 125 MM AG(V) 12, AGV 13, AGV 15 SERIES AND FUEL™ GRINDERS.

ARTICLE NUMBER 4932430467



AGV 10 EK | 1000 W ANGLE GRINDER WITH AVS

- Powerful, 1000 W motor for strong performance in all applications
- Extreme compact design with an overall short length of 276 mm and 2.2 kg for most comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Soft start for smooth start up
- Anti-vibration side handle for less fatigue
- Burst resistant and tool-free quick release safety guard for fast adjustment
- Ramped slide switch for easy start up, even when wearing gloves
- 4 m cable



AGV 10-125 EK	
Power input (W)	1000
No load speed (rpm)	11,000
Disc diameter (mm)	125
Max. cutting depth (mm)	33
Spindle size	M 14
Weight (kg)	2.2
FIXTEC flange nut	No
Line lock out function	Yes
Supplied in	-
Article Number	4933451222

THIN METAL CUTTING DISC PRO+, SCS 41 / 125, 1 MM THICKNESS, 22.2 MM BORE SIZE

ARTICLE NUMBER 4932451487



AG 10 EK | 1000 W ANGLE GRINDER

- Powerful, 1000 W motor for strong performance in all applications
- Extreme compact design with an overall short length of 276 mm and 2.1 kg for most comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Soft start for smooth start up
- Burst resistant and tool-free quick release safety guard for fast adjustment
- Ramped slide switch for easy start up, even when wearing gloves
- 4 m cable



	AG 10-115 EK	AG 10-125 EK
Power input (W)	1000	1000
No load speed (rpm)	11,000	11,000
Disc diameter (mm)	115	125
Max. cutting depth (mm)	28	33
Spindle size	M 14	M 14
Weight (kg)	2.1	2.1
FIXTEC flange nut	No	No
Line lock out function	Yes	Yes
Supplied in	-	-
Article Number	4933451219	4933451220

THIN METAL CUTTING DISC PRO+, SCS 41 / 125, 1 MM THICKNESS, 22.2 MM BORE SIZE

ARTICLE NUMBER 4932451487



AG 9 | 850 W ANGLE GRINDER

- Powerful, 850 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Light weight, slim and compact: a versatile all-purpose angle grinder
- New digital electronic pack offers constant speed, soft start, motor overload protection and no-load speed limitation
- Flat metal gear head for excellent visibility of work piece and optimised cutting depth
- Die-cast magnesium alloy gear case
- Dust protected bearings and switch
- Effective cooling fan keeps the motor cool even under heavy duty conditions
- FIXTEC nut for fast and easy disc change
- Burst resistant quick release safety guard for easy adjustment
- Automatic cut-off carbon brushes
- 4 m rubber cable



	AG 9-125 XC	AG 9-125 XE
Power input (W)	850	850
No load speed (rpm)	10,000	2700 - 10,000
Disc diameter (mm)	125	125
Max. cutting depth (mm)	33	33
Spindle size	M 14	M 14
Weight (kg)	1.8	1.8
Variable speed	No	Yes
FIXTEC flange nut	Yes	Yes
Line lock out function	Yes	Yes
Supplied in	-	-
Article Number	4933403200	4933403206

THIN METAL CUTTING DISC PRO+, SCS 41 / 125, 1 MM THICKNESS, 22.2 MM BORE SIZE

ARTICLE NUMBER 4932451487



AG 800 EK | 800 W ANGLE GRINDER WITH KEYLESS GUARD

- Powerful 800 Watt motor for various applications with only 2.0 kg of weight for comfortable use during longer working periods
- Very compact and slim body grip design with only 194 mm for most comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Soft start for smooth start up
- Durable steel gears for long life time
- Protected air inlets for improved cooling
- Flat metal gear head for excellent visibility of workpiece, optimised cutting depth and work in restricted areas
- Burst resistant and tool-free quick release safety guard for fast adjustment
- 4 m cable



	AG 800-115 EK	AG 800-125 EK
Power input (W)	800	800
No load speed (rpm)	11,500	11,500
Disc diameter (mm)	115	125
Max. cutting depth (mm)	28	33
Spindle size	M 14	M 14
Weight (kg)	2.0	2.0
FIXTEC flange nut	No	No
Line lock out function	Yes	Yes
Supplied in	-	-
Article Number	4933451212	4933451213

THIN METAL CUTTING DISC PRO+, SCS 41 / 125, 1 MM THICKNESS, 22.2 MM BORE SIZE

ARTICLE NUMBER 4932451487



AG 800 E | 800 W ANGLE GRINDER

- Powerful 800 Watt motor for various applications with only 2.0 kg of weight for comfortable use during longer working periods
- Very compact and slim body grip design with only 194 mm for most comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Soft start for smooth start up
- Durable steel gears for long life time
- Protected air inlets for improved cooling
- Flat metal gear head for excellent visibility of workpiece, optimised cutting depth and work in restricted areas



	AG 800-115 E	AG 800-125 E	AG 800-115 E D-SET
Power input (W)	800	800	800
No load speed (rpm)	11,500	11,500	11,500
Disc diameter (mm)	115	125	115
Max. cutting depth (mm)	28	33	28
Spindle size	M 14	M 14	M 14
Weight (kg)	2.0	2.0	2.0
FIXTEC flange nut	No	No	No
Line lock out function	Yes	Yes	Yes
Supplied in	-	-	Kitbox
Article Number	4933451210	4933451211	4933451281

THIN METAL CUTTING DISC PRO+, SCS 41 / 125, 1 MM THICKNESS, 22.2 MM BORE SIZE

ARTICLE NUMBER 4932451487



AGS 15-125 C | 1500 W GRINDER/SANDER

- Powerful, 1500 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Aligned to the optimum speed for flap grinding discs
- Constant power electronics providing constant speed under load
- Soft start for smooth start up
- Line lock out function to prevent automatic start up after power breakdown
- Motor overload protection
- Burst resistant and tool-free quick release safety guard for fast adjustment
- Filter metal mesh
- 4 m rubber cable



AGS 15-125 C	
Power input (W)	1500
No load speed (rpm)	7600
Disc diameter (mm)	125
Spindle size	M 14
Weight (kg)	2.4
FIXTEC flange nut	No
Line lock out function	Yes
Supplied in	-
Article Number	4933407480

AS 12 E | 1200 W SANDER WITH ELECTRONIC VARIABLE SPEED

- High motor torque and ideal speed range for sanding
- Ergonomic design for long work shifts
- Variable speed selection for ideal speed to any material
- Thermal overload protection to prevent overheating
- Supplied with a hand guard, backing pad and 4 m cable



AS 12 E	
Power input (W)	1200
No load speed (rpm)	1800 - 4800
Disc diameter (mm)	180
Spindle size	M 14
Weight (kg)	2.5
Variable speed	Yes
Line lock out function	Yes
Supplied in	-
Article Number	4933383940

Ø125 X 22.2 MM FLAP DISC FOR GRINDING STAINLESS STEEL, BRONZE, TITANIUM & ALUMINIUM

Article Number 4932430408



AP 12 E | 1200 W POLISHER WITH ELECTRONIC VARIABLE SPEED

- 1200 watt motor
- Ergonomic design for long work shifts
- Special gear for high spindle torque and ideal polishing speed
- Variable speed selection for ideal speed
- Thermal overload protection
- No load speed limitation
- 6 m cable



AP 12 E	
Power input (W)	1200
No load speed (rpm)	900 - 2500
Disc diameter (mm)	150
Spindle size	M 14
Weight (kg)	2.2
Variable speed	Yes
Line lock out function	Yes
Supplied in	-
Article Number	4933383925

POLISHING SPONGE HARD. POLISH UP OF WEATHER-BEATEN LACQUER, LACQUER RE-CONDITIONING

Article Number 4932373165



AP 14-2 200 E 1450 W POLISHER

- Powerful 1450 watt motor for high performance polishing
- Premium high torque gear maintains speed under load
- Variable speed selection from 490 - 2100 RPM for all applications
- 7 speed settings for accurate speed selection
- Thermal overload protection to prevent overheating
- Unique "finger grip" for comfortable working position, especially when working with the tool vertically
- Protected spindle lock button ensures against accidental use
- Lock-on function
- Flexible and soft hook and loop backing pad avoids scratches on paint work
- 6 m long PUR cord to prevent marks on the paint work and allows the user to work easily around the complete car



Premium high torque gear



Unique "finger grip" for comfortable working position



7 speed settings for accurate speed selection

	AP 14-2 200 E	AP 14-2 200 E SET
Power input (W)	1450	1450
No load speed (rpm)	490 - 2100	490 - 2100
Disc diameter (mm)	200	200
Spindle size	M 14	M 14
Standard equipment	Side handle, flexible backing pad	Side handle, flexible backing pad, soft & hard polishing sponge, lambswool pad, sanding & finishing compound, cloth
Weight (kg)	2.3	2.3
Variable speed	Yes	Yes
Line lock out function	Yes	Yes
Soft start function	Yes	Yes
Supplied in	-	HD Box
Article Number	4933432800	4933432795

FELT POLISHING DISC. SECOND POLISHING / FINISH OF NEW LACQUER WORK, NON-FERROUS METALS AND STAINLESS STEEL, CAN ALSO BE USED WITH POLISHING PASTE

Article Number 4932373163



DGL 34 | SINGLE HIGH SPEED 2-HANDED DIE GRINDER

- Long spindle for easy access to awkward places
- High rotation precision metal gearbox with double bearing seating of the spindle
- Extra high speed of 34,000 rpm
- Cut-out carbon brushes
- Favourable weight/performance relationship
- Supplied with spanner SW 17 / SW 15, 4 m cable and collet 6 mm



DGL 34	
Power input (W)	500
No load speed (rpm)	34,000
Max. grinding wheel diameter (mm)	40
Max. grinding pin diameter (mm)	25
Collet capacity (mm)	6
Weight (kg)	1.8
Supplied in	-
Article Number	4933385110

DGL 30 E | VARIABLE SPEED 2-HANDED DIE GRINDER

- Long spindle for easy access to awkward places
- Soft start electronic
- Electronic speed control
- Extra high speed of 30,000 rpm
- High rotation precision metal gearbox with double bearing seating of the spindle
- Cut-out carbon brushes
- Supplied with spanner SW 17 / SW 15, 4 m cable and collet 6 mm



DGL 30 E	
Power input (W)	600
No load speed (rpm)	10,000 - 30,000
Max. grinding wheel diameter (mm)	40
Max. grinding pin diameter (mm)	20
Collet capacity (mm)	6
Weight (kg)	1.9
Supplied in	-
Article Number	4933385120

DG 30 E | VARIABLE SPEED SINGLE HANDED DIE GRINDER

- Short compact design for easy handling
- Soft start electronic
- Electronic speed control
- Metal gearbox for precise rotation
- Cut-out carbon brushes
- Ergo switch
- Also suitable for stationary use in drilling stands or on turning systems with gear neck diameter of 43 mm
- Supplied with spanner SW 17 / SW 15, 4 m cable and collet 6 mm



DG 30 E	
Power input (W)	500
No load speed (rpm)	10,000 - 30,000
Max. grinding wheel diameter (mm)	40
Max. grinding pin diameter (mm)	20
Collet capacity (mm)	6
Weight (kg)	1.3
Supplied in	-
Article Number	4933385100

DG 7 E | LOW SPEED DIE GRINDER

- Long spindle for easy access to awkward places
- Electronic speed control
- Reduced speed maximum 7000 rpm for sanding and milling in metal
- Heavy Duty metal gear box
- Supplied with 6 mm collet, spanner SW 17 / SW 15 and 4 m cable



DG 7 E	
Power input (W)	600
No load speed (rpm)	3000 - 7000
Max. grinding wheel diameter (mm)	45
Collet capacity (mm)	6 + 8
Weight (kg)	1.5
Supplied in	-
Article Number	4933391200

MCS 66 | DRY CUT METAL CIRCULAR SAW

- Powerful 1800 watt, 4000 rpm motor
- Dry-cutting technology provides fast, clean and burr-free metal cutting
- Cuts steel, stainless steel, aluminium, insulated foam panel
- Large cutting depth of 66 mm
- Exclusive chip-release shield latch for fast waste disposal and blade changing
- Plunge lever for fast and effective plunge cuts
- Supplied with 42 tooth cermet tipped blade



MCS 66	
Power input (W)	1800
No load speed (rpm)	4000
Blade diameter (mm)	203
Max. cutting depth 90° (mm)	66
Bore size (mm)	15.87
Weight (kg)	6.4
Supplied in	Kitbox
Article Number	4933440615

CIRCULAR SAW BLADE FOR METAL, 50 TOOTH, 1.8 MM CUTTING WIDTH FOR 1 - 2.5 MM MATERIAL THICKNESS

Article Number 48404520



BS 125 DEEP CUT BAND SAW

- Powerful 1100 watt motor provides maximum performance and durability
- Largest cutting capacity up to 125 x 125 mm material diameter
- 4 step variable speed selection from 0 - 116 m/min
- Constant power technology maintains cut speed in the toughest applications for optimal performance
- Gear protecting clutch extends gear and motor life by absorbing high impact forces caused by blade lock-ups
- Slim full metal motor housing design and LED work surface illumination for best cut visibility
- Tool-free blade locking mechanism for quick and easy saw blade changes
- Tool-free adjustable shoe



Largest cutting capacity up to 125 x 125 mm material diameter



4 step variable speed selection



Tool-free blade locking mechanism

BS 125	
Power input (W)	1100
No load speed (m/min)	0 - 116
Cutting capacity rect. stock (mm)	125 x 125
Max. cutting capacity metal pipe Ø (mm)	125
Blade length (mm)	1139.83
Weight (kg)	6.5
Supplied in	Kitbox
Article Number	4933448245

BAND SAW BLADE FOR CORDED BANDSAW WITH 1139.83 MM LENGTH (3 PCS)

Article Number 48390521



CHS 355 | 2300 W CHOPSAW

- 2300 watt motor with 3800 rpm for excellent cutting performance
- Lock pin function keeps the saw closed position during transportation (no chain required)
- Quick release vice adjustment for fast angle adjustment from -45° to +45°
- Quick release mitre clamp for fast work piece change
- Spindle lock for fast and easy disc change
- Easy brush change due to external brush doors
- Integrated metal fan for best durability and long life
- Stamped steel base with additional ribs to prevent deforming



	CHS 355
Power input (W)	2300
No load speed (rpm)	3800
Wheel size (mm)	355
Cutting capacity round profile 90° and 45° (mm)	125 / 100
Cutting cap. square profile 90° and 45° (mm)	115 / 80
Cutting capacity rectangle 90° and 45° (mm)	230 x 70 / 100 x 80
Cutting cap. L-shape profile 90° and 45° (mm)	130 / 80
Bore size (mm)	25.4
Weight (kg)	18
Supplied in	-
Article Number	4933411760

METAL CUTTING DISC (10 PCS), Ø 355 MM, Ø 25.4 MM BORE SIZE, 2.5 MM THICKNESS

Article Number 4932451505



HDE 6 RQ | 725 W SINGLE HIGH SPEED ROTARY DRILL

- Compact and powerful 725 W motor
- Metal gearbox for exact seating of bearings and gears
- Keyed chuck 1.5 - 10 mm
- Ergonomic design with soft grip
- Reverse operation
- 4 m QUIK-LOK cable



	HDE 6 RQ
Power input (W)	725
No load speed (rpm)	0 - 4000
Max. drilling steel (mm)	6
Max. drilling wood (mm)	16
Max. static stalling torque (Nm)	30
Chuck capacity (mm)	10
Tool reception	1/2" x 20
Weight (kg)	1.4
Supplied in	-
Article Number	010150

RED COBALT - HSS GROUND - DIN 338 DRILL BIT SET (19 PCS)

Article Number 4932352470



DE 10 RX | 630 W SINGLE HIGH SPEED ROTARY DRILL

- Compact and powerful 630 W motor
- Electronics: variable preselection of speed for optimum drilling
- Integrated metal block technology for highest durability and stability
- Planetary gearbox for low speed and high torque applications
- Metal FIXTEC chuck (1.0 - 10 mm)
- Reversible action
- Easy access and exchange of carbon brushes by removing soft grip
- 4 m cable



	DE 10 RX
Power input (W)	630
No load speed (rpm)	0 - 2700
Max. drilling steel (mm)	10
Max. drilling wood (mm)	30
Max. static stalling torque (Nm)	21
Chuck capacity (mm)	10
Tool reception	1/2" x 20
Weight (kg)	1.6
Supplied in	-
Article Number	4933409211

MDE 42 | MAGNETIC DRILLING PRESS

- Lightweight, portable and powerful magnetic drill stand
- 1200 watts of motor power transmitted through three reduction gears provide the power to drill a massive 42 mm hole through 50 mm thick steel
- High magnet power and the latest developments in electronics provide the control and comply to all safety demands
- Electronic switch panel for easy operation
- Supplied with an adjustable safety guard, cutting oil and hex keys



	MDE 42
Power input (W)	1200
No load speed (rpm)	300 - 640
Full load speed (rpm)	170 - 330
Max. diameter broaching capacity (mm)	42
Max. depth broaching capacity (mm)	50
Max. drilling solid bit (mm)	16
Max. static stalling torque (Nm)	85
Magn. holding power (at drill point pressure) (N)	10,000
Weight (kg)	11.5
Supplied in	Kitbox
Article Number	4933380832

6 PC HSS ANNULAR CUTTER SET 19 MM WELDON RECEPTION AND EJECTOR PIN SHORT SERIES - 30 MM

Article Number 4932372533



MDE 41 | MAGNETIC DRILLING PRESS WITH ELECTRO MAGNET

- 1200 Watt powerful motor with optimised drilling speed
- 2 speed gear box for optimised drilling speed with 475 and 730 RPM's when using annual cutters or twist drill bits
- AUTOSTOP™ lift-off detection: Detects excess rotation and automatically cuts power to the drill for best user protection
- Electro powered magnet with 9930 N of holding force
- Maximum drilling capacity of 41 mm with use of annual cutters and 13 mm straight shank twist drill bits
- Keyless 19 mm Weldon reception for fast and easy accessory change
- 146 mm stroke length for usage of different accessories
- Tool-free detachable handle for right or left hand usage
- On board LED light to illuminate the work surface



AUTOSTOP

	MDE 41
Power input (W)	1200
No load speed (rpm)	475 / 730
Max. diameter broaching capacity (mm)	41
Max. depth broaching capacity (mm)	50
Max. drilling solid bit (mm)	13
Magn. holding power (at drill point pressure) (N)	9930
Weight (kg)	13.5
Supplied in	Kitbox
Article Number	4933451015

MDP 41 | MAGNETIC DRILLING PRESS WITH PERMANENT MAGNET

- 1200 Watt powerful motor with optimised drilling speed
- 2 speed gear box for optimised drilling speed with 475 and 730 RPM's when using annual cutters or twist drill bits
- AUTOSTOP™ lift-off detection: Detects excess rotation and automatically cuts power to the drill for best user protection
- Self-powered permanent magnet with 8890 N of holding force prevent accidental magnet deactivation for improved user protection and easy alignment
- Maximum drilling capacity of 41 mm with use of annual cutters and 13 mm straight shank twist drill bits
- Keyless 19 mm Weldon reception for fast and easy accessory change
- 146 mm stroke length for usage of different accessories
- Tool-free detachable handle for right or left hand usage
- On board LED light to illuminate the work surface



AUTOSTOP

	MDP 41
Power input (W)	1200
No load speed (rpm)	475 / 730
Max. diameter broaching capacity (mm)	41
Max. depth broaching capacity (mm)	50
Max. drilling solid bit (mm)	13
Magn. holding power (at drill point pressure) (N)	8890
Weight (kg)	14.0
Supplied in	Kitbox
Article Number	4933451014

WOODWORKING



SSPE 1500 X 1500 W SUPER SAWZALL®

- 1500 W Milwaukee® motor - highest overload protection in the industry; prevents motor burn up/failure
- Constant power technology - maintains constant speed under load for unmatched cutting performance
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups
- FIXTEC blade clamp system - provides fast and easy blade changes
- Patented AVS Anti-Vibration-System ensures unsurpassed low-vibration running at 12.5 m/s²
- Variable speed trigger and dial speed control - maximum speed control
- Adjustable shoe for optimised use of saw blades
- Supplied with a SAWZALL® blade, additional keyed blade clamp and 4 m cable



FIXTEC blade clamp system & adjustable shoe



Counter balance mechanism ensures low vibrations - 12.5 m/s²



Orbital action

SSPE 1500 X	
Power input (W)	1500
No load stroke rate (spm)	0 - 2800
Stroke length (mm)	32
Weight (kg)	4.5
Supplied in	Kitbox
Article Number	4933428900

AX CARBIDE DEMOLITION BLADE, 230 MM BLADE LENGTH, 5 MM TOOTH PITCH, 5 MM TEETH PER INCH

Article Number **48005226**



SSPE 1300 RX | 1300 W SAWZALL® WITH ROTATING HANDLE

- High cutting performance due to powerful 1300 watt motor combined with a 32 mm saw stroke
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups
- 360° rotating handle for optimal user comfort
- FIXTEC blade clamp system - provides fast and easy blade changes
- Patented AVS Anti-Vibration-System ensures unsurpassed low-vibration running at 12.5 m/s²
- Variable speed trigger and dial speed control - maximum speed control
- Adjustable shoe for optimised use of saw blades
- Supplied with a SAWZALL® blade and 4 m cable



SSPE 1300 RX	
Power input (W)	1300
No load stroke rate (spm)	0 - 3000
Stroke length (mm)	32
Weight (kg)	4.2
Supplied in	Kitbox
Article Number	4933440590

AX CARBIDE DEMOLITION BLADE, 230 MM BLADE LENGTH, 5 MM TOOTH PITCH, 5 MM TEETH PER INCH

Article Number **48005226**



SSPE 1300 SX | 1300 W SAWZALL®

- High cutting performance due to powerful 1300 watt motor combined with a 32 mm saw stroke
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups
- FIXTEC blade reception as well as change kit to keyed blade change
- Patented AVS Anti-Vibration-System ensures unsurpassed low-vibration running at 14.5 m/s²
- Variable speed trigger and dial speed control - maximum speed control
- Adjustable shoe for optimised use of saw blades
- Supplied with a SAWZALL® blade, additional keyed blade clamp and 4 m cable



SSPE 1300 SX	
Power input (W)	1300
No load stroke rate (spm)	0 - 2800
Stroke length (mm)	32
Weight (kg)	3.9
Supplied in	Kitbox
Article Number	4933428520

SAWZALL® BLADE SET

Article Number **49222229**



SSD 1100 X | 1100 W SAWZALL®

- High cutting performance due to powerful 1100 watt motor combined with a 28 mm saw stroke
- FIXTEC blade clamp for fast and easy blade changes without any key
- Water & finger protection nose for safer work and better rust protection
- Variable speed trigger switch
- Durable long lasting slider mechanism
- Supplied with a SAWZALL® blade and 4 m cable



SSD 1100 X	
Power input (W)	1100
No load stroke rate (spm)	0 - 2900
Stroke length (mm)	28
Weight (kg)	3.2
Supplied in	Kitbox
Article Number	4933416710

SAWZALL® BLADE SET

Article Number **49222229**



FSPE 110 X | HEAVY DUTY BODY GRIP JIGSAW

- Very slim motor housing for easy grip in any application and excellent view on the cutting line
- Powerful 710 W motor
- Precision blade guidance for precise cuts
- Patented FIXTEC system for fast keyless blade change and bevel adjustment with snap-in at 0° and 45°
- Electronic with variable speed pre-selection, soft start and constant speed under load
- Four-stage pendulum action adjustment for even more powerful cutting performance and longer saw blade life
- Adjustable chipping blower to the front and rear
- Low vibration and smooth operation due to anti-vibration technology
- Supplied with 5 saw blades, anti-splintering device, dust cap, absorption adaptor, sliding shoe and 4 m cable



FSPE 110 X	
Power input (W)	710
No load stroke rate (spm)	500 - 3000
Max. cutting capacity wood (mm)	120
Max. cutting capacity steel (mm)	10
Max. cutting capacity aluminium (mm)	30
Mitre capacity (°)	45
Stroke length (mm)	26
Weight (kg)	2.5
Supplied in	Kitbox
Article Number	4933357990

75 X 2.5 MM T 101 B JIGSAW BLADE, 5 PCS

Article Number **4932254061**



JSPE 135 | HEAVY DUTY TOP HANDLE JIGSAW


- Robust and powerful top handle jig saw for fast cutting action in wood, aluminium, steel or ceramics
- Powerful 750 W motor
- Precision blade guidance for precise cuts
- Patented FIXTEC system for fast keyless blade change and bevel adjustment with snap-in at 0° and 45°
- Electronic with variable speed preselection, soft start and constant speed under load
- Four-stage pendulum action adjustment for even more powerful cutting performance and longer saw blade life
- Adjustable chipping blower to the front and the rear
- LED light for illumination of cutting area
- Supplied with 5 saw blades, anti-splintering device, dust cap, absorption adaptor, sliding shoe and 4 m cable



JSPE 135 TX	
Power input (W)	750
No load stroke rate (spm)	800 - 3000
Max. cutting capacity wood (mm)	135
Max. cutting capacity steel (mm)	10
Max. cutting capacity aluminium (mm)	30
Mitre capacity (°)	45
Stroke length (mm)	26
Weight (kg)	2.5
Supplied in	Kitbox
Article Number	4933381230

75 X 2.5 MM T 101 B JIGSAW BLADE, 5 PCS

Article Number	4932254061
----------------	------------



JS 120 X | HEAVY DUTY BODY GRIP JIGSAW


- Slim, streamlined motor housing design and optimised weight for easy handling
- Powerful 710 W motor
- Patented FIXTEC system for fast keyless blade change and bevel adjustment with snap-in at 0° and 45°
- Digital electronics with variable speed preselection, soft start and constant speed under load
- 4 stage pendulum action for increased performance
- Excellent visibility of saw blade and cutting area
- Integrated-Metal-Block technology - robust metal casing for bearings, gears and base plate for maximum durability and stability
- Anti-vibration mechanism for lowest possible vibration
- Integrated dust extraction
- Supplied with 5 saw blades, anti-splintering device, dust cap, sliding shoe and 4 m cable



JS 120 X	
Power input (W)	710
No load stroke rate (spm)	500 - 2800
Max. cutting capacity wood (mm)	120
Max. cutting capacity steel (mm)	10
Max. cutting capacity aluminium (mm)	30
Mitre capacity (°)	45
Stroke length (mm)	26
Weight (kg)	2.3
Supplied in	Kitbox
Article Number	4933381680

75 X 2.5 MM T 101 B JIGSAW BLADE, 5 PCS

Article Number	4932254061
----------------	------------



CS 85 SB | 235 MM CIRCULAR SAW (85 MM DOC)

- 2200 Watt motor allows smooth cutting at full depth of cut
- Soft start minimises the tripping of circuit breakers
- Dust extraction DEK26 compatible
- Integrated cable hatch, the cable can be replaced easily without the need to dismantle the whole saw
- Aluminium stamped base for strength and durability
- Spindle lock for easy and quick blade change



CS 85 SB	
Power input (W)	2200
No load speed (rpm)	4500
Blade diameter (mm)	235
Bevel capacity (°)	50
Max. cutting depth 45° (mm)	67
Max. cutting depth 90° (mm)	85
Bore size (mm)	30
Weight (kg)	6.6
Supplied in	-
Article Number	4933451117

235 X 30 MM 40 TOOTH BLADE WITH 1.6 MM CUTTING WIDTH

Article Number	4932451726
----------------	------------



CS 85 CBE | 235 MM CIRCULAR SAW (85 MM DOC)

- 2200 Watt motor allows smooth cutting at full depth of cut
- 60° bevel capacity gives the saw the ability to achieve a wide range of roofing cuts
- Sprung loaded riving knife allows the saw to be plunged into the material without the removal of the riving knife
- Guide rail compatible, the saw can be used in conjunction with a guide rail
- Soft start minimises the tripping of circuit breakers
- Brake stops the saw in 3.5 seconds
- Double fence is anchored at the front and the back of the saw allowing for greater accuracy
- Dust extraction DEK26 compatible
- Integrated cable hatch, the cable can be replaced easily without the need to dismantle the whole saw



60° bevel capacity



Sprung loaded riving knife




Double fence is anchored at the front and the back of the saw

CS 85 CBE	
Power input (W)	2200
No load speed (rpm)	4500
Blade diameter (mm)	235
Bevel capacity (°)	60
Max. cutting depth 45° (mm)	67
Max. cutting depth 90° (mm)	85
Bore size (mm)	30
Weight (kg)	7.7
Supplied in	Kitbox
Article Number	4933451116

235 X 30 MM 24 TOOTH BLADE WITH 2.4 MM CUTTING WIDTH

Article Number	4932451725
----------------	------------



SCS 65 Q | 190 MM CIRCULAR SAW (65 MM DOC)

- 1900 watt motor with large power reserves
- Unrivaled balance and comfort due to the adjustable "TILT-LOK" handle with soft grip
- Large cutting capacity of 65 mm
- Ideally positioned levers for depth and bevel cut adjustments
- Good visibility of blade at the cutting edge for improved control
- Robust aluminium base plate
- Supplied with a carbide tipped 20 tooth saw blade, parallel guide and 4 m QUIK-LOK cable



SCS 65 Q	
Power input (W)	1900
No load speed (rpm)	5800
Blade diameter (mm)	190
Max. cutting depth 45° (mm)	52
Max. cutting depth 90° (mm)	65
Bore size (mm)	30
Weight (kg)	5.5
Supplied in	Kitbox
Article Number	638051

190 X 30 MM 24 TOOTH BLADE WITH 2.4 MM CUTTING WIDTH

Article Number	4932327969
----------------	------------



CS 60 | 184 MM CIRCULAR SAW (61 MM DOC)

- 1600 W powerful motor with 5800 rpm for fast cutting through tough materials
- Large cutting capacity of 61 mm
- 0 - 56° bevel capacity and 45° positive stop
- Quick release locking lever design for fast bevel adjustments
- Integrated dust blower keeps cut line clear
- Large, ergonomic handles and levers for improved ergonomics and control
- Long side fence for straight cuts and precise guidance
- Supplied with a carbide tipped 24 tooth saw blade, parallel guide and 4 m cable



CS 60	
Max. cutting depth 45° (mm)	49
Bore size (mm)	30
Weight (kg)	4.8
Article Number	4933419225

184 X 30 MM 24 TOOTH BLADE WITH 1.8 MM CUTTING WIDTH

Article Number 4932352327



BS 100 LE | 4" (100 MM) BELT SANDER

- Compact design, ideal for sanding close to edges
- Sanding surface 100 x 160 mm, for fast smooth sanding
- Variable preselection of belt speed for versatile use
- Control wheel for precise adjustment of belt alignment
- Integrated dust extraction and dust bag for dust free work and less sanding belt wear
- Easy changing of sanding belt
- Stationary work possible
- Supplied with 100 x 620 mm sanding belt (grit 100) and 4 m cable



BS 100 LE	
Power input (W)	1150
Belt speed (rpm)	230 - 400
Belt length (mm)	620
Belt width (mm)	100
Sanding surface (mm)	100 x 160
Weight (kg)	5.3
Supplied in	-
Article Number	4933385150

SANDING BELT - 5 PCS, 100 X 610 MM, 60 GRIT

Article Number 4932355067



ROS 150 E-2 | 6" (150 MM) RANDOM ORBIT SANDER

- Random orbital sander with unmatched sanding properties through simultaneous rotation and oscillation of sanding disc
- Reduction gear makes full, efficient use of the powerful 440 W motor
- 6.4 / 3.2 mm orbits for fast removal & finishing
- Variable speed (4000-10,000 rpm) - especially needed for heat-sensitive materials
- Fast and easy change of sandpaper with hook and loop system
- Removable dustbag and also fits standard 26 mm vacuum hose
- Through body sealed slide switch
- Additional handle for a balanced and even weight distribution over the work piece
- Supplied with a dust bag, sanding disc and 4 m cable



ROS 150 E-2	
Power input (W)	440
No load speed (rpm)	4000 - 10,000
Oscillation diameter (mm)	6.4 / 3.2
Sanding pad size (mm)	150
Weight (kg)	2.8
Supplied in	-
Article Number	4933431170

Ø 150 MM, 60 GRIT ABRASIVE DISC - 5 PCS, HOOK AND LOOP

Article Number 4932371591



ROS 125 E | 5" (125 MM) RANDOM ORBIT SANDER

- Ideal for sanding of wood, metal and plastics within confined spaces
- 300 Watt powerful motor with 2.4 mm orbital action
- Variable speed (7000-12,000 rpm) - especially needed for heat-sensitive materials
- Hook & Loop paper fitment
- Excellent dust extraction - 90% dust collection efficiency with larger dust bag
- Easy to clean dust bag
- On board vac adaptor- fits standard 36 mm vacuum hoses
- Supplied with textile dust bag and sanding paper set (60, 80, 120 grit)



ROS 125 E	
Power input (W)	300
No load speed (rpm)	7000 - 12,000
Oscillation rate (opm)	14,000 - 26,000
Oscillation diameter (mm)	2.4
Sanding pad size (mm)	125
Weight (kg)	1.7
Supplied in	Tool bag
Article Number	4933433180

Ø 125 MM, 60 GRIT ABRASIVE DISC - 5 PCS, HOOK AND LOOP

Article Number 4932367741



SPS 140 | 1/4" SHEET SANDER

- Powerful 260 W motor for sustained use
- 1.6 mm oscillation movement allows for fine sanding
- Quick connection to dust extractor or dust bag
- Sanding paper is attached by hook and loop or by a clamping system
- 4 m of durable rubber cable allows the user to move easily around his work piece



SPS 140	
Power input (W)	260
No load speed (rpm)	14,700
Oscillation rate (opm)	28,000
Oscillation diameter (mm)	1.6
Sanding pad size (mm)	113 x 105
Weight (kg)	1.6
Supplied in	-
Article Number	4933447015

TSS 1000 | TABLE SAW STAND

- Light weight of only 6.6 kg - easy to transport onto the job site
- Will hold up to 82 kg
- Quick release bracket to hold the saw firmly in place
- One point leg adjustment for leveling on uneven ground
- Comfortable work height at 559 mm
- To be used with M18 FTS210 FUEL™ ONE-KEY™ table saw



TSS 1000	
Height (mm)	559
Bearing force (kg)	82
Weight (kg)	6.6
Supplied in	-
Article Number	4933464227

AS 42 MAC

42 L M-CLASS DUST EXTRACTOR

- o Compact 42 litre tank for site/workshop use
- o 4500 litres/min airflow with 250 mbar suction
- o Dust class M. Standard MAK-factor > 0.1 mg/m³: mineral dust, wood dust (oak, beech)
- o Power take off for auto switching of powertools
- o Durable PTFE filter with high filtration efficiency and washable non-stick membrane
- o Automatic filter cleaning with minimised performance loss
- o Airflow and filter monitoring with visual LED and acoustic warning signal
- o Easy access filter hatch for convenient servicing and cleaning
- o Super silent turbine for low noise
- o Anti-static hose to prevent shocks caused by static build up
- o Trolley handle for convenient transportation onto the job site
- o Supplied with 2 x tool adaptor, hand tube, 2 x extension tube, floor / crevice nozzle, fleece filter bag, disposal bag, hose 4 m x 38 mm



AS 42 MAC	
Power input (W)	1200
Air volume (l/min)	4500
Filter type	PTFE
Max. vacuum (mbar)	250
Capacity (l)	42
Hose diameter (mm)	38
Hose length (m)	4
Weight (kg)	17.5
Supplied in	-
Article Number	4933459418



Durable PTFE filter



Power take off for auto switching of powertools



Trolley handle for convenient transportation onto the job site

AS 30 MAC | 30 L M-CLASS DUST EXTRACTOR

- o Compact 30 litre tank for site/workshop use
- o 4500 litres/min airflow with 250 mbar suction
- o Dust class M. Standard MAK-factor > 0.1 mg/m³: mineral dust, wood dust (oak, beech)
- o Power take off for auto switching of powertools
- o Durable PTFE filter with high filtration efficiency and washable non-stick membrane
- o Automatic filter cleaning with minimised performance loss
- o Airflow and filter monitoring with visual LED and acoustic warning signal
- o Easy access filter hatch for convenient servicing and cleaning
- o Super silent turbine for low noise
- o Anti-static hose to prevent shocks caused by static build up
- o Supplied with 2 x tool adaptor, hand tube, 2 x extension tube, floor / crevice nozzle, fleece filter bag, disposal bag, hose 4 m x 38 mm



AS 30 MAC	
Power input (W)	1200
Air volume (l/min)	4500
Filter type	PTFE
Max. vacuum (mbar)	250
Capacity (l)	30
Hose diameter (mm)	38
Hose length (m)	4
Weight (kg)	14.5
Supplied in	-
Article Number	4933459415

AS 30 LAC | 30 L L-CLASS DUST EXTRACTOR

- o Compact 30 litre tank for site/workshop use
- o 4500 litres/min airflow with 250 mbar suction
- o Dust class L. Standard MAK-factor > 1 mg/m³
- o Power take off for auto switching of powertools
- o Durable PTFE filter with high filtration efficiency and washable non-stick membrane
- o Automatic filter cleaning with minimised performance loss
- o Easy access filter hatch for convenient servicing and cleaning
- o Super silent turbine for low noise
- o Anti-static hose to prevent shocks caused by static build up
- o Supplied with 2 x tool adaptor, hand tube, 2 x extension tube, floor / crevice nozzle, fleece filter bag, disposal bag, hose 4 m x 36 mm



AS 30 LAC	
Power input (W)	1200
Air volume (l/min)	4500
Filter type	PTFE
Max. vacuum (mbar)	250
Capacity (l)	30
Hose diameter (mm)	36
Hose length (m)	4
Weight (kg)	14.5
Supplied in	-
Article Number	4933459411

AS 2-250 ELCP | 25 L L-CLASS DUST EXTRACTOR

- o Large 25 litre tank capacity ideal for workshop use
- o 1250 W motor power with over 210 mbar suction - 10% more efficient
- o Power take off with auto switching for powertools
- o 2600W power take off capacity allows for use with high wattage tools
- o Clear press filter cleaning system maintains suction efficiency
- o Washable PET filter provides longer filter life
- o Dust class L Standard MAK-factor > 1 mg/m³
- o Wet and dry capability
- o Hose and cable storage enables easy transportation
- o Dust blower function
- o 7.5 m rubber cable
- o Supplied with 3.5 m hose with floor cleaning kit, PET filter, 2x powertool connection adaptor, 1x disposable bag, 1x fleece bag & 1x crevice nozzle



AS 2-250 ELCP	
Power input (W)	1250
Air volume (l/min)	3600
Max. vacuum (mbar)	210
Capacity (l)	25
Hose diameter (mm)	32
Weight (kg)	10.4
Supplied in	-
Article Number	4933447480

MS 304 DB 12" (305 MM) DUAL BEVEL SLIDING MITRE SAW

- 1800 Watt direct drive motor ensures a quick, clean cut even in hardwood materials
- Dual integral jobsite lights illuminate the cut line
- Integral dust channel captures 75 % of all dust by capturing dust near the cut on both sides of the blade and directing it to the back of the saw
- Unique inline motor design - for excellent visibility from both sides to the work piece and better balanced transport
- Mitre capacity 55° to the left and 60° to the right - for maximum versatility. Mitre detents L & R at: 0°, 15°, 22.5°, 31.6°, 45°, 60°
- Dual-bevel design - to incline the saw head left and right 0° - 48° with bevel detents L & R at: 0°, 22.5°, 33,85°, 45°, 48°
- Fast and accurate bevel adjustment
- Supplied with Work piece clamp, saw blade (60 teeth), vacuum adaptor Ø35 / 58 mm, wrench and 3 m cable



MS 304 DB	
Power input (W)	1800
No load speed (rpm)	3900
Blade diameter (mm)	305
Bevel capacity left (°)	48
Bevel capacity right (°)	48
Mitre capacity left (°)	55
Mitre capacity right (°)	60
Max. cutting capacity 45° mitre/ 45° bevel (mm)	57 x 241
Max. cutting capacity 45° mitre/ 90° bevel (mm)	102 x 241
Max. cutting capacity 90° mitre/ 45° bevel (mm)	57 x 342
Max. cutting capacity 90° mitre/ 90° bevel (mm)	102 x 342
Weight (kg)	29.5
Supplied in	-
Article Number	4933471052

60 TOOTH BLADE WITH 3.2 MM CUTTING WIDTH FOR CUTTING SOLID WOOD, CHIPBOARD, MDF/FIBREBOARD, LAMINATED CHIPBOARD, BLOCK BOARD, PLYWOOD & OSB BOARDS. 305 X 30 MM



Article Number **4932352141**



Dual-bevel design



Micro mitre adjustment for accurate mitre cuts



Rebate stop

MS 216 SB	
Power input (W)	1800
No load speed (rpm)	6000
Blade diameter (mm)	216
Bevel capacity left (°)	48
Bevel capacity right (°)	-2
Mitre capacity left (°)	50
Mitre capacity right (°)	50
Max. cutting capacity 45° mitre/ 45° bevel (mm)	190 x 48
Max. cutting capacity 45° mitre/ 90° bevel (mm)	190 x 60
Max. cutting capacity 90° mitre/ 45° bevel (mm)	270 x 48
Max. cutting capacity 90° mitre/ 90° bevel (mm)	270 x 60
Bore size (mm)	30
Weight (kg)	14.5
Supplied in	-
Article Number	4933471055

MS 216 | 8 1/2" (216 MM) SLIDING MITRE SAW

- 1800 Watt motor for high performance cutting in hard timber
- Durability - dual vertical steel rails with linear bearings deliver smooth sliding action
- Rail lock - the saw head locks in the back position automatically
- Adjustable laser - for perfect and quick alignment to cut line
- Steel detent plate with preset angles - gives repeatable accurate cuts
- Lock lever/handle over mold - allows the user to make repeated cuts comfortably and without fatigue
- Mitre release system - for quick and smooth change of cutting orientation
- Integral LED jobsite light
- Spindle lock - for quick and easy blade change
- Heavy duty cast base and fence ensures durability and accuracy
- 48°/-2° bevel capacity
- Supplied with saw blade (48 teeth), blade spanner and work clamp



MSL 1000 | MITRE SAW STAND EXTENDABLE UP TO 2 M

- Light weight aluminium, easy to transport onto the job site
- 1.08 m total length, will fit into most small vans and cars
- Extendable each side - 2.08 m extended
- Will hold up to 180 kg
- One point leg adjustment for leveling on uneven ground
- Quick release brackets
- Height adjustable length stops
- Compact foldable design



MSL 1000	
Height (mm)	850
Base size (mm)	1065
Extendable up to (mm)	2125
Collapsed size (mm)	1065
Bearing force (kg)	180
Weight (kg)	17.0
Supplied in	-
Article Number	4933428970

MSL 2000 | MITRE SAW STAND EXTENDABLE UP TO 2.5 M

- Light weight aluminium, easy to transport onto the job site
- 1.09 m total length, will fit into most small vans and cars
- Extendable each side - 2.54 m extended
- Will hold up to 227 kg
- One point leg adjustment for leveling on uneven ground
- Quick release brackets
- Height adjustable length stops
- Compact foldable design with quick release latches



MSL 2000	
Height (mm)	860
Base size (mm)	1093
Extendable up to (mm)	2542
Collapsed size (mm)	1093
Bearing force (kg)	227
Weight (kg)	14.0
Supplied in	-
Article Number	4933459617

WORK TABLE FOR MSL 2000

Article Number **4932459713**



MSL 3000 | MITRE SAW STAND EXTENDABLE UP TO 3 M

- Lightweight construction and wheel set - provides portability on the jobsite
- Folds down to 1200 mm - thanks to the collapsible legs and compact design
- Extendable up to 3 m - makes it easy to cut large workpieces to length
- Heavy Duty - carries up to 250 kg
- One point leg adjustment for leveling on uneven ground
- Comfortable working height at 81 cm
- Fully adjustable work piece rests - provide support for long lengths of material - single knob adjustment
- Quick to assemble - set up within seconds
- Roller supports - for effective material support



MSL 3000	
Height (mm)	810
Base size (mm)	1100
Extendable up to (mm)	3000
Collapsed size (mm)	1200
Bearing force (kg)	250
Weight (kg)	23.0
Supplied in	-
Article Number	4933411565

HANDTOOLS



LEVELS

	Magnetic	Length (cm)	Handles	Article Number	
REDSTICK™ BACKBONE™ box levels	Yes	40	0	4932459061	
		60	0	4932459063	
		80	1	4932459065	
		100	0	4932459067	
		120	2	4932459069	
		180	2	4932459071	
		200	2	4932459073	
		240	2	4932459075	
	No	40	0	4932459060	
		60	0	4932459062	
		80	1	4932459064	
		100	0	4932459066	
		120	2	4932459068	
		180	2	4932459070	
200		2	4932459072		
240		2	4932459074		
REDSTICK™ compact box levels	Yes	40	0	4932459079	
		60	0	4932459081	
		80	0	4932459083	
		100	0	4932459085	
		120	0	4932459087	
		180	0	4932459089	
	No	40	0	4932459078	
		60	0	4932459080	
		80	0	4932459082	
		100	0	4932459084	
		120	0	4932459086	
		180	0	4932459088	

LEVELS

	Magnetic	Length (cm)	Handles	Article Number	
REDSTICK™ concrete levels	No	60	0	4932459893	
		120	0	4932459894	
		180	0	4932459895	
Slim box levels	No	40	0	4932459090	
		60	0	4932459091	
		80	0	4932459092	
		100	0	4932459093	
		120	0	4932459094	
		180	0	4932459095	
	Yes	40	0	4932464854	
		60	0	4932464855	
		100	0	4932464856	
		180	0	4932464857	
REDCAST die-cast level 60 cm	No	60	0	4932459098	
REDCAST die-cast level 80 cm	No	80	0	4932459099	
Block torpedo level	Yes	25	0	4932459096	
Billet torpedo level	Yes	17	0	4932459097	
Minibox level	No	10	0	4932459100	
Pocket level	Yes	7.8	0	4932459597	

INKZALL™ MARKERS



			Colour	Article Number
1.	INKZALL™ marker	Acrylic nib ideal for rough surfaces such as OSB and concrete.	Black	48223100
2.	Chisel point marker		Black	48223103
3.	INKZALL™ colour markers		Blue, red, green and black	48223106
4.	INKZALL™ marker		Red	48223170
5.	INKZALL™ marker with stylus	For use with gloves on iPads, iPhones, tablets, and touch phones.	Black	48223101
6.	INKZALL™ liquid paint marker - yellow	Durable acrylic nib for the most demanding environmental conditions: surface temperature from -10° up to + 145°.	Yellow	48223721
7.	INKZALL™ liquid paint marker - white		White	48223711
8.	INKZALL™ liquid paint marker - black		Black	48223731
9.	INKZALL™ highlighter - yellow		Yellow	48223201
10.	INKZALL™ highlighter - coloured	Durable tip stays sharp longer.	Yellow, pink, orange, green and blue	48223206
11.	INKZALL™ fine tip markers		Black	48223154
12.	INKZALL™ fine tip pens (4pc) - black		Black	48223164
13.	INKZALL™ fine tip pens (4pc) - coloured	Main applications: marking of labels for electrical wires, adding comments to architect plans.	Black, red and blue	48223165

TAPE MEASURES

		Length (m)	Blade width (mm)	Article Number	
Premium magnetic tape measures	Strong magnet at start of the tape allows easy hooking onto flat surfaces and round pipe.	5	27	48227305	
		8	27	48227308	
		10	27	48227310	
		5 / 16'	27	48227216	
		8 / 26'	27	48227225	
		10 / 33'	27	48227233	
Tape measures pro compact	Jobsite durability.	3	16	4932459591	
		5	19	4932459592	
		5	25	4932459593	
		8	25	4932459594	
		5 / 16'	25	4932459595	
		8 / 26'	25	4932459596	
Tape measures slimline	Flat base for horizontal stability and back rest for easy vertical measuring.	3	16	48227703	
		5	19	48227705	
		5	25	48227706	
		8	25	48227708	
		5/16'	25	48227717	
		8/26'	25	48227726	
Tape measure Autolock	Autolock break: tape automatically locks in place as blade is pulled out.	5	25	4932464663	
		8	25	4932464664	
		5	25	4932464665	
		8	25	4932464666	
Tape measure STUD™	EXO 360™ blade technology delivers long lasting, rip and wear resistance.	5	27	48229905	
		7.5	27	48229908	
		5 / 16"	27	48229917	
		7.5 / 25"	27	48229926	
Tape measure with LED Light	19 LUX LED Light: helps finding measured spot.	3	12	48226602	
Tape measure - 2 m / 6 ft	Compact design and overmould gripping area for extra comfort and durability.	2	13	48225502	

LONG TAPES

		Length (m)	Blade width (mm)	Article Number	
Long open tape combi 30m/100ft	<ul style="list-style-type: none"> Steel blade design with nylon clad (extra thick nylon coating) for increased durability. Best in class stretch performance: up to 50% less stretch vs. fibreglass tapes. Ultra durable design: reinforced metal handle and drop durability. 3:1 clutched planetary gearing for 10x longer gear durability and smooth rewind. GRIME GUARD: debris wiper keeps blade clean and clear of abrasive material. Class II accuracy. 2 sided scale printing. Metric measurements shown on the top side and imperial (inches and feet) on the underside of the blade. 	30	13	48225203	
Long open tape combi 100m/330ft		100	9.5	48225211	
Long closed tape 30m	<ul style="list-style-type: none"> Single sided 30 m metric tape with 9.5 mm blade width. GRIME GUARD: debris wiper keeps blade clean and clear of abrasive material. Ultra durable design: reinforced metal frame housing, reinforced handle and steel blade with nylon coating. 3:1 clutched planetary gearing for 10x longer gear durability and smooth rewind. Class II accuracy 	30	9.5	48225103	
Fibreglass long tape combi 30m/100ft	<ul style="list-style-type: none"> Fibreglass blade ensures a low tape weight. 3:1 clutched planetary gearing for 10x longer gear durability and smooth rewind. GRIME GUARD: debris wiper keeps blade clean and clear of abrasive material. 2 sided scale printing. Metric measurements shown on the top side and imperial (inches and feet) on the underside of the blade. 	30	13	48225330	
Fibreglass long tape combi 60m/200ft		60	13	48225360	

FOLDING RULES

	Length (m)	Blade width (mm)	Accuracy	Links	Hinge	Article Number	
Composite folding rule	2	15 x 3.20	Class 2	10	Plastic and stainless steel	4932459301	
Wood folding rule	2	16 x 3.20	Class 3	10	Brass	4932459302	
Slim wood folding rule	2	16 x 2.70	Class 3	10	Brass	4932459303	

KNIVES



		Article Number
1.	FASTBACK™ folding knife	48221990
2.	Hardline™ folding knife smooth	48221994
3.	Hardline™ folding knife serrated	48221998
4.	FASTBACK™ flip utility knife with blade storage	48221903
5.	FASTBACK™ compact flip utility knife	48221906
6.	Sliding utility knife	48229910
7.	Self-retracting safety knife	48221915
8.	Safety cutter	48221916
9.	Snap knife 9 mm	48221960
10.	Snap knife 18 mm	48221961
11.	Snap knife 25 mm	48221962

	Piercing tip allows controlled piercing and smooth cutting.	
	Smooth / serrated 75mm blade and piercing tip. Ideal for tearing through material and tip allows controlled piercing.	
	Storage for 4 extra blades.	
	Press and flip one-handed opening provides fast access to the blade.	
	Side blade activation: Reduces the risk of exposing the blade accidentally.	
	Self-retract mechanism: Retracts blade when the button is released.	
	Reduce cut injuries thanks to recessed blade prevents contact with fingers.	
	Iron carbide blade for longer lifetime, increased sharpness and clean cut finish.	

JOBSITE SCISSORS

- Iron carbide cutting edge for maximum durability. Longer lifetime vs. stainless steel.
- Chrome plated blades for maximum rust protection.
- All metal core: full metal handle construction to protect from drops and handle breakage.
- Bolt lock technology protects blades from loosening to ensure precise cutting.
- Large handle loops for use with gloves.
- Index finger groove for more comfort.
- Laser edged ruler markings on the blade allows to measure and cut in one go.
- Jobsite offset scissors with micro-serrated blades for maximum durability and better grip.
- Jobsite offset scissors with 60°-offset head allows to keep hand above cutting material.



	Offset scissors	Straight scissors
Total length (mm)	240	230
Blade length (mm)	115	95
Article Number	48224043	48224044

CHEATER - ADAPTABLE PIPE WRENCH

- New-to-world 3 length design - 107/250 mm mode for tight spaces, 187/450 mm mode for general purpose, 247/600 mm mode for maximum leverage and reach.
- Overbite jaw for secure grip on pipes and fittings.
- Dual coil springs for maximum durability and tool life.
- Ergonomic handle for maximum comfort, won't dig into the palm.
- Ergonomic hook jaw design - for easy detachment from the workpiece.
- Hardened jaws for increased durability and better grip.
- Lanyard hole.



	Adaptable pipe wrench
Total length (mm)	250/450/600
Total length (inch)	10/18/24
Jaw opening capacity for pipe (mm)	63
Jaw opening capacity for pipe (inch)	2.5
Weight (g)	3243
Article Number	48227314

10 IN 1 RATCHET MULTI-BIT SCREWDRIVER

- Ergonomic 152 mm long screwdriver with 1/4" Hex nut driver (in reception) and built in wire stripper and loop maker.
- Full metal high torque ratchet for 2 x driving speed and control.
- 88 mm long power groove bits, power tool compatibility.
- Precision hardened bit tips: durable driving tips for secure fitment and long life.
- Revolver style bit storage in handle.
- Chrome plated marine grade rust protected bits.



	10 in 1 Ratchet Multi-Bit screwdriver - universal	10 in 1 Ratchet Multi-Bit screwdriver - Hex
Contents	PH1 / PH2 / PZ1 / PZ2 / TX15 / TX20 / Slotted 0.8 x 5.5 mm.	Hex 1.5 mm / Hex 2 mm / Hex 2.5 mm / Hex 3 mm / Hex 4 mm / Hex 5 mm / Hex 6 mm
Pack quantity	1	1
Article Number	48222311	48229306

VDE SCREWDRIVERS


- VDE tested to 10, 000 V and guaranteed to 1,000 V.
- Premium quality steel with molybdenum and vanadium for flexibility and lifetime.
- CNC milled tips for high precision for best fit and reduced cammout effect.
- Black phosphate on the tip for grip and corrosion resistance.
- 2 component grip with softgrip for comfortable handling.
- 3 sided design for non slip and maximum power transfer.
- Slim design at front for low power/torque applications and fine electrical work.
- Laser engraved with the reception on the top of handle for easy identification.
- Anti roll, 3 sided collar on handle.



	Article Number	
SL 0.4 x 2.5 x 75	4932464034	
SL 0.5 x 3 x 100	4932464035	
SL 0.6 x 3.5 x 100	4932464036	
SL 0.8 x 4 x 100	4932464037	
SL 1.0 x 5.5 x 125	4932464038	
SL 1.2 x 6.5 x 150	4932464039	
SL 1.2 x 8 x 175	4932464040	
SL 0.5 x 3 x 65	4932464041	
PH0 x 60	4932464042	
PH1 x 80	4932464043	
PH2 x 100	4932464044	
PH3 x 150	4932464045	
PZ0 x 60	4932464046	
PZ1 x 80	4932464047	
PZ2 x 100	4932464048	
PZ3 x 150	4932464049	
T10 x 60	4932464050	
T15 x 75	4932464051	
T20 x 100	4932464052	
T25 x 100	4932464053	
T30 x 100	4932464054	
PH/SL1 x 80	4932464055	
PH/SL2 x 100	4932464056	
PZ/SL1 x 80	4932464057	
PZ2/SL2 x 100	4932464058	
SW6 x 125	4932464059	
SW7 x 125	4932464060	
SW8 x 125	4932464061	
SW9 x 125	4932464062	
SW10 x 125	4932464063	
SW11 x 125	4932464064	
SW13 x 125	4932464065	
VDE screwdriver set (5pc)	4932464066	
VDE Screwdriver set 1 (7pc)	4932464067	
VDE Screwdriver set 2 (7pc)	4932464068	

VDE PLIERS

- VDE (DIN EN/IEC 60900) certified tools. Tested to 10,000 volts and guaranteed to 1,000 volts. Tested against cold to -40°.
- Steel blades are fully forged, hardened and tempered for best durability. Grey titanium surface finish is non reflective and ensures maximum corrosion resistance.
- Induction hardened cutting edges to cut even the hardest of materials.
- Precision machined joint for maximum power transmission with optimum leverage for easy and effortless work.
- Ergonomic grip with softgrip for comfortable handling and good grip.



	Article Number	
VDE 160 mm cable cutter	4932464562	
VDE 210 mm cable cutter	4932464563	
VDE 205 mm long round nose plier	4932464564	
VDE 205 mm long 45° round nose plier	4932464565	
VDE 145 mm diagonal cutter	4932464566	
VDE 160 mm diagonal cutter	4932464567	
VDE 180 mm diagonal cutter	4932464568	
VDE 180 mm heavy duty diagonal cutter	4932464569	
VDE 200 mm heavy duty diagonal cutter	4932464570	
VDE 165 mm combination plier	4932464571	
VDE 180 mm combination plier	4932464572	
VDE 160 mm wire stripping plier	4932464573	
VDE 240 mm wire stripping plier	4932464574	
VDE 3 piece plier set	4932464575	



MILWAUKEE® INTRODUCTION 2 - 3

M18™ RANGE

M18™ SUMMARY	4 - 5
M18 FUEL™ INTRODUCTION	6 - 7
REDLITHIUM-ION™ BATTERY INTRODUCTION	8 - 9
ONE-KEY™ INTRODUCTION	10 - 11
C18 HZ	M18™ HACKZALL™ 43
C18 PCG/310	M18™ CAULK GUN WITH 310 ML CANISTER 49
C18 PCG/400	M18™ CAULK GUN WITH 400 ML TUBE 48
C18 PCG/600	M18™ CAULK GUN WITH 600 ML TUBE 48
C18 RAD	M18™ COMPACT RIGHT ANGLE DRILL 22
HD18 AG-115	M18™ 115 MM ANGLE GRINDER WITH PADDLE SWITCH 35
HD18 AG-125	M18™ 125 MM ANGLE GRINDER WITH PADDLE SWITCH 35
HD18 BS	M18™ METAL BANDSAW 37
HD18 CS	M18™ 55MM CIRCULAR SAW FOR WOOD AND PLASTIC 40
HD18 H	M18™ 4-MODE SDS-PLUS HAMMER 14
HD18 HIW	M18™ IMPACT WRENCH WITH PIN DETENT 29
HD18 HIWF	M18™ IMPACT WRENCH WITH FRICTION RING 29
HD18 HX	M18™ 4-MODE SDS-PLUS HAMMER WITH FIXTEC CHUCK 14
HD18 PD	M18™ PERCUSSION DRILL 20
M12-18 JSSP	M12™ - M18™ BLUETOOTH® SPEAKER 50
M18 AF	M18™ AIR FAN 47
M18 BBL	M18™ BATTERY BLOWER 47
M18 BDD	M18™ COMPACT DRILL DRIVER 20
M18 BH	M18™ COMPACT 2-MODE SDS-PLUS HAMMER 15
M18 BHG	M18™ HEAT GUN 48
M18 BID	M18™ COMPACT 1/4" HEX IMPACT DRIVER 24
M18 BIW12	M18™ 1/2" IMPACT WRENCH 31
M18 BIW38	M18™ 3/8" IMPACT WRENCH 31
M18 BJS	M18™ TOP HANDLE JIGSAW 44
M18 BLCS66	M18™ BRUSHLESS 66 MM CIRCULAR SAW FOR WOOD AND PLASTICS 40

M18 BLDD2	M18™ BRUSHLESS DRILL DRIVER 18
M18 BLID2	M18™ BRUSHLESS 1/4" HEX IMPACT DRIVER 24
M18 BLPD2	M18™ BRUSHLESS PERCUSSION DRILL 18
M18 BMS12	M18™ METAL SHEAR 36
M18 BMS20	M18™ METAL SHEAR 36
M18 BMT	M18™ MULTI-TOOL 38
M18 BOS125	M18™ 125 MM RANDOM ORBITAL SANDER 45
M18 BP	M18™ PLANER 44
M18 BPD	M18™ COMPACT PERCUSSION DRILL 20
M18 BRAID	M18™ RIGHT ANGLE IMPACT DRIVER 25
M18 BRAIW	M18™ 3/8" RIGHT ANGLE IMPACT WRENCH 31
M18 BSX	M18™ SAWZALL® 42
M18 CAG115X	M18 FUEL™ 115 MM ANGLE GRINDER WITH SLIDE SWITCH 35
M18 CAG115XPD	M18 FUEL™ 115 MM ANGLE GRINDER WITH PADDLE SWITCH 34
M18 CAG115XPDB	M18 FUEL™ 115 MM BRAKING GRINDER WITH PADDLE SWITCH 33
M18 CAG125X	M18 FUEL™ 125 MM ANGLE GRINDER WITH SLIDE SWITCH 34
M18 CAG125XPD	M18 FUEL™ 125 MM ANGLE GRINDER WITH PADDLE SWITCH 34
M18 CAG125XPDB	M18 FUEL™ 125 MM BRAKING GRINDER WITH PADDLE SWITCH 32
M18 CBLDD	M18™ COMPACT BRUSHLESS DRILL DRIVER 19
M18 CBLID	M18™ COMPACT BRUSHLESS 1/4" HEX IMPACT DRIVER 24
M18 CBLPD	M18™ COMPACT BRUSHLESS PERCUSSION DRILL 19
M18 CBS125	M18 FUEL™ DEEP CUT BAND SAW 36
M18 CCS55	M18 FUEL™ 55 MM CIRCULAR SAW FOR WOOD AND PLASTICS 40
M18 CDEX	M18 FUEL™ SDS-PLUS DUST EXTRACTOR 15
M18 CHM	M18 FUEL™ 5 KG SDS-MAX DRILLING AND BREAKING HAMMER 13
M18 CHPX	M18 FUEL™ HIGH PERFORMANCE 4-MODE SDS-PLUS HAMMER WITH FIXTEC CHUCK 13
M18 CHX	M18 FUEL™ 4-MODE SDS-PLUS HAMMER WITH FIXTEC CHUCK 13
M18 CN15GA	M18 FUEL™ 15 GA ANGLED NAIL FINISH NAILER 45

M18 CN16GA	M18 FUEL™ 16 GA ANGLED NAIL FINISH NAILER 45
M18 CN18GS	M18 FUEL™ 18 GA BRAD NAIL FINISH NAILER 46
M18 CRAD	M18 FUEL™ RIGHT ANGLE DRILL 21
M18 CSX	M18 FUEL™ SAWZALL® 42
M18 CV	M18™ HAND VAC 47
M18 FAP	M18 FUEL™ POLISHER 37
M18 FBJS	M18 FUEL™ BODY GRIP JIGSAW 43
M18 FBPV	M18™ GREASE GUN 49
M18 FCS66	M18 FUEL™ 66 MM CIRCULAR SAW FOR WOOD AND PLASTICS 39
M18 FDD2	M18 FUEL™ DRILL DRIVER 17
M18 FDG	M18 FUEL™ DIE GRINDER 37
M18 FHIWF12	M18 FUEL™ 1/2" HIGH TORQUE IMPACT WRENCH WITH FRICTION RING 27
M18 FHIWF12	M18 FUEL™ 1/2" HIGH TORQUE IMPACT WRENCH WITH PIN DETENT 28
M18 FHM	M18 FUEL™ ONE-KEY™ 8 KG SDS-MAX DRILLING AND BREAKING HAMMER 12
M18 FHZ	M18 FUEL™ HACKZALL™ 43
M18 FID2	M18 FUEL™ 1/4" HEX IMPACT DRIVER 23
M18 FWF12	M18 FUEL™ 1/2" IMPACT WRENCH WITH FRICTION RING 30
M18 FWP12	M18 FUEL™ 1/2" IMPACT WRENCH WITH PIN DETENT 30
M18 FJS	M18 FUEL™ TOP HANDLE BRUSHLESS DRILL DRIVER 44
M18 FLAG230XPDB	M18 FUEL™ 230 MM LARGE BRAKING GRINDER WITH PADDLE SWITCH 33
M18 FMCS	M18 FUEL™ METAL SAW 38
M18 FMDP	M18 FUEL™ MAGNETIC DRILLING PRESS WITH PERMANENT MAGNET 32
M18 FMS190	M18 FUEL™ 190 MM MITRE SAW 39
M18 FMS254	M18 FUEL™ 254 MM MITRE SAW 38
M18 FMTWF12	M18 FUEL™ 1/2" MID TORQUE IMPACT WRENCH WITH FRICTION RING 28
M18 FMTWP12	M18 FUEL™ 1/2" MID TORQUE IMPACT WRENCH WITH PIN DETENT 28
M18 FP02	M18 FUEL™ PERCUSSION DRILL 17
M18 FPM	M18 FUEL™ PADDLE MIXER 32
M18 FQID	M18 FUEL™ SURGE™ 1/4" HEX HYDRAULIC IMPACT DRIVER 23

M18™ POWERPACKS

M18 BLPP2A2	M18™ BRUSHLESS POWERPACK 52
M18 BLPP2B2	M18™ BRUSHLESS POWERPACK 53
M18 BPP2C	M18™ POWERPACK 53
M18 CBLPP2A	M18™ COMPACT BRUSHLESS POWERPACK 53
M18 CBLPP2B	M18™ COMPACT BRUSHLESS POWERPACK 52
M18 FHPP3A	M18™ HIGH PERFORMANCE POWERPACK 51
M18 FPP2A2	M18 FUEL™ POWERPACK 51

M18 FPP2C2	M18 FUEL™ POWERPACK 52
M18 FPP4F2	M18 FUEL™ POWERPACK 53
M18 FPP6C2	M18 FUEL™ POWERPACK 52
M18 ONEPP2A2	M18 FUEL™ ONE-KEY™ POWERPACK 51
M18 ONEPP2B2	M18 FUEL™ ONE-KEY™ POWERPACK 51

M12™ RANGE

M12™ SUMMARY	54 - 55
M12 FUEL™ INTRODUCTION	56 - 57
C12 HZ	M12™ SUB COMPACT HACKZALL™ 68
C12 JSR	M12™ SUB COMPACT RADIO WITH MP3 PLAYER CONNECTION 75
C12 MT	M12™ SUB COMPACT MULTI-TOOL 70
C12 PC	M12™ SUB COMPACT COPPER PIPE CUTTER 74
C12 PN	M12™ SUB COMPACT PALM NAILER 70
C12 PPC	M12™ SUB COMPACT PEX CUTTER 74
C12 RAD	M12™ SUB COMPACT RIGHT ANGLE DRILL 61
C12 RT	M12™ SUB COMPACT ROTARY TOOL 71
M12 BD	M12™ SUB COMPACT DRIVER 62
M12 BDD	M12™ SUB COMPACT DRILL DRIVER 61
M12 BDDX	M12™ SUB COMPACT DRILL DRIVER WITH REMOVABLE CHUCK 60
M12 BI	M12™ SUB COMPACT INFLATOR 68
M12 BID	M12™ SUB COMPACT 1/4" HEX IMPACT DRIVER 63
M12 BIW12	M12™ SUB COMPACT 1/2" IMPACT WRENCH 65
M12 BIW38	M12™ SUB COMPACT 3/8" IMPACT WRENCH 66
M12 BPD	M12™ SUB COMPACT PERCUSSION DRILL 61
M12 BPRT	M12™ SUB COMPACT RIVET TOOL 70
M12 BPS	M12™ SUB COMPACT POLISHER / SANDER 72
M12 BRAID	M12™ SUB COMPACT RIGHT ANGLE IMPACT DRIVER 64
M12 BS	M12™ SUB COMPACT BANDSAW 71
M12 BSD	M12™ SUB COMPACT SINGLE SPEED DRIVER 62
M12 BST	M12™ SUB COMPACT STAPLER 69
M12 CC	M12™ SUB COMPACT CABLE CUTTER 74
M12 CCS44	M12 FUEL™ SUB COMPACT CIRCULAR SAW 69

M12 CD	M12 FUEL™ SUB COMPACT DRIVER 62
M12 CH	M12 FUEL™ SUB COMPACT SDS-PLUS HAMMER 58
M12 CHZ	M12 FUEL™ SUB COMPACT HACKZALL™ 68
M12 DE	M12™ UNIVERSAL HAMMER VAC 59
M12 FCOT	M12 FUEL™ SUB COMPACT MULTI-MATERIAL CUT-OFF TOOL 71
M12 FDD	M12 FUEL™ SUB COMPACT DRILL DRIVER 60
M12 FD	M12 FUEL™ SUB COMPACT 1/4" HEX IMPACT DRIVER 63
M12 FIR12	M12 FUEL™ SUB COMPACT 1/2" RATCHET 66
M12 FIR14	M12 FUEL™ SUB COMPACT 1/4" RATCHET 67
M12 FIR38	M12 FUEL™ SUB COMPACT 3/8" RATCHET 66
M12 FIW14	M12 FUEL™ SUB COMPACT 1/4" IMPACT WRENCH 65
M12 FIW38	M12 FUEL™ SUB COMPACT 3/8" IMPACT WRENCH 65
M12 FIWF12	M12 FUEL™ SUB COMPACT 1/2" IMPACT WRENCH 64
M12 FPD	M12 FUEL™ SUB COMPACT PERCUSSION DRILL 59
M12 FPDX	M12 FUEL™ SUB COMPACT PERCUSSION DRILL WITH REMOVABLE CHUCK 60
M12 GG	M12™ SUB COMPACT GREASE GUN 72
M12 H	M12™ SUB COMPACT SDS-PLUS HAMMER 58
M12 HV	M12™ SUB COMPACT STICK VAC 72
M12 IR	M12™ SUB COMPACT RATCHET 67
M12 JS	M12™ SUB COMPACT JIGSAW 69
M12 JSSP	M12™ JOBSITE BLUETOOTH® SPEAKER 75
M12 PCG/310	M12™ SUB COMPACT CAULK GUN WITH 310 ML CARTRIDGE HOLDER 73
M12 PCG/400	M12™ SUB COMPACT CAULK GUN WITH 400 ML TUBE 73
M12 PCG/600	M12™ SUB COMPACT CAULK GUN WITH 600 ML TUBE 73
M12 SI	M12™ PREMIUM SOLDERING IRON 67
M12-18 JSSP	M12™ - M18™ BLUETOOTH® SPEAKER 75

M12™ POWERPACKS

M12 BPP2B	M12™ POWERPACK 76
M12 BPP2C	M12™ POWERPACK 76
M12 BPP2D	M12™ POWERPACK 77
M12 BPP3A	M12™ POWERPACK 77

M12 BPP4A	M12™ POWERPACK 77
M12 FPP2A	M12 FUEL™ POWERPACK 76
M12 FPP2B	M12 FUEL™ POWERPACK 76

T&M TOOLS

2200-40	VOLTAGE DETECTOR 82
2205-40	FORK METER FOR ELECTRICIANS 80
2212-20	AUTO VOLTAGE / CONTINUITY TESTER 80
2216-40	LIGHT COMMERCIAL MULTIMETER 80
2217-40	DIGITAL MULTIMETER 81
2235-40	LIGHT COMMERCIAL CLAMP METER 81
2267-40	10-1 INFRARED TEMP-GUN™ 81
2309-60	ALKALINE INSPECTION CAMERA 79
LDM 100	100 M LASER DISTANCE METER 83
LDM 30	30 M LASER DISTANCE METER 82
LDM 45	45 M LASER DISTANCE METER 82
LDM 50	50 M LASER DISTANCE METER 83
M12 IC	M12™ SUB COMPACT M-SPECTOR™ 360° CAMERA 79
M12 IC AV3	M12™ DIGITAL INSPECTION CAMERA 79

WORKGEAR

EQUIPMENT	91
M12 HBWP	M12™ HEATED HYBRID PUFFER VEST 85
M12 HBWP LADIES	M12™ HEATED HYBRID LADIES PUFFER VEST 86
M12 HH BL3	M12™ BLACK HEATED HOODIE 88
M12 HH GREY3	M12™ GREY HEATED HOODIE 87
M12 HJ BL4	M12™ PREMIUM HEATED JACKET 87
M12 HJ CAM05	M12™ PREMIUM HEATED CAMOUFLAGE JACKET 86
M12 HJ GREY4	M12™ PREMIUM HEATED JACKET 86
M12 HJ LADIES2	M12™ LADIES HEATED JACKET 87
M12 HJP	M12™ HEATED HYBRID PUFFER JACKET 85
M12 HJP LADIES	M12™ HEATED HYBRID LADIES PUFFER JACKET 85
PACKOUT™ BACKPACK	95
PACKOUT™ BOXES	93

PACKOUT™ COMPACT ORGANISER	93
PACKOUT™ COMPACT SLIM ORGANISER	94
PACKOUT™ DUFFEL BAG	94
PACKOUT™ INTRODUCTION	92
PACKOUT™ JOBSITE COOLER	95
PACKOUT™ ORGANISER	93
PACKOUT™ SLIM ORGANISER	94
PACKOUT™ TECH BAG	95
PACKOUT™ TOTE TOOLBAG	94
PACKOUT™ TROLLEY BOX	93
WGJCBL	GRIDIRON™ TRADESMAN JACKET 90
WGJHBL	GRIDIRON™ HOODED JACKET BLACK 90
WGT-R	GRIDIRON™ WORK GEAR TROUSERS 88
WORK GLOVES	90
WWLSG	WORKSKIN™ LIGHT WEIGHT PERFORMANCE LONG SLEEVE SHIRT - GREY 88
WWLSY	WORKSKIN™ LIGHT WEIGHT PERFORMANCE LONG SLEEVE SHIRT - HI-VIS 89
WWSSG	WORKSKIN™ LIGHT WEIGHT PERFORMANCE SHORT SLEEVE SHIRT - GREY 89
WWSSY	WORKSKIN™ LIGHT WEIGHT PERFORMANCE SHORT SLEEVE SHIRT - HI-VIS 89

GARDEN TOOLS

M18 CHT	M18 FUEL™ HEDGE TRIMMER 98
M18 CLT	M18 FUEL™ LINE TRIMMER 98
M18 FBL	M18 FUEL™ BLOWER 98
M18 FCHS	M18 FUEL™ CHAINSAW 97
M18 FOPH	M18 FUEL™ OPE ATTACHMENTS 99

FORCE LOGIC™ TOOLS

C12 PXP	M12™ SUB COMPACT UPONOR® Q&E EXPANSION TOOL 111
CRIMPING DIES	103
EXPANDER HEADS	111
HD18 PXP	M18™ UPONOR® Q&E EXPANSION TOOL 110
M12 HPT	M12™ SUB COMPACT FORCE LOGIC™ HYDRAULIC PRESS TOOL 108

M18 BLHPT	M18™ FORCE LOGIC™ BRUSHLESS PRESSTOOL	108
M18 HCC45	M18™ FORCE LOGIC™ HYDRAULIC 44 MM CABLE CUTTER	105
M18 HCC75	M18™ FORCE LOGIC™ HYDRAULIC UNDERGROUND CABLE CUTTER	105
M18 HCC75R	M18™ FORCE LOGIC™ HYDRAULIC REMOTE UNDERGROUND CABLE CUTTER	104
M18 HCCT	M18™ FORCE LOGIC™ HYDRAULIC 53 KN CABLE CRIMPER	102
M18 HCCT109/42	M18™ FORCE LOGIC™ HYDRAULIC 109 KN CABLE CRIMPER	102
M18 HKP	M18™ FORCE LOGIC™ HYDRAULIC KNOCKOUT PUNCH	107
M18 ONEBLXPXL	M18™ ONEKEY™ FORCE LOGIC™ UPONOR® Q&E HYDRAULIC PIPE EXPANDING TOOL	110
M18 ONEHCC	M18™ FORCE LOGIC™ HYDRAULIC 35 MM CABLE CUTTER	106
PRESS JAWS		109

DRAIN CLEANERS

M12 BDC6	M12™ SUB COMPACT DRAIN CLEANER WITH SPIRAL DIAMETER 6 MM	114
M12 BDC8	M12™ SUB COMPACT DRAIN CLEANER WITH SPIRAL DIAMETER 8 MM	114
M12™ DRAIN CLEANER ACCESSORIES		114
M18 FDCPF10	M18 FUEL™ DRAIN CLEANER - POWER FEED 10 MM	115
M18 FDCPF8	M18 FUEL™ DRAIN CLEANER - POWER FEED 8 MM	115
M18 FFSDC10	M18 FUEL™ FREE STANDING DRAIN CLEANER 10 MM	117
M18 FFSDC13	M18 FUEL™ FREE STANDING DRAIN CLEANER 13 MM	117
M18 FFSDC16	M18 FUEL™ FREE STANDING DRAIN CLEANER 16 MM	116
M18 FS DRAIN CLEANER ACCESSORIES		117
M18 PF DRAIN CLEANER ACCESSORIES		115

TRUEVIEW™ HIGH DEFINITION LIGHTING

FL-LED	ALKALINE FLOOD LIGHT	129
HL-LED	ALKALINE SLIM HEADLAMP	129

HOBL 7000	HIGH OUTPUT BAY LIGHT	120
IPL-LED	ALKALINE PEN LIGHT	128
L4 FFL	USB RECHARGEABLE FOLDING FLOOD LIGHT	127
L4 FL	USB RECHARGEABLE POCKET FLOOD LIGHT	127
L4 HL	USB RECHARGEABLE HEADLAMP	128
L4 MLED	USB RECHARGEABLE COMPACT FLASHLIGHT	128
L4 PWL	USB RECHARGEABLE PIVOTING WORK LIGHT	127
M12 AL	M12™ LED AREA LIGHT	123
M12 LL	M12™ LED LANTERN LIGHT	125
M12 MLED	M12™ LED HIGH PERFORMANCE FLASHLIGHT	126
M12 SAL	M12™ STAND LIGHT	122
M12 SL	M12™ LED stick light	125
M12 SLED	M12™ LED SPOT LIGHT	124
M12 TLED	M12™ LED TORCH	126
M12 UHL	M12™ LED UNDERHOOD LIGHT	124
M18 AL	M18™ LED AREA LIGHT	123
M18 HAL	M18™ HIGH PERFORMANCE LED AREA LIGHT	122
M18 HSAL	M18™ HIGH PERFORMANCE LED STAND LIGHT CHARGER	121
M18 IL	M18™ LED INSPECTION LIGHT	124
M18 LL	M18™ LED LANTERN LIGHT	125
M18 ONERSAL	M18™ ONE-KEY™ LED REMOTE STAND LIGHT	121
M18 ONESLDP	M18™ ONE-KEY™ LED COMPACT SITE LIGHT CHARGER	119
M18 ONESLSP	M18™ ONE-KEY™ LED COMPACT SITE LIGHT	119
M18 PAL	M18™ PIVOTING AREA LIGHT	122
M18 SAL	M18™ LED STAND LIGHT	121
M18 SLED	M18™ LED SEARCH LIGHT	123
M18 SLSP	M18™ LED COMPACT SITE LIGHT	120
M18 TAL	M18™ TRADESMAN AREA LIGHT	120
M18 TLED	M18™ LED TORCH	126
ML-LED	ALKALINE FLASHLIGHT	129

M28™ RANGE

HD28 AG115	M28™ 115 MM ANGLE GRINDER	132
HD28 AG125	M28™ 125 MM ANGLE GRINDER	132

HD28 CS	M28™ 54 MM CIRCULAR SAW	134
HD28 IW	M28™ 1/2" DRIVE IMPACT WRENCH WITH PIN DETENT	133
HD28 JSB	M28™ BODY GRIP JIGSAW	134
HD28 MS	M28™ METAL DRY CUT SAW	133
HD28 PD	M28™ PERCUSSION DRILL	132
HD28 SG	M28™ STRAIGHT GRINDER	133
HD28 SX	M28™ SAWZALL®	134
M18-28 CPDEX	M18-28 FUEL™ SDS-PLUS DUST EXTRACTOR	131
M28 CHPX	M28 FUEL™ 4-MODE SDS-PLUS HAMMER WITH FIXTEC CHUCK	131
M28 CHPXDE	M28 FUEL™ 4-MODE SDS-PLUS HAMMER WITH FIXTEC CHUCK AND DEDICATED DUST EXTRACTOR	131
M28 PACK D	M28™ POWERPACK	135

M4™ RANGE

M4 D	M4™ DRILL DRIVER	135
------	------------------	-----

BATTERIES AND CHARGERS

BATTERIES AND CHARGER KITS	138 - 138
CHARGERS	137
M12™ BATTERIES	136
M18™ BATTERIES	136
OTHER BATTERIES	137

CONSTRUCTION

AGV 12 DEC	1200 W ANGLE GRINDER WITH DUST MANAGEMENT (28 MM DOC)	160
AGV 12 DEG	1200 W ANGLE GRINDER WITH DUST MANAGEMENT	161
AGV 15 DEC	1550 W ANGLE GRINDER WITH DUST MANAGEMENT (28 MM DOC)	159
AGV 15 DEG	1550 W ANGLE GRINDER WITH DUST MANAGEMENT	160
B2E 16 RLD	900 W 2-SPEED ROTARY DRILL	154
BRT	BREAKER TROLLEY	142
DCM 2-250 C	DIAMOND DRILLING MOTOR	159
DCM 2-350 C	DIAMOND DRILLING MOTOR	158
DD 2-160 XE	2-SPEED DRY DIAMOND DRILL	158

DD 3-152	3-SPEED COMBI DIAMOND DRILL	157
DE 13 RP	630 W SINGLE SPEED ROTARY DRILL	155
DR 152 T	DIAMOND DRILL STAND FOR DD 3-152	157
DR 250 TV	DIAMOND DRILL STAND FOR DCM 2-250 C	159
DR 350 T	DIAMOND DRILL STAND FOR DCM 2-350 C	158
DWSE 4000 Q	DRYWALL SCREWDRIWER	156
HD2E 13 R	705 W 2-SPEED ROTARY DRILL	154
HDE 13 RQD	825 W SINGLE SPEED ROTARY DRILL	155
HDE 13 RQX	950 W SINGLE SPEED ROTARY DRILL	155
IPWE 400 R	1/2" DRIVE IMPACT WRENCH	156
IPWE 520 R	3/4" DRIVE IMPACT WRENCH	157
K 1000 S	10 KG CLASS BREAKING HAMMER	144
K 1528 H	15 KG CLASS 28 MM HEX BREAKING HAMMER	143
K 1530 H	15 KG CLASS 30 MM HEX BREAKING HAMMER	143
K 2000 H	20 KG CLASS 28 MM HEX BREAKING HAMMER	142
K 2500 H	25 KG CLASS 28 MM HEX BREAKING HAMMER	142
K 500 S	5 KG CLASS BREAKING HAMMER	147
K 500 ST	5 KG CLASS TRADESMAN BREAKING HAMMER	147
K 540 S	5 KG CLASS DRILLING AND BREAKING HAMMER	146
K 545 S	5 KG CLASS DRILLING AND BREAKING HAMMER	146
K 750 S	7 KG CLASS DRILLING AND BREAKING HAMMER	146
K 850	8 KG CLASS DRILLING AND BREAKING HAMMER	145
K 900	10 KG CLASS BREAKING HAMMER	145
K 950	10 KG CLASS DRILLING AND BREAKING HAMMER	144
PCE 3/K	3 KG SDS-PLUS CHIPPING HAMMER	147
PD2E 22 R	850 W 2-SPEED PERCUSSION DRILL	153
PD2E 24 R	1020 W 2-SPEED PERCUSSION DRILL	152
PD2E 24 RS	1010 W 2-SPEED PERCUSSION DRILL	152
PD2E 24 RST	1200 W 2-SPEED PERCUSSION DRILL	152
PD-705	705 W PERCUSSION DRILL	153
PDE 13 RX	630 W SINGLE SPEED PERCUSSION DRILL	154
PDE 16 RP	630 W SINGLE SPEED PERCUSSION DRILL	153
PFH 24	24 MM SDS-PLUS 2-MODE FIXING HAMMER	151
PFH 26	26 MM SDS-PLUS 2-MODE FIXING HAMMER	150

PFH 26 T	26 MM SDS-PLUS 2-MODE HAMMER	150
PH 26	26 MM SDS-PLUS 3-MODE HAMMER	149
PH 26 T	26 MM SDS-PLUS 3-MODE HAMMER	150
PH 27	26 MM SDS-PLUS 3-MODE HAMMER	149
PH 28	28 MM SDS-PLUS 3-MODE HAMMER	149
PH 30	30 MM SDS-PLUS 3-MODE HAMMER	148
PLH 20	20 MM SDS-PLUS 2-MODE L-SHAPED FIXING HAMMER	151
PLH 28	28 MM SDS-PLUS 3-MODE L-SHAPED HAMMER	148
PLH 32	32 MM SDS-PLUS 3-MODE L-SHAPED HAMMER	148
SB 2-35 D	1010 W 2-SPEED PERCUSSION DRILL	151
TKSE 2500 Q	TECH GUN FOR SELF DRILLING SCREWS	156
WCE 30	1500 W 125 MM (30 MM DOC) WALL CHASER	161
WCS 45	1900 W 150 MM (45 MM DOC) WALL CHASER	161

METALWORKING

AG 10 EK	1000 W ANGLE GRINDER	170
AG 13 XSPD	1250 W ANGLE GRINDER WITH SLIM PADDLE SWITCH	169
AG 22	2200 W ANGLE GRINDER	166
AG 24	2400 W ANGLE GRINDER	165
AG 800 E	800 W ANGLE GRINDER	171
AG 800 EK	800 W ANGLE GRINDER WITH KEYLESS GUARD	171
AG 9	850 W ANGLE GRINDER	171
AGS 15-125 C	1500 W GRINDER/SANDER	172
AGV 10 EK	1000 W ANGLE GRINDER WITH AVS	170
AGV 12	1200 W ANGLE GRINDER WITH AVS	170
AGV 13	1250 W ANGLE GRINDER WITH AVS AND SLIDE SWITCH	169
AGV 13 XSPDE	1250 W ANGLE GRINDER WITH AVS AND SLIM PADDLE SWITCH	169
AGV 13 XSPDEB	1250 W BRAGING GRINDER WITH AVS AND PADDLE SWITCH	168
AGV 15	1550 W ANGLE GRINDER WITH AVS	168
AGV 17	1750 W ANGLE GRINDER WITH AVS	167
AGV 17 INOX	1750 W LOW SPEED GRINDER WITH AVS	167
AGV 21 GEX	2100 W ANGLE GRINDER WITH AVS	166
AGV 22	2200 W ANGLE GRINDER WITH AVS	166

AGV 24	2400 W ANGLE GRINDER WITH AVS	165
AGV 26	2600 W ANGLE GRINDER WITH AVS	164
AGVK 24	2400 W ANGLE GRINDER WITH AVS AND KICKBACK PROTECTION	165
AGVM 24	2400 W ANGLE GRINDER WITH AVS AND KICKBACK PROTECTION	164
AGVM 26	2600 W ANGLE GRINDER WITH AVS AND KICKBACK PROTECTION	164
AP 12 E	1200 W POLISHER WITH ELECTRONIC VARIABLE SPEED	172
AP 14-2 200 E	1450 W POLISHER	173
AS 12 E	1200 W SANDER WITH ELECTRONIC VARIABLE SPEED	172
BS 125	DEEP CUT BAND SAW	175
CHS 355	2300 W CHOPSAW	176
DE 10 RX	630 W SINGLE HIGH SPEED ROTARY DRILL	176
DG 30 E	VARIABLE SPEED SINGLE HANDED DIE GRINDER	174
DG 7 E	LOW SPEED DIE GRINDER	174
DGL 30 E	VARIABLE SPEED 2-HANDED DIE GRINDER	174
DGL 34	SINGLE HIGH SPEED 2-HANDED DIE GRINDER	173
HDE 6 RQ	725 W SINGLE HIGH SPEED ROTARY DRILL	176
MCS 66	DRY CUT METAL CIRCULAR SAW	175
MDE 41	MAGNETIC DRILLING PRESS WITH ELECTRO MAGNET	177
MDE 42	MAGNETIC DRILLING PRESS	177
MDP 41	MAGNETIC DRILLING PRESS WITH PERMANENT MAGNET	177

WOODWORKING

AS 2-250 ELCP	25 L L-CLASS DUST EXTRACTOR	187
AS 30 LAC	30 L L-CLASS DUST EXTRACTOR	187
AS 30 MAC	30 L M-CLASS DUST EXTRACTOR	187
AS 42 MAC	42 L M-CLASS DUST EXTRACTOR	186
BS 100 LE	4" (100 MM) BELT SANDER	184
CS 60	184 MM CIRCULAR SAW (61 MM DOC)	184
CS 85 CBE	235 MM CIRCULAR SAW (85 MM DOC)	183
CS 85 SB	235 MM CIRCULAR SAW (85 MM DOC)	182
FSPE 110 X	HEAVY DUTY BODY GRIP JIGSAW	181
JS 120 X	HEAVY DUTY BODY GRIP JIGSAW	182

JSPE 135	HEAVY DUTY TOP HANDLE JIGSAW	182
MS 216	8 1/2" (216 MM) SLIDING MITRE SAW	188
MS 304 DB	12" (305 MM) DUAL BEVEL SLIDING MITRE SAW	188
MSL 1000	MITRE SAW STAND EXTENDABLE UP TO 2 M	189
MSL 2000	MITRE SAW STAND EXTENDABLE UP TO 2.5 M	189
MSL 3000	MITRE SAW STAND EXTENDABLE UP TO 3 M	189
ROS 125 E	5" (125 MM) RANDOM ORBIT SANDER	185
ROS 150 E-2	6" (150 MM) RANDOM ORBIT SANDER	184
SCS 65 Q	190 MM CIRCULAR SAW (65 MM DOC)	183
SPS 140	1/4" SHEET SANDER	185
SSD 1100 X	1100 W SAWZALL®	181
SSPE 1300 RX	1300 W SAWZALL® WITH ROTATING HANDLE	180
SSPE 1300 SX	1300 W SAWZALL®	181
SSPE 1500 X	1500 W SUPER SAWZALL®	180
TSS 1000	TABLE SAW STAND	185

HANDTOOLS

10IN 1 RATCHET MULTI-BIT SCREWDRIVER	198
ADAPTABLE PIPE WRENCHES	198
FOLDING RULES	196
INKZALL™ MARKERS	194
JOBSITE SCISSORS	198
KNIVES	197
LEVELS	192 - 193
LONG TAPES	196
TAPE MEASURES	195
VDE PLIERS	200
VDE SCREWDRIVERS	199

INDEX



Nothing but **HEAVY DUTY.**[™]

Techtronic Industries GmbH

Postfach 320
D-71361 Winnenden
Germany
Tel +497195120
Fax +49719512666

Distributed by: